



Peterbilt of Richmond (H830)
2800A Deepwater Terminal
Richmond, Virginia 23212

Virginia Sheriffs Association
901 East Byrd St Suite 1301
Richmond, Virginia 23219
United States of America

David Askew
Cell Phone:
Office Phone:
Email: daskew@thepetestore.com

Kaylyn Mitman
Office Phone: 919-459-6471
Email: kmitman@virginiasheriffs.org

Vehicle Summary

Unit		Chassis	
Model:	Model 579	Fr Axle Load (lbs):	13220
Type:	Tractor	Rr Axle Load (lbs):	46000
Description 1:	579 Standard Specs	G.C.W. (lbs):	80000
Description 2:	579 Option Specs		
Application		Road Conditions:	
Intended Serv.:	Construction Dump-On/Off Highway	Class A (Highway)	100
Commodity:	Construction Materials	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:		Wheelbase (in):	205
Length (ft):	0	Overhang (in):	54.7
Height (ft):	0	Fr Axle to BOC (in):	74.1
Max Laden Weight (lbs):	0		
Trailer		Cab to Axle (in):	130.9
No. of Trailer Axles:	2	Cab to EOF (in):	185.6
Type:	Semi-End Dump	Overall Comb. Length (in):	854.38
Length (ft):	53	Special Req.	
Height (ft):	13.5		
Kingpin Inset (in):	36		
Corner Radius (in):	1		
Restrictions			
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	\$ List	Weight
Base Model				
0005791	S	Model 579 The Model 579 combines aerodynamic innovation and powertrain optimization to deliver confidence and efficiency for the most cost-conscious companies. A solid and durable aluminum cab consists of the highest quality fit and finish. An in-mold process embeds color directly onto the dash for a long-lasting finish that virtually eliminates fading, scratching and peeling. Electrical wiring carriages support wiring and reduce wear and tear, adding to the overall durability of the components. Peterbilt's flexible Aero Packages provide the right combination of fairings, skirts and closeouts to exceed application-specific aerodynamic requirements. Available in a day cab, or with detachable sleeper, that adds versatility and longevity of a second life for highest resale value.	201,683	14,680
0091070	O	Construction Materials	0	0
0093060	O	Construction Dump-On/Off Highway Truck or tractor without liftable trailing axle which carries bulk materials (excavated earth, sand/gravel, asphalt, demolition debris, etc.) and unloads by dumping out the back, over the side of the body, or out the bottom of the trailer.	0	0
0096110	O	Semi-End Dump A tractor-trailer combination in which the trailer contains the hydraulic hoist. Equipped for use with a large payload.	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200614	S	SmartWay Designated - Not Selected or Unavailable For this vehicle configuration.	0	0
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514000	O	10-3/4" Steel Rails To 354" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	553	226
0601500	O	Full Steel Inner Liner	1,752	606
0611330	O	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	387	4
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
0644000	S	EOF Tractor Tapered with Crossmember Includes Kingpin Cutout	0	0
0651820	O	Peterbilt Rear Mudflaps, Stainless Steel Hangers Peterbilt Rear Mudflaps, Spring loaded (requires two additional inches of overhang for tractors), Stainless Steel Hangers. Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	114	26
0671040	O	Peterbilt Stainless Steel Quarter Fenders Stainless steel 24" x 24" Quarter Fenders, made of high polished 18 guage 430 stainless steel with hidden mounting bolts create a seamless appearance.	214	30
0854110	S	JOST JSK37 Fifth Wheel Top Plate JOST's fifth wheels are the simplest and safest design in the market, with only four moving parts. JOST's simple mechanism allows infinite adjustments versus competitors' notched adjustments.	0	0
0870000		Rear Or Fixd Setting Centerline Bogie	0	0
0890090	S	LH Fifth Wheel Release	0	0
0890550	O	7.6in - 8in Fifth Wheel Height	0	16
0890665	S	Jost Lightweight Inboard Slider	0	0
0891240	O	24" Air Slide	117	62
0898030	S	Fifth Wheel Slide Controls Provided with Speed Interlock to prevent accidental activation above 7 MPH. Configurable from 5 to 10 MPH. Required with sliding Fifth Wheels.	0	0
0940380	O	Locate Frame Access Steps Rearward As far as possible	0	0
0960020	O	Frame Mounted Deckplate And Access Pkg,Both Sides	659	68
Front Axle & Equipment				
1012300	O	Meritor MFS14 14,600 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 14,600 pounds. Axle includes special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service. Combination of Meritor Easy Steer king pin bushings, computer-designed and optimized I-beam construction and stiff axle assembly delivering a tight turning radius, superior vehicle control and longer tire life.	597	29
1112150	O	Taper Leaf Springs, Shocks 14,600 lb Hendrickson Taper Leaf Springs, shocks 14,6000 lb.	324	57
1233050	O	Power Steering TRW TAS85 TRW TA85 Power Steering for use with 14,600 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	372	7

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022

Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
1250250	O	Power Steering Reservoir Frame Mounted w/Cooler A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	374	2
1353550	S	PHP10 Aluminum PreSet PLUS Hubs Air Disc PHP10 aluminum PreSet PLUS hubs air disc have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug, with a seal and bearings. Use with Front Axle.	0	0
1380070	O	Greasable Front Spring Pins	78	0
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1380380	S	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0
1380470	O	Meritor Wide Track IPO Standard, Front Axle Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	0	15
1390630		80mm Front Spring Spacer Blocks	0	0
1391490	O	Pad And Rotor Dust Shields for Air Disc Brakes Front Axle	273	7
Rear Axle & Equipment				
1526120	O	Meritor RT46-160 46,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life. If code 1526120 (RT46-160) is ordered with 1680460 (Heavy Wall), you will get the 16 mm wall, but not the improved carrier that is in 1526130 code (RT46-160E) that also has a 16 mm wall. This could affect Heavy Haul service warranty length in Canada per Meritor.	2,700	634
1616295	S	PHP10 Aluminum Preset PLUS Hubs - Air Disc	0	0
1680390	S	Bendix ESP Electronic Stability Program With ATC Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022

Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
1680985	S	Bendix Fusion Bendix Fusion is an integrated driver assistance technology, utilizing a windshield mounted camera, bumper mounted radar and brake system information for the following features: Collision Mitigation, Stationary Vehicle Braking, Multi-lane Autonomous Emergency Braking, Highway Departure Warning and Braking, Following Distance Alerts, Lane Departure Warning, Overspeed Alert and Adaptive Cruise Control with Auto-Resume at speed.	0	0
1681015	O	Radio Mute When Lane Departure Detected Requires Fusion/OnAlert And Radio	0	0
1681025	O	Adjustable Following Distance Adaptive CC	0	0
1681035	O	Standard Following Distance Adaptive CC	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1683225	S	SmarTire Tire Pressure Monitoring System Next generation TPMS.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687040	S	Air Disc Rear Brakes, Tandem Drive Axle Includes Automatic Slack Adjusters.	0	0
1703910	O	Ratio 3.91 Rear Axle	0	0
1821640	O	Peterbilt Air Trac 46,000 lbs, 54in Axle Spacing Light Weight	1,763	291
Engine & Equipment				
2059793	O	X15 500V@1900 GOV@2000 1650@950 Productivity Series (2021 Emissions) N21350 C121 64....Maximum Accelerator Vehicle N21370 C128 64....Maximum Cruise Control Speed N21460 C132 1400..PTO Maximum Engine Speed N21520 C133 5.....Idle Shutdown Timer N21610 C188 39....Idle Shutdown Cold Ambient A N21620 C189 60....Idle Shutdown Intermediate A N21630 C190 80....Idle Shutdown Hot Ambient Ai N21550 C206 35....Idle Shutdown Percent Engine N21340 C209 120...Maximum Vehicle Speed N21510 C225 NO....Idle Shutdown with Parking B N21450 C231 NO....Gear Down Protection N21570 C233 NO....Idle Shutdown Manual Overrid N21440 C234 NO....Engine Protection Shutdown	10,699	465

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022

Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21480 C238 NO....Cruise Control and Engine Br		
		N21470 C239 NO....Cruise Control Auto-Resume		
		N21430 C333 0.....Driver Initiated OverrideMax		
		N21410 C334 0.....Driver Initiated Override Ma		
		N21590 C382 YES...Idle Shutdown Hot Ambient Au		
		N21500 C395 0.....Green House Gas Automatic En		
		N21530 C396 YES...Idle Shutdown Warning Period		
		N21540 C397 60....Idle Shutdown Warning Period		
		N21320 C399 120...Green House Gas Vehicle Spee		
		N21400 C400 252...Driver Initiated Override Re		
		N21420 C401 10....Green House Gas Vehicle Spee		
		N21330 C402 0.....Green House Gas Vehicle Spee		
2091130	S	VMUX Electronics Architecture	0	0
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091638		Effective VSL Setting 65.0 MPH or Greater (USA)	0	0
2092014	S	Typical Operating Speed 65 MPH	0	0
2092033	O	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2092079	O	Decline Driver Performance Assistant	0	0
2092108	S	Predictive Cruise Control Package	0	0
2120160	O	Cummins TRV For DAVCO Only For Fuel Filter, X15	48	0
2140220	S	CARB Engine Idling Compliance DECLINED By Dealer/Customer	0	0
2140410	S	Engine Brake Controls Located on RH Column	0	0
2140450	O	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision	31	0
2140670	O	EPA Emission Warranty	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022

Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
		heater keeps the coolant in the engine block from freezing when the engine is not running.		
2522090	O	PACCAR Premium Starter - X15 Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 5-yr/500K miles.	373	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	129	4
2539720	S	Low Voltage Disconnect System	0	0
2621090	O	DM Advantage ON/OFF Fan Clutch Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	412	0
2723220	O	18.7 CFM Naturally Aspirated Air Compressor X15 Only	0	0
2812170	O	Intebrate (Furnished on Engine) Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.	0	0
2921130	O	DAVCO 382 Fuel/Water Separator The Fuel Pro 382 is a combination of diesel fuel filtration and water separator that is recommended for heavy-duty diesel engines with flow rates up to 180 gallon/hour.	418	0
2921320	O	12V Heat for Fuel Filter Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	66	0
3010400	O	Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	6	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 367 1325 sq in, 367 HH Fepto 1325 sq in, 365 Fepto 1183 sq in, 365 Full Frame Extension 1000 sq in, 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 389/367 HH 1604 sq in, 365/567 1379 sq in.	0	0
3211140	S	(1) Air Cleaner Engine Mounted	0	0
3365250	O	Exhaust Single RH Back of Cab DPF/SCR right-hand Under Cab.	322	38
3381770	O	Curved Tip Standpipe(s)	51	1

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022

Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
3387370	O	60" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	1,066	24
3387880	O	7" Dia Chrome Plated Steel Standpipe(s) IPO 5"	220	8

Transmission & Equipment

4024120	O	Eaton FO16E313A-MHP 13-Speed Ultrashift Plus Multi-Purpose High Performance. Includes water-to-oil cooler. Features two-pedal operation for driver convenience. A Hill Start Aid (HSA) feature is included to prevent roll back or roll forward while launching on grades by employing the trucks foundation brakes. Synthetic lubricant to reduce friction, improve efficiency, and extend component life. Magnetic transmission oil drain plug captures and holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward ratios: 1st-12.29, 2nd-8.51, 11th-1.00, 12th-0.86, 13th-0.73. Reverse ratios: R1-15.06, R2-12.85, R3-4.03.	2,877	363
4210280	O	1810 HD Driveline, 2 Midship Bearings 4.5in x .180 wall tubing	1,651	215
4216590	O	1710 Driveline Interaxle For tandem rear axles	337	0
4233900	O	(1) Dash Mounted Single Acting EOA PTO Control Electric-over-air (EOA), spec'ing PTO (power-take-off) control switch does not ensure the PTO will fit.	93	0
4252610	S	Column Mounted Shifter RH Side	0	0
4257090	O	Neutral Coast Mode At Pedal Only Automated Transmission; X15 Only	0	0

Air & Trailer Equipment

4510210	O	Bendix AD-HF EP Air Dryer, Heater Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	138	-2
4540420	S	Nylon Chassis Hose	0	0
4542330	O	Central Location For Air Tank Drain Valves Frame mounted BOC tanks, includes pull cords. Only available horizontal/transverse tanks	265	4
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022

Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
4543390	O	High Mount Air Tanks BOC/BOS Where Possible Subject to frame review	0	0
4610920	S	Self-Returning Brake Hand Valve Dash mounted controls	0	0
4611200	O	12' AE Lines Straight, 3 In 1, (2) 7-Way Plugs BOC socket, QCMS2 type on one end	435	8
4614810	S	AE Connections BOC/BOS, Hose Tenna	0	0

Tires & Wheels

5066050	O	FF: BR 16ply 11R22.5 R213 Ecopia	187	4
5166610	O	RR: BR 14ply 11R22.5 M726ELA Efficiency Rating: Poor Diameter= 42.2 inches; SLR= 19.6 inches	860	152
5190008	S	Code-rear Tire Qty 08	0	0
5220600	O	FF: Peterbilt 88U677 22.5X8.25 High Polish Aluminum, Ultra ONE technology.	329	-46
5320600	O	RR: Peterbilt 88U677 22.5X8.25 High Polish Aluminum. Ultra ONE technology.	1,316	-184
5390008	S	Code-rear Rim Qty 08	0	0

Fuel Tanks

5552190	O	26" Aluminum 100 Gallon Fuel Tank RH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	68	9
5556160	O	26" Aluminum 90 Gallon Fuel Tank LH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	253	7
5603100	O	Location RH BOC 100 Gallon	0	0
5604090	O	Location LH BOC 90 Gallon	0	0
5650260	O	Split Aluminum Fuel Tank RH BOC	-82	4
5652600	O	Fuel Rear In Split Tank	0	0
5652620	O	50 Gallon Fuel In Split Tank	0	0
5652890	O	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655029	O	DEF Tank Medium, 24 Gal	120	22
Battery Box & Bumper				
6010030	S	Aluminum Battery Box LH Under Cab, Non-Slip Step Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models	0	0
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6112540	S	Aero Bumper Molded 3-Piece Molded Black	0	0
Cab & Equipment				
6515800	O	Aero 124" BBC Alum Cab & Metton Hood w/ SBFA Hood has stainless steel grille with chrome plated grille surround and Peterbilt bird. Includes anti-blow down hood device.	2,831	55
6540160	O	Thermal Insulation Package in Cab The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	21	2
6540740	O	Peterbilt Keyless Entry The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the drivers door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.	165	2
6700000	S	No Sleeper Selected	0	0
6911740	O	Peterbilt LX Driver Peterbilt LX Air seat, high height backrest, adjustable seat track length, 2 chamber lumbar support, premium suspension with adjustable damping, auto leveling, exit air dump, memory for sitting height, fore-aft isolator with lockout, vinyl bellows over suspension, Requires folding armrests, side and back storage pocket. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal cargo/luggage. Standard with fabric/vinyl finish - color coordinated with interior color	209	3
6921130	O	Peterbilt LX Passenger seat Peterbilt LX Air seat, high height backrest, adjustable seat track length, 2 chamber lumbar support, premium suspension with adjustable damping, auto leveling, exit air dump, memory for sitting height, fore-aft isolator with lockout and vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal cargo/luggage. Standard with fabric / vinyl - color coordinated with interior color.	626	28

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022

Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
6930580	O	Drivers Armrests - LH & RH	170	4
6930590	O	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	125	2
6931120	O	Seat Belt Color Orange IPO Standard Black	10	0
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939480	O	Mordura Driver	92	0
6939500	O	Air Ride Passenger	0	0
6939520	S	High Back Passenger	0	0
6939580	O	Mordura Passenger	92	0
7000045	O	High-Visibility Interior Grabhandles, Painted Bright yellow interior grabhandle for vocational vehicles.	48	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7001630	O	Premium Steering Wheel with Multi Function Premium Multi-functional Leather Wrapped Steering Wheel with Peterbilt logo over horn button. Includes audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	149	5
7037175	O	Platinum Interior - Sterling Gray	1,930	25
7040150	O	Rubber Floor IPO Carpet (Black Only) Rubber Floor Covering in Cab. Standard in Prestige interior, optional in Platinum/Premier interiors.	-36	-6
7210510	O	3-Piece Glass Rear Cab Window, All Pieces Fixed	227	12
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7230060	S	1-Piece Curved Windshield	0	0
7230360	S	Power Door Locks and Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	885	8
7510070	S	Aero Rear View Mirror Housing, Molded Black	0	0

Price Level: January 1, 2022
Deal: 579 Standard Specs
Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022
Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
7514010	O	Peterbilt Aero Rear View Mirror, Motorized Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	335	3
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7561320	O	LH/RH Rect Hood Mirrors, Black Housing and Black Molded arm and base; Rearward View.	225	10
7610500	S	Air Horn Mounted Under Cab	0	0
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	373	10
7725710	O	Standard Speaker Package For Cab (2) Speakers	59	4
7728030	O	Radio Mute When In Reverse For automatic or automated transmission	0	0
7728040	O	Bluetooth Phone and Audio Requires USB Port	56	0
7728050	O	USB Port	56	0
7740140	O	Cobra 29 CB Radio Mounted Center Of Header Without weatherband. Mounted in center of header with sound tracker & illuminated panel. Includes wiring, microphone clip, & speaker. Must select antenna(s) option.	310	10
7743020	O	(1) Antenna for Factory Installed Or F/O CB, mounted vertical center BOC/BOS.	88	1
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0	0
7788058	O	24 Months SmartLINQ Subscription Cummins Engines.	0	0
7850555	O	Dual USB Charging Port	185	2
7851040	O	Removable Bugscreen Behind Grille	183	2
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022

Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
7852020	O	Cab Air Suspension	240	15
7852050	O	Auto Reset Circuit Protection Daycab and Sleeper	19	0
7852080	O	Pull Out Tray/Work Surface Over Glove Box	238	3
7870560	O	18 Inch Cab Side Extenders, Includes 6.5 Inch Rubber flares for daycab only.	997	46
8011830	S	Engine Oil Temperature Located in Digital Cluster Display.	0	0
8021800	S	Air Filter Restriction Pressure Gauge Located in Digital Cluster Display	0	0
8021810	S	Brake Application Air Pressure (Tractor) Located in Digital Cluster Display.	0	0
8070810	S	Engine Manifold Pressure (Turbo Boost) Located in Digital Cluster Display	0	0
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0	0
8070830	O	Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.	0	0
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0	0
8120990	S	(5) Marker Lights, Aero LED On roof, visor, or fairing	0	0
8133960	S	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8134160	O	Self-Canceling Turn Signal	0	0
8140060	O	LED Oval Stop/Turn/Tail/Backup In tractor taper end of frame crossmember	27	-7
8151190	O	(2) Load Lights, LED, Flush Mounted Low Inboard Back of cab / back of sleeper	177	4
Paint				
8500710	S	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:52:37 PM

Date: July 07, 2022

Quote Number: QUO-970636-L1Y6T9



Sales Code	Std/ Opt	Description	\$ List	Weight
Shipping Destination				
Options Not Subject To Discount				
9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9407103	O	Prepaid Freight Increase For 2022 Delivery	500	0
9407147	O	Fuel Price Index Factor \$507 Net	507	0
9408703	O	Base Warr: Emissions 5YR/100K MI-EPA Engine	0	0
Miscellaneous				
9409002	O	Day Cab / Platinum Interior (DP)	0	0
9409096	O	State Registry: Virginia	0	0

Promotions

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$245,560
Marketing and Service Support Fee	\$995
Prepaid Freight	\$2,825
Total Surcharge/Options Not Subject To Discount	\$1,007
Total Weight	18,099

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------