


Wellpoint Pump 4 inch discharge



The ideal pump for small dewatering projects:

- Utility line connections
- Utility line repairs
- Small tank installations
- Swimming pool installations
- Lift station installations
- Wellpoint systems
- Sock underdrain

Diesel Configuration:

Model 4VAWP-1z3-C3-F(W)

Isuzu 3CH1 EPA Tier 4 Final liquid cooled diesel engine, 18 cont. hp @ 2100 rpm
Full instrument panel with safety shutdowns


Electric Configuration:

Model 4VAWP-E20-C3-F(W)

20 HP, 1800 rpm, 460 volt, 3 phase TEFC motor
23.7 FL Amps @ 460 volts, 1.15 SF
NEMA control panel with external disconnect, fuse block, magnetic contactor, adjustable overload

Specifications:

- 870 GPM cast iron centrifugal pump
- 6" Suction x 4" Discharge
- up to 24' suction lift
- C3 vacuum pump, 65 cfm air handling, air cooled
- Closed loop vacuum oil recovery system with heat exchanger
- Air/water separation tank with peeler valve assembly
- Integral fuel tank / frame, 52-gallon capacity
- Single point lifting bale
- Optional: wheel mount with highway lights, fenders



“The finest dewatering pumps and wellpoint equipment since 1923”

