



Effective March 16, 2023 - March 15, 2024

#### Wanco Inc.

Catalog Discount: Message Trailers, Camera Trailers, Speed Trailers, Arrow Boards, Generator Light Tower

### 8% Discount off MSRP for Main Line Items

**Key Notes:** 

Upgrades/Downgrades are available.

All Prices are FOB Wanco Factory.

Freight & Sales Tax are not included in pricing

Services are available – please contact Paula Sauls or Tony Bailey for details

MSRP prices are subject to change





Effective March 16, 2023 – March 15, 2024

PRODUCT	MODEL	PRODUCT	PRODUCT DESCRIPTION
#	CODE	NAME	
N/A	WCTS- MINI-520	Wanco® WCTS-MINI Camera Trailer WCTS Mini trailer, 520W solar and IR HD single camera (800Ah Battery Bank @ 12VDC – 45A battery charger)	Standard Features Trailer: Welded tubular steel construction, extendable rear bumper for added wind stability, front access fork lift pockets, round full wheel fenders that are bolted to the trailer frame, axle assembly 2,000 lb., double-eye leaf springs, 13" wheel / tires, Four 2,000 lb. corner stabilizer jacks, red and white conspicuity tape Drawbar: Tilting, 2" ball hitch, swivel wheel tongue jack, flat-four trailer lights plug Tower: Telescoping 20ft hand crank tower, rotates approximately 360 degrees, tower top holds two Mini-Dome cameras, cables up mast protected in liquid tight loom Solar panel: Two choices of solar, hand crank tilting frame, solar charge controller with LVD -12VDC (520W Trailer) – Morningstar 30A solar charge controller with onboard display -24VDC (750W Trailer) – Victron solar charging package with 5-year online trailer health data & local Bluetooth Batteries: Heavy-duty steel security box with dual puck locks, Four 4D AGM Batteries -12VDC system, 800 Ah Total Capacity for the 520W solar, 45A smart battery charger -24VDC system, 400 Ah for the 750W solar, 50A smart battery charger Standard Colors: Powder-coated flat black frame and tower, white battery box Primary Camera: Primary IR HD Mini Dome PTZ camera, 1080p resolution, 23x optical zoom, 2 TB SSD, smart switch, IRrange 150 ft. 4G modem with 10GB/month plan 2 year service**, Wi-Fi®, GPS, Analytics

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

N/A	WCTS-	Wanco®	Standard Features
	MINI-520-2	WCTS-MINI	Trailer: Welded tubular steel construction, extendable rear bumper
		Camera	for added wind stability, front access fork lift pockets, round full wheel
		Trailer	fenders that are bolted to the trailer frame, axle assembly 2,000 lb.,
		WCTS Mini	double-eye leaf springs, 13" wheel / tires, Four 2,000 lb. corner
		trailer,	stabilizer jacks, red and white conspicuity tape
		520W solar	Drawbar: Tilting, 2" ball hitch, swivel wheel tongue jack, flat-four
		and IR HD	trailer lights plug
		dual	<b>Tower:</b> Telescoping 20ft hand crank tower, rotates approximately 360
		camera	degrees, tower top holds two Mini-Dome cameras, cables up mast
		(800Ah	protected in liquid tight loom
		Battery	<b>Solar panel:</b> Two choices of solar, hand crank tilting frame, solar
		Bank @	charge controller with LVD
		12VDC -	-12VDC (520W Trailer) – Morningstar 30A solar charge controller with
		45A battery	onboard display
		charger)	-24VDC (750W Trailer) – Victron solar charging package with 5-year
			online trailer health data & local Bluetooth
			<b>Batteries:</b> Heavy-duty steel security box with dual puck locks, Four 4D AGM Batteries
			-12VDC system, 800 Ah Total Capacity for the 520W solar, 45A smart
			battery charger
			-24VDC system, 400 Ah for the 750W solar, 50A smart battery charger
			Standard Colors: Powder-coated flat black frame and tower, white
			battery box
			Primary Camera: Primary IR HD Mini Dome PTZ camera, 1080p
			resolution, 23x optical zoom, 2 TB SSD, smart switch, IRrange 150 ft.
			4G modem with 10GB/month plan 2 year service**, Wi-Fi®, GPS,
			Analytics

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

N/A	WCTS-	Wanco®	Standard Features
	MINI-750	WCTS-MINI	Trailer: Welded tubular steel construction, extendable rear bumper
		Camera	for added wind stability, front access fork lift pockets, round full wheel
		Trailer	fenders that are bolted to the trailer frame, axle assembly 2,000 lb.,
		WCTS Mini	double-eye leaf springs, 13" wheel / tires, Four 2,000 lb. corner
		trailer,	stabilizer jacks, red and white conspicuity tape
		750W solar	Drawbar: Tilting, 2" ball hitch, swivel wheel tongue jack, flat-four
		and IR HD	trailer lights plug
		single	<b>Tower:</b> Telescoping 20ft hand crank tower, rotates approximately 360
		camera	degrees, tower top holds two Mini-Dome cameras, cables up mast
		(400Ah	protected in liquid tight loom
		Battery	<b>Solar panel:</b> Two choices of solar, hand crank tilting frame, solar
		Bank @	charge controller with LVD
		24VDC -	-12VDC (520W Trailer) – Morningstar 30A solar charge controller with
		50A battery	onboard display
		charger)	-24VDC (750W Trailer) – Victron solar charging package with 5-year
			online trailer health data & local Bluetooth
			<b>Batteries:</b> Heavy-duty steel security box with dual puck locks, Four 4D AGM Batteries
			-12VDC system, 800 Ah Total Capacity for the 520W solar, 45A smart
			battery charger
			-24VDC system, 400 Ah for the 750W solar, 50A smart battery charger
			<b>Standard Colors:</b> Powder-coated flat black frame and tower, white
			battery box
			Primary Camera: Primary IR HD Mini Dome PTZ camera, 1080p
			resolution, 23x optical zoom, 2 TB SSD, smart switch, IRrange 150 ft.
			4G modem with 10GB/month plan 2 year service**, Wi-Fi®, GPS,
			Analytics

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

N/A	WCTS-	Wanco®	Standard Features
	MINI-750-2	WCTS-MINI	Trailer: Welded tubular steel construction, extendable rear bumper
		Camera	for added wind stability, front access fork lift pockets, round full wheel
		Trailer	fenders that are bolted to the trailer frame, axle assembly 2,000 lb.,
		WCTS Mini	double-eye leaf springs, 13" wheel / tires, Four 2,000 lb. corner
		trailer,	stabilizer jacks, red and white conspicuity tape
		750W solar	Drawbar: Tilting, 2" ball hitch, swivel wheel tongue jack, flat-four
		and IR HD	trailer lights plug
		dual	<b>Tower:</b> Telescoping 20ft hand crank tower, rotates approximately 360
		camera	degrees, tower top holds two Mini-Dome cameras, cables up mast
		(400Ah	protected in liquid tight loom
		Battery	<b>Solar panel:</b> Two choices of solar, hand crank tilting frame, solar
		Bank @	charge controller with LVD
		24VDC -	-12VDC (520W Trailer) – Morningstar 30A solar charge controller with
		50A battery	onboard display
		charger)	-24VDC (750W Trailer) – Victron solar charging package with 5-year
			online trailer health data & local Bluetooth
			<b>Batteries:</b> Heavy-duty steel security box with dual puck locks, Four 4D AGM Batteries
			-12VDC system, 800 Ah Total Capacity for the 520W solar, 45A smart battery charger
			-24VDC system, 400 Ah for the 750W solar, 50A smart battery charger
			Standard Colors: Powder-coated flat black frame and tower, white
			battery box
			Primary Camera: Primary IR HD Mini Dome PTZ camera, 1080p
			resolution, 23x optical zoom, 2 TB SSD, smart switch, IRrange 150 ft.
			4G modem with 10GB/month plan 2 year service**, Wi-Fi®, GPS,
			Analytics

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

N/A	WCTS-750	Wanco	Trailer: Tubular steel welded construction, four 2,000 lb. stabilizer
		Integrator	corner jacks for added wind stability, front access fork lift pockets,
		Trailer	crane lifting eyes, round full wheel fenders that are bolted to the
		750W	trailer frame, axle assembly 3,500 lb., double-eye leaf springs, 15"
			wheels / tires, red and white conspicuity tape
			<b>Drawbar:</b> Tilting, 2" ball hitch, swivel wheel tongue jack, flat-four
			trailer lights plug
			<b>Tower:</b> 24-foot telescoping tower rotating 355 degrees, hand-
			operated winch for raising and lowering tower,
			Camera mount: Multi-head camera box: 4x pendant arms (1-1/2"
			NPT), 5X Cat5E cable, 1X 16/2 power, in NYCOIL tubing
			<b>Solar:</b> High-efficiency photovoltaic solar modules, electric actuator-tilt
			solar panel array, solar panel capacity 750, Smart MPPT blue-tooth
			solar controller, battery "time-remaining" feature, communication module.
			Control Box: Aluminum control box with 3-point locking door, solar /
			battery power management meter, master battery disconnect switch,
			power inverter 375W, Solar panel tilt switch
			Batteries: Single Wanco battery box with bolted Lid, four 12V sealed
			AGM Batteries (400 Ah Total Capacity), 50 Amp battery charger
			Standard color: Powder coated flat black frame and mast, white
			battery box and NEMA box

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

N/A	WCTS-1500	Wanco	Trailer: Tubular steel welded construction, four 2,000 lb. stabilizer
		Integrator	corner jacks for added wind stability, front access fork lift pockets,
		Trailer	crane lifting eyes, round full wheel fenders that are bolted to the
		1500W	trailer frame, axle assembly 3,500 lb., double-eye leaf springs, 15"
			wheels / tires, red and white conspicuity tape
			<b>Drawbar:</b> Tilting, 2" ball hitch, swivel wheel tongue jack, flat-four
			trailer lights plug
			<b>Tower:</b> 24-foot telescoping tower rotating 355 Degrees, hand-
			operated winch for raising and lowering tower,
			Camera mount: Multi-head camera box: 4x pendant arms (1-1/2"
			NPT), 5X Cat5E cable, 1X 16/2 power. In NYCOIL tubing
			<b>Solar:</b> High-efficiency photovoltaic solar modules, electric actuator-tilt
			solar panel array, solar panel capacity 1500W, Smart MPPT blue-tooth
			solar controller, battery "time-remaining" feature, communication module.
			Control Box: Aluminum control box with 3-point locking door, solar /
			battery power management meter, master battery disconnect switch,
			power inverter 375W, solar panel tilt switch
			Batteries: Dual Wanco battery box with bolted Lid, eight 12V sealed
			AGM batteries (800 Ah total capacity), 50 Amp battery charger
			Standard color: Powder coated flat black frame and mast, white
			battery box and NEMA box

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

N/A	WCTS_DOT-	Wanco 730	Trailer: Welded tubular steel construction, Extendable Rear Bumper
	730	W DOT	for Added wind Stability, Front access fork lift pockets, Round Full
		Surveillance	Wheel Fenders that are Bolted to the Trailer Frame, Axle Assembly
		Trailer with	2,000 lb., Double-Eye Leaf Springs, 13" Wheel / tires, Four 2,000 lb.
		2 Axis	Corner Stabilizer Jacks, Red and White Conspicuity Tape
		Cameras	Drawbar: Removable, 2" Ball Hitch, Swivel Wheel Tongue Jack, Flat-
			four trailer lights plug
			<b>Tower:</b> Telescoping hand crank tower, Rotates approximately 360
			degrees, Tower top holds one PTZ Dome Cameras and adjustable
			tubing for Radar sensor, cables up mast protected in liquid tight loom
			<b>Solar panel:</b> 730W solar configuration, hand crank tilting frame, Solar
			charge controller 30A with LVD
			Batteries: Heavy-duty steel Security box with dual puck locks,
			Two 4D AGM Batteries (12Vdc system, 400 Ah Total Capacity on 520W
			solar), 45 Amp Smart Battery Charger, Master disconnect switch
			Two 4D AGM Batteries (24Vdc system, 200 Ah Total Capacity on 730W
			solar), 50 Amp Smart Battery Charger, Master disconnect switch
			Standard colors: Powder-Coated black frame, tower and white battery
			box

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

WSP25-	WSP25	WSP25 RHINO Light Tower, Tier 4 Final Towable Generator 24KW
Trailered	RHINO	Prime Power with LIGHT TOWER PACKAGE 24.5FT TOWER, (4) 480W
	Light	LED FIXTURES
	Tower, Tier	• Tier 4 Final 4 cylinder 2.2L Isuzu engine (Model # 4LE2TAGV-02)
	4 Final	Prime – 24kW @1800 rpm (Single phase 17kW)
	Towable	• ECP28-LC/2LA Brushless Mecc Alte "Maux PMG" generator for 300%
	Generator	motor-starting capability. Type: Insulation H.
		Automatic Voltage Regulation with upgraded +/- 0.5% DER1 voltage
		regulator
		KRAUS & NAIMER Three - position voltage selector switch, easily
		adjust to any of the following voltages or phases: 480/277V 3Ø -
		208/120V 3Ø - 240/120 1Ø.
		Deep Sea 7320 Series Digital controller with heated display
		ABB breaker 100 amp with shunt trip
		Emergency E Stop button
		Battery disconnect switch
		• 120% Containment
		• Fuel tank size: 60.8 gallons – with external JIC fittings for external
		fuel hook up
		Level 1 cold weather package hot start 120V block heater
		Rental Grade Standard Package: Lugs/Distribution Connection,
		Weather Proof Female Camlocks, and convenience receptacles:
		Leviton series 16 Camlocks – 400amp weather proof.
		(x2) CS6369 RECEPTACLE 50 A, 125V/250V
		(x2) LEVITON TBR20-W 20A, 125 V, NEMA 5-20R outlets
		Trailered RHINO Light Tower, Tier 4 Final Towable

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

N/A	WSP12-	WSP12 Tier	WSP12 Tier 4 final Towable Generator
	Trailered	4 final	• Tier 4 final 3 cylinder 1.5L Perkins engine (Model # 403F-15G)
		Towable	naturally aspirated. Prime Power – 11.2kW @ 1800 RPM (single phase
		Generator	power 11.2kW)
			Mecc Alte ECP28-2S4C "Maux" generator for 300% motor-starting
			capability. Type: Insulation H. Automatic Voltage Regulation with
			upgraded +/- 1% DSR voltage regulator
			Electrical Controls:
			Deep Sea 7320 Series Digital controller with heated display
			Siemens 50AMP Main breaker
			Emergency E Stop button
			(x2) 20AMP GFCI receptacles
			(x1) 30AMP TT30RV style receptacle
			(x1) 240V 30 Amp locking (Nema L14-30R)
			(x1) 50AMP CS6369 California receptacle
			Fuel Tank:
			50 gallon fuel tank with external JIC-10 fittings for external fuel hook
			up.
			110% containment capacity.
			Enclosure:
			Heavy duty rental grade steel with sound attenuated foam, closed cell
			and fire retardant foam.

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

Automated	Wanco®	Standard Features
Flagger	AFAD	Trailer: Welded Structural Steel Frame, Round Full Wheel Fenders that
Assistance	Trailer	are Bolted to the Trailer Frame, 1,200 lb. Axle Assembly, Double-Eye
Device	Hallel	, ,
Device		Leaf Springs, 13" wheels/tires, Four corner swivel jacks.
		<b>Drawbar:</b> Removable, 2" Ball Hitch, Swivel Tongue Footpad Jack, Flat-
		four trailer lights plug
		<b>Rear tow:</b> Receiver with 2" ball and flat-four tail light plug for tandem towing
		Standard Color: Powder-Coated Safety Orange
		Vertical Configuration: Vertical Mast Tower with Hand Operated Winch
		<b>Controller:</b> Wireless touchscreen controller provides access to all
		control functions for one or two synched AFADs. On-board charger for
		touchscreen controller battery.
		<b>Gate Arm:</b> Two Section Actuator Pivoting Arm, 3"x 4ft with Dual
		Conspicuity Tape
		Signal Beacons: One Red LED 12" and One Yellow LED 12"
		Warning Siren: Operator Activated Intrusion Alarm, 110 dB Output
		Stop Here Sign: R10-6 Regulatory "Stop Here on Red" sign, standard
		size 24" x 36" (61 x 91cm) W x H
		<b>Solar Panel:</b> One 85W Solar Panel top mounted, Wanco solar charge
		controller
		<b>Batteries:</b> Wanco standard battery box, Four 6V Flooded Batteries
		(400 Ah Total Capacity), 15 Amp Battery Charger
WTSP55-	Wanco®	Trailer: Welded Structural Steel Frame, Ballasted Trailer Deck, Axle
LSA	Arrow	Assembly 2,000 lb. with Double-Eye Leaf Springs, Four Adjustable Drop
LSA	Board	Stabilizer Legs, Round Polyethylene Full Wheel Fenders with LED Lights
	Trailers 15-	Bolted to the Trailer Frame, Hand Crank Winch Raises Sign and Solar
		Panel
	Light Arrow Board with	
		Standard Color: Powder-Coated Safety Orange
	7 Display	<b>Drawbar:</b> Removable, 2" Ball Hitch, Swivel Footpad Tongue Jack, Flat-
	Patterns	four Trailer Lights Plug
		Board Assembly: 48" x 96" Aluminum Sign, PAR 46 Amber LED Lamps,
		Visors to Enhance Visibility, Separate Weather Resistant Rotary Knob
		Controller with Solar Charger and LVD
		Batteries: Two 12V Sealed Lead Acid Batteries (36 Ah Total Capacity)
		<b>Solar:</b> High-Efficiency Photovoltaic Solar Module, 50/55W Solar Panel
		Mounted Above Cabinet

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

	WTSP55-	Wanco®	Same as above
	LSAC	Arrow	Same as above
	25/10	Board	
		Trailers 25-	
		Light Arrow	
		Board with	
		12 Display	
212275	=	Patterns	
218376-	WTMMB(A)	Full Matrix	Trailer: Welded Structural Steel Frame, Removable Drawbar
C1		Message	Adjustable 2" Ball Hitch, One Top-Wind Swivel Wheel Tongue Jack,
		Sign with	Rectangular Polyethylene Fenders that are Bolted to the Trailer Frame,
		Hydraulic	3,500 lb. Axle Assembly, Double-Eye Leaf Springs, 15" Wheels/Tires,
		Lift	Four 2,000 lb. Corner Stabilizer Swivel Jacks, Telescoping Tower with
			360° Rotation
			Standard Color: Powder-Coated Safety Orange
			<b>Three Line Display:</b> Three Lines of Eight 18" LED Characters, Weather-
			Resistant Aluminum Cabinet, Powder-Coated Flat Black, Lexan®
			Window, Stainless Steel Hinges, Cooling Fans to Circulate Air
			Full Matrix Display: 12 Variable Fonts, Full Range of MUTCD Graphics,
			Weather-Resistant Aluminum Cabinet, Powder- Coated Flat Black,
			Lexan® Window, Stainless Steel Hinges, Cooling Fans to Circulate Air
			ICC (In Cabinet Controller): Capacitive 7" Touchscreen Controller, Full-
			color Touchscreen Display, Multi-level Password Protection, NTCIP
			Compliant, Easy to Use, Vandal Resistant when Deployed
			5 Year Wanco Manufactured Electronics Warranty
			Batteries: Wanco Standard Battery Box, Four 6V Flooded Batteries
			(400 Ah Total Capacity), 15 Amp Battery Charger
			<b>Solar:</b> High-Efficiency Photovoltaic Solar Module, 130W Solar Panel,
			Regulated by the Wanco Message Sign Control System
219108-	WTMMB(B)	Full Matrix	Same as above
C1	VV I IVIIVID(D)		Jame as above
		Message	
		Sign with	
		Hand-	
		Operated	
		Winch	
218658-	WTLMB(A)	3-Line	Same as above
C1		Message	
		Sign with	

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

219107- C1	WTLMB(B)	Hydraulic Lift 3-Line Message Sign with Hand-	Same as above
218682- C1	WVT3(A)	Operated Winch Mini 3-Line Message Sign with Hydraulic Lift	Trailer: Welded Structural Steel Frame, Removable Drawbar 2" Ball Hitch, One Top-Wind Swivel Wheel Tongue Jack, Round Polyethylene Fenders that are Bolted to the Trailer Frame, 2,000 lb. Axle Assembly, Double-Eye Leaf Springs, 15" Wheels/Tires, Four 2,000 lb. Corner Stabilizer Swivel Jacks, Telescoping Tower with 360° Rotation Standard Color: Powder-Coated Safety Orange Three Line Display: Three Lines of Eight 14" LED Characters, Weather-Resistant Aluminum Cabinet, Powder-Coated Flat Black, Lexan® Window, Stainless Steel Hinges, Cooling Fans to Circulate Air Full Matrix Display: 12 Variable Fonts, Full Range of MUTCD Graphics,
			Weather-Resistant Aluminum Cabinet, Powder- Coated Flat Black, Lexan® Window, Stainless Steel Hinges, Cooling Fans to Circulate Air 5 Year Wanco, Manufactured Electronics Warranty Batteries: Wanco Standard Battery Box, Four 6V Batteries (400 Ah Total Capacity), 15 Amp Battery Charger Solar: High-Efficiency Photovoltaic Solar Module, 85W Solar Panel, Regulated by the Wanco Message Sign Control System
218685- C1	WVT3(B)	Mini 3-Line Message Sign with Hand- Operated Winch	Same as above
218678- C1	WVTM(A)	Mini-Matrix Message Sign with Hydraulic Lift	Same as above

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

218686-	WVTM(B)	Mini-Matrix	Same as above
C1	, ,	Message	
		Sign with	
		Hand-	
		Operated	
		Winch	
Wanco® Metro™ Matrix Message Signs		/lessage Signs	
218648- C1	WVTMM-M	Medium Metro™ Matrix Display*	Trailer: Welded Structural Steel Frame, Removable Drawbar 2" Ball Hitch, One Top-Wind Pad Tongue Jack, Round Polyethylene Fenders that are Bolted to the Trailer Frame, 2,000 lb. Axle Assembly, Double-Eye Leaf Springs, 15" Wheels/Tires, Four 2,000 lb. Corner Stabilizer Swivel Jacks, Telescoping Tower with 360° Rotation  Standard Color: Powder-Coated Safety Orange  Metro™ Matrix Display: 12 Variable Fonts, Full Range of MUTCD  Graphics, Weather-Resistant Aluminum Cabinet, Powder-Coated Flat Black, Lexan® Window, Stainless Steel Hinges, Cooling Fans to Circulate Air  ICC (In Cabinet Controller): Capacitive 7" Touchscreen Controller, Full-color Touchscreen Display, Multi-level Password Protection, NTCIP Compliant, Easy to Use, Vandal Resistant when Deployed 5 Year Wanco Manufactured Electronics Warranty  Batteries: Wanco Standard Battery Box, Four 6V Batteries (400 Ah Total Capacity), 15 Amp Battery Charger  Solar: High-Efficiency Photovoltaic Solar Module, 85W Solar Panel
			(Medium Display), 130W Solar Panel (Large Display), Regulated by the Wanco Message Sign Control System
218052-	WVTMM-L	Large	Same as above
C1		Metro™	
		Matrix	
		Display*	

### For quotes or more information, contact:





Effective March 16, 2023 – March 15, 2024

### For quotes or more information, contact: