



**L3HARRIS™**  
FAST. FORWARD.

## **XL EXTREME™ 400P**

Rugged and Ready for Anything

You don't flinch in the face of danger. Neither should your radio. L3Harris' XL Extreme™ 400P is tailor-made to keep everyone connected even in the most extreme conditions.

This radio's rock-solid construction is engineered to withstand anything the environment can throw at it. With new hardware designed to the toughest industry standards, the 400P features extreme thermal materials, reinforced seal design, and unique thermal-rated displays and speakers. All new heavy-duty, glove-friendly keypad, knobs, and large Emergency button with L3Harris' unique visual zone indication, ambient temperature, and optional in-building location capabilities keep your team in sync when the heat is on. Just like the rest of our XL radios, the XL Extreme™ 400P is:

### **RELENTLESSLY RELIABLE**

XL Radios run on systems that double-down on redundancy, champion open networks, and connect seamlessly with P25-compliant organizations.

### **POINT-TO-POINT SECURE**

Our AES secure configurations are ironclad, keeping your systems safe from threats.

### **BACKED WITH ALL-IN, 24/7 SUPPORT**

Our service packages get your radios up and running and keep them running with preventative maintenance and automatic software upgrades.

### **Stay connected in the most extreme conditions.**

- > Hardware designed to withstand extreme temperatures and environments
- > Intuitive, comfortable, and easy to use
- > Large glove-friendly keypad, buttons, and knobs
- > LTE operation over AT&T and Verizon networks
- > Ambient temperature sensor
- > Loud and clear audio with industry-leading noise cancellation
- > Visual zone indication provides quick visual confirmation that all users are on the same group or channel
- > Advanced connectivity with secure voice and data encryption
- > Includes Wi-Fi and Bluetooth integration

## SPECIFICATIONS FOR: XL EXTREME 400 PORTABLE FULL-SPECTRUM MULTIBAND RADIO

GENERAL		
<b>Radio Models:</b> Extreme Keypad	Full heat-resistant DTMF keypad, integrated navigation cluster, and soft keys	
<b>Dimensions w/Battery (H x W x D)</b>	6.6 x 2.5 x 1.7 in (168.0 x 64.0 x 43.7 mm)	
<b>Weight</b>	14.7 oz (418 g)	
<b>Housing Colors</b>	Green and Black	
<b>Interfaces:</b>		
<b>Front Display</b>	320 x 178 pixels, 1.8 in transfective LCD, 16-bit color with backlight	
<b>Top Display</b>	128 x 64 pixels, 1.1 in multicolor backlight, sunlight readable	
<b>Keypad</b>	Backlight, 3 soft keys, 5-way navigation key	
<b>Buttons</b>	SIDE: Large PTT button, 2 programmable side buttons. TOP: Rotary volume control with on/off switch, 2-position rotary concentric switch, 16 position top-mounted rotary switch, 4-position rotary concentric switch, 1 programmable top button, 1 large int'l orange emergency button	
<b>Tx/Rx Indicator</b>	2-position concentric switch, 4-position toggle switch, 2 programmable side buttons, programmable top button, multicolored LEDs 1 Multicolored TX/RX indicator, 1 Bluetooth indicator	
<b>Channel/Talkgroup Capacity</b>	1,250 total conventional channels and 13,824 total talkgroups	
<b>Radio programming</b>	Firmware, personalities and feature set over Wi-Fi	
<b>Transceiver</b>	<b>Supported Bands</b> VHF, UHF and 700/800 MHz and LTE (optional)	<b>Channel Capacity</b> 12,500 (1,250 per mission plan)
<b>Environmental:</b>		
<b>Relative Humidity</b>	5% @ 140°F (60°C), 95% @ 122°F (50°C)	
<b>Vibration</b>	USDA LMR Standard, Section 2.15 and MIL-STD-810G, Test Method 514.6	
<b>Drop Shock</b>	3.0 m drop to concrete (exceeds TIA-603-D)	
<b>Immersion</b>	2 m for 4 hours in accordance with MIL-STD-810G 5 m for 4 hours in accordance with IP68	
<b>Dust Resistance</b>	IP6X	
<b>Water Resistance</b>	IPX8 (5m, 4 hours)	
<b>Heat Rating</b>	NIST Class I, II, III, IV compliant 100C (212°F) 25 minutes 160C (320°F), 15 minutes 260C (500°F), 5 minutes 1700°F (926°C). <1 minute	
<b>Operating Temperature<sup>1</sup></b>	-22° to 140°F (-30° to 60°C)	
<b>Storage Temperature<sup>2</sup></b>	-40° to 176°F (-40° to 80°C)	
<b>Altitude</b>	<b>Operational</b> 15,000 ft (4,572 m)	<b>In Transit</b> 40,000 ft (12,192 m)
<b>Electrical Input Voltage</b>	7.5 VDC (nominal)	
<b>GPS/GNSS Specifications:</b>	P25 standard Tier 2 and L3Harris in-band	
<b>Channels</b>	52	
<b>Tracking Sensitivity (dBm)</b>	-166 (GPS), -163 (GLONASS)	
<b>Acquisition Sensitivity (dBm)</b>	-146 (GPS)	
<b>Cold Start w/-130 dBm input</b>	<35 seconds	
<b>Hot Start w/-130 dBm input</b>	<1 second	
<b>Safety:</b>		
<b>Hazardous Location Options</b>	Approved for use in the U.S. and Canada in Class I, Division 2 Groups A, B, C and D hazardous locations	
<b>RoHS Compliant</b>		

<sup>1</sup> Extremely low temperatures adversely affect battery life

<sup>2</sup> Store batteries at 77°F ±41°F (25°C ± 5°C)

LMR TRANSMITTER			
Frequency Bands	VHF*	UHF*	700/800 MHz
<b>Frequency Ranges (MHz)</b>	136-174	378-522	763-776, 793-806, 806-825, 851-870
<b>Rated RF Power/Talkaround (W)</b>	0.5-6	0.5-5	0.5-3
<b>Frequency Stability -22 to 140°F (-30 to +60°C)</b>	±1.0 ppm	±1.0 ppm	±1.0 ppm
<b>Modulation Limiting (kHz)</b>	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)	2.5, 4, 5 (FM)
<b>Audio Response (dB)</b>	+1/-3	+1/-3	+1/-3
<b>Spurious and Harmonics (dBc)</b>	-80 (FCC Part 90)	-80 (FCC Part 90)	-80 (FCC Part 90)
<b>FM Hum and Noise Companion Receiver (dB):</b>			
<b>@ 25 kHz</b>	-70	-60	-55
<b>@ 12.5 kHz</b>	-47	-47	-45
<b>Audio Distortion (%)</b>	<1.25	<1.25	<1.25
<b>Project 25 Modulation Fidelity (%)</b>	1.0	1.0	1.0
<b>Project 25 Adjacent Channel Power (dBc)</b>	>71	>71	>71

\*Full-spectrum multiband VHF and UHF product is compliant with applicable FCC narrowbanding mandate below 512 MHz

## SPECIFICATIONS FOR: XL EXTREME 400 PORTABLE FULL-SPECTRUM MULTIBAND RADIO

REGULATORY DATA							
Frequency Range	RF Output	Frequency Stability	FCC Type Acceptance No.	Applicable FCC Rules	Industry Canada Certification No.	Applicable Industry Canada Rules	NTIA Cert. No.
136-174 MHz	6 W	+/- 1.0 PPM	OWDTR-0164-E	22, 74, 80, 90	3636B-0164	RSS-119	SPS-217 49/1
378-522 MHz	5 W	+/- 1.0 PPM	OWDTR-0164-E	22, 74, 80, 91	3636B-0165	RSS-119	SPS-217 49/1
768-776 MHz	3 W	+/- 1.0 PPM	OWDTR-0164-E	90	3636B-0166	RSS-119	NA
798-806 MHz	3 W	+/- 1.0 PPM	OWDTR-0164-E	90	3636B-0167	RSS-119	NA
806-816 MHz	3 W	+/- 1.0 PPM	OWDTR-0164-E	90	3636B-0144	RSS-119	NA
851-861 MHz	3 W	±1.0 ppm	OWDTR-0144-E	90	3636B-0144	RSS-119	NA
851-869 MHz	3 W	+/- 1.0 PPM	OWDTR-0164-E	90	3636B-0169	RSS-119	NA
2402-2480	0.2 W	NA	OWDTR-0164-E	15	3636B-0171	RSS-119	NA
5180-5825	0.1 W	NA	OWDTR-0164-E	15	3636B-0172	RSS-119	NA

LMR RECEIVER			
Frequency Bands	VHF	UHF	700/800 MHz
Frequency Ranges (MHz):	136-174	378-522	763-776, 851-870
Channel Spacing (kHz)	25 (wideband*), 12.5 (narrowband), 6.25 equiv (TDMA P25 Phase 2)		
Frequency Stability (-30 to +60°C)	±1.0 ppm	±1.0 ppm	±1.0 ppm
Sensitivity (dBm): @ 12 dB SINAD	-122	-121	-121 (700 MHz) -120 (800 MHz)
Project 25 Reference Sensitivity (dBm): @ 5% BER	-122	-121	-120.5
Analog Selectivity (dB): @ 25 kHz	77	77	74
@ 12.5 kHz	71	70	64
Project 25 Adjacent Channel Rejection (dB)	66.2	62.2	62
Offset Channel Selectivity (dB): @ NPS PAC	NA	NA	30
Intermodulation (dB)	80	81	77
Spurious and Image Rejection (dB)	90	87	80
FM Hum and Noise (dB): @ 25 kHz	-60	-60	-55
@ 12.5 kHz	-55	-53	-50
Audio Output - RATED (W)	1.5	1.5	1.5
Audio Distortion @ Rated Power	1.1	1.1	1.1

\*Full-spectrum multiband VHF and UHF product is compliant with applicable FCC narrowbanding mandate below 512 MHz

ENVIRONMENTAL STANDARD			
Applicable Standards	Parameter	Methods	Procedure/Categories
MIL-STD-810G	Low pressure	500.5	1, 2
	High temperature	501.5	1, 2
	Low temperature	502.5	1, 2
	High Temperature Continuous TX	501.5	2
	Low Temperature Continuous TX	502.5	2
	Temperature shock	503.5	1B
	Contamination by fluids	504.1	2
	Solar radiation (240 Hours)	505.5	1 (cycling)
	Blowing Rain	506.5	1
	Dripping Water Exposure	506.5	3
	Humidity	507.5	2
	Salt fog	509.5	1
	Blowing dust and sand	510.5	1, 2
	Explosive atmosphere	511.5	1
	Immersion in water	512.5	1
	Vibration (minimum integrity)	514.6	1, Category 24
	Vibration (basic transportation)	514.6	1, Category 4
	Shock (functional/basic)	516.6	1
	Shock (transit drop)	516.6	4
	Shock (bench handling)		
IEC 60529	Dust Tight, 2 meters continuous water immersion, 4 hours		IP68
	IPX6 High Pressure Spray		
USDA LMR Standard	Vibration, U.S. Forest Service		Section 2.15

## SPECIFICATIONS FOR: XL EXTREME 400 PORTABLE FULL-SPECTRUM MULTIBAND RADIO

ENVIRONMENTAL STANDARD			
TIA-603-D Increased to 1.5 meters.	TIA/EIA 1 Meter Shock (Drop) MODIFIED		Section 3.3.5.3
UL-60950-1	Steel Ball Impact		4.2.5-6
IEC61000-4-2	Electrostatic Discharge		

BROADBAND	
LTE Protocol	3GPP Release 11, Category 12, Power Class 3 UE with support for QoS QCI
North American LTE Option	FCC ID: N7NEM75S 4G LTE Bands: B2, B4, B5, B12, B13, B14, B17, B29, B30, B66 3G Bands: B2, B5 Carrier Certification: AT&T, Verizon, Telus
International LTE Option (In selected countries)	4G LTE Bands: B1, B3, B5, B7, B8, B28 3G Bands: B1, B5, B8
Wi-Fi	802.11 b/g/n 2.4 GHz and 5 GHz; supports 24 preconfigured and 8 user configured networks
Bluetooth	Bluetooth 4.0 (128-bit encryption)
Vibration Resistance	Vibrated for 3 hours, 1" (25mm) orbital path at 250 rpm
Impact Acceleration	9.8 ft (3m) dropped 8 times
Corrosion	48-hour salt spray, 48-hour 50% humidity chamber
Display Surface Abrasion	2.2lb (1kg) load, for 200 cycles
High Temperature Functionality	500°F (260°C) for 5 minutes
Heat and Flame	203°F (95°C) for 15 minutes, 10 seconds 1742°F (950°C) direct flame
Product Label Durability	Label examination post heat and immersion test, corrosion test, high temperature test
Cable Pullout	35 lbf (156 N) force
Case Integrity	442 lb. (200 kg) compression load, 1 minute, 4 faces
Water Drainage	Water is introduced into all openings, indentations, and grills until water overflows. Speech and data logging is tested.
Tumble	3hrs, 15 RPM, Tumble Test in 46 in (117 cm) Metal Drum (2,700 total rotations)
TIA Transmit Power	Tested for carrier output and RF power output
TIA Carrier Frequency Stability	Tested for frequency stability and operating frequency accuracy
TIA Receiver Sensitivity	Tested for analog and digital reference sensitivity
Power Source Performance	Continuously operated for 8 hours on standard duty cycle 10-10-80 at max rated transmit power
Electronic Temperature Stress	Operated after temperature exposure of -4°F (-20°C) for 4 hours, and 160°F (71°C) for 4 hours
Antenna VSWR Swept Frequency	Antenna performance must be maintained after Drop/Impact, Tumble and Corrosion tests
HazLoc	Class I Division 2, Groups A, B, C, D

DIGITAL OPERATION		
Protocol	ProVoice™	P25
Vocoding Method	AMBE+2™ enhanced full rate	AMBE+2 enhanced full rate and enhanced half rate
Signaling Rate (kbps)	9.6	9.6
Modulation	GFSK	Phase 1 Tx: C4FM, Rx: C4FM and WCQPSK

ENCRYPTION	
Encryption Algorithms	Voice Encryption: Single-key AES/DES, Multiple-key AES/DES, DES-OFB, Encryption Lite (ARC4), 256-bit AES P25, 64-bit DES Control Channel Encryption: 128-bit AES (LLA)
Encryption Keys per Radio	192 Key Programmable for 96 (64 AES, 32 DES) Common Key References (CKR)
Keying	Local Key Loader, Wi-Fi, LTE and Over-The-Air Rekeying (OTAR), Motorola KVL 3000+/4000
Standards	FIPS 140-2 Level 1, FIPS 197

BATTERIES			
Type	Dimensions (H x W x D)	Weight	Capacity (mAh)
Li-Ion	3.94 x 2.52 X 1.22 in (100 x 64 x 31 mm)	7.6 oz (215.4 g)	4200

Content subject to change without notice. Product sales are subject to applicable U.S. export control laws.

XL Extreme 400P Full-spectrum Multiband Radio

© 2022 L3Harris Technologies, Inc. | 07/2022 DS688F

### Non-Export Controlled Information

L3Harris Technologies is an agile global aerospace and defense technology innovator, delivering end-to-end solutions that meet customers' mission-critical needs. The company provides advanced defense and commercial technologies across air, land, sea, space and cyber domains.



1025 W. NASA Boulevard  
Melbourne, FL 32919