

Access Control MSRP - USD

US Pricelist effective February 20, 2023

CONFIDENTIAL

The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

© 2023 Motorola Solutions. All rights reserved. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners.

Summary Of Changes

- 2022-03-07 : Effective Mar. 7, 2022, in all currencies, price increase on all Access Control Manager appliances and licensing by ~7%
- 2022-05-06 : Effective June 9, 2022, price increase in all currencies on ACM OEM LifeSafety Power ~3% to ~27%, Abloy UK ~3% to ~22%, Schlage ~8%
- 2022-05-23 : Effective July 4, 2022, price increase in all currencies on ACM OEM HID Global EasyLobby® products ~10% to ~17%
- 2021-09-22 : Effective October 31, 2021, price increase on ACM OEM Allegion/Schlage: ~3%, Elmdene: ~5%, ASSA ABLOY: ~3%, HID Easy Lobby: ~1%-14%, HID CARDS: ~1.5%, HID READERS: ~1.5%, HID pivCLASS: ~1.5%, HID Mercury: ~4.50%, LifeSafety Power: ~8% to 13%, ROLEC: ~8%
- 2022-02-21 : Effective February 21, 2022, price increase on ACM OEM Allegion/Schlage: ~5% to 8%, ASSA ABLOY: ~7% to 40%, HID Easy Lobby: ~10%, Salto ~4% to 19%, Farpointe Data ~4% to 39%
- 2022-04-14 : Effective April 14, 2022, price increase on ACM OEM HID Cards and Readers: ~1% to 14%, HID pivCLASS: ~5% to 20%, HID Mercury: ~7%, HID VertX ~4%, ACM Kits ~4%
- 2022-08-19 : Effective August 19, 2022, price increase in all currencies on ACM OEM ASSA ABLOY (Locks and accessories) ~9.5%, Farpointe Data ~6% to ~22%, Elmdene (available in the EU and UK only) ~7%
- 2021-05-05 : HID Signo Promotion Discount Off MSRP Valid Until September 30, 2021.
- 2021-05-05 : ASSA ABLOY European Aperio Manufacturer Price Increase.
- 2022-12-06 : Effective Jan. 6, 2023 price increase on all ACM Professional Appliances: 15% to 20%, ACM Enterprise Appliances: 7% to 15%, ACM Enterprise Plus Appliances: 3% to 11%, ACM Virtual Appliances: 1% to 14%, 16 Doors Expansion Software Licenses: 30% and ACM OEM HID Mercury Controllers: ~2% to 8%, HID Credentials : ~3% to 10%, HID EasyLobby: ~10% to 20%, HID Readers: ~8% to 10%, Salto: ~8.5%

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

ACM Solutions

ACM Enterprise

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-APP-128R-ENT2-6	Access Control Manager Enterprise 6 – Web-Based PACS Enterprise Appliance for 128 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 128 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 128 to 400 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 250K identities and 150M stored events and twenty (20) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	11,500.00
AC-APP-16R-ENT2-6	Access Control Manager Enterprise 6 – Web-Based PACS Enterprise Appliance for 16 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 16 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 16 to 400 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 250K identities and 150M stored events and twenty (20) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	4,300.00
AC-APP-256R-ENT2-6	Access Control Manager Enterprise 6 – Web-Based PACS Enterprise Appliance for 256 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 256 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 256 to 400 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 250K identities and 150M stored events and twenty (20) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	19,600.00
AC-APP-32R-ENT2-6	Access Control Manager Enterprise 6 – Web-Based PACS Enterprise Appliance for 32 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 32 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 32 to 400 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 250K identities and 150M stored events and twenty (20) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	5,450.00
AC-APP-64R-ENT2-6	Access Control Manager Enterprise 6 – Web-Based PACS Enterprise Appliance for 64 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 64 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 64 to 400 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 250K identities and 150M stored events and twenty (20) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	7,750.00
AC-APP-ENT2-WARR-EXTEND-1YR	1 Year Extended Warranty for Access Control Manager Enterprise Appliance	698.50
AC-APP-ENT2-WARR-EXTEND-2YR	2 Year Extended Warranty for Access Control Manager Enterprise Appliance	1,396.99

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

ACM Enterprise Plus

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-APP-1024R-ENT-PLUS-6	Access Control Manager Enterprise Plus 6 – Web-Based PACS Plus Appliance for 1024 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 1024 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 1024 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	52,400.00
AC-APP-16R-ENT-PLUS-6	Access Control Manager Enterprise Plus 6 – Web-Based PACS Plus Appliance for 16 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 16 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 16 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	13,300.00
AC-APP-2048R-ENT-PLUS-6	Access Control Manager Enterprise Plus 6 – Web-Based PACS Plus Appliance for 2048 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 2048 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity cannot be expanded Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	67,600.00
AC-APP-256R-ENT-PLUS-6	Access Control Manager Enterprise Plus 6 – Web-Based PACS Plus Appliance for 256 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 256 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 256 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	25,500.00
AC-APP-512R-ENT-PLUS-6	Access Control Manager Enterprise Plus 6 – Web-Based PACS Plus Appliance for 512 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 512 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 512 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	38,000.00
AC-APP-ENT-PLUS-WARR-EXTEND-1YR	1 Year Extended Warranty for Access Control Manager Enterprise Plus Appliance	824.01
AC-APP-ENT-PLUS-WARR-EXTEND-2YR	2 Year Extended Warranty for Access Control Manager Enterprise Plus Appliance	1,653.47

ACM Professional

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-APP-16R-PRO-6	Access Control Manager Professional 6 – Web-Based PACS Professional Appliance for 16 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 16 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total	2,100.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

reader capacity can be expanded from 16 to 32 readers with the purchase of one AC-SW-LIC-16RCU-6-P 16 Reader Count Software License | Supports up to 32 controllers, 75K identities, 75M stored transactions and ten (10) simultaneous operators (via browser) | Three (3) year appliance hardware warranty begins at date of shipment

AC-APP-32R-PRO-6	Access Control Manager Professional 6 – Web-Based PACS Professional Appliance for 32 Readers - includes: physical appliance embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 32 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity cannot be expanded Supports up to 32 controllers, 75K identities and 75M stored transactions and ten (10) simultaneous operators (via browser) Three (3) year appliance hardware warranty begins at date of shipment	3,250.00
AC-APP-PRO-WARR-EXTEND-1YR	1 Year Extended Warranty for Access Control Manager Professional Appliance	245.57
AC-APP-PRO-WARR-EXTEND-2YR	2 Year Extended Warranty for Access Control Manager Professional Appliance	491.13

ACM Virtual

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-SW-1024R-VM-6-P	Access Control Manager Virtual 6 - Web-Based PACS Virtual for 1024 Readers - includes: embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 1024 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 1024 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) VMware software is required and not included	41,000.00
AC-SW-128R-VM-6-P	Access Control Manager Virtual 6 - Web-Based PACS Virtual for 128 Readers - includes: embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 128 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 128 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) VMware software is required and not included	9,850.00
AC-SW-16R-VM-6-P	Access Control Manager Virtual 6 - Web-Based PACS Virtual for 16 Readers - includes: embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 16 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 16 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) VMware software is required and not included	3,000.00
AC-SW-2048R-VM-6-P	Access Control Manager Virtual 6 - Web-Based PACS Virtual for 2048 Readers - includes: embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 2048 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity cannot be expanded Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) VMware software is required and not included	58,750.00
AC-SW-256R-VM-6-P	Access Control Manager Virtual 6 - Web-Based PACS Virtual for 256 Readers - includes: embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 256 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 256 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) VMware software is required and not included	16,900.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-SW-32R-VM-6-P	Access Control Manager Virtual 6 - Web-Based PACS Virtual for 32 Readers - includes: embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 32 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 32 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) VMware software is required and not included	4,150.00
AC-SW-512R-VM-6-P	Access Control Manager Virtual 6 - Web-Based PACS Virtual for 512 Readers - includes: embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 512 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 512 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) VMware software is required and not included	31,300.00
AC-SW-64R-VM-6-P	Access Control Manager Virtual 6 - Web-Based PACS Virtual for 64 Readers - includes: embedded 64 bit Linux OS & Open LDAP for configuration database Access Control Manager Security Management Software 64 Reader Count Software License One (1) ACM Verify ACC Video Integration Five (5) partitions Identities CSV export, recurring, one-time, long & short format Total reader capacity can be expanded from 64 to 2048 readers, in increments of 16, with the purchase of the desired quantity of AC-SW-LIC-16RCU-6-P, 16 Reader Count Software Licenses Supports up to 512 controllers 500K identities and 150M stored events and Fifty (50) simultaneous operators (via browser) VMware software is required and not included	6,200.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

ACM Software Options

Video Integration

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-SW-LIC-EXACQ-6-P	Access Control Manager 6 License for Video Integration for Exacq (per appliance)	4,546.77
AC-SW-LIC-MILEST-6-P	Access Control Manager 6 License for Video Integration for Milestone (per appliance)	4,546.77

ACM Options

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-SW-ACM-DEMO-30D-6-P	Access Control Manager 6 License 30 Day Demonstration: includes licensing for Badging, Exacq, Milestone, one Bosch intrusion panel, ViRIDI BEManager integration, Replication, Hot Stand By Auto Failover, SQL collaboration, Oracle collaboration, LDAP collaboration, XML collaboration, REST collaboration	0.00
AC-SW-LIC-16RCU-6-P	Additional 16 Doors Expansion Software Licenses for Avigilon Access Control Manager Professional, Enterprise, Enterprise Plus & Virtual	1,180.00
AC-SW-LIC-AF-6-P	Access Control Manager 6 Hot Standby - Auto Failover Software License (per Appliance) includes AC-SW-LIC-REP-6-P; Requires duplicate licensing for failover appliance	5,457.00
AC-SW-LIC-BDGE-6-P	Badging Software Licenses for Avigilon Access Control Manager Professional, Enterprise, Enterprise Plus & Virtual	909.14
AC-SW-LIC-PART-6-P	Access Control Manager 6 Partitioning License for additional partitions (per appliance)	4,547.86
AC-SW-LIC-REP-6-P	Access Control Manager 6 Multi-Appliance Replication Software License (per appliance)	3,637.64
AC-SW-LIC-REST-6-P	Access Control Manager 6 REST Connectivity Software License (per appliance)	909.14
AC-SW-LIC-WIRELESS-LOCK-6-P	Access Control Manager 6 Wireless Lock Connectivity Software License for each wireless locks not purchased from Motorola Solutions	200.00

Collaborations

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-SW-LIC-LDAP-6-P	Access Control Manager 6 LDAP Directory Connectivity Software License (required for integration with Microsoft Active Directory or other directory products)(per appliance)	2,728.50
AC-SW-LIC-ORCL-6-P	Access Control Manager 6 Oracle Server Connectivity Software License (from Oracle DB 9i forward)(per appliance)	3,637.64
AC-SW-LIC-SQL-6-P	Access Control Manager 6 Microsoft SQL Server Connectivity Software License (from Microsoft SQL 2000 forward)(per appliance)	1,819.36
AC-SW-LIC-XML-6-P	Access Control Manager 6 XML Events Connectivity Software License (per appliance)	909.14

Hardware Licensing

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-SW-LIC-ACMEC-MIG-6-P	Access Control Manager 6 License for the migration and conversion of a single ACM Embedded Controller into an ACM Professional, Enterprise or Virtual system. One license is required for each ACM Embedded Controller to be migrated. License includes migration of Cardholders into Identities and conversion of the ACM EC into a HID VertX EVO V1000	218.28

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

controller. The ACM system does require the appropriate number of HID licensing (AC-SW-HID-RDR).

AC-SW-LIC-BOSCHINTR-10PANEL-6-P	Bosch Intrusion (10 Panel) Integration Software Licenses for Avigilon Access Control Manager 6 Professional, Enterprise, Enterprise Plus & Virtual	3,274.20
AC-SW-LIC-BOSCHINTR-1PANEL-6-P	Bosch Intrusion (1 Panel) Integration Software Licenses for Avigilon Access Control Manager 6 Professional, Enterprise, Enterprise Plus & Virtual	354.71
AC-SW-LIC-DMPINTR-10PANEL-6-P	Access Control Manager 6 for 10 panel license for DMP intrusion panel integration. Panels supported: XR150 & XR550 Command Processor Intrusion Panels	3,274.20
AC-SW-LIC-DMPINTR-1PANEL-6-P	Access Control Manager 6 per panel license (one panel) for DMP intrusion panel integration. Panels supported: XR150 & XR550 Command Processor Intrusion Panels	354.71
AC-SW-LIC-HID-VERTEX-ASM-6-P	Access Control Manager 6 NON OEM (Non Avigilon Ordered) HID VertX EVO V1000 or HID VertX EVO V2000 Assimilation License (One required per VertX EVO Controller)	545.70
AC-SW-LIC-VIRDI-BIO-6-P	ViRDI BE Manager Integration Software Licenses for Avigilon Access Control Manager 6 Professional, Enterprise, Enterprise Plus & Virtual	2,728.50

Virtual Stations

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-SW-LIC-AVO-VER-16VS-6-P	Access Control Manager 6 (ACM) Verify license for 16 virtual stations (per appliance)	909.14
AC-SW-LIC-AVO-VER-5VS-6-P	Access Control Manager 6 (ACM) Verify license for 5 virtual stations (per appliance)	327.42

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

Controller and Sub Panels

Mercury

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-MER-A-BAT23MM	LITHIUM COIN CELLS BR/CR2325, 20-pack(Mercury Part Number: A-BAT23MM)	92.77
AC-MER-A-RES-1K32	AXIAL LEADED 1K1%1/4W RESISTORS, 32-pack(Mercury Part Number: RES-1K32)	11.85
AC-MER-A-TC-MR50	CABLE FOR MR-50 TAMPER (Mercury Part Number: A-TC-MR50)	5.00
AC-MER-A-TERM5-3	Replace 3-Position Terminal Blocks, 10-pack(Mercury Part Number: A-TERM5-3)	33.37
AC-MER-A-TERM5-4	Replace 4-Position Terminal Blocks, 10-pack(Mercury Part Number: A-TERM5-4)	43.29
AC-MER-A-TERM5-5	Replace 5-Position Terminal Blocks, 10-pack(Mercury Part Number: A-TERM5-5)	55.65
AC-MER-A-TERM5-6	Replace 6-Position Terminal Blocks, 10-pack(Mercury Part Number: A-TERM5-6)	65.56
AC-MER-CON-MR16IN	16 Zone Input Monitor Module with 2 relays (Mercury Part Number: MR16in-S3)	1,088.36
AC-MER-CON-MR16OUT	16 Relay Output Control Module (Mercury Part Number: MR16out-S3)	1,088.36
AC-MER-CON-MR50	Series 3 Single Reader Interface Module: mag or wiegand, 2 inputs, 2 relays (Mercury Part Number: MR50-S3)	443.86
AC-MER-CON-MR52-S3B	HID® Mercury™ MR52-S3B Controller Serial I/O Dual Card Reader Interface, 2-Reader Interface Module - (2 reader: mag, wiegand, 4 reader OSDP, 8 inputs, 6 relays) (Mercury MR52-S3B)	880.89
AC-MER-CONT-LP1501	Intelligent Controller, Linux Based with 1 door, 2 inputs and 2 outputs, PoE+ Support, expandable up to 17 doors. (Mercury Part #: LP1501)	833.78
AC-MER-CONT-LP1502	Intelligent Controller, Linux Based with 2 doors, 8 inputs and 4 outputs, expandable up to 64 doors. (Mercury Part #: LP1502)	1,551.46
AC-MER-CONT-LP2500	Intelligent Controller, Linux Based, expandable up to 64 doors. (Mercury Part #: LP2500)	2,348.65
AC-MER-CONT-LP4502	Intelligent Controller, Linux Based with 2 doors, 8 inputs and 4 outputs, expandable up to 64 doors. (Mercury Part #: LP4502)	3,223.04
AC-MER-M5-16DO-1	Mercury M5 Bridge 16 DO, 16 Digital Output Control Module-(16 digital arrays) (1 board)(Mercury Part Number: M5-16DO-1)	671.81
AC-MER-M5-16DOR-1	Mercury M5 Bridge 16 DOR, 16 Relay Output Controller Module-(16 solid state relays) (1 board)(Mercury Part Number: M5-16DOR-1)	671.81
AC-MER-M5-20IN-1	Mercury M5 Bridge 20 IN, 20 Zone Input Monitor Module (1 board)(Mercury Part Number: M5-20IN-1)	703.81
AC-MER-M5-2K	Mercury M5 Bridge M2000 with with M5 IC, Multi-device interface panel for replacement of the Casi M2000 reader controller, includes the M5-IC as well as the 4 reader daughter board (Mercury Part Number: M5-2K)	2,399.31
AC-MER-M5-2K-BASE	Mercury M5 Bridge M2000 only, Multi-device interface panel for replacement of the Casi M2000 reader controller, does NOT include M5-IC that is sold separately (Mercury Part Number: M5-2K-BASE)	1,141.01
AC-MER-M5-2SRP-1	Mercury M5 Bridge 2SRP, Supervised Reader Interface Module-(2 Rdr, 4 Inputs, 6 Outputs) (1 board)(Mercury Part Number: M5-2SRP-1)	671.81
AC-MER-M5-8RP-1	Mercury M5 Bridge 8RP, Supervised Reader Interface Module-(8 Supervised Rdr Connections) (1 board)(Mercury Part Number: M5-8RP-1)	1,066.35
AC-MER-M5-COM-1	Mercury M5 Bridge COM, Combination Power & RS485; Communications Bridge (1 board)(Mercury Part Number: M5-COM-1)	320.65
AC-MER-M5-IC-1	Mercury M5 Bridge IC, Intelligent Controller, 32MB RAM, Ethernet, Dual RS485 ports (1 board)(Mercury Part Number: M5-IC-1)	1,375.59
AC-MER-MUX8	RS-232/485 to 8 RS-485 Channel Mux (Mercury Part Number: MUX8)	1,099.27

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

Power Supplies

LifeSafety Power

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-LSP-16DR-MER	Sixteen Door Mercury Single Voltage Integrated Power System supporting one AC-MER-CONT-2DR with Seven AC-MER-CON-MR52 (Mercury hardware sold separately). Includes painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 150 watt 12V/12A or 24V/6A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board) delivering a regulated independent power connection to Mercury boards and auxiliary equipment. The power supply features dual outputs, form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet. Cabinet size: 20" x 24" x 6.5" with door lock, tamper switch and two (2) keys. Weight 25 lb.(LifeSafety Power Part Number: FPO150-D8PE4M1)	902.83
AC-LSP-16DR-MER-LCK	Sixteen Door Mercury Dual Voltage Integrated Power System supporting one AC-MER-CONT-2DR with seven AC-MER-CON-MR52 (Mercury hardware sold separately). The advantage of a dual voltage power supply is the ability to power Mercury boards and door locks. Includes a painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws. System includes one 150 watt 12V/12A pre-wired to sixteen Class 2, Power Limited (CL2PL) outputs (two D8P Boards) delivering regulated independent power connection to each Mercury board and one 250 watt 24V/10A power supply-battery chargers pre-wired to sixteen fused output (two C8 Boards) for independent relay lock power. Both power supplies features dual outputs (12 & 24volts DC), form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Cabinet size: 20" x 24" x 6.5" with door lock and two (2) keys. Weight 26 lb.(LifeSafety Power Part Number: FPO150/250-2C82D8PE4M1)	1,516.23
AC-LSP-2DR-MER	Two Door Mercury Single Voltage Integrated Power System supporting two AC-MER-CONT-1DR or one AC-MER-CONT-2DR (Mercury hardware sold separately). Includes painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 75 watt 12V/6A or 24V/3A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board) delivering a regulated independent power connection to Mercury boards and auxiliary equipment. The power supply features dual outputs, form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet (unless using two AC-MER-CONT-1DR). Cabinet size: 12" x 14" x 4.5" with door lock, tamper switch and two (2) keys. Weight 14 lb.(LifeSafety Power Part Number: FPO75-D8PE1M)	498.50
AC-LSP-2DR-MER-LCK	Two Door Mercury Dual Voltage Integrated Power System supporting two AC-MER-CONT-1DR or one AC-MER-CONT-2DR (Mercury hardware sold separately). The advantage of a dual voltage power supply is the ability to power both Mercury boards and door locks from the same supply. Includes a painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 75 watt 12V/2A and 24V/2A power supply-battery charger. The power supply is pre-wired to four Class 2, Power Limited (CL2PL) outputs (C4P Board) delivering a regulated independent power connection to each Mercury board and lock power and control. The power supply features dual outputs (12 & 24volts DC), form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet (unless using two AC-MER-CONT-1DR). Cabinet size: 12" x 14" x 4.5" with door lock and two (2) keys. Weight 14 lb.(LifeSafety Power Part Number: FPO75-B100C4PE1M)	590.40
AC-LSP-4DR-MER	Four Door Mercury Single Voltage Integrated Power System supporting one AC-MER-CONT-2DR with one AC-MER-CON-MR52 (Mercury hardware sold separately). Includes painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 75 watt 12V/6A or 24V/3A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board)	546.75

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	delivering a regulated independent power connection to Mercury boards and auxiliary equipment. The power supply features dual outputs, form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet. Cabinet size: 16" x 20" x 4.5" with door lock, tamper switch and two (2) keys. Weight 19 lb.(LifeSafety Power Part Number: FPO75-D8PE2M)	
AC-LSP-4DR-MER-LCK	Four Door Mercury Dual Voltage Integrated Power System supporting one AC-MER-CONT-2DR with one AC-MER-CON-MR52 (Mercury hardware sold separately). The advantage of a dual voltage power supply is the ability to power both Mercury boards and door locks from the same supply. Includes a painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 75 watt 12V/2A and 24V/2A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board) delivering a regulated independent power connection to each Mercury board and four fused output (C4 Board) for independent relay lock power. The power supply features dual outputs (12 & 24volts DC), form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet. Cabinet size: 16" x 20" x 4.5" with door lock and two (2) keys. Weight 19 lb.(LifeSafety Power Part Number: FPO75-B100C4D8PE2M)	693.78
AC-LSP-8DR-MER	Eight Door Mercury Single Voltage Integrated Power System supporting one AC-MER-CONT-2DR with three AC-MER-CON-MR52 (Mercury hardware sold separately). Includes painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 75 watt 12V/6A or 24V/3A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board) delivering a regulated independent power connection to Mercury boards and auxiliary equipment. The power supply features dual outputs, form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet. Cabinet size: 20" x 24" x 6.5" with door lock, tamper switch and two (2) keys. Weight 25 lb.(LifeSafety Power Part Number: FPO75-D8PE4M)	643.24
AC-LSP-8DR-MER-LCK	Eight Door Mercury Dual Voltage Integrated Power System supporting one AC-MER-CONT-2DR with three AC-MER-CON-MR52 (Mercury hardware sold separately). The advantage of a dual voltage power supply is the ability to power both Mercury boards and door locks from the same supply. Includes a painted steel enclosure, removable pre drilled back plate, controller standoffs and mounting screws and a 150 watt 12V/4A and 24V/4A power supply-battery charger. The power supply is pre-wired to eight Class 2, Power Limited (CL2PL) outputs (D8P Board) delivering a regulated independent power connection to each Mercury board and eight fused output (C8 Board) for independent relay lock power. The power supply features dual outputs (12 & 24volts DC), form 'C' fault relay contacts, a fire alarm input and network interface (interface module sold separately) to enable monitoring, reporting and control of the power system from Access Control Manager (ACM) link. Battery space for two 12V, 8Ah batteries is available in cabinet. Cabinet size: 20" x 24" x 6.5" with door lock and two (2) keys. Weight 25 lb.(LifeSafety Power Part Number: FPO150-B100C8D8PE4M)	948.78
AC-LSP-B100	The B100 Secondary Voltage Module provides a means to easily and economically add an additional voltage to any power system. Primary power for the B100 is derived from an main FPO power supply and the B100 steps the FPO voltage down to the user defined range (typically 12VDC). B100 delivers up to 4A maximum current at 12VDC.(LifeSafety Power Part Number: B100)	80.40
AC-LSP-C4	The C4 (4 Door) Lock Control Module adds four (4) fused outputs to a FPO power supply for "buffered" lock control and is typically supplied as part of a system or purchased as an expansion piece to an existing system. The C4 provides four (4) access control inputs capable of voltage or dry contact activation and four (4) relay controlled outputs, individually fuse protected at 3A per output. (LifeSafety Power Part Number: C4)	91.89
AC-LSP-C8	The C8 (8 Door) Lock Control Module lock adds eight (8) fused outputs to a FPO power supply for "buffered" lock control and is typically supplied as part of a system or purchased as an expansion piece to an existing system. The C8 provides eight (8) access control inputs capable of voltage or dry contact activation and eight (8) relay controlled outputs, individually fuse protected at 3A per output.(LifeSafety Power Part Number: C8)	117.16
AC-LSP-CAMLOCKSET	Replacement Camlock and key (set of three) for LifeSafety Power enclosures, keyed alike (Lifesafety Power # Camlock Set)(LifeSafety Power Part Number: Camlock_Set)	25.50
AC-LSP-D8P	The D8P (8 Out) Power Distribution Module provides 8 auxiliary power outputs, each one individually protected by a solid state circuit breaker	52.84

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	(D8P) rated at 2.5A each. Each output is programmable to either of the two voltages available when used in a dual voltage power system, or to the continuous output or the resettable output of the power supply when used in a single voltage system. (LifeSafety Power Part Number: D8P)	
AC-LSP-E1M	Backplate, Standoffs & E1M size cabinet kit: Size: 12" x 14" x 4.5", Weight: 9 lb. (LifeSafety Power Part Number: E1M)	362.97
AC-LSP-E2-BOXED	LifeSafety Power E series enclosures are engineered to house FlexPower® power management boards in multiple configurations for maximum design flexibility. The modular mounting pattern on the back wall allows flexible positioning of FlexPower modules within the enclosure. E series enclosures are black powdercoated steel. All enclosures come with installed door ground strap, lockset and tamper switch. 20 x 16 x 4.5" (510 x 410 x 120 mm) 18 lbs. (8 kg). LifeSafety Part Number: E2-BOXED	268.77
AC-LSP-E2-BS1	Locking battery enclosure with one 4" battery shelf. 20x16x4.5 enclosure with pre-installed lock set and tamper switch.	330.80
AC-LSP-E2M	Backplate, Standoffs & E2M size cabinet kit: Size: 16" x 20" x 4.5", Weight: 13 lb. (LifeSafety Power Part Number: E2M)	415.81
AC-LSP-E4-3BS1	Locking battery enclosure with three 4" battery shelf. 24x20x4.5 enclosure with pre-installed lock set and tamper switch.	480.13
AC-LSP-E4M	8 Door Mercury enclosure with removable backplate Battery space for 12V or 24V, 8Ah batteries is available within the cabinet. Comes with door lock and two (2) keys. Weight: 24 lb. Size: 20" x 24" x 4.5"(LifeSafety Power Part Number: E4M)	498.54
AC-LSP-E4M1	16 Door Mercury enclosure with door mount & removable backplate. Battery space for 12V or 24V, 8Ah batteries is available within the cabinet. Comes with door lock and two (2) keys. Weight: 26 lb. Size: 20" x 24" x 4.5"(LifeSafety Power Part Number: E4M1)	705.31
AC-LSP-E4M2-BOXED	LifeSafety Power FLEXPOWER E4M2 12 Door Mercury Security® MCLASS multi-purpose enclosures offer maximum flexibility, functionality and savings to access system designers. MCLASS enclosures are engineered to house FlexPower® power management boards alongside Mercury Security™ access hardware in one compact, secure UL294 listed system.	489.31
AC-LSP-E4V	8 Door HID VertX enclosure with removable backplate *** Accommodates single voltage only *** Battery space for 12V or 24V, 8Ah batteries is available within the cabinet. Comes with door lock and two (2) keys. Weight: 24 lb. Size: 20" x 24" x 4.5"(LifeSafety Power Part Number: E4V)	574.32
AC-LSP-E4V1	8 - 16 Door HID VertX enclosure with door mount & removable backplate *** Accommodates single or dual voltage *** Battery space for 12V or 24V, 8Ah batteries is available within the cabinet. Comes with door lock and two (2) keys. Weight: 75 lb. Size: 20" x 24" x 4.5"(LifeSafety Power Part Number: E4V1)	783.35
AC-LSP-E6M-BOXED	MCLASS multi-purpose enclosures offer maximum flexibility, functionality and savings to access system designers. MCLASS enclosures are engineered to house FlexPower® power management boards alongside Mercury Security™ access panels (sold separately) in one compact, secure UL294 listed system. The E6M1 enclosures cover a door count from eight to eighteen with dual voltage distribution and network monitoring. To prevent damage to system electronics, the backplate(s) separate from the enclosure for access hardware mounting in the shop while wiring is pulled to the enclosure at the job site. Once configured, the backplate can be remounted for final ties and checkout.	1,029.18
AC-LSP-E6M1-BOXED	MCLASS multi-purpose enclosures offer maximum flexibility, functionality and savings to access system designers. MCLASS enclosures are engineered to house FlexPower® power management boards alongside Mercury Security™ access panels (sold separately) in one compact, secure UL294 listed system. The E6M1 enclosures cover a door count from four to eight with dual voltage distribution and network monitoring. To prevent damage to system electronics, the backplate(s) separate from the enclosure for access hardware mounting in the shop while wiring is pulled to the enclosure at the job site. Once configured, the backplate can be remounted for final ties and checkout.	1,265.82
AC-LSP-E8M-BOXED	MCLASS multi-purpose enclosures offer maximum flexibility, functionality and savings to access system designers. MCLASS enclosures are engineered to house FlexPower® power management boards alongside Mercury Security® access panels (sold separately) in one compact, secure system. The E8M can be configured for a maximum of twelve doors with dual voltage distribution.	1,242.83
AC-LSP-E8M2-BOXED	LifeSafety Power FLEXPOWER E8M2 16 Door Mercury Security® MCLASS multi-purpose enclosures offer maximum flexibility, functionality and savings to access system designers. MCLASS enclosures are engineered to house FlexPower® power management boards alongside Mercury Security® access panels in one compact, secure system. The E8M2 can be configured for a maximum of sixteen doors with dual voltage	1,366.88

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	distribution.To prevent damage to system electronics, the backplates separate from the enclosure for access hardware mounting in the shop while wiring is pulled to the enclosure at the job site. Once configured, the backplates can be remounted for final ties and checkout.	
AC-LSP-EPLT-1M	LifeSafety Power - FLEXPOWER EPLT-1M - Mercury Expansion Plate for MCLASS- Mercury/LSP board addition.	62.03
AC-LSP-F8	The F8 module provides 8 protected outputs, each output programmable to enable voltage on activation of the fire alarm interface (FAI), disable voltage on FAI or provide a constant output voltage ATM style fuse: 3A/per output	62.03
AC-LSP-F8P	The F8P module provides 8 protected outputs, each output programmable to enable voltage on activation of the fire alarm interface (FAI), disable voltage on FAI or provide a constant output voltage Solid state circuit breaker: 2.5A/per output Class 2 power limited	62.03
AC-LSP-FPO150	150W-12/24VDC PS, Backplate, Standoffs, & E4M size cabinet kit: The FlexPower AC-LSP-FPO150 (FPO150-2D8E4M1) is an offline switchmode power supply battery charger system. The unit is user selectable for 12 or 24VDC. Providing two independent outputs, the first output provides continuous output power for system use and the second is programmable for either fail-safe or fail-secure operation, activated when the fire alarm disconnect is initiated. Also providing 16 auxiliary power distributed outputs, the unit has provisions for mounting a variety of Mercury boards in the cabinet proper (E4M) and cabinet door (EM1). The unit is configured in painted, steel, locking enclosure with tamper switch and integral battery space. Size: 20" x 24" x 4.5", Weight: 21 lb. (LifeSafety Power Part Number: FPO150-2D8E4M1)	951.07
AC-LSP-FPO150-8DR-DV	8 Door Access/Dual Voltage 150W PS/C , 12VDC@4A and 24VDC@4A System Features: One battery set supports all voltages, microprocessor battery charging, 80Ah charge capability, continuous and switched DC outputs, eight 12 or 24VDC auxiliary outputs fused at 3A (Class 2 power limited version also available), fire alarm input (FAI), eight opto isolated, NO/NC, access control inputs, eight relay lock control outputs, programmable for either 12 or 24VDC, failsafe or failsecure, and FAI, fault detection reporting with delay, system can be web-managed (w/ NetLink module), 120V/230VAC, locking enclosure: 16" X 20" X 4.5", ten year warranty, US/Canada agency listed for access, security, fire, CCTV, mass notification (LifeSafety Power Part Number: FPO150-B100C8D8E2)	742.01
AC-LSP-FPO150-8DR-SV	8 Door Access/Single Voltage 150W PS/C , 12VDC@12A or 24VDC@6A System Features: 80Ah charge capability, microprocessor battery charging, charger software algorithm minimizes effects of deep battery discharge, continuous and switched DC outputs, eight 12 or 24VDC auxiliary outputs fused at 3A (Class 2 power limited version also available), fire alarm input (FAI), eight opto isolated, NO/NC, access control inputs, eight relay lock control outputs, programmable for either 12 or 24VDC, failsafe or failsecure, and FAI, fault detection reporting with delay, system can be web-managed (w/ NetLink module), 120V/230VAC, locking enclosure: 16" X 20" X 4.5", ten year warranty, US/Canada agency listed for access, security, fire, CCTV, mass notification (LifeSafety Power Part Number: FPO150-C8D8E2)	670.81
AC-LSP-FPO150-B1002D8PM8NL4E4M/T8-C	LifeSafety Power, Mercury 8DR, ProWire, Tie Wrap Cable Management, Networked, 170W dual voltage, 120/230VAC Input access power system.	2,235.24
AC-LSP-FPO150-B100C82D8PE4M-T8-A	150W power supply, 12A/12V or 6A/24V 12V secondary voltage power module. Adjustable 5-18V output @ 4A max, class 2 power limited 8 relay lock control outputs fused at 3A per output, each output selectable for FAI, failsafe, failsecure 16 DC auxiliary outputs class 2 power limited at 2.5A per output, each output selectable for Bus1 or Bus2 E4 enclosure size 24H x 20W x 4.5D with Mercury back plate, Prewired, Tiewrap, 8 doors, Mercury MR52 / LP1502 board(s) (LifeSafety Power Part Number: FPO150-B100C82D8PE4M/T8-A)	1,699.98
AC-LSP-FPO150-B100C8D8E4-4SL1	LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0, CU4200, or CU4EB8 Modules (sold separately) in one compact and secure UL Listed solution. This unit is a 150W 12V and 24V DC dual voltage access power system. The C8 lock control module provides eight access control inputs capable of voltage or dry contact activation, and eight fused outputs programmable for failsafe / failsecure operation at either 12 or 24 VDC and controlled by the integrated fire alarm interface circuit on the FPO. One D8 module provides eight fused outputs and each output is configurable for 12 or 24VDC operation. SALTO access enclosures are painted steel with four removable controller backplates and include lock, two (2) keys and tamper switch. Size: 24.00H x 20.00W x 6.50D in. (61.00 x 50.00 x 17.50 cm) Weight: 38 lbs., Pre-installed brackets for four (4) SALTO controllers - CU42E0, CU4200, CU4EB8	974.05
AC-LSP-FPO150-B100C8P2D8PE4M-T8-A	LifeSafety Power AC-LSP-FPO150-B100C8P2D8PE4M-T8-A , Mercury ProWire Power Systems, 150W Dual Voltage, 120 VAC, 8 Lock Outputs / 16 Auxiliary Outputs, Size: 24.0H x 20.0W x 6.5D in (60.96 x 50.8 x 16.51 cm), 8 Doors, TieWrap, Prewired for one LP1502 and three MR52 boards, 31.50 lbs (14.29kg)	1,699.98

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-LSP-FPO150-B100D8M8NL4E4-4SL1	LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0, CU4200, or CU4EB8 Modules (sold separately) in one compact and secure UL Listed solution. This unit is a 12V and 24V DC dual voltage network managed access power system. One M8 managed control module provides eight access control inputs capable of voltage or dry contact activation, and eight outputs programmable for failsafe / failsecure operation at either 12 or 24 VDC and controlled by the integrated fire alarm interface circuit on the FPO. All inputs / outputs are software controlled for remote operation. One D8 module provides eight fused outputs and each output is configurable for 12 or 24VDC operation. SALTO access enclosures are painted steel with four removable controller backplates and include lock, two (2) keys and tamper switch. Size: 24.00H x 20.00W x 6.50D in. (61.00 x 50.00 x 17.50 cm) Weight: 38 lbs., Pre-installed brackets for four (4) SALTO controllers - CU42E0, CU4200, CU4EB8	1,552.95
AC-LSP-FPO150-B100D8PM8NL4E4M	Power supply board 150W, 12A/12V or 6A/24V Secondary voltage power supply, 5-18V adjustable @ 4A max, class 2 power limited output 8 auxiliary DC outputs class 2 power limited at 2.5A per output Eight output smart distribution module, fused at 3A per output Four port network monitoring module Enclosure, Size 24. (20W x 24H x 4.5D) with backplate which can hold up to four Mercury boards. Battery space available in front of Mercury boards.	1,477.30
AC-LSP-FPO150-B100D8PM8NL4E6M	Power supply board 150W, 4A/12V or 4A/24V Secondary voltage power supply, 5-18V adjustable @ 4A max, class 2 power limited output Eight output smart distribution module, fused at 3A per output Four port network monitoring module Enclosure, Size 30W x 23H x 6.5D with Mercury backplate (Lifesafety Power Part #: FPO150-B100D8PM8NL4E6M)	1,987.29
AC-LSP-FPO150-PS	The FPO150 150W Power Supply Board is a high efficiency, off-line switchmode power supply-battery charger designed as a general purpose power supply to provide uninterrupted power for locks, auxiliary equipment and access controllers. Capable of providing two power outputs and featuring user selectability for 12 or 24 VDC, the unit provides multiple outputs, fire alarm interface, AC fault reporting, system faultreporting, form 'C' fault relay contacts and a host of features and functions designed to support the access control industry.(LifeSafety Power Part Number: FPO150)	381.35
AC-LSP-FPO150/150-16DR-DV	16 Door Access/Dual Voltage 300W PS/C, 12VDC@12A and 24VDC@6A System Features: 80Ah charge capability, microprocessor battery charging, charger software algorithm minimizes effects of deep battery discharge, continuous and switched DC outputs, sixteen 12 or 24VDC auxiliary outputs fused at 3A (Class 2 power limited version also available), fire alarm input (FAI), sixteen opto isolated, NO/NC, access control inputs, sixteen relay lock control outputs, programmable for either 12 or 24VDC, failsafe or failsecure, and FAI, fault detection reporting with delay, system can be web-managed (w/ NetLink module), 120V/230VAC, locking enclosure, 20" X 24" X 4.5", ten year warranty, US/Canada agency listed for access, security, fire, CCTV, mass notification (LifeSafety Power Part Number: FPO150/150-2C82D8E4)	1,178.49
AC-LSP-FPO150/250-2D82M8NL4E6M1	LifeSafety Power Mercury Unified Unified Power Systems, 400W Dual Voltage, 120 VAC, 16 Managed / 16 Auxiliary Outputs	2,798.07
AC-LSP-FPO150/250-2D8P2M8NL4E4M1	Power supply board 150W, 12A/12V or 6A/24V Power supply board 250W, 20A/12V or 10A/24V 16 auxiliary DC outputs class 2 power limited at 2.5A per output Eight output smart distribution module, fused at 3A per output Eight output smart distribution module, fused at 3A per output Four port network monitoring module Enclosure 20W x 24H x 4.5D with backplate and door mount which can hold up to eight Mercury boards. Requires separate enclosure for batteries.	2,184.67
AC-LSP-FPO150/250-2D8P2M8NL4E6M1	Power supply board 150W, 12A/12V or 6A/24V Power supply board 250W, 20A/12V or 10A/24V 16 auxiliary DC outputs class 2 power limited at 2.5A per output Eight output smart distribution module, fused at 3A per output Eight output smart distribution module, fused at 3A per output Four port network monitoring module Enclosure 30W x 23H x 6.5D with Mercury backplate and door mount option (Lifesafety Power Part #: FPO150/250-2D8P2M8NL4E6M1)	2,797.97
AC-LSP-FPO150/250-2D8P2M8NL4E8M2	Power supply board 150W, 12A/12V or 6A/24V Power supply board 250W, 20A/12V or 10A/24V 16 auxiliary DC outputs class 2 power limited at 2.5A per output 16 output smart distribution module, fused at 3A per output Four port network monitoring module Enclosure 30W x 36H x 4.5D with backplate which can hold up to eight Mercury boards. Battery space available.	3,012.00
AC-LSP-FPO150/250-3D8P2M8NL4E4M1/T16-A	LifeSafety Power, Mercury 16DR, ProWire, Tie Wrap Cable Management, Networked, 452W dual voltage, 120/230VAC Input access power system.	3,723.87
AC-LSP-FPO150/250-3D8P2M8NL4E4M1/T16-C	LifeSafety Power, Mercury 16DR, ProWire, Tie Wrap Cable Management, Networked, 452W dual voltage, 120/230VAC Input access power system.	3,723.87
AC-LSP-FPO150/250-3D8P2M8NL4E8M2/P16-B		4,688.72

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	LifeSafety Power ProWire 16 Door Panduit Unified Power wall mount dual voltage access power system, precision wired for MERCURY controllers (sold separately). ProWire enables the specification and installation of standardized access power equipment across an enterprise for uniform operation, maintenance and servicing.	
AC-LSP-FPO150-B100-2D8PM8NL4E4M1-P8-A	150W power supply, 12A/12V or 6A/24V 12V secondary voltage power module. Adjustable 5-18V output @ 4A max, class 2 power limited 16 DC auxiliary outputs class 2 power limited at 2.5A per output, each output selectable for Bus1 or Bus2 8 out managed distribution module, fused at 3A per output Four port network monitoring module E4 enclosure size 24H x 20W x 4.5D with Mercury back plate and door mount kit, Panduit, 8 Doors, Mercury LP1502/MR52 board(s) (LifeSafety Power AC-LSP-FPO150-B100C8P2D8PE4M-T8-A)	2,657.94
AC-LSP-FPO250	The FPO250 250W Power Supply Board is a high efficiency, off-line switchmode power supply-battery charger designed as a general purpose power supply to provide uninterrupted power for locks, auxiliary equipment and access controllers. Capable of providing two power outputs and featuring user selectability for 12 or 24 VDC, the unit provides multiple outputs, fire alarm interface, AC fault reporting, system faultreporting, form 'C' fault relay contacts and a host of features and functions designed to support the access control industry.(LifeSafety Power Part Number: FPO250)	477.82
AC-LSP-FPO250-16DR-SV	16 Door Access/Single Voltage 250W PS/C, 12VDC@20A or 24VDC@10A System Features: 80Ah charge capability, microprocessor battery charging, charger software algorithm minimizes effects of deep battery discharge, continuous and switched DC outputs, sixteen 12 or 24VDC auxiliary outputs fused at 3A (Class 2 power limited version also available), fire alarm input (FAI), sixteen opto isolated, NO/NC, access control inputs, sixteen relay lock control outputs, programmable for either 12 or 24VDC, failsafe or failsecure, and FAI, fault detection reporting with delay, system can be web-managed (w/ NetLink module), 120V/230VAC, locking enclosure, 20" X 24" X 4.5", ten year warranty, US/Canada agency listed for access, security, fire, CCTV, mass notification (LifeSafety Power Part Number: FPO250-2C82D8E4)	992.42
AC-LSP-FPO250-2M8PNL4E4M	LifeSafety Power Mercury Unified Power Systems, 250W Single Voltage, 120 VAC, for 8 Doors	1,686.19
AC-LSP-FPO250-B100D8PM8NL4E6M	250W power supply, 20A/12V or 10A/24V 12V secondary voltage power module. Adjustable 5-18V output @ 4A max, class 2 power limited 8 DC auxiliary outputs class 2 power limited at 2.5A per output, each output selectable for Bus1 or Bus2 8 out managed distribution module, fused at 3A per output Four port network monitoring module E6 enclosure size 30H x 23W x 6.5D with Mercury back plate. (LifeSafety Power Part Number: FPO250-B100D8PM8NL4E6M)	2,049.16
AC-LSP-FPO250-M8PNL4E4M-NU02	LifeSafety Power Mercury Unified Unified Power Systems, 250W NETWORKED / 12/24VDC / 8 Doors, 8 Managed Outputs	1,318.63
AC-LSP-FPO250/250-16DR-DV	16 Door Access/Dual Voltage 500W PS/C, 12VDC@20A and 24VDC@10A System Features: 80Ah charge capability, microprocessor battery charging, charger software algorithm minimizes effects of deep battery discharge, continuous and switched DC outputs, sixteen 12 or 24VDC auxiliary outputs fused at 3A (Class 2 power limited version also available), fire alarm input (FAI), sixteen opto isolated, NO/NC, access control inputs, sixteen relay lock control outputs, programmable for either 12 or 24VDC, failsafe or failsecure, and FAI, fault detection reporting with delay, system can be web-managed (w/ NetLink module), 120V/230VAC, locking enclosure, 20" X 24" X 4.5", ten year warranty, US/Canada agency listed for access, security, fire, CCTV, mass notification (LifeSafety Power Part Number: FPO250/250-2C82D8E4)	1,325.53
AC-LSP-FPO250/250-3C85D8PE12M/T24-A	LifeSafety Power, Mercury 24DR, ProWire, Tie Wrap Cable Management, Networked, 564W dual voltage, 120/230VAC Input access power system.	8,063.41
AC-LSP-FPO250/250-4M8PNLXE8M2-NU01	LifeSafety Power MCLASS™ WIRED UNIFIED POWER SYSTEM, NETWORKED 500W / 12 & 24VDC / 16 Doors, 32 Managed Outputs	3,034.69
AC-LSP-FPO250/250-5M8NLXE8M2/P16-A	LifeSafety Power FPO250/250-5M8NLXE8M2/P16-A Mercury ProWire Power System, 500W Dual Voltage, 120VAC, 40 network managed fused outputs, 16 Doors, Panduit, Prewired for one LP1502 and seven MR52 boards, Enclosure Size: 36.0H x 30.0W x 6.5D in (91.44 x 76.2 x 16.51 cm) System Weight 61.90 lbs (28.08kg)	5,711.00
AC-LSP-FPO250/250-NLXE4M	LifeSafety Power - Mercury Unified Power Systems - 500W Dual Voltage, 120 VAC	1,918.22
AC-LSP-FPO250/250-NLXE8M2	Mercury Unified Power System combine FlexPower modules alongside preview access control hardware in one compact and secure UL listed solution. ProWire system are prewired for power to the access control modules, faults, tamper switch, lock control wiring (where applicable) and communication.	2,715.87
AC-LSP-FPO75	The FPO75 75W Power Supply Board is a high efficiency, off-line switchmode power supply-battery charger designed as a general purpose	232.02

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	power supply to provide uninterrupted power for locks, auxiliary equipment and access controllers. Capable of providing two power outputs and featuring user selectability for 12 or 24 VDC, the unit provides multiple outputs, fire alarm interface, AC fault reporting, system faultreporting, form 'C' fault relay contacts and a host of features and functions designed to support the access control industry.(LifeSafety Power Part Number: FPO75)	
AC-LSP-FPO75-2D8E2-5SL1	LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0, CU4200, or CU4EB8 Modules (sold separately) in one compact and secure UL Listed solution. This unit is a 75W 12V DC single voltage access power system. Two D8 modules provides sixteen fused protected outputs. SALTO access enclosures are painted steel with five removable controller backplates and include lock, two (2) keys and tamper switch. Size: 20.00H x 16.00W x 4.50D in. (50.00 x 40.00 x 11.50 cm) Weight: 18 lbs., Pre-installed brackets for five (5) SALTO controllers - CU42E0, CU4200, CU4EB8	657.02
AC-LSP-FPO75-2E2M	One (1) 75W-12/24VDC PS, Backplate, Standoffs; & two (2) E2M size cabinets kit: The FlexPower FPO75-2E2M is an offline switchmode 75 watt power supply-battery charger specifically designed for the lifesafety industry. Capable of providing two power outputs, user selectable for 12 or 24 VDC, the unit is configured in a painted-steel, locking enclosure with tamper switch and integral battery space. One output provides continuous output power for system use, the second is programmable for either fail-safe or fail-secure operation, activated when the fire alarm disconnect is initiated. Size: 16" x 20" x 4.5", Weight: 13 lb. (LifeSafety Power Part Number: FPO75-2E2BP2)	895.96
AC-LSP-FPO75-4DR-SV	4 Door Access/Single Voltage 75W PS/C, 12VDC@4A or 24VDC@2A System Features: 40Ah charge capability, microprocessor battery charging, charger software algorithm minimizes effects of deep battery discharge, continuous and switched DC outputs, fire alarm input (FAI), four opto isolated, NO/NC, access control inputs, four relay lock control outputs, failsafe or failsecure, and FAI – each output fused for 3A (Class 2 power limited version also available). Fault detection reporting with delay, system can be web-managed (w/ NetLink module), 120V/230VAC, locking enclosure: 12" X 14" X 4.5", ten year warranty, US/Canada agency listed for access, security, fire, CCTV, mass notification (LifeSafety Power Part Number: FPO75-C4E1)	427.29
AC-LSP-FPO75-B100C4E1-2SL1	LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0, CU4200, or CU4EB8 Modules (sold separately) in one compact and secure UL Listed solution. This unit is a 75W 12V and 24V DC dual voltage access power system. The C4 lock control module provides four access control inputs capable of voltage or dry contact activation, and four fused outputs programmable for failsafe / failsecure operation at either 12 or 24 VDC and controlled by the integrated fire alarm interface circuit on the FPO. Salto access enclosures are painted steel with two removable controller backplates and include lock, two (2) keys and tamper switch. Size: 14.00H x 12.00W x 4.50D in. (35.00 x 31.00 x 11.50 cm) Weight: 14 lbs, Pre-installed brackets mount for two (2) Salto modules - CU42E0, CU4200, CU4EB8.	565.13
AC-LSP-FPO75-B100C8D8E2-3SL1	LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0, CU4200, or CU4EB8 Modules (sold separately) in one compact and secure UL Listed solution. This unit is a 75W 12V and 24V DC dual voltage access power system. The C8 lock control module provides eight access control inputs capable of voltage or dry contact activation, and eight fused outputs programmable for failsafe / failsecure operation at either 12 or 24 VDC and controlled by the integrated fire alarm interface circuit on the FPO. One D8 module provides eight fused outputs and each output is configurable for 12 or 24VDC operation. SALTO access enclosures are painted steel with three removable controller backplates and include lock, two (2) keys and tamper switch. Size: 20.00H x 16.00W x 4.50D in. (50.00 x 40.00 x 11.50 cm) Weight: 18 lbs., Pre-installed brackets for three (3) SALTO modules - CU42E0, CU4200, CU4EB8	735.12
AC-LSP-FPO75-B100M8NL4E2M	Power supply board 75W, 6A/12V or 3A/24V Secondary voltage power supply, 5-18V adjustable @ 4A max, class 2 power limited output Eight output smart distribution module, fused at 3A per output Four port network monitoring module Enclosure, Size 18. (16W x 20H x 4.5D) with backplate which can hold up to two Mercury boards. Battery space available.	1,185.45
AC-LSP-FPO75-D8E1-2SL1	LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0, CU4200, or CU4EB8 Modules (sold separately) in one compact and secure UL Listed solution. This unit is a 75W 12V DC single voltage access power system. One D8 module provides eight fused protected outputs. SALTO access enclosures are painted steel with two removable controller backplates and include lock, two (2) keys and tamper switch. Size: 20.00H x 16.00W x 4.50D in. (50.00 x 40.00 x 11.50 cm) Weight: 18 lbs., Pre-installed brackets mount for two (2) Salto modules - CU42E0, CU4200, CU4EB8	454.86
AC-LSP-FPO75-D8E2-4SL1		595.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	LifeSafety Power SALTO Unified Power Systems combine FlexPower® power modules alongside Salto CU42E0, CU4200, or CU4EB8 Modules (sold separately) in one compact and secure UL Listed solution. This unit is a 75W 12V DC single voltage access power system. One D8 module provides eight fused protected outputs. SALTO access enclosures are painted steel with four removable controller backplates and include lock, two (2) keys and tamper switch. Size: 20.00H x 16.00W x 4.50D in. (50.00 x 40.00 x 11.50 cm) Weight: 18 lbs., Pre-installed brackets for (4) SALTO controllers - CU42E0, CU4200, CU4EB8	
AC-LSP-FPO75-E1M	75W-12/24VDC PS, Backplate, Standoffs, & E1 size cabinet kit: The FlexPower FPO75-E1M is an offline switchmode power supply-battery charger specifically designed for the lifesafety industry. Capable of providing two power outputs, user selectable for 12 or 24 VDC, the unit is configured in a painted-steel, locking enclosure with tamper switch and integral battery space. One output provides continuous output power for system use, the second is programmable for either fail-safe or fail-secure operation, activated when the fire alarm disconnect is initiated. Size: 12" x 14" x 4.5", Weight: 9 lb. (LifeSafety Power Part Number: FPO75-E1BP1)	415.82
AC-LSP-FPO75-E2M	75W-12/24VDC PS, Backplate, Standoffs & E2 size cabinet kit: The FlexPower FPO75-E2M is an offline switchmode 75 watt power supply-battery charger specifically designed for the lifesafety industry. Capable of providing two power outputs, user selectable for 12 or 24 VDC, the unit is configured in a painted-steel, locking enclosure with tamper switch and integral battery space. One output provides continuous output power for system use, the second is programmable for either fail-safe or fail-secure operation, activated when the fire alarm disconnect is initiated. Size: 16" x 20" x 4.5", Weight: 13 lb. (LifeSafety Power Part Number: FPO75-E2BP2)	493.92
AC-LSP-FPO75/150-D8M8NL4E4M1	LifeSafety Power Mercury Unified Unified Power Systems, 225W Dual Voltage, 120 VAC, 8 Managed / 8 Auxiliary Outputs	1,670.11
AC-LSP-FPO75/75-8DR-DV	8 Door Access/Dual Voltage 150W PS/C , 12VDC@6A and 24VDC@3A System Features: 40Ah charge capability, microprocessor battery charging, charger software algorithm minimizes effects of deep battery discharge, continuous and switched DC outputs, eight 12 or 24VDC auxiliary outputs fused at 3A (Class 2 power limited version also available), fire alarm input (FAI), eight opto isolated, NO/NC, access control inputs, eight relay lock control outputs, programmable for either 12 or 24VDC, failsafe or failsecure, and FAI, fault detection reporting with delay, system can be web-managed (w/ NetLink module), 120V/230VAC, locking enclosure: 16" X 20" X 4.5", ten year warranty, US/Canada agency listed for access, security, fire, CCTV, mass notification (LifeSafety Power Part Number: FPO75/75-C8D8E2)	700.67
AC-LSP-M8	The M8 smart power controller communicates with the NL4 network module and provides eight (8) monitored and controlled relay outputs accessible from a network or internet. The M8 provides eight (8) control INPUTS capable of voltage or dry contact activation and eight (8) controlled and monitored OUTPUTS, with each output network programmable for fail-safe, fail-secure, fire alarm over ride, and AC loss over ride for egress lock control. (LifeSafety Power Part Number: M8)	296.36
AC-LSP-MSM25	LifeSafety Power MSM-Enterprise, Multi-Site Power Manager for Access Installations, Server Application / Web Browser Based	659.32
AC-LSP-NL2	The NL2 Network Communication Module communicates and controls power status over a local or wide area network to Access Control Manager (ACM). Provides two SPI ports for connection of one or two power supplies to enable monitoring, reporting and control of the power system. Enables remote testing of one battery set (12 or 24VDC). Recommended for use with single voltage systems or dual voltage systems using B100 12V module.(LifeSafety Power Part Number: NL2)	298.65
AC-LSP-NL4	The NL4 Network Communication Module communicates and controls power status over a local or wide area network to Access Control Manager (ACM). Provides four SPI ports for connection of one or two power supplies to enable monitoring, reporting and control of the power system. Enables remote testing of two battery sets (12 and 24VDC). Recommended for use with dual voltage systems requiring independent FPO power supplies (i.e. sixteen door dual voltage systems).(LifeSafety Power Part Number: NL4)	454.84
AC-LSP-NLX-BOXED	LifeSafety Power NETLINK™ NLX module is part of LifeSafety Power's Flex-Power® modular power management system for security and life safety applications.	836.21
AC-LSP-OSE-16DR-MER	16 Door Mercury Over Sized Enclosure (OSE) with door mount & removable backplate. Enclosure holds a total of 10 boards - 8 mercury panels and two (2) I/O modules, 6 placed in the main box and 4 on the door. This enclosure has two D8P auxiliary distribution modules for 16 class II power limited outputs. Battery space for 12V or 24V, 8Ah batteries is available. Enclosure comes standard with installed AC on/off switch, a low battery disconnect module and dual door lock key sets. Enclosure weight: 77 lb. Size: 36" x 30" x 4.5". CE approved. UL/CUL listed with Mercury panels installed.	1,762.05

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-LSP-OSE-16DR-MER-IO	16 Door 12 or 24 VDC Mercury Over Sized Enclosure (OSE) with door mount & removable backplate. 150W power supply for system power and 250W power supply for lock power. Enclosure holds a total of 10 boards - 8 mercury panels and two (2) I/O modules, 6 placed in the main box and 4 on the door. Enclosure has two C8 lock control modules for 16 distributed lock outputs and two D8P auxiliary distribution modules for 16 class II power limited outputs. Battery space for 12V or 24V, 8Ah batteries is available. Enclosure comes standard with installed AC on/off switch, a low battery disconnect module and dual door lock key sets. Enclosure weight: 77 lb. Size: 36" x 30" x 6.5". CE approved. UL/CUL listed with Mercury panels installed. (LifeSafety Power Part Number: FPO150-2D8PE8M1)	1,897.61
AC-LSP-OSE-16DR-MER-LCK	16 Door Mercury Over Sized Enclosure (OSE) with removable backplate. Enclosure holds a total of 8 mercury panel boards and two D8P auxiliary distribution modules for 16 class II power limited outputs. Battery space for 12V or 24V, 8Ah batteries is available. Enclosure comes standard with installed AC on/off switch, a low battery disconnect module and dual door lock key sets. Enclosure weight: 75 lb. Size: 36" x 30" x 4.5". CE approved. UL/CUL listed with Mercury panels installed.	2,336.36
AC-LSP-OSE-16DR-MER-LCK-IO	16 Door Dual Voltage Mercury Over Sized Enclosure (OSE) with removable backplate. 150W power supply for system power and 250W power supply for lock power. Enclosure holds a total of 8 Mercury boards, two C8 lock control modules for 16 distributed lock outputs and two D8P auxiliary distribution modules for 16 class II power limited outputs. Battery space for 12V or 24V, 8Ah batteries is available. Enclosure comes standard with installed AC on/off switch, a low battery disconnect module and dual door lock key sets. Enclosure weight: 75 lb. Size: 36" x 30" x 4.5". CE approved. UL/CUL listed with Mercury panels installed.	2,460.43
AC-LSP-PS-MCLASS-E5M	E5 enclosure size 8.5W x 11H x 3D with Mercury/LNL hole mount pattern Fits up to Mercury 1501 or Mr51e Controllers(LifeSafety Power Part Number: E5M)	124.05
AC-LSP-RACK-MOUNT-MERC-RGM75-D8PNZ	75W 12V/6A or 24V/3A UL listed 4DR Mercury rack mount, networked, 12/24V 8 class 2 power limited outputs fused at 2.5A/ea. Fits (2) MR52 sized Mercury controllers, Standard 2U EIA, 19" rack mount chassis, UL/CUL listed system / z wire mgmt cable arm(LifeSafety Power Part Number: RGM75-D8PNZ)	1,506.95
AC-LSP-RACK-MOUNT-MERC-RGM75-D8PZ	75W 12V/6A or 24V/3A UL listed 4DR Mercury rack mount, 12/24V 8 class 2 power limited outputs fused at 2.5A/ea. Fits (2) MR52 sized Mercury controllers, Standard 2U EIA, 19" rack mount chassis, UL/CUL listed system / z wire mgmt cable arm(LifeSafety Power Part Number: RGM75-D8PZ)	1,189.96
AC-LSP-RACK-MOUNT-MERC-RGM75-M8PNZ	75W 12V/6A or 24V/3A UL listed 4DR Mercury rack mount, networked 12/24V 8 managed class 2 power limited outputs fused at 2.5A/ea. Fits (2) MR52 sized Mercury controllers, Standard 2U EIA, 19" rack mount chassis, UL/CUL listed system / z wire mgmt cable arm(LifeSafety Power Part Number: RGM75-M8PNZ)	1,803.29
AC-LSP-RACK-MOUNT-MERC-RGM75B-C4PNZ	75W 12V/2A and 24V/2A UL listed Dual Voltage 12 & 24VDC 12 & 24VDC: 4DR Mercury rack mount, 4 class 2 power limited outputs fused at 2.5A/ea. Fits (2) MR52 sized Mercury controllers, Standard 2U EIA, 19" rack mount chassis, UL/CUL listed system / z wire mgmt cable arm(LifeSafety Power Part Number: RGM75B-C4PNZ)	1,670.06
AC-LSP-RACK-MOUNT-MERC-RGM75B-C4PZ	75W 12V/2A and 24V/2A UL listed Dual Voltage 12 & 24VDC 12 & 24VDC: 4DR Mercury rack mount, 4 class 2 power limited outputs fused at 2.5A/ea. Fits (2) MR52 sized Mercury controllers, Standard 2U EIA, 19" rack mount chassis, UL/CUL listed system / z wire mgmt cable arm(LifeSafety Power Part Number: RGM75B-C4PZ)	1,286.42
AC-LSP-RACK-MOUNT-MERC-RGM75B-M8PNZ	75W 12V/2A and 24V/2A UL listed Dual Voltage 12 & 24VDC 12 & 24VDC: 4DR Mercury rack mount, 8 class 2 power limited outputs fused at 2.5A/ea. Fits (2) MR52 sized Mercury controllers, Standard 2U EIA, 19" rack mount chassis, UL/CUL listed system / z wire mgmt cable arm(LifeSafety Power Part Number: RGM75B-M8PNZ)	1,860.72
AC-LSP-RACK-MOUNT-RGM75B-M8PNZ1	75W power supply, 6A/12V or 3A/24V, 12V secondary voltage power module. Adjustable 5-18V output @ 4A max, class 2 power limited, 8 out managed distribution module, class 2 pwr ltd at 2.5A per output, Four port network monitoring module, Single FPO with Dual B100 Buss/Flex Cable Kit 5	2,441.99
AC-LSP-RM-BAT-RBE	RBE rackmount battery enclosure for 7-8Ah batteries, Standard 2U EIA, 19" rack mount chassis(LifeSafety Power Part Number: RBE)	521.52
AC-LSP-SDU	LifeSafety Power OneDrop™ SDU (Single Drop USB) adapter allows a single IP connection to be used in Mercury applications when using a LSP Netlink network communication module. The SDU cable connects the Netlink's ethernet port to a micro-b USB connector, allowing direct connection of the NetLink to an LP series controller's USB port. Allows shared NetLink and Mercury Controller IP connection. Reduces addresses	126.35

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	on the network, Lowers network drop fees, Reduces cybersecurity risks, Makes managed power possible in installations where adding network drops is not an option.	
AC-LSP-WALL-MOUNT-FPO150-B100C8D8E2M	Power supply board 150W, 12A/12V or 6A/24V Secondary voltage power supply, 5-18V adjustable @ 4A max, class 2 power limited output 8 relay lock control outputs fused at 3A per output 8 auxiliary DC outputs fused at 3A per output Enclosure, Size 18. (16W x 20H x 4.5D) with Mercury backplate (Non-stock item)(LifeSafety Power Part Number: FPO150-B100C8D8E2M)	845.41
AC-LSP-WALL-MOUNT-FPO75-B100C4D8NL2E2M	Power supply board 75W, 6A/12V or 3A/24V Secondary voltage power supply, 5-18V adjustable @ 4A max, class 2 power limited output 4 relay lock control outputs fused at 3A per output 8 auxiliary DC outputs fused at 3A per output Network communication module 2nd Gen. Enclosure, Size 18. (16W x 20H x 4.5D) with Mercury backplate (Non-stock item)(LifeSafety Power Part Number: FPO75-B100C4D8NL2E2M)	771.12
AC-LSP-WIRED-FPO150-B1002D8PM8NL4E6M/P8-A	Eight Door Mercury Panduit ProWire Unified Power wall mount Power supply board 150W, 4A/24V Secondary voltage module, 4A/12V class 2 power limited Eight relay managed outputs fused at 3A 8 auxiliary output power limited at 2.5A Four port monitoring module Enclosure size: 30" x 23" x 6.5" 47 lbs Wired for MR52/EP1502. NOTE: All ProWire Unified Power wall mounts are custom made to order. After 48 hours of Avigilon's order acknowledgment, all changes to an accepted purchase order will be subject to a Change Order charge of 30% of the net deliverable value. Returns and cancellations of an order or portion of an order that includes deliverables that have been manufactured and prepped for shipping will be applied with a 50% restocking fee. (Lifesafety Power Part #: FPO150-B1002D8PM8NL4E6M/P8-A)	2,965.72
AC-LSP-WIRED-FPO150-B100C82D8PE6M/P8-A	Eight Door Mercury Panduit ProWire Unified Power wall mount Power supply board 150W, 4A/24V Secondary voltage module, 4A/12V class 2 power limited Eight relay lock control outputs fused at 3A 8 auxiliary output power limited at 2.5A Enclosure size: 30" x 23" x 6.5" 47 lbs Wired for MR52/EP1502. NOTE: All ProWire Unified Power wall mounts are custom made to order. After 48 hours of Avigilon's order acknowledgment, all changes to an accepted purchase order will be subject to a Change Order charge of 30% of the net deliverable value. Returns and cancellations of an order or portion of an order that includes deliverables that have been manufactured and prepped for shipping will be applied with a 50% restocking fee. (Lifesafety Power Part #: FPO150-B100C82D8PE6M/P8-A)	2,432.74
AC-LSP-WIRED-FPO150/250-2C83D8PE8M2/P16-A	Sixteen Door Mercury Panduit ProWire Unified Power wall mount Power supply board 150W, 12A/12V Power supply board 250W, 10A/24V 16 relay lock control outputs fused at 3A 16 auxiliary outputs power limited at 2.5A Enclosure size: 36" x 30" x 4.5" 73 lbs Wired for MR52/EP1502. NOTE: All ProWire Unified Power wall mounts are custom made to order. NOTE: All ProWire Unified Power wall mounts are custom made to order. After 48 hours of Avigilon's order acknowledgment, all changes to an accepted purchase order will be subject to a Change Order charge of 30% of the net deliverable value. Returns and cancellations of an order or portion of an order that includes deliverables that have been manufactured and prepped for shipping will be applied with a 50% restocking fee. (Lifesafety Power Part #: FPO150/250-2C83D8PE8M2/P16-A)	4,029.32
AC-LSP-WIRED-FPO150/250-2C83D8PE8M2/P16-C	Sixteen Door Mercury Panduit ProWire Unified Power wall mount Power supply board 150W, 12A/12V Power supply board 250W, 10A/24V 16 relay lock control outputs fused at 3A 16 auxiliary outputs power limited at 2.5A Enclosure size: 36" x 30" x 4.5" 73 lbs Wired for all MR52s. NOTE: All ProWire Unified Power wall mounts are custom made to order. After 48 hours of Avigilon's order acknowledgment, all changes to an accepted purchase order will be subject to a Change Order charge of 30% of the net deliverable value. Returns and cancellations of an order or portion of an order that includes deliverables that have been manufactured and prepped for shipping will be applied with a 50% restocking fee. (Lifesafety Power Part #: FPO150/250-2C83D8PE8M2/P16-C)	4,029.32
AC-LSP-WIRED-FPO150/250-3D8P2M8NL4E8M2/P16-A	Sixteen Door Mercury Panduit ProWire Unified Power wall mount Power supply board 150W, 12A/12V Power supply board 250W, 10A/24V 16 relay managed outputs fused at 3A 16 auxiliary outputs power limited at 2.5A Four port monitoring module Enclosure size: 36" x 30" x 4.5" 73 lbs Wired for MR52/EP1502. NOTE: All ProWire Unified Power wall mounts are custom made to order. After 48 hours of Avigilon's order acknowledgment, all changes to an accepted purchase order will be subject to a Change Order charge of 30% of the net deliverable value. Returns and cancellations of an order or portion of an order that includes deliverables that have been manufactured and prepped for shipping will be applied with a 50% restocking fee. (Lifesafety Power Part #: FPO150/250-3D8P2M8NL4E8M2/P16-A)	4,688.63
AC-LSP-WIRED-FPO150/250-3D8P2M8NL4E8M2/P16-C	Sixteen Door Mercury Panduit ProWire Unified Power wall mount Power supply board 150W, 12A/12V Power supply board 250W, 10A/24V 16 relay managed outputs fused at 3A 16 auxiliary outputs power limited at 2.5A Four port monitoring module Enclosure size: 36" x 30" x 4.5" 73	4,688.63

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

lbs | Wired for All MR52s. NOTE: All ProWire Unified Power wall mounts are custom made to order. After 48 hours of Avigilon's order acknowledgment, all changes to an accepted purchase order will be subject to a Change Order charge of 30% of the net deliverable value. Returns and cancellations of an order or portion of an order that includes deliverables that have been manufactured and prepped for shipping will be applied with a 50% restocking fee. (Lifesafety Power Part #: FPO150/250-3D8P2M8NL4E8M2/P16-C)

Rolec

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-RO-SMALL-ENC	6.5W x 6.5W x 3D small size enclosure suitable for 1 x Mercury LP1501 or 1 x Mercury MR62e , IP67 rated, Includes removable non-metallic backplane for mounting the controller. Stock Item	82.92

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

Readers

STid

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT	Programming Kit for Bluetooth®/Ultralight® C/MIFARE® Classic & Classic EV1/MIFARE Plus®/DESFire® EV2 & EV3/NFC HCE + SECard Software	1,492.50
AC-STID-EM+HID-LF-MODULE-SE810	SE8 - 125 kHz EM + HID module for Architect Blue reader - Standard reader black - 125 kHz EM + HID module. 125KHz Single Format Module, In addition to EM Format, it can be configured to read either HID Prox 26bit or 37bit, Only one format can be selected	103.43
AC-STID-ENROLL-READER-UHF-SWEDGE-W45	UHF EPC1 Gen2 Enrollment Kit SWEDGE: ARC UHF desktop reader - ETSI - USB (cable included) + SWEDGE Software (Europe)	898.46
AC-STID-ENROLL-READER-UHF-SWEDGE-W55	UHF EPC1 Gen2 Enrollment Kit SWEDGE: ARC UHF desktop reader - FCC - USB (cable included) + SWEDGE Software (Americas)	898.46
AC-STID-ENROLL-READER-USB-ARCS-R35-H/BT1-5AB/1A	ARCS-H/BT - Architect® Blue Desktop reader/enroller - Secure storage EAL5+ - Secure Read only - USB + WEDGE with keypad emulation interface (cable included) - AZERTY default configuration	433.72
AC-STID-ENROLL-READER-USB-ARCS-R35-H/BT1-5AQ/1A	ARCS-H/BT - Architect® Blue Desktop reader/enroller - Secure storage EAL5+ - Secure Read only - USB + WEDGE with keypad emulation interface (cable included) - QWERTY default configuration	433.72
AC-STID-KIT-STKIT-BT-V3.5-OSDP	Starter Kit Blue -ARCS-A/BT + ARCS-G/BT + USB with SECard v3.5.1 + 15 Virtual Credits - OSDP V1 & V2 secure protocol - RS485 interface. Kit includes Architect® Blue 13.56 MHz MIFARE® encoder, SECard software (USB stick), 2 MIFARE® Classic 1K cards, 4 MIFARE® DESFire® EV1 4K cards.	1,255.00
AC-STID-LF-MT-MODULE-SE8M10	SE8M - 125 kHz Multi-technology module for Architect Blue reader - Standard reader black - 125 kHz Multi-technology module. All the following can be selected, and the reader send information as raw data. HID Prox – 26, 35, 37, AWID – 26, 35, 37, Kantec, ioProx - XSF 39 bits, 26 bits, 24 bits, Indala – 27bits	205.17
AC-STID-QR-BARCODE-MODULE-SE910	SE9 Architect® Blue QR Code / Barcode module - QR and Barcode module for Standard reader black	1,101.84
AC-STID-READER-ARC1S-R31-B/BT1-3I/1A	NON PROGRAMED ARC1S/BT - Architect® One Blue Mullion reader - Secure storage EAL5+ - Secure Read only - TTL interface - 3m cable with connector - NO LOGO- Mullion Reader Black Wiegand 26bit - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	307.02
AC-STID-READER-ARC1S-W33-B/BT1-7OS/1A	NON PROGRAMED ARC1S/BT - Architect® One Blue Mullion reader - OSDP™ v1 & v2 secure protocol - Secure storage EAL5+ - RS485 interface - 3m cable with connector - NO LOGO - Mullion Reader Black OSDP v1 & v2 - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	307.02
AC-STID-READER-ARCS-R31-A/BT1-3I/1A	NON PROGRAMED ARCS-A/BT - Architect® Blue Upgradable Standard reader black - Wiegand Interface- Secure storage EAL5+ - Secure Read only - TTL interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	375.00
AC-STID-READER-ARCS-R31-B/BT1-3I/1A	NON PROGRAMED ARCS-B/BT - Architect® Blue Upgradable Keypad reader black - Wiegand Interface - Secure storage EAL5+ - Secure Read only - TTL interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	570.00
AC-STID-READER-ARCS-RX1-IM/BT2-3I/1A	NON PROGRAMED ARCS-IM/BT - Architect® Blue Hybrid 125 kHz Multi-technology + 13.56 MHz + Bluetooth® Upgradable reader - Secure storage EAL5+ - Secure Read only - Standard Multi-technology Reader black Wiegand interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	546.67
AC-STID-READER-ARCS-RX1-JM/BT2-3I/1A	NON PROGRAMED ARCS-JM/BT - Architect® Blue Hybrid 125 kHz Multi-technology + 13.56 MHz + Bluetooth® Upgradable Keypad reader - Secure storage EAL5+ - Secure Read only - Standard Multi-technology Keypad Reader black Wiegand interface - NO LOGO -Requires	695.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	
AC-STID-READER-ARCS-W33-A/BT1-7OS/1A	NON PROGRAMED ARCS-A/BT - Architect® Blue Upgradable Standard reader - OSDP™ v1 & v2 secure protocol - Secure storage EAL5+ - RS485 interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration	375.00
AC-STID-READER-ARCS-W33-AQ/BT1-7OS/1A	NON PROGRAMED ARCS-AQ/BT - Architect® Blue Upgradable QR Code, Bluetooth® & RFID reader - OSDP™ v1 & v2 secure protocol - Secure storage EAL5+ - RS485 interface - NO LOGO - Standard Reader black with QR module OSDP - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	1,280.04
AC-STID-READER-ARCS-W33-B/BT1-7OS/1A	NON PROGRAMED ARCS-B/BT - Architect® Blue Upgradable Keypad reader - OSDP™ v1 & v2 secure protocol - Secure storage EAL5+ - RS485 interface - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration	570.00
AC-STID-READER-ARCS-W33-BQ/BT1-7OS/1A	NON PROGRAMED ARCS-BQ/BT Architect® Blue Upgradable QR Code, Bluetooth® & RFID Keypad reader - OSDP™ v1 & v2 secure protocol - Secure storage EAL5+ - RS485 interface - NO LOGO - Standard reader black with Keypad and QR module OSDP - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	1,445.25
AC-STID-READER-ARCS-W33-C/BT1-7OS/1A	NON PROGRAMED ARCS-C/BT - Architect® Blue Upgradable Touchscreen reader - OSDP™ v1 & v2 secure protocol - Secure storage EAL5+ - RS485 interface - NO LOGO - Standard reader black with touchscreen OSDP - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	671.68
AC-STID-READER-SNA-W43-A/BT4-7OS/1	SNA - SPECTRE nano UHF - Europa Low Band 865-868 MHz - USB cable & ULTRYS software included	1,581.73
AC-STID-READER-SNA-W53-A/BT4-7OS/1	SNA - SPECTRE nano UHF - USA Upper Band 902-928 MHz- USB cable & ULTRYS software included	1,581.73
AC-STID-SPACER-PLA-ADAP-V2-ARC-NO	Stackable spacer with cable passage for Architect® Blue reader - Black	26.75
AC-STID-SPACER-PLAQ-ARC1-NO-V2	Stackable spacer with cable passage for Architect® One Blue mullion reader - Black	26.75
AC-STID-SPECTRE-PROGRAMMING-KIT-ULTRYSV2	UHF Programming kit for SPECTRE, SPECTRE nano & ATX UHF reader configuration and user credentials encoding - ARC UHF (cable included) + Ultrys v2 software included	995.88

Allegion

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-ALL-READ-APTIQ-OSDP-KEYPD-MTK15-485	Schlage (formerly aptiQ™) Multi-Technology Keypad - Single Gang Reader - OSDP (Allegion Part Number: MTK15-485)	549.15
AC-ALL-READ-APTIQ-OSDP-MULL-MT11-485	Schlage (formerly aptiQ™) Multi-Technology – Mullion Reader - OSDP (Allegion Part Number: MT11-485)	342.59
AC-ALL-READ-APTIQ-OSDP-SNG-MT15-485	Schlage (formerly aptiQ™) Multi-Technology - Single Gang Reader - OSDP (Allegion Part Number: MT15-485)	342.59
AC-ALL-READ-APTIQ-WIEGAND-MTMSK15	Schlage (formerly aptiQ™) Multi-Technology with Magnetic Stripe and Keypad - Single Gang Reader - Wiegand (Allegion Part Number: MTMSK15)	835.65
AC-ALL-SCH-WPR400-MT	Wireless Portable Reader (with Multi-Technology Reader Module)Handheld, battery-operated unit with Multi-Technology(Allegion Part Number: WPR400-MT)	2,183.01
AC-ALL-SCH-WRI400	Outdoor Wireless Reader Interface Compatible with Wiegand or Magnetic Stripe Interface. Includes Weatherproof Enclosure, inputs for two parallel readers. Requires 12 or 24 VDC power supply (Non-stock item)(Allegion Part Number: WRI400)	989.44
AC-ING-READ-APTIQ-ENROLL-MT20	Schlage (formerly aptiQ™) MT20 Multi-technology enrollment reader with ENGAGE™ technology (Allegion Part Number: MT20)	543.67
AC-ING-READ-APTIQ-KEYPD-MTK15	Schlage (formerly aptiQ™) Multi-Technology Keypad - Single Gang Reader (Allegion Part Number: MTK15)	544.48
AC-ING-READ-APTIQ-MINI-SM10	Schlage (formerly aptiQ™) 13.56 MHz Smart - Mini Mullion Reader (Allegion Part Number: SM10)	163.45

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-ING-READ-APTIQ-MULL-MT11	Schlage (formerly aptiQ™) Multi-Technology – Mullion Reader (Allegion Part Number: MT11)	342.59
AC-ING-READ-APTIQ-SNG-MT15	Schlage (formerly aptiQ™) Multi-Technology - Single Gang Reader (Allegion Part Number: MT15)	342.59
AC-ING-READ-XCEEDID-PROX	Schlage (formerly XceedID) - 125 kHz Proximity - Mini Mullion Reader (Allegion Part Number: PR10)	172.66
AC-ING-READ-XCEEDID-PROX-C	Schlage (formerly XceedID) - 125 kHz Proximity - Mini Mullion Crème Reader (Allegion Part Number: PR10-C)	172.66
AC-SCH-READ-OSDP-MT15-C	Schlage MT-15 Single gang mount multi-technology reader, RS485 OSDP, Cream Color	342.57
AC-SCH-READ-WIEGAND-MT15-C	Schlage MT-15 Single gang mount multi-technology reader, Wiegand, Cream Color	342.57
AC-SCH-READER-MTB11	Mobile Enabled Multi-Technology Reader – Mullion Mount - Dimensions: 5.91" x 1.72" x 0.81". Power required: 5-24 VDC - RS-485 capability included in standard product offering	358.38
AC-SCH-READER-MTB15	Mobile Enabled Multi-Technology Reader – Wall Mount - Dimensions: 5.1" x 3.25" x 0.76". Power required: 5-24 VDC - RS-485 capability included in standard product offering	358.38
AC-SCH-READER-MTKB15	Mobile Enabled Multi-Technology Reader – Wall Mount with Keypad - Dimensions: 5.1" x 3.25" x 0.76". Power required: 5-24 VDC - RS-485 capability included in standard product offering	575.81

Farpointe Data

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-FP-READ-CSR-35L-OSDP	CONEKT OSDP, Long Range, Mullien and Single-gang Mount, Mobile-Ready Contactless Smartcard Readers (2.4-GHz/13.56-MHz) — MIFARE® DESFire® EV1 and EV2 Support	459.15
AC-FP-READ-CSR-35L-WG	CONEKT Wiegand, Long Range, Mullien and Single-gang Mount, Mobile-Ready Contactless Smartcard Readers (2.4-GHz/13.56-MHz) — MIFARE® DESFire® EV1 and EV2 Support	338.89
AC-FP-READ-DELTA-62-OSDP-F05552-600SCN	Delta6.2 OSDP Contactless Smartcard Reader and Keypad - The model Delta6.2 is designed to be mounted directly to location requiring mullion mount, and integrates both a contactless smartcard reader (13.56-MHz) and a keypad into a single-unit making it ideal for applications requiring an access credential and/or personal identification number (PIN) (Non Stock Item) (Farpointe Data Part Number: F05552-600SCN)	663.35
AC-FP-READ-DELTA-62-OSDP-F05662-600	Delta 6.2 OSDP Contactless Smartcard Reader and Keypad - The model Delta 6.2 is designed to be mounted directly to location requiring mullion mount, and integrates both a contactless smartcard reader (13.56-MHz) and a keypad into a single-unit making it ideal for applications requiring an access credential and/or personal identification number (PIN) (Non Stock Item) (Farpointe Data Part Number: F05552-600SCN)	664.14
AC-FP-READ-DELTA3-SECTOR	Delta3 Contactless Smartcard Reader - With a compact design the model Delta3 may be mounted to metal door or window frames, and other flat surfaces (Stock Item) (Farpointe Data Part Number: Delta3 Sector)	298.44
AC-FP-READ-DELTA5-OSDP	Delta5 OSDP Contactless Smartcard Reader - With a thin profile the model Delta5 may be mounted to a standard North American single-gang wall switch box, and other flat surfaces, OSDP Only.	450.06
AC-FP-READ-DELTA5-SECTOR	Delta5 Contactless Smartcard Reader - With a thin profile the model Delta5 may be mounted to a standard North American single-gang wall switch box, and other flat surfaces (Stock Item) (Farpointe Data Part Number: Delta5 Sector)	323.60
AC-FP-READ-DELTA5.3-SECTOR	Delta5.3 Contactless Smartcard Reader - With distinctive contemporary styling the model Delta5.3 lends itself to mounting to a standard European-sized (60 mm) wall switch box, and other flat surfaces (Non Stock Item) (Farpointe Data Part Number: Delta5.3 Sector)	323.60
AC-FP-READ-DELTA6.4-SECTOR	Delta6.4 Contactless Smartcard Reader and Keypad - The model Delta6.4 is designed to be mounted directly to a standard North American sized single-gang wall box, and integrates both a contactless smartcard reader (13.56-MHz) and a keypad into a single-unit making it ideal for applications requiring an access credential and/or personal identification number (PIN) (Stock Item) (Farpointe Data Part Number: Delta6.4 Sector)	539.41
AC-FP-READ-GIBRALTER-BR-P-453-HA	Gibraltar Proximity Reader, Bullet-resistant reader designed to be mounted to mullion, door or window frames.(Farpointe Data Part Number: P-453-HA)	709.36
AC-FP-READ-GIBRALTER-BR-P-455-HA		781.62

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	Gibraltar Proximity Reader, Bullet-resistant reader designed to mount to standard North American single-gang wall switch boxes.(Farpointe Data Part Number: P-455-HA)	
AC-FP-READ-GUARDIAN-VR-P-403-HA	Guardian Proximity Reader, Vandal-resistant reader designed to mount to a metal door and window frame.(Farpointe Data Part Number: P-403-HA)	482.83
AC-FP-READ-GUARDIAN-VR-P-405-HA	Guardian Proximity Reader, Vandal-resistant reader designed to mount to a standard North American single-gang wall switch box.(Farpointe Data Part Number: P-405-HA)	573.08
AC-FP-READ-GUARDIAN-VR-P-410-HA	Guardian Proximity Reader, Vandal-resistant reader designed to mount to a standard North American double-gang wall switch box.(Farpointe Data Part Number: P-410-HA)	718.74
AC-FP-READ-P-300-H	P-300 Cascade Proximity Reader - Designed to be mounted to metal door and window frames (Stock Item) (Farpointe Data Part Number: P-300-H)	94.86
AC-FP-READ-P-300-H-A	Mullion mount reader, supports Farpointe + certain HID® and AWID® 125-kHz Proximity protocols (Farpointe Data Part Number: P-300-H-A)	96.90
AC-FP-READ-P-500-H	P-500 Alps Proximity Reader - Designed to be mounted to a standard North American single-gang wall switch box (Stock Item) (Farpointe Data Part Number: P-500-H)	128.54
AC-FP-READ-P-500-H-A	Single-gang mount reader, supports Farpointe + certain HID® and AWID® 125-kHz Proximity protocols (Farpointe Data Part Number: P-500-H-A)	126.14
AC-FP-READ-P-640-H	P-640 Patagonia Proximity Reader and Keypad - Designed to be mounted directly to standard North American sized single-gang wall box, and integrates both a proximity reader and keypad into a single-unit making it ideal for applications requiring an access credential and/or personal identification number (PIN) (Stock Item) (Farpointe Data Part Number: P-640-H)	303.21
AC-FP-READ-P-640-H-A	Keypad + reader, single-gang mount, supports Farpointe + certain HID® and AWID® 125-kHz Proximity protocols (Farpointe Data Part Number: P-640-H-A)	305.36
AC-FP-READ-P-640-H-OSDP	P-640 Patagonia Proximity Reader and Keypad - Designed to be mounted directly to standard North American sized single-gang wall box, and integrates both a proximity reader and keypad into a single-unit making it ideal for applications requiring an access credential and/or personal identification number, OSDP Only	425.73
AC-FP-READ-P-710-H	P-710 Andes Proximity Reader - Intended for applications calling for heightened levels of convenience, such as parking lots and high-volume employee entrances (Non Stock Item)(Farpointe Data Part Number: P-710-H)	392.90
AC-FP-READ-P-710-H-A	Parking, single-gang mount reader, supports Farpointe + certain HID® and AWID® 125-kHz Proximity protocols (Farpointe Data Part Number: P-710-H-A)	391.68
AC-FP-READ-P-900-H	P-900 Proximity Reader - A high performance design, it is classified as a long range reader, and is capable of delivering read ranges of up to 20-inches (508 mm). The longer read range of the P-900 adds convenience to a wide range of access applications, including turnstiles and parking control (Stock Item) (Farpointe Data Part Number: P-900-H)	777.49
AC-FP-READ-P-900-H-A	Single-gang/double-gang, standard parking bollard mount reader, supports Farpointe + certain HID® and AWID® 125-kHz Proximity protocols (Farpointe Data Part Number: P-900-H-A)	776.27
AC-FP-READ-PROX-EURO-P-530-HA	EuroMount Proximity Reader, designed to be mounted to a standard European-sized (60 mm) wall switch box. (Non-stock item)(Farpointe Data Part Number: P-530-HA)	128.54
AC-FP-READ-PROX-KEYPAD-P-620-HA	Mullion Mount Keypad reader + proximity, designed to be mounted to window or door frames(Farpointe Data Part Number: P-620-HA)	303.21
AC-FP-READ-WG-MCR-50-H	MCR-50 Proximity Reader - Supports Farpointe + certain Indala® ASP Advantage Series Proximity formats + certain HID® 125-kHz Proximity protocols; single-gang mount. (Non-stock item) (Farpointe Data Part Number: MCR-50-H)	217.87
AC-FP-REC-LONG-RANGE-WRR-22	Long-Range Receiver, designed to output Transmitter data from buttons 1 and 2 over two separate Wiegand outputs and install similar to a Pyramid Series Proximity® reader, making for easy integration with most access control systems. (Non-stock item)(Farpointe Data Part Number: WRR-22)	240.72
AC-FP-REC-WRR-44	WRR-44 Ranger Receiver - Long range radio-type receiver, features a Transmitter receive range of up to 200-feet (61-m), and is ideal for applications involving vehicle or disabled access(Stock Item) (Farpointe Data Part Number: WRR-44)	396.58

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-VT-READ-BIO-RFID-AC2000IC	VIRDI fingerprint smart card reader with live fingerprint detection embedded. Supports fingerprint, HID iClass Card, User Capacity: 10,000, Finger Capacity: 1,500, TCP/IP Server Communication, No LCD, No Function Key, bluetooth support. Power Supply not included. (VIRDI Part Number: AC2000iClass)	918.00
AC-VT-READ-BIO-RFID-AC2000IC-EU	Reader bundle including AC-VT-READ-BIO-RFID-AC2000IC and power supply with type C plug for Europe	918.00
AC-VT-READ-BIO-RFID-AC2000IC-NA	Reader bundle including AC-VT-READ-BIO-RFID-AC2000IC and power supply with type B plug for North America	918.00
AC-VT-READ-BIO-RFID-AC2000IC-UK	Reader bundle including AC-VT-READ-BIO-RFID-AC2000IC and power supply with type G plug for United Kingdom	918.00
AC-VT-READ-BIO-RFID-AC2000PROX	VIRDI fingerprint smart card reader with live fingerprint detection embedded. Supports fingerprint, HID prox Card, User Capacity : 10,000, Finger Capacity: 1,500, TCP/IP Server Communication, No LCD, No Function Key, bluetooth support. Power Supply not included. (VIRDI Part Number: AC2000Prox)	918.00
AC-VT-READ-BIO-RFID-AC2000PROX-EU	Reader bundle including AC-VT-READ-BIO-RFID-AC2000Prox and power supply with type C plug for Europe	918.00
AC-VT-READ-BIO-RFID-AC2000PROX-NA	Reader bundle including AC-VT-READ-BIO-RFID-AC2000Prox and power supply with type B plug for North America	918.00
AC-VT-READ-BIO-RFID-AC2000PROX-UK	Reader bundle including AC-VT-READ-BIO-RFID-AC2000Prox and power supply with type G plug for United Kingdom	918.00
AC-VT-READ-BIO-RFID-AC2000SC	ViRDI fingerprint smart card reader with live fingerprint detection embedded. Supports fingerprint, Mifare 13.56Mhz Card & PIN Authentication, User Capacity: 1,500, Finger Capacity: 1500, TCP/IP Server Communication, No LCD, No Function Key, Bluetooth support. (ViRDI Part Number: AC2000SC)	714.00
AC-VT-READ-BIO-RFID-AC2000SC-EU	Reader bundle including AC-VT-READ-BIO-RFID-AC2000SC and power supply with type C plug for Europe	714.00
AC-VT-READ-BIO-RFID-AC2000SC-NA	Reader bundle including AC-VT-READ-BIO-RFID-AC2000SC and power supply with type B plug for North America	714.00
AC-VT-READ-BIO-RFID-AC2000SC-UK	Reader bundle including AC-VT-READ-BIO-RFID-AC2000SC and power supply with type G plug for United Kingdom	714.00
AC-VT-READ-BIO-RFID-AC5000IC	VIRDI Fingerprint and card enrollment reader with touchscreen keypad, live fingerprint detection embedded, supports HID iClass Card & PIN authentication. User Capacity : 20,000, Finger Capacity: 20,000, IP 65 Weatherproof, TCP/IP server communication. Power Supply not included. (VIRDI Part Number: AC5000PlusiClass)	1,275.00
AC-VT-READ-BIO-RFID-AC5000IC-EU	Reader bundle including AC-VT-READ-BIO-RFID-AC5000IC and power supply with type C plug for Europe	1,275.00
AC-VT-READ-BIO-RFID-AC5000IC-NA	Reader bundle including AC-VT-READ-BIO-RFID-AC5000IC and power supply with type B plug for North America	1,275.00
AC-VT-READ-BIO-RFID-AC5000IC-UK	Reader bundle including AC-VT-READ-BIO-RFID-AC5000IC and power supply with type G plug for United Kingdom	1,275.00
AC-VT-READ-BIO-RFID-AC5000PROX	VIRDI Fingerprint and card enrollment reader with touchscreen keypad, live fingerprint detection embedded, supports HID Prox Card & PIN authentication. User Capacity : 20,000, Finger Capacity: 20,000, IP 65 Weatherproof, TCP/IP server communication. Power Supply not included. (VIRDI Part Number: AC5000PlusProx)	1,275.00
AC-VT-READ-BIO-RFID-AC5000PROX-EU	Reader bundle including AC-VT-READ-BIO-RFID-AC5000Prox and power supply with type C plug for Europe	1,275.00
AC-VT-READ-BIO-RFID-AC5000PROX-NA	Reader bundle including AC-VT-READ-BIO-RFID-AC5000Prox and power supply with type B plug for North America	1,275.00
AC-VT-READ-BIO-RFID-AC5000PROX-UK	Reader bundle including AC-VT-READ-BIO-RFID-AC5000Prox and power supply with type G plug for United Kingdom	1,275.00
AC-VT-READ-BIO-RFID-AC5000SC-BLK	VIRDI Fingerprint and card enrollment reader with touchscreen keypad, live fingerprint detection embedded, supports Mifare 13.56Mhz Card & PIN authentication. User Capacity : 20,000, Finger Capacity: 20,000, IP 65 Weatherproof & PoE 13W, TCP/IP server communication. Power Supply Not Included.(ViRDI Part Number: AC5000PlusSC)	1,071.00
AC-VT-READ-BIO-RFID-AC5000SC-BLK-EU	Reader bundle including AC-VT-READ-BIO-RFID-AC5000SC-BLK and power supply with type C plug for Europe	1,071.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-VT-READ-BIO-RFID-AC5000SC-BLK-NA	Reader bundle including AC-VT-READ-BIO-RFID-AC5000SC-BLK and power supply with type B plug for North America	1,071.00
AC-VT-READ-BIO-RFID-AC5000SC-BLK-UK	Reader bundle including AC-VT-READ-BIO-RFID-AC5000SC-BLK and power supply with type G plug for United Kingdom	1,071.00
AC-VT-READ-BIO-USB-FOH02	ViRDI Fingerprint and card enrollment USB reader, live fingerprint detection embedded, Fingerprint Platen Area: 16 x 19.6mm / Image Size: 15 x 17mm, (ViRDI Part Number: FOH02)	142.80
AC-VT-READ-BIO-USB-FOH02-SC	ViRDI Fingerprint and card enrollment reader, live fingerprint detection embedded, supports Mifare 13.56Mhz Card (Read & Write), Fingerprint Platen Area: 16 x 19.6mm / Image Size: 15 x 17mm, Read /Write - supports TOC (Template on Card) (ViRDI Part Number: FOH02SC) Note - This product is not available for sale in Spain and South Africa.	188.70

HID Readers

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-HID-GASKET-IP65GSKT-R10	GASKET PACK, IP65, R10 SIZE, ICLASS SE, PACK OF 10 GASKETS (HID Part Number: IP65GSKT-R10)	33.41
AC-HID-GASKET-IP65GSKT-R15	GASKET PACK, IP65, R15 SIZE, ICLASS SE, PACK OF 10 GASKETS (HID Part Number: IP65GSKT-R15)	33.41
AC-HID-GASKET-IP65GSKT-R40	GASKET PACK, IP65, R40 SIZE, ICLASS SE, PACK OF 10 GASKETS (HID Part Number: IP65GSKT-R40)	33.41
AC-HID-GASKET-IP65GSKT-RK40	GASKET PACK, IP65, RK40 SIZE, ICLASS SE, PACK OF 10 GASKETS (HID Part Number: IP65GSKT-RK40)	33.41
AC-HID-MCLASS-SE-PROX-OSDP-900PTPNEK00387	RDR, RP10, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, 485HDX, PIG, BLK, STD-1, A/V OFF, OSDP V1, OPN COL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF (HID Part #: 900PTPNEK00387)	277.15
AC-HID-MCLASS-SE-PROX-OSDP-900PTPTEK00387	RDR, RP10, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V1, OPN COL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF (HID Part #: 900PTPTEK00387)	277.15
AC-HID-MCLASS-SE-PROX-OSDP-910PTPNEK00387	RDR, RP15, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, 485HDX, PIG, BLK, STD-1, A/V OFF, OSDP V1, OPN COL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF (HID Part #: 910PTPNEK00387)	420.09
AC-HID-MCLASS-SE-PROX-OSDP-910PTPTEK00387	RDR, RP15, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V1, OPN COL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF (HID Part #: 910PTPTEK00387)	420.09
AC-HID-MCLASS-SE-PROX-OSDP-920PTPNEK00387	RDR, RP40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, 485HDX, PIG, BLK, STD-1, A/V OFF, OSDP V1, OPN COL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF (HID Part #: 920PTPNEK00387)	420.09
AC-HID-MCLASS-SE-PROX-OSDP-920PTPTEK00387	RDR, RP40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V1, OPN COL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF (HID Part #: 920PTPTEK00387)	420.09
AC-HID-MCLASS-SE-PROX-OSDP-921PTPNEK00385	RDR, RPK40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, 485HDX, PIG, BLK, STD-1, A/V OFF, OSDP V1, OPN COL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, KP, ASCII, BFFRD 1 KEY, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF (HID Part #: 921PTPNEK00385)	699.03
AC-HID-MCLASS-SE-PROX-OSDP-921PTPTEK00385	RDR, RPK40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V1, OPN COL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, KP, ASCII, BFFRD 1 KEY, IPM OFF, UART OFF, WIEG OFF (HID Part #: 921PTPTEK00385)	699.03
AC-HID-READ-ICLASS-SE-MOB-OSDP-900NMPNEKEA005	R10 Mini-mullion reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 900NMPNEKEA005)	287.08
AC-HID-READ-ICLASS-SE-MOB-OSDP-900NMPNEKMA005	RDR, R10, ICLASS, SE E, LF OFF, HF STD/SIO/SEOS/MA, OSDP, PIG, BLK, A/V OFF, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 900NMPNEKMA005)	289.72
AC-HID-READ-ICLASS-SE-MOB-OSDP-900NMPTEKEA005		287.08

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	R10 Mini-mullion reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 900NMPTEKMA005)	
AC-HID-READ-ICLASS-SE-MOB-OSDP-900NMPTEKMA005	RDR, R10, ICLASS, SE E, LF OFF, HF STD/SIO/SEOS/MA, OSDP, TERM, BLK, A/V OFF, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 900NMPTEKMA005)	289.72
AC-HID-READ-ICLASS-SE-MOB-OSDP-910NMPNEKEA005	R15 Mullion reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 910NMPNEKEA005)	430.09
AC-HID-READ-ICLASS-SE-MOB-OSDP-910NMPNEKMA005	RDR, R15, ICLASS, SE E, LF OFF, HF STD/SIO/SEOS/MA, OSDP, PIG, BLK, A/V OFF, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 910NMPNEKMA005)	432.75
AC-HID-READ-ICLASS-SE-MOB-OSDP-910NMPTEKEA005	R15 Mullion reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 910NMPTEKEA005)	430.09
AC-HID-READ-ICLASS-SE-MOB-OSDP-910NMPTEKMA005	RDR, R15, ICLASS, SE E, LF OFF, HF STD/SIO/SEOS/MA, OSDP, TERM, BLK, A/V OFF, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 910NMPTEKMA005)	432.75
AC-HID-READ-ICLASS-SE-MOB-OSDP-920NMPNEKEA005	R40 Standard wall switch reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 920NMPNEKEA005)	430.09
AC-HID-READ-ICLASS-SE-MOB-OSDP-920NMPNEKMA005	RDR, R40, ICLASS, SE E, LF OFF, HF STD/SIO/SEOS/MA, OSDP, PIG, BLK, A/V OFF, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 920NMPNEKMA005)	432.75
AC-HID-READ-ICLASS-SE-MOB-OSDP-920NMPTEKEA005	R40 Standard wall switch reader; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 920NMPTEKEA005)	430.09
AC-HID-READ-ICLASS-SE-MOB-OSDP-920NMPTEKMA005	RDR, R40, ICLASS, SE E, LF OFF, HF STD/SIO/SEOS/MA, OSDP, TERM, BLK, A/V OFF, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 920NMPTEKMA005)	432.75
AC-HID-READ-ICLASS-SE-MOB-OSDP-921NMPNEKEA006	RK40 Standard wall switch reader with keypad input; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 921NMPNEKEA006)	709.03
AC-HID-READ-ICLASS-SE-MOB-OSDP-921NMPNEKMA006	RDR, RK40, ICLASS, SE E, LF OFF, HF STD/SIO/SEOS/MA, OSDP, PIG, BLK, A/V OFF, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, KPF, ASCII, BFFRD 1 KEY, IPM OFF, MOBILE-READY (HID Part #: 921NMPNEKMA006)	711.71
AC-HID-READ-ICLASS-SE-MOB-OSDP-921NMPTEKEA006	RK40 Standard wall switch reader with keypad input; OSDP; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 921NMPTEKEA006)	709.03
AC-HID-READ-ICLASS-SE-MOB-OSDP-921NMPTEKMA006	RDR, RK40, ICLASS, SE E, LF OFF, HF STD/SIO/SEOS/MA, OSDP, TERM, BLK, A/V OFF, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, KPF, ASCII, BFFRD 1 KEY, IPM OFF, MOBILE-READY (HID Part #: 921NMPTEKMA006)	711.71
AC-HID-READ-ICLASS-SE-MOB-WG-900NBNEK20000	R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; Pigtail (HID Part #: 900NBNEK20000)	287.08
AC-HID-READ-ICLASS-SE-MOB-WG-900NBNEKE0000	R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Elite and Mobile-Enabled; Pigtail (HID Part #: 900NBNEKE0000)	287.08
AC-HID-READ-ICLASS-SE-MOB-WG-900NBNTEK20000	R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; Terminal Strip (HID Part #: 900NBNTEK20000)	287.08
AC-HID-READ-ICLASS-SE-MOB-WG-900NBNTEKE0000	R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Elite and Mobile-Enabled; Terminal Strip (HID Part #: 900NBNTEKE0000)	287.08
AC-HID-READ-ICLASS-SE-MOB-WG-900NMNNEKEA001	R10 Mini-mullion reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 900NMNNEKEA001)	287.08
AC-HID-READ-ICLASS-SE-MOB-WG-900NMNTEKEA001		287.08

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	R10 Mini-mullion reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 900NMNTEKEA001)	
AC-HID-READ-ICLASS-SE-MOB-WG-910NMNNEKEA001	R15 Mullion reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 910NMNNEKEA001)	430.09
AC-HID-READ-ICLASS-SE-MOB-WG-910NMNTEKEA001	R15 Mullion reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 910NMNTEKEA001)	430.09
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNNEK20000	R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; Pigtail (HID Part #: 920NBNNEK20000)	430.09
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNNEKE0000	R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Elite and Mobile-Enabled; Pigtail (HID Part #: 920NBNNEKE0000)	430.09
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNNEKES077	R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Elite and Mobile-Enabled; Pigtail; Non-standard configuration (HID Part #: 920NBNNEKES077)	430.09
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNTEK20000	R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; Terminal Strip (HID Part #: 920NBNTEK20000)	430.09
AC-HID-READ-ICLASS-SE-MOB-WG-920NBNTEKE0000	R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Elite and Mobile-Enabled; Terminal Strip (HID Part #: 920NBNTEKE0000)	430.09
AC-HID-READ-ICLASS-SE-MOB-WG-920NMNNEKEA001	R40 Standard wall switch reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 920NMNNEKEA001)	430.09
AC-HID-READ-ICLASS-SE-MOB-WG-920NMNTEKEA001	R40 Standard wall switch reader; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 920NMNTEKEA001)	430.09
AC-HID-READ-ICLASS-SE-MOB-WG-921NBNNEK20000	RK40 Standard wall switch reader with keypad input; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; Pigtail (HID Part #: 921NBNNEK20000)	709.03
AC-HID-READ-ICLASS-SE-MOB-WG-921NBNNEKE0000	RK40 Standard wall switch reader with keypad input; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Elite and Mobile-Enabled; Pigtail (HID Part #: 921NBNNEKE0000)	709.03
AC-HID-READ-ICLASS-SE-MOB-WG-921NBNTEK20000	RK40 Standard wall switch reader with keypad input; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; Terminal Strip (HID Part #: 921NBNTEK20000)	709.03
AC-HID-READ-ICLASS-SE-MOB-WG-921NBNTEKE0000	RK40 Standard wall switch reader with keypad input; Wiegand; No Prox; iCLASS Seos; Mobile IDs via NFC and Bluetooth Smart; HID Elite and Mobile-Enabled; Terminal Strip (HID Part #: 921NBNTEKE0000)	709.03
AC-HID-READ-ICLASS-SE-MOB-WG-921NMNNEKEA002	RK40 Standard wall switch reader with keypad input; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 921NMNNEKEA002)	709.03
AC-HID-READ-ICLASS-SE-MOB-WG-921NMNTEKEA002	RK40 Standard wall switch reader with keypad input; Wiegand; No Prox; Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 921NMNTEKEA002)	709.03
AC-HID-READ-ICLASS-SE-R10	R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 900NTNNEK00000)	190.50
AC-HID-READ-ICLASS-SE-R10-AVG	R10 Mini-mullion reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail; Avigilon logo (HID Part #: 900NTNNEK00000-A001)	190.50
AC-HID-READ-ICLASS-SE-R15	R15 Mullion reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 910NTNNEK00000)	333.39
AC-HID-READ-ICLASS-SE-R40	R40 Standard wall switch reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 920NTNNEK00000)	333.39

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-READ-ICLASS-SE-R40-WG-920NSNNEK20000	RDR, R40, ICLASS, SE E, LF OFF, HF SEOS, WIEG, PIG, BLK, STD-2, LED RED, FLSH GRN, BZR ON, VAR BIT OUTPUT PER SIO, IPM OFF, VEL ON	336.09
AC-HID-READ-ICLASS-SE-R90-WG-940NNNTEK2037P	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; Terminal Strip (HID Part #: 940NNNTEK2037P)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK00000	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK00000)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK00015	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK00015)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK0001F	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK0001F)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK00021	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK00021)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK00029	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK00029)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK0002B	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK0002B)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK0002J	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK0002J)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK0002Q	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK0002Q)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK0003V	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK0003V)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK0005J	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK0005J)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK00061	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK00061)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK0006K	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK0006K)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK0009D	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK0009D)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK000DG	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK000DG)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK000JF	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK000JF)	820.13
AC-HID-READ-ICLASS-SE-R90-WG-940NTNTEK000K4	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTNTEK000K4)	820.13

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-READ-ICLASS-SE-R90-WG-940NTPTEK0007V	R90 Extended range (up to 18in/45cm) reader; OSDP; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Terminal Strip (HID Part #: 940NTPTEK0007V)	856.01
AC-HID-READ-ICLASS-SE-R90-WG-940NWNTKE00GD	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; MIFARE Classic and DESFire EV1 (Custom data); Mobile enabled; Terminal Strip (HID Part #: 940NWNTKE00GD)	881.97
AC-HID-READ-ICLASS-SE-R90-WG-940NWNTKE0324	R90 Extended range (up to 18in/45cm) reader; Wiegand; No Prox; MIFARE Classic and DESFire EV1 (Custom data); Mobile enabled; Terminal Strip (HID Part #: 940NWNTKE0324)	881.97
AC-HID-READ-ICLASS-SE-RK40	RK40 Standard wall switch reader with keypad input; Wiegand; No Prox; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 921NTNNEK00000)	612.33
AC-HID-READ-ICLASS-SE-RK40-WG-921NSNNEK20000	RDR, RK40, ICLASS, SE E, LF OFF, HF SEOS, WIEG, PIG, BLK, STD-2, LED RED, FLISH GRN, BZR ON, VAR BIT OUTPUT PER SIO, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, VEL ON	613.69
AC-HID-READ-ICLASS-SE-RP10	RP10 Mini-mullion reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 900PTNNEK00000)	237.51
AC-HID-READ-ICLASS-SE-RP15	RP15 Mullion reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 910PTNNEK00000)	380.46
AC-HID-READ-ICLASS-SE-RP40	RP40 Standard wall switch reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 920PTNNEK00000)	380.46
AC-HID-READ-ICLASS-SE-RP40-AVG	RP40 Standard wall switch reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail; Avigilon logo (HID Part #: 920PTNNEK00000-A001)	380.46
AC-HID-READ-ICLASS-SE-RPK40	RPK40 Standard wall switch reader with keypad input; Wiegand; HID Prox, AWID and EM4102 (32 bits); iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); Mobile IDs via NFC; ISO 14443 UID; Pigtail (HID Part #: 921PTNNEK00000)	659.36
AC-HID-READ-MAXIPROX	MaxiProx Long Range Proximity Reader (HID # 5375AGN00)	895.74
AC-HID-READ-MCLASS-SE-CSN-WG-920PTNNEK0050X	RDR, RP40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOSMIFSPR, WIEG, PIG, BLK, STD-1, LED RED, FLISH OFF, BZR ON, OPT TAMP, OPEN COLL, CSN MIF SUPPR, FSK PROX READ ONLY, PROX PRIORITY, IPM OFF (HID Part #: 920PTNNEK0050X)	383.15
AC-HID-READ-MCLASS-SE-INDALA-900LTNNEK00017	RDR, RP10, MULTICLASS, SE E, LF CST, HF STD/SIO/SEOS, SE INDALA MODULE, WIEG, PIG, BLK, STD-1, LED RED, FLISH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, IPM OFF (HID Part #: 900LTNNEK00017)	240.17
AC-HID-READ-MCLASS-SE-INDALA-910LTNNEK00017	RDR, RP15, MULTICLASS, SE E, LF CST, HF STD/SIO/SEOS, SE INDALA MODULE, WIEG, PIG, BLK, STD-1, LED RED, FLISH GRN, BZR ON, CSN 32-BIT MSB, IPM OFF (HID Part #: 910LTNNEK00017)	383.15
AC-HID-READ-MCLASS-SE-INDALA-920LTNNEK00017	RDR, RP40, MULTICLASS, SE E, LF CST, HF STD/SIO/SEOS, SE INDALA MODULE, WIEG, PIG, BLK, STD-1, LED RED, FLISH GRN, BZR ON, CSN 32-BIT MSB, IPM OFF (HID Part #: 920LTNNEK00017)	383.15
AC-HID-READ-MCLASS-SE-INDALA-921LTNNEK00027	RDR, RPK40, MULTICLASS, SE E, LF CST, HF STD/SIO/SEOS, SE INDALA MODULE, WIEG, PIG, BLK, STD-1, LED OFF, FLISH OFF, BZR ON, CSN 32-BIT MSB, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF (HID Part #: 921LTNNEK00027)	662.08
AC-HID-READ-MCLASS-SE-MOB-OSDP-900PMPNEKEA007	R10 Mini-mullion reader; OSDP; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 900PMPNEKEA007)	334.08
AC-HID-READ-MCLASS-SE-MOB-OSDP-900PMPNEKMA007	RDR, RP10, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, 485HDX, A/V OFF, OSDP V1, PIG, BLK, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF, MOBILE-READY (HID Part #: 900PMPNEKMA007)	332.78
AC-HID-READ-MCLASS-SE-MOB-OSDP-900PMPTEKEA007	R10 Mini-mullion reader; OSDP; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 900PMPTEKEA007)	334.08

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-READ-MCLASS-SE-MOB-OSDP-900PMPTEKMA007	RDR, RP10, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, OSDP, TERM, BLK, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 900PMPTEKMA007)	332.78
AC-HID-READ-MCLASS-SE-MOB-OSDP-910PMPNEKEA007	R15 Mullion reader; OSDP; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 910PMPNEKEA007)	477.13
AC-HID-READ-MCLASS-SE-MOB-OSDP-910PMPNEKMA007	RDR, RP15, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, OSDP, PIG, BLK, A/V OFF, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 910PMPNEKMA007)	475.79
AC-HID-READ-MCLASS-SE-MOB-OSDP-910PMPTEKEA007	R15 Mullion reader; OSDP; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 910PMPTEKEA007)	477.13
AC-HID-READ-MCLASS-SE-MOB-OSDP-910PMPTEKMA007	RDR, RP15, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, OSDP, TERM, BLK, A/V OFF, OSDP V1, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF, NO CST SPC KEYS, MOBILE-READY (HID Part #: 910PMPTEKMA007)	475.79
AC-HID-READ-MCLASS-SE-MOB-OSDP-920PMPNEKEA007	R40 Standard wall switch reader; OSDP; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 920PMPNEKEA007)	477.13
AC-HID-READ-MCLASS-SE-MOB-OSDP-920PMPNEKMA007	RDR, RP40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, OSDP, PIG, BLK, A/V OFF, OSDP V1, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF, MOBILE READY (HID Part #: 920PMPNEKMA007)	475.79
AC-HID-READ-MCLASS-SE-MOB-OSDP-920PMPTEKEA007	R40 Standard wall switch reader; OSDP; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 920PMPTEKEA007)	477.13
AC-HID-READ-MCLASS-SE-MOB-OSDP-920PMPTEKMA007	RDR, RP40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, OSDP, TERM, BLK, A/V OFF, OSDP V1, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, UART OFF, WIEG OFF, MOBILE READY (HID Part #: 920PMPTEKMA007)	475.79
AC-HID-READ-MCLASS-SE-MOB-OSDP-921PMPNEKEA008	RK40 Standard wall switch reader with keypad input; OSDP; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 921PMPNEKEA008)	754.71
AC-HID-READ-MCLASS-SE-MOB-OSDP-921PMPNEKMA008	RDR, RPK40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, OSDP, PIG, BLK, A/V OFF, OSDP V1, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, KPF, ASCII, BFFRD 1 KEY, IPM OFF, UART OFF, WIEG OFF, MOBILE READY (HID Part #: 921PMPNEKMA008)	754.71
AC-HID-READ-MCLASS-SE-MOB-OSDP-921PMPTEKEA008	RK40 Standard wall switch reader with keypad input; OSDP; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 921PMPTEKEA008)	754.71
AC-HID-READ-MCLASS-SE-MOB-OSDP-921PMPTEKMA008	RDR, RPK40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, OSDP, TERM, BLK, A/V OFF, OSDP V1, OPT TAMP, OC, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, CSN 32-BIT MSB, EM4102 32-BIT, KPF, ASCII, BFFRD 1 KEY, IPM OFF, UART OFF, WIEG OFF, MOBILE READY (HID Part #: 921PMPTEKMA008)	754.71
AC-HID-READ-MCLASS-SE-MOB-WG-900PBNNEK20000	RDR, RP10, MULTICLASS, SE E, LF FSK ONLY, HF SEOS, WIEG, PIG, BLK, STD-2, LED RED, FLSH GRN, BZR ON, VAR BIT OUTPUT PER SIO, IPM OFF, VEL ON, MOBILE READY (HID Part #: 900PBNNEK20000)	332.78
AC-HID-READ-MCLASS-SE-MOB-WG-900PBNTEK20000	RDR, RP10, MULTICLASS, SE E, LF FSK ONLY, HF SEOS, WIEG, TERM, BLK, STD-2, LED RED, FLSH GRN, BZR ON, VAR BIT OUTPUT PER SIO, IPM OFF, VEL ON, MOBILE READY (HID Part #: 900PBNTEK20000)	332.78
AC-HID-READ-MCLASS-SE-MOB-WG-900PMNNEKEA003	R10 Mini-mullion reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 900PMNNEKEA003)	334.08
AC-HID-READ-MCLASS-SE-MOB-WG-900PMNNEKMA003		332.78

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RP10, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, WIEG, PIG, BLK, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 900PMNNEKMA003)	
AC-HID-READ-MCLASS-SE-MOB-WG-900PMNTEKEA003	R10 Mini-mullion reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 900PMNTEKEA003)	334.08
AC-HID-READ-MCLASS-SE-MOB-WG-900PMNTEKMA003	RDR, RP10, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, WIEG, TERM, BLK, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 900PMNTEKMA003)	332.78
AC-HID-READ-MCLASS-SE-MOB-WG-910PBNNEK20000	RDR, RP15, MULTICLASS, SE E, LF STD, HF SEOS/MA, WIEG, PIG, BLK, STD-2, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, I'M ALIVE, VAR OUTPUT PER SIO, IPM OFF, VEL ON, MOBILE READY (HID Part #: 910PBNNEK20000)	475.79
AC-HID-READ-MCLASS-SE-MOB-WG-910PMNNEKEA003	R15 Mullion reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 910PMNNEKEA003)	477.13
AC-HID-READ-MCLASS-SE-MOB-WG-910PMNNEKMA003	RDR, RP15, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, WIEG, PIG, BLK, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 910PMNNEKMA003)	475.79
AC-HID-READ-MCLASS-SE-MOB-WG-910PMNTEKEA003	R15 Mullion reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 910PMNTEKEA003)	477.13
AC-HID-READ-MCLASS-SE-MOB-WG-910PMNTEKMA003	RDR, RP15, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, WIEG, TERM, BLK, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 910PMNTEKMA003)	475.79
AC-HID-READ-MCLASS-SE-MOB-WG-920PBNNEK20000	RDR, RP40, MULTICLASS, SE E, LF FSK ONLY, HF SEOS, WIEG, PIG, BLK, STD-2, LED RED, FLSH GRN, BZR ON, VAR BIT OUTPUT PER SIO, IPM OFF, VEL ON, MOBILE READY (HID Part #: 920PBNNEK20000)	475.79
AC-HID-READ-MCLASS-SE-MOB-WG-920PBNTEK20000	RDR, RP40, MULTICLASS, SE E, LF FSK ONLY, HF SEOS, WIEG, TERM, BLK, STD-2, LED RED, FLSH GRN, BZR ON, VAR BIT OUTPUT PER SIO, IPM OFF, VEL ON, MOBILE READY (HID Part #: 920PBNTEK20000)	475.79
AC-HID-READ-MCLASS-SE-MOB-WG-920PMNNEKEA003	R40 Standard wall switch reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 920PMNNEKEA003)	477.13
AC-HID-READ-MCLASS-SE-MOB-WG-920PMNNEKMA003	RDR, RP40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, WIEG, PIG, BLK, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 920PMNNEKMA003)	475.79
AC-HID-READ-MCLASS-SE-MOB-WG-920PMNTEKEA003	R40 Standard wall switch reader; Wiegand; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 920PMNTEKEA003)	477.13
AC-HID-READ-MCLASS-SE-MOB-WG-920PMNTEKMA003	RDR, RP40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, WIEG, TERM, BLK, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, IPM OFF, MOBILE-READY (HID Part #: 920PMNTEKMA003)	475.79
AC-HID-READ-MCLASS-SE-MOB-WG-921PBNNEK20000	RDR, RPK40, MULTICLASS, SE E, LF FSK ONLY, HF SEOS, WIEG, PIG, BLK, STD-2, LED RED, FLSH GRN, BZR ON, VAR BIT OUTPUT PER SIO, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, VEL ON, MOBILE READY (HID Part #: 921PBNNEK20000)	754.71
AC-HID-READ-MCLASS-SE-MOB-WG-921PBNTEK20000	RDR, RPK40, MULTICLASS, SE E, LF FSK ONLY, HF SEOS, WIEG, TERM, BLK, STD-2, LED RED, FLSH GRN, BZR ON, VAR BIT OUTPUT PER SIO, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, VEL ON, MOBILE READY (HID Part #: 921PBNTEK20000)	754.71
AC-HID-READ-MCLASS-SE-MOB-WG-921PMNNEKEA004	RK40 Standard wall switch reader with keypad input; Wiegand; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Pigtail (HID Part #: 921PMNNEKEA004)	754.71

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-READ-MCLASS-SE-MOB-WG-921PMNNEKMA004	RDR, RPK40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, WIEG, PIG, BLK, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, MOBILE-READY (HID Part #: 921PMNNEKMA004)	754.71
AC-HID-READ-MCLASS-SE-MOB-WG-921PMNTEKEA004	RK40 Standard wall switch reader with keypad input; Wiegand; HID Prox, AWID and EM4102 (32 bits); Mobile IDs via NFC and Bluetooth Smart; iCLASS Seos, SE, SR, Standard; MIFARE Classic (SIO), MIFARE DESFire EV1 (SIO); ISO 14443 UID; Mobile enabled; Terminal Strip (HID Part #: 921PMNTEKEA004)	754.71
AC-HID-READ-MCLASS-SE-MOB-WG-921PMNTEKMA004	RDR, RPK40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/MA, WIEG, TERM, BLK, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, CSN 32-BIT MSB, EM4102 32-BIT, KPF, BFFRD 1 KEY, NO PAR, 4 BIT MSG, IPM OFF, MOBILE READY (HID Part #: 921PMNTEKMA004)	754.71
AC-HID-READ-MCLASS-SE-PROX-WG-900PTNTEK00000	RDR, RP10, MULTICLASS, SE REV E, STD PROX, STD, WIEGAND, TERM, BLK, STD 1 SECURITY, LED RED, FLASH GRN, BZR ON, IPM OFF, 32 BIT (HID Part #: 900PTNTEK00000)	240.17
AC-HID-READ-MCLASS-SE-PROX-WG-910PTNTEK00000	RDR, RP15, MULTICLASS, SE REV E, STD PROX, STD, WIEGAND, TERM, BLK, STD 1 SECURITY, LED RED, FLASH GRN, BZR ON, IPM OFF, 32 BIT (HID Part #: 910PTNTEK00000)	383.15
AC-HID-READ-MCLASS-SE-PROX-WG-920PTNTEK00000	RDR, RP40, MULTICLASS, SE REV E, STD PROX, STD, WIEGAND, TERM, BLK, STD 1 SECURITY, LED RED, FLASH GRN, BZR ON, IPM OFF, 32 BIT (HID Part #: 920PTNTEK00000)	383.15
AC-HID-READ-MCLASS-SE-PROX-WG-921PTNTEK00000	RDR, RPK40, MULTICLASS, SE REV E, KPD, STD PROX, STD, WIEGAND, TERM, BLK, STD 1 SECURITY, LED RED, FLASH GRN, BZR ON, IPM OFF, KPF-4-BIT, 32 BIT (HID Part #: 921PTNTEK00000)	662.08
AC-HID-READ-MCLASS-WIEG-900PTNNEKE0000	RDR, RP10, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, WIEG, PIG, BLK, STD-1, ELITE, LED RED, FLSH GRN, BZR OFF, IPM OFF (HID Part #: 900PTNNEKE0000)	240.17
AC-HID-READ-MCLASS-WIEG-910PTNNEKE0000	RDR, RP15, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, WIEG, PIG, BLK, ELITE KEYS, LED RED, FLSH GRN, BZR ON, CSN 32-BIT MSB, IPM OFF (HID Part #: 910PTNNEKE0000)	383.15
AC-HID-READ-MCLASS-WIEG-920PTNNEKE0000	RDR, RP40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, WIEG, PIG, BLK, ELITE KEYS, LED RED, FLSH GRN, BZR ON, CSN 32-BIT MSB, IPM OFF (HID Part #: 920PTNNEKE0000)	383.15
AC-HID-READ-MCLASS-WIEG-921PTNNEKE0000	RDR, RPK40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS, WIEG, PIG, BLK, ELITE KEYS, LED RED, FLSH GRN, BZR ON, CSN 32-BIT MSB, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF (HID Part #: 921PTNNEKE0000)	662.08
AC-HID-READ-MINIPROX	MiniProx Proximity Reader (HID # 5365EKP00)	307.90
AC-HID-READ-OMNIKEY-R54270101	5427 CK standard omnikey USB Enrollment reader, iCLASS Seos®, HID Prox®, iCLASS SE®, MIFARE Classic® and MIFARE® DESFire® EV1; supports NFC (HID Part Number: R54270001)	383.22
AC-HID-READ-PROXPRO	ProxPro Proximity Reader (HID # 5355AGN00)	347.33
AC-HID-READ-PROXPRO-KEYPD	ProxPro Proximity Reader with Keypad (HID # 5355AGK00)	548.36
AC-HID-READ-PROXPROII	ProxPro II Proximity Reader (HID # 5455BKN00)	314.27
AC-HID-READ-THINLINE	ThinLine II Switch Plate Proximity Reader (HID # 5395CK100)	314.27
AC-HID-READ-U90-ICLASS-SE-RDRSEU908K00000	RDR, U90, ICLASS, SE REV E, NO PROX, UHF, 865-868 MHZ, STD, WIEGAND, TERM, BK, STD 1 SECURITY (HID Part Number: RDRSEU908K00000)	1,437.40
AC-HID-READ-U90-ICLASS-SE-RDRSEU909K00000	RDR, U90, ICLASS, SE REV E, NO PROX, UHF, 902-928 MHZ, STD, WIEGAND, TERM, BK, STD 1 SECURITY	1,437.40
AC-HID-READER-SIGNO-20KNKS-00-000000	Signo20K, Mullion w/Keypad, 13.56mHz & 125kHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE	610.90
AC-HID-READER-SIGNO-20KNKS-00-000000-AVG	Signo20K, Mullion w/Keypad, Standard Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, Avigilon Logo	607.76
AC-HID-READER-SIGNO-20KNKS-01-000000	Signo20K, Mullion w/Keypad, Seos Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE	523.45
AC-HID-READER-SIGNO-20KNKS-01-00001H	Signo20K, Mullion w/Keypad, Seos Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE	523.45
AC-HID-READER-SIGNO-20KNKS-02-000000	Signo20K, Mullion w/Keypad, 13.56mHz Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE	567.19
AC-HID-READER-SIGNO-20KNKS-02-000000-AVG	Signo20K, Mullion w/Keypad, Smart Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, Avigilon Logo	672.87
AC-HID-READER-SIGNO-20KNKS-02-0002BL		567.19

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	Signo20K, Mullion w/Keypad, 13.56mHz Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	
AC-HID-READER-SIGNO-20KNKS-T0-000000	Signo20K, Mullion w/Keypad, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY STANDARD CREDENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 20K PIGTAIL MODEL - Profile T0 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO), MIFARE DESFire EV1/EV2 (CSN), MIFARE Classic (CSN)	650.49
AC-HID-READER-SIGNO-20KNKS-T1-000000	Signo20K, Mullion w/Keypad, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY SEOS CREDENTIAL PROFILE OPTION (T1) FOR THE SIGNO READER 20K PIGTAIL MODEL - Profile T1 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos	557.56
AC-HID-READER-SIGNO-20KNKS-T2-000000	Signo20K, Mullion w/Keypad, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY SMART CREDENTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 20K PIGTAIL MODEL - Profile T2 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO)	604.03
AC-HID-READER-SIGNO-20KTKS-00-000000	Signo20K, Mullion w/Keypad, 13.56mHz &125kHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE	610.90
AC-HID-READER-SIGNO-20KTKS-00-000000-AVG	Signo20K, Mullion w/Keypad, Standard Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	607.76
AC-HID-READER-SIGNO-20KTKS-01-000000	Signo20K, Mullion w/Keypad, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	523.45
AC-HID-READER-SIGNO-20KTKS-01-000000-AVG	Signo20K, Mullion w/Keypad, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	523.45
AC-HID-READER-SIGNO-20KTKS-01-00001H	Signo20K, Mullion w/Keypad, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	523.45
AC-HID-READER-SIGNO-20KTKS-02-000000	Signo20K, Mullion w/Keypad, 13.56mHz Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	567.19
AC-HID-READER-SIGNO-20KTKS-02-000000-AVG	Signo20K, Mullion w/Keypad, Smart Profile, OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	564.35
AC-HID-READER-SIGNO-20KTKS-02-0002BL	Signo20K, Mullion w/Keypad, 13.56mHz Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	567.19
AC-HID-READER-SIGNO-20KTKS-T0-000000	Signo20K, Mullion w/Keypad, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY STANDARD CREDENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 20K TERMINAL STRIP MODEL - Profile T0 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO), MIFARE DESFire EV1/EV2 (CSN), MIFARE Classic (CSN)	650.49
AC-HID-READER-SIGNO-20KTKS-T1-000000	Signo20K, Mullion w/Keypad, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY SEOS CREDENTIAL PROFILE OPTION (T1) FOR THE SIGNO READER 20K TERMINAL STRIP MODEL - Profile T1 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos	557.56
AC-HID-READER-SIGNO-20KTKS-T2-000000	Signo20K, Mullion w/Keypad, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY SMART CREDENTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 20K TERMINAL STRIP MODEL - Profile T2 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO)	604.03
AC-HID-READER-SIGNO-20NKS-00-000000	Signo20, Mullion, 13.56mHz &125kHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE	359.50
AC-HID-READER-SIGNO-20NKS-00-000000-AVG	Signo20, Mullion, Standard Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, Avigilon Logo	358.15
AC-HID-READER-SIGNO-20NKS-01-000000	Signo20, Mullion, Seos Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	272.05
AC-HID-READER-SIGNO-20NKS-01-00001H	Signo20, Mullion, Seos Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	272.05
AC-HID-READER-SIGNO-20NKS-02-000000	Signo20, Mullion, 13.56mHz Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	315.76
AC-HID-READER-SIGNO-20NKS-02-000000-AVG	Signo20, Mullion, Smart Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, Avigilon Logo	314.71
AC-HID-READER-SIGNO-20NKS-02-0002BL	Signo20, Mullion, 13.56mHz Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	315.76

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-READER-SIGNO-20NKS-T0-000000	Signo20, Mullion, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY STANDARD CREDENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 20 PIGTAIL MODEL - Profile T0 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO), MIFARE DESFire EV1/EV2 (CSN), MIFARE Classic (CSN)	383.33
AC-HID-READER-SIGNO-20NKS-T1-000000	Signo20, Mullion, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY SEOS CREDENTIAL PROFILE OPTION (T1) FOR THE SIGNO READER 20 PIGTAIL MODEL - Profile T1 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos	290.40
AC-HID-READER-SIGNO-20NKS-T2-000000	Signo20, Mullion, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY SMART CREDENTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 20 PIGTAIL MODEL - Profile T2 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO)	336.87
AC-HID-READER-SIGNO-20TKS-00-000000	Signo20, Mullion, 13.56mHz & 125kHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE	359.50
AC-HID-READER-SIGNO-20TKS-00-000000-AVG	Signo20, Mullion, Standard Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	358.15
AC-HID-READER-SIGNO-20TKS-01-000000	Signo20, Mullion, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	272.05
AC-HID-READER-SIGNO-20TKS-01-000000-AVG	Signo20, Mullion, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	271.32
AC-HID-READER-SIGNO-20TKS-01-00001H	Signo20, Mullion, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	272.05
AC-HID-READER-SIGNO-20TKS-01-00001H-AVG	Signo20, Mullion, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	272.05
AC-HID-READER-SIGNO-20TKS-02-000000	Signo20, Mullion, 13.56mHz Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	315.76
AC-HID-READER-SIGNO-20TKS-02-000000-AVG	Signo20, Mullion, Smart Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	314.71
AC-HID-READER-SIGNO-20TKS-02-0002BL	Signo20, Mullion, 13.56mHz Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	315.76
AC-HID-READER-SIGNO-20TKS-T0-000000	Signo20, Mullion, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY STANDARD CREDENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 20 TERMINAL STRIP MODEL - Profile T0 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO), MIFARE DESFire EV1/EV2 (CSN), MIFARE Classic (CSN)	383.33
AC-HID-READER-SIGNO-20TKS-T1-000000	Signo20, Mullion, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY SEOS CREDENTIAL PROFILE OPTION (T1) FOR THE SIGNO READER 20 TERMINAL STRIP MODEL - Profile T1 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos	290.40
AC-HID-READER-SIGNO-20TKS-T2-000000	Signo20, Mullion, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY SMART CREDENTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 20 TERMINAL STRIP MODEL - Profile T2 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO)	336.87
AC-HID-READER-SIGNO-40KNKS-00-000000	Signo40K, Wall mount w/Keypad, 13.56mHz & 125kHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE	610.90
AC-HID-READER-SIGNO-40KNKS-00-000000-AVG	Signo40K, Wall mount w/Keypad, Standard Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, Avigilon Logo	607.76
AC-HID-READER-SIGNO-40KNKS-01-000000	Signo40K, Wall mount w/Keypad, Seos Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	523.45
AC-HID-READER-SIGNO-40KNKS-01-00001H	Signo40K, Wall mount w/Keypad, Seos Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	523.45
AC-HID-READER-SIGNO-40KNKS-02-000000	Signo40K, Wall mount w/Keypad, 13.56mHz Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	567.19
AC-HID-READER-SIGNO-40KNKS-02-000000-AVG	Signo40K, Wall mount w/Keypad, Smart Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, Avigilon Logo	564.35
AC-HID-READER-SIGNO-40KNKS-02-0002BL	Signo40K, Wall mount w/Keypad, 13.56mHz Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	567.19

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-READER-SIGNO-40KNKS-T0-000000	Signo40K, Wall mount w/Keypad, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY STANDARD CREDENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 40K PIGTAIL MODEL - Profile T0 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO), MIFARE DESFire EV1/EV2 (CSN), MIFARE Classic (CSN)	650.49
AC-HID-READER-SIGNO-40KNKS-T1-000000	Signo40K, Wall mount w/Keypad, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY SEOS CREDENTIAL PROFILE OPTION (T1) FOR THE SIGNO READER 40K PIGTAIL MODEL - Profile T1 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos	557.56
AC-HID-READER-SIGNO-40KNKS-T2-000000	Signo40K, Wall mount w/Keypad, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY SMART CREDENTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 40K PIGTAIL MODEL - Profile T2 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO)	604.03
AC-HID-READER-SIGNO-40KTKS-00-000000	Signo40K, Wall mount w/Keypad, 13.56mHz &125kHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE	610.90
AC-HID-READER-SIGNO-40KTKS-00-000000-AVG	Signo40K, Wall mount w/Keypad, Standard Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	607.76
AC-HID-READER-SIGNO-40KTKS-01-000000	Signo40K, Wall mount w/Keypad, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	523.45
AC-HID-READER-SIGNO-40KTKS-01-000000-AVG	Signo40K, Wall mount w/Keypad, Seos Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE, Avigilon Logo	523.45
AC-HID-READER-SIGNO-40KTKS-01-00001H	Signo40K, Wall mount w/Keypad, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	523.45
AC-HID-READER-SIGNO-40KTKS-02-000000	Signo40K, Wall mount w/Keypad, 13.56mHz Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	567.19
AC-HID-READER-SIGNO-40KTKS-02-000000-AVG	Signo40K, Wall mount w/Keypad, Smart Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	564.35
AC-HID-READER-SIGNO-40KTKS-02-0002BL	Signo40K, Wall mount w/Keypad, 13.56mHz Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	567.19
AC-HID-READER-SIGNO-40KTKS-T0-000000	Signo40K, Wall mount w/Keypad, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY STANDARD CREDENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 40K TERMINAL STRIP MODEL - Profile T0 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO), MIFARE DESFire EV1/EV2 (CSN), MIFARE Classic (CSN)	650.49
AC-HID-READER-SIGNO-40KTKS-T1-000000	Signo40K, Wall mount w/Keypad, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY SEOS CREDENTIAL PROFILE OPTION (T1) FOR THE SIGNO READER 40K TERMINAL STRIP MODEL - Profile T1 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos	557.56
AC-HID-READER-SIGNO-40KTKS-T2-000000	Signo40K, Wall mount w/Keypad, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY SMART CREDENTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 40K TERMINAL STRIP MODEL - Profile T2 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO)	604.03
AC-HID-READER-SIGNO-40NKS-00-000000	Signo40, Wall mount, 13.56mHz &125kHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE	370.43
AC-HID-READER-SIGNO-40NKS-00-000000-AVG	Signo40, Wall mount, Standard Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, Avigilon Logo	369.00
AC-HID-READER-SIGNO-40NKS-01-000000	Signo40, Wall mount, Seos Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	282.99
AC-HID-READER-SIGNO-40NKS-01-00001H	Signo40, Wall mount, Seos Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	282.99
AC-HID-READER-SIGNO-40NKS-02-000000	Signo40, Wall mount, 13.56mHz Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	326.70
AC-HID-READER-SIGNO-40NKS-02-000000-AVG	Signo40, Wall mount, Smart Profile, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, Avigilon Logo	325.58
AC-HID-READER-SIGNO-40NKS-02-0002BL	Signo40, Wall mount, 13.56mHz Profile , OSDP/Wiegand, Pigtail, Mobile Ready, BLE	326.70
AC-HID-READER-SIGNO-40NKS-T0-000000	Signo40, Wall mount, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY STANDARD CREDENTIAL PROFILE OPTION (T0) FOR	394.95

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	THE SIGNO READER 40 PIGTAIL MODEL - Profile T0 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO), MIFARE DESFire EV1/EV2 (CSN), MIFARE Classic (CSN)	
AC-HID-READER-SIGNO-40NKS-T1-000000	Signo40, Wall mount, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY SEOS CREDENTIAL PROFILE OPTION (T1) FOR THE SIGNO READER 40 PIGTAIL MODEL - Profile T1 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos	302.03
AC-HID-READER-SIGNO-40NKS-T2-000000	Signo40, Wall mount, 13.56mHz, OSDP/Wiegand, Pigtail, Mobile Ready, BLE, PRIORITY SMART CREDENTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 40 PIGTAIL MODEL - Profile T2 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO)	348.49
AC-HID-READER-SIGNO-40TKS-00-000000	Signo40, Wall mount, 13.56mHz & 125kHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE	370.43
AC-HID-READER-SIGNO-40TKS-00-000000-AVG	Signo40, Wall mount, Standard Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	369.00
AC-HID-READER-SIGNO-40TKS-01-000000	Signo40, Wall mount, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	282.99
AC-HID-READER-SIGNO-40TKS-01-000000-AVG	Signo40, Wall mount, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	282.18
AC-HID-READER-SIGNO-40TKS-01-00001H	Signo40, Wall mount, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	282.99
AC-HID-READER-SIGNO-40TKS-01-00001H-AVG	Signo40, Wall mount, Seos Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	282.99
AC-HID-READER-SIGNO-40TKS-02-000000	Signo40, Wall mount, 13.56mHz Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	326.70
AC-HID-READER-SIGNO-40TKS-02-000000-AVG	Signo40, Wall mount, Smart Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE, Avigilon Logo	325.58
AC-HID-READER-SIGNO-40TKS-02-0002BL	Signo40, Wall mount, 13.56mHz Profile , OSDP/Wiegand, Terminal, Mobile Ready, BLE	326.70
AC-HID-READER-SIGNO-40TKS-T0-000000	Signo40, Wall mount, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY STANDARD CREDENTIAL PROFILE OPTION (T0) FOR THE SIGNO READER 40 TERMINAL STRIP MODEL - Profile T0 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO), MIFARE DESFire EV1/EV2 (CSN), MIFARE Classic (CSN)	394.95
AC-HID-READER-SIGNO-40TKS-T1-000000	Signo40, Wall mount, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY SEOS CREDENTIAL PROFILE OPTION (T1) FOR THE SIGNO READER 40 TERMINAL STRIP MODEL - Profile T1 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos	302.03
AC-HID-READER-SIGNO-40TKS-T2-000000	Signo40, Wall mount, 13.56mHz, OSDP/Wiegand, Terminal, Mobile Ready, BLE, PRIORITY SMART CREDENTIAL PROFILE OPTION (T2) FOR THE SIGNO READER 40 TERMINAL STRIP MODEL - Profile T2 includes the following NFC/BLE/High Frequency only - Seos® (Mobile ID's via NFC/BLE), Seos, iCLASS SE®, iCLASS SR®, iCLASS®, MIFARE DESFire EV1/EV2 (SIO)/EV3, MIFARE Classic (SIO)	348.49
AC-HID-SPACER-05-R10-6132AKB-M	R10 Mini-mullion spacer, black 0.5" with metal plate	32.18
AC-HID-SPACER-05-R15-6132AKC-M	R15 Mullion spacer, black 0.5" with metal plate	32.18
AC-HID-SPACER-05-R40-6132AKT-M	R40 Standard wall switch, black 0.5" with metal plate	32.18
AC-HID-SPACER-05-RK40-6132AKU-M	RK40 Standard wall switch with keypad, black 0.5" with metal plate	32.18
AC-HID-SPACER-10-R40-6132AKE-M	R40 Standard wall switch, black 1.0" with metal plate	32.18
AC-HID-SPACER-SIGNO-20-K-05	HID SIGNO 20 SERIES, 0.5 INCH SPACER, BLACK	28.41
AC-HID-SPACER-SIGNO-40-K-05	HID SIGNO 40 SERIES, 0.5 INCH SPACER, BLACK	28.41
AC-HID-UPGKIT-BLEOSDP-UPG-A-900	R10/RP10 ICLASS/MULTICLASS, SE RDR BLE OSDP UPGRADE KIT, 1 BLE OSDP MODULE, 1 METALIC BACKPLATE STICKER	139.77
AC-HID-UPGKIT-BLEOSDP-UPG-A-910	R15/RP15 ICLASS/MULTICLASS, SE RDR BLE OSDP UPGRADE KIT, 1 BLE OSDP MODULE, 1 METALIC BACKPLATE STICKER	139.77
AC-HID-UPGKIT-BLEOSDP-UPG-A-920	R40/RP40 ICLASS/MULTICLASS, SE RDR BLE OSDP UPGRADE KIT, 1 BLE OSDP MODULE, 1 METALIC BACKPLATE STICKER	139.77
AC-HID-UPGKIT-BLEOSDP-UPG-A-921		139.77

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

Credentials

HID Credentials

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-HID-CARD-2122BGGMNN	COMPOSITE ICLASS/PROX, 16K/16, PROG, F-GLOSS, F-GLOSS, MATCHING ICLASS#, NO SLOT, NO PROX#	15.79
AC-HID-CARD-3000PG1MN	ICLASS 2K/2 SE, PROG, F-GLOSS, B-GLOSS W/MAG, MATCH, NO SLOT, Minimum Order 100 (HID Part Number: 3000PG1MN)	7.66
AC-HID-CARD-3150RGGMNM	COMPOSITE ICLASS PROX SE 2K/2, PROG ICLASS/PROX, F-GLOSS, B-GLOSS, MATCH ICLASS#, NO SLOT, MATCH PROX # MIN ORDER QUANTITY 100	13.91
AC-HID-CARD-ADMIN-SEC9X-CRD-0-005J	Configuration card used to adjust CSN output settings from 32 bit MSB to 56 bit LSB on iCLASS Standard, SE and SEOS readers. (HID #: SEC9X-CRD-0-005J)	45.78
AC-HID-CARD-DUOPROXII-CL	DuoProx II Graphics Quality PVC, Proximity Access Card, w/ Magnetic Stripe, Minimum Order 100 (HID Part Number: 1336LGGMN)	8.11
AC-HID-CARD-ICLASS-2000	iCLASS Contactless Smart Card, 2k bit with 2 application areas, Minimum Order 100 (HID Part Number: 2000PGGMN)	6.18
AC-HID-CARD-ICLASS-2002	iCLASS Contactless Smart Card, 16k bit with 16 application areas, Minimum Order 100 (HID Part Number: 2002PGGMN)	11.22
AC-HID-CARD-ICLASS-2004	iCLASS Contactless Smart Card, 32k bit with 16k/16 + 16k/1 application areas, Minimum Order 100 (HID Part Number: 2004PGGMN)	11.67
AC-HID-CARD-ICLASS-2050	iCLASS Key II Contactless Smart Key Fob 2k bit with 2 application areas, Minimum Order 100 (HID Part Number: 2050PNNMN)	8.06
AC-HID-CARD-ICLASS-2080	iCLASS Clamshell Contactless Smart Card, 2k bit with 2 application areas, Minimum Order 100 (HID Part Number: 2080PMSMV)	4.16
AC-HID-CARD-ICLASS-2100	COMPOSITE ICLASS, 2K/2, PROG, F-GLOSS, F-GLOSS W/ MAG, MATCHING#, Minimum Order 100, (HID Part Number: 2100PG1MN)	8.21
AC-HID-CARD-ICLASS-3000PGGMB	HID ICLASS 2K/2, PROG, SE, F-GLOSS, B-GLOSS W/ BOTH VERT. & HORZ. SLOT INDICATORS, MATCH #, NO SLOT Minimum Order 100 (HID Part Number: 3000PGGMB)	6.20
AC-HID-CARD-ICLASS-3000PGGMV	ICLASS 2K/2 SE, PROG, F-GLOSS, B-GLOSS, MATCH, VERT SLOT, Minimum Order 100 (HID Part Number: 3000PGGMV)	6.18
AC-HID-CARD-ICLASS-3050PGGMN	ICLASS 2K/2 SE, COMPOSITE, PROG, F-GLOSS, B-GLOSS, MATCHING, NO SLOT, Minimum Order 100 (HID Part Number: 3050PGGMN)	6.79
AC-HID-CARD-ICLASS-3350PMSMV	iCLASS SE Clamshell Card, 2k bits with 2 application areas, plain white vineyl with matte finish, HID logo on back, vertical slot punch. Minimum Order 100 (HID Part Number: 3350PMSMV).	4.15
AC-HID-CARD-ICLASS-PROX-2120BG1MNN	iCLASS + Prox Contactless Smart Card, 2k bits with 2 application areas, plain white with gloss finish on front, plain white with magnetic stripe on back, no slot punch (HID #: 2120BG1MNN), Minimum Order 100. Specify programming information for 125kHz Proximity and iCLASS.	15.35
AC-HID-CARD-ICLASS-PROX-2120BGGMNM	iCLASS + Prox Contactless Smart Card, 2k bits with 2 application areas, plain white with gloss finish, no slot punch (HID #: 2120BGGMNM), Minimum Order 100. Specify programming information for 125kHz Proximity and iCLASS.	13.90
AC-HID-CARD-ICLASS-PROX-2120BGGMVM	COMPOSITE ICLASS PROX 2K/2, PROGRAMMED, F-GLOSS, B-GLOSS, MATCHING, VERT SLOT, MATCH 125K #	13.90
AC-HID-CARD-ICLASS-PROX-3150RGGMNM	COMPOSITE ICLASS PROX SE 2K/2, PROG ICLASS/PROX, F-GLOSS, B-GLOSS, MATCH ICLASS#, NO SLOT, NO PROX #	13.90
AC-HID-CARD-ICLASS-SE-3000	iCLASS SE Contactless Smart Card, 2k bit with 2 application areas, Minimum Order 100 (HID Part Number: 3000PGGMN)	6.18
AC-HID-CARD-ICLASS-SE-3000-AVG	iCLASS SE Contactless Smart Card, 2k bit with 2 application areas, Avigilon Format, Avigilon logo on back, Order quantity must be in boxes of 100, no partial boxes allowed, packaged in box of 100 (Stock Item)	6.62
AC-HID-CARD-ICLASS-SE-3000-AVG-NL		6.71

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	iCLASS SE Contactless Smart Card, 2k bit with 2 application areas, Avigilon Format, Without Avigilon logo, Order quantity must be in boxes of 100, no partial boxes allowed, packaged in box of 100 (Stock Item)	
AC-HID-CARD-ICLASS-SE-3002	iCLASS SE Contactless Smart Card, 16k bit with 16 application areas, Minimum Order 100 (HID Part Number: 3002PGGMN)	11.22
AC-HID-CARD-ICLASS-SE-3004	iCLASS SE Contactless Smart Card, 32k bit with 16k/16 + 16k/1 application areas, Minimum Order 100 (HID Part Number: 3004PGGMN)	11.70
AC-HID-CARD-ICLASS-SE-UHF-6011TGGANA	ISO CARD COMPOSITE UHF/ICLASS 16K, PROG, WHITE, LASER MATCHING, 860-960 MHz, Minimum Order 100 (HID Part Number: 6011TGGANA)	13.68
AC-HID-CARD-ICLASS-SE-UHF-6011TGGNNN-001	ISO CARD COMPOSITE UHF/ICLASS 16K, PROG, WHITE, NO #, NO SALES ORDER, 860-960 MHz, Minimum Order 100 (HID Part Number: 6011TGGNNN-001)	14.21
AC-HID-CARD-ICLASS-SE-UHF-6013TGGANN	ISO CARD COMPOSITE UHF/ICLASS 32K, PROG, WHITE, UHF LASER MATCHING, 860-960 MHz Application areas 16k/2+16k/1, Minimum Order 100 (HID Part Number: 6013TGGANN)	14.21
AC-HID-CARD-ICLASS-SE-UHF-6014SGGANN	ISO CARD COMPOSITE UHF/ICLASS 32K, PROG, WHITE, UHF LASER MATCHING, 860-960 MHz Application areas 16k/16+16k/1, Minimum Order 100 (HID Part Number: 6014SGGANN)	14.21
AC-HID-CARD-ICLASS-SEOS-5005PG1MN	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 16K, PROG, F-GLOSS, B-GLOSS W/MAG, MATCHING #, NO SLOT, MIN ORDER QUANTITY 100 (HID Part Number 5005PG1MN)	13.38
AC-HID-CARD-ICLASS-SR-2080	iCLASS SR (note: SR instead of SE is correct for this card) Clamshell Contactless Smart Card, 2k bit with 2 application areas, Minimum Order 100 (HID Part Number: 2080HPMSMV)	4.16
AC-HID-CARD-ICLASS-UHF-600TGGAN	ISO CARD COMPOSITE UHF, PROG, WHITE, LASER MATCHING, 860-960 MHz, Minimum Order 100 (HID Part Number: 600TGGAN)	10.58
AC-HID-CARD-ICLSEOS-ICLASS-PROX-52060PHNGGMNNN	ISO CARD COMPOSITE ICLASS SEOS 8K, ICLASS 2K, PROX, PROG SEOS, PROG STD ICLASS, NO PROX PROG, F-GLOSS, B-GLOSS, MATCH SEOS, NO ICLASS, NO PROX, NO SLOT, Minimum Order 100 (HID Part Number: 52060PHNGGMNNN)	13.31
AC-HID-CARD-ISOPROXII-GRPH	ISOProx II Graphics Quality PVC, Proximity Access Card, Minimum Order 100 (HID Part Number: 1386LGGMN)	7.33
AC-HID-CARD-MIFARE-DESFIRE-EV3-801FPGGAN	HID MIFARE® DESFire® EV3 Card - Compatibility Profile	7.04
AC-HID-CARD-MOB-ADMIN-SEC9X-CRD-MADD	Configuration card which enables the use of the Mobile Configuration App used to adjust Bluetooth range settings on Mobile-Enabled Readers. Require automated onboarding form to be filled. (LINK to Automated Onboarding: https://managedservices.hidglobal.com/faces/maUserOnBoardingStart) (HID Part Number: ADMIN-SEC9X-CRD-MADD)	46.89
AC-HID-CARD-MOB-SEC9X-CRD-E-MKYD	Configuration Card used to personalize and convert a Mobile-Ready reader to a Mobile-Enabled reader. (HID Part #: SEC9X-CRD-E-MKYD)	34.74
AC-HID-CARD-PROXCARDII-CL	ProxCARD II Proximity Access Card (Clam Shell), Minimum Order 100 (HID Part Number: 1326LMSMV)	3.98
AC-HID-CARD-SEOS-5005PGGMN	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 16 KB MEMORY, PROG., F-GLOSS, B-GLOSS, MATCH. ICLASS #, NO SLOT, LAM, Minimum Order 100 (HID Part Number: 5005PGGMN)	11.90
AC-HID-CARD-SEOS-5005PGGSN	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 16 KB MEMORY, PROG., F-GLOSS, B-GLOSS, SEQ. #. ICLASS #, NO SLOT, Minimum Order 100 (HID Part Number: 5005PGGSN)	11.90
AC-HID-CARD-SEOS-5006PG1MN	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8K, SEOS OS LOADED, PROG., F-GLOSS, B-GLOSS, W/MAG, MATCHING ICLASS #, NO SLOT, Minimum Order 100 (HID Part Number: 5006PG1MN)	7.33
AC-HID-CARD-SEOS-5006PGCMN-AVG	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8K, PROG, F-GLOSS, B-AVIGILON, MATCHING #, NO SLOT, CUSTOM AVIGILON PACKAGING-SHRINK WRAP IN LOTS OF 50, PACK 100/BOX, LAM, AVIGILON LOGO, (AVIGILON FORMAT- NO PROGRAMMING INFORMATION REQUIRED)(MOQ 100)(HID - 5006PGCMN)	7.64
AC-HID-CARD-SEOS-5006PGGMN	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8 KB MEMORY, PROG., F-GLOSS, B-GLOSS, MATCH. ICLASS #, NO SLOT, LAM, Minimum Order 100 (HID Part Number: 5006PGGMN)	5.84
AC-HID-CARD-SEOS-5006PGGMN-AVG	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8K, PROG, F-GLOSS, B-GLOSS, MATCHING #, NO SLOT, CUSTOM AVIGILON PACKAGING-SHRINK WRAP IN LOTS OF 50, PACK 100/BOX, LAM, (AVIGILON FORMAT- NO PROGRAMMING INFORMATION REQUIRED)(MOQ 100)(HID - 5006PGGMN) No Logo	7.81

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-CARD-SEOS-5006PGGMNT	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8 KB MEMORY, PROG., F-GLOSS, B-GLOSS, MATCH. ICLASS #, NO SLOT, LAM, 10 PACK, Minimum Order 100 (HID Part Number: 5006PGGMNT)	5.84
AC-HID-CARD-SEOS-5006PGGNN	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8 KB MEMORY, PROG., F-GLOSS, B-GLOSS, NO ICLASS #, NO SLOT, LAM, Minimum Order 100 (HID Part Number: 5006PGGNN)	5.84
AC-HID-CARD-SEOS-5006PGGSN	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8 KB MEMORY, PROG., F-GLOSS, B-GLOSS, SEQ. ICLASS #, NO SLOT, Minimum Order 100 (HID Part Number: 5006PGGSN)	5.84
AC-HID-CARD-SEOS-5006VGGNN	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD 8K, SEOS LOADED, ER PROG., F-GLOSS, B-GLOSS, NO ICLASS #, NO SLOT, Minimum Order 100 (HID Part Number: 5006VGGNN)	5.84
AC-HID-CARD-SEOS-5656PMSAV	SEOS CLAMSHELL 8K CARD, PROG. SEOS, F-MATT, B-HID LOGO, LASER MATCH SEOS#, Minimum Order 100 (HID Part Number: 5656-PMSAV)	5.85
AC-HID-CARD-SEOS-ICLASS-PROX-5105PGGMNN	COMPOSITE ICLASS SEOS PROX 16K, PROG. ICLASS, F-GLOSS, B-GLOSS, MATCH. ICLASS #, NO SLOT, NO PROX #, Minimum Order 100 (HID Part Number: 5105PGGMNN)	15.58
AC-HID-CARD-SEOS-ICLASS-PROX-5105PGGNNN	COMPOSITE ICLASS SEOS PROX 16K, PROG. ICLASS, F-GLOSS, B-GLOSS, NO ICLASS #, NO SLOT, NO PROX #, Minimum Order 100 (HID Part Number: 5105PGGNNN)	15.58
AC-HID-CARD-SEOS-ICLASS-PROX-5105RG1MNM	COMPOSITE ICLASS SEOS PROX 16K, PROG. ICLASS, F-GLOSS, B-GLOSS W/MAG, MATCH. ICLASS #, NO SLOT, MATCH. PROX #, LAM, Minimum Order 100 (HID Part Number: 5105RG1MNM)	17.06
AC-HID-CARD-SEOS-ICLASS-PROX-5105RG1MNN	COMPOSITE ICLASS SEOS PROX 16K, PROG. ICLASS, F-GLOSS, B-GLOSS W/MAG, MATCH. ICLASS #, NO SLOT, MATCH. PROX #, Minimum Order 100 (HID Part Number: 5105RG1MNN)	17.06
AC-HID-CARD-SEOS-ICLASS-PROX-5105RG1NNM	COMPOSITE ICLASS SEOS PROX 16K, PROG. ICLASS/PROX F-GLOSS, B-GLOSS W/MAG, NO ICLASS #, NO SLOT, MATCH. PROX #, LAM, Minimum Order 100 (HID Part Number: 5105RG1NNM)	15.58
AC-HID-CARD-SEOS-ICLASS-PROX-5105RGGMNM	COMPOSITE ICLASS SEOS PROX 16K, PROG. ICLASS, F-GLOSS, B-GLOSS, MATCH. ICLASS #, NO SLOT, MATCH. PROX #, Minimum Order 100 (HID Part Number: 5105RGGMNM)	15.58
AC-HID-CARD-SEOS-ICLASS-PROX-5105RGGMNN	COMPOSITE ICLASS SEOS PROX 16K, PROG. ICLASS, F-GLOSS, B-GLOSS, MATCH. ICLASS #, NO SLOT, NO PROX #, Minimum Order 100 (HID Part Number: 5105RGGMNN)	15.58
AC-HID-CARD-SEOS-ICLASS-PROX-5105RGGNNS	COMPOSITE ICLASS SEOS PROX 16K, PROG. ICLASS, F-GLOSS, B-GLOSS, NO ICLASS #, NO SLOT, SEQ. PROX #, Minimum Order 100 (HID Part Number: 5105RGGNNS)	15.58
AC-HID-CARD-SEOS-ICLASS-PROX-5105RGGSNN	COMPOSITE ICLASS SEOS PROX 16K, PROG. ICLASS, F-GLOSS, B-GLOSS, SEQ. ICLASS #, NO SLOT, NO PROX #, Minimum Order 100 (HID Part Number: 5105RGGSNN)	15.58
AC-HID-CARD-SEOS-ICLASS-PROX-5105VGGNNN	COMPOSITE ICLASS SEOS CONTACTLESS SMART CARD, 16/KG PROX ER PROG, F-GLOSS, B-GLOSS, NO. ICLASS #, NO SLOT, NO PROX #, Minimum Order 100 (HID Part Number: 5105VGGNNN)	15.58
AC-HID-CARD-SEOS-ICLASS-PROX-5106PG1MNN	COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K, PROG. ICLASS , F - GLOSS, B - GLOSS W/MAG, MATCHING ICLASS #, NO SLOT, NO PROX #, LAM, Minimum Order 100 (HID Part Number: 5106PG1MNN)	13.69
AC-HID-CARD-SEOS-ICLASS-PROX-5106PGGMNN	COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K, PROG. ICLASS, NON PROGRAM PROX, F-GLOSS, B-GLOSS, MATCHING ICLASS #, NO SLOT, NO PROX #, Minimum Order 100 (HID Part Number: 5106PGGMNN)	12.22
AC-HID-CARD-SEOS-ICLASS-PROX-5106PGGNNN	COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K, PROG. ICLASS, NON PROGRAM PROX, F-GLOSS, B-GLOSS, NO ICLASS #, NO SLOT, NO PROX #, Minimum Order 100 (HID Part Number: 5106PGGNNN)	12.22
AC-HID-CARD-SEOS-ICLASS-PROX-5106RGGMNM	COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K, PROG. ICLASS/PROX, F-GLOSS, B-GLOSS, MATCH ICLASS #, NO SLOT, MATCH PROX #, Minimum Order 100 (HID Part Number: 5106RGGMNM)	12.22
AC-HID-CARD-SEOS-ICLASS-PROX-5106RGGMNN	COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K, PROG. ICLASS/PROX, F-GLOSS, B-GLOSS, MATCH ICLASS #, NO SLOT, NO PROX #, Minimum Order 100 (HID Part Number: 5106RGGMNN)	12.22
AC-HID-CARD-SEOS-ICLASS-PROX-5106RGGNNN	COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K, ICLASS SIO PROGRAMMED, PROX HID FORMAT, F-GLOSS, B-GLOSS, NO ICLASS #, NO PROX #, NO SLOT, LAM, Minimum Order 100 (HID Part Number: 5106RGGNNN)	12.22

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-CARD-SEOS-ICLASS-PROX-5106VGGNNN	COMPOSITE ICLASS SEOS PROX CONTACTLESS SMART CARD 8K, SEOS LOADED, ER PROG., F-GLOSS, B-GLOSS, NO ICLASS #, NO PROX #, NO SLOT, Minimum Order 100 (HID Part Number: 5106VGGNNN)	12.22
AC-HID-CORP1K-MC-1000	Service fee per card for Corporate 1000 card format. (HID Part Number: MC-1000)	0.46
AC-HID-ELITE-FEE-MC-0036	Service fee, per card, Elite Card Maintenance Fee (HID Part Number: MC-0036)	0.47
AC-HID-FOB-3250PNNMN	ICLASS SE KEYFOB 2K/2, PROG ICLASS, BLACK W/BBLUE HID, MATCH ICLASS #, Minimum Order 100 (HID Part Number: 3250PNNMN)	8.06
AC-HID-FOB-ICLASS-3250PNNMN-AVG	ICLASS SE KEYFOB 2K/2, PROG ICLASS, BLACK W/BBLUE HID, MATCH ICLASS #, Available with Avigilon format, Stock Item, Order quantity must be in boxes of 100, no partial boxes allowed, Packed in box of 100	8.06
AC-HID-FOB-PROXKEYIII-CL	ProxKey III Proximity Access Keyfob, Minimum Order 100 (HID Part Number: 1346LNSMN)	7.92
AC-HID-FOB-SEOS-5266PNNA-AVG	SEOS KEY FOB 8K, PROG SEOS, F-BLACK W/HID ARTWORK, B-BLACK, LASER MATCH SEOS #, (AVIGILON FORMAT - NO PROGRAMMING INFORMATION REQUIRED)(MOQ 100)(HID - 5266PNNA)	7.83
AC-HID-MOB-MID-SUB-CRD	HID Origo Mobile Identities - User licenses - Additional credential format - one time fee. Minimum Order Quantity: 1	110.47
AC-HID-MOB-MID-SUB-T100	HID Origo Mobile Identities - User licenses - initial and renewal. Number of user licenses (maximum number of concurrent users) valid for one year in an HID Origo account (linked to the Organization ID). Please provide the organization and credential access control data format information (Organization ID, Organization Name, MOB or ICE and format: facility/site code, card number range, etc.). Require automated onboarding form to be completed. (LINK to Automated Onboarding: https://managedservices.hidglobal.com/faces/maUserOnBoardingStart). Minimum Order Quantity: 20. (HID Part Number: MID-SUB-T100)	5.90
AC-HID-MOB-MID-SUB-T100-ADD-1-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 1 month. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD1).	0.76
AC-HID-MOB-MID-SUB-T100-ADD-10-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 10 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD10).	7.56
AC-HID-MOB-MID-SUB-T100-ADD-11-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 11 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD11).	8.31
AC-HID-MOB-MID-SUB-T100-ADD-2-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 2 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD2).	1.52
AC-HID-MOB-MID-SUB-T100-ADD-3-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 3 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD3).	2.28
AC-HID-MOB-MID-SUB-T100-ADD-4-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 4 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD4).	3.01
AC-HID-MOB-MID-SUB-T100-ADD-5-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 5 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD5).	3.78

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-MOB-MID-SUB-T100-ADD-6-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 6 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD6).	4.53
AC-HID-MOB-MID-SUB-T100-ADD-7-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 7 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD7).	5.29
AC-HID-MOB-MID-SUB-T100-ADD-8-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 8 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD8).	6.06
AC-HID-MOB-MID-SUB-T100-ADD-9-MONTH	HID Origo Mobile Identity user Account - User license - add-on order cost for 9 months. Number of user accounts (maximum number of concurrent users) valid till the end of the contract of an existing HID Origo account (linked to the Organization ID). Valid HID Org ID, Org Name, Contact ID and subscription start date required at time of order. Minimum Order Quantity: 20 (HID Part Number: MID-SUB-T100-ADD9).	6.81
AC-HID-TAG-ICLASS-SE-3300	iCLASS SE Tag, Contactless Smart Tag , 2k bit with 2 application areas, Black with HID Standard Artwork, Sequential Matching Internal/External – Peel-off self-adhesive back, Minimum Order 100 (HID Part Number: 3300PKSMN)	5.79
AC-HID-TAG-MICROPROX-ADH	MICROPROX TAG, PROG, GRAY, MATCH #, Minimum Order 100 (HID Part Number: 1391LGSMN)	5.33
AC-HID-TAG-PROXPASSII-VEH	ProxPass II Long Range Active Proximity Access Tag for Vehicle Access, Minimum Order 10 (HID Part Number: 1351LBSMN)	45.24

STid Credentials

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-STID-CARD-NONPROGRAMED-CCTW670	NON PROGRAMED 13.56 MHz NXP MIFARE® DESFire® EV2 2K chip - DESFire EV2 2K ISO Card (MOQ 200) - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	5.58
AC-STID-KEYFOB-NONPROGRAMED-PCGW671	NON PROGRAMED 13.56 MHz NXP MIFARE® DESFire® EV2 2K chip - DESFire EV2 2K Keyfob (MOQ 100) - NO LOGO - Requires AC-STID-ARCHITECT-PROGRAMMING-KIT-SECARD-BT for configuration programming	10.44
AC-STID-TAG-UHF-WINDSHIELD-ETA-W75B-574BE10	NON PROGRAMMED UHF GEN2 Self-destroying programable adhesive windshield tag (MOQ 100) Requires AC-STID-SPECTRE-PROGRAMMING-KIT-ULTRYSV2 for configuration programming	5.65

Allegion Credentials

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-ALL-SCH-FOB-9651	Schlage 13.56 MHz smart credential, keyfob, MIFARE Classic, 1K byte/8Kbit, minimum order quantity: 50 (Allegion Part Number: 9651)	6.99
AC-ALL-SCH-FOB-9651T	Schlage 13.56 MHz smart credential, thin keyfob, MIFARE Classic, 1K byte/8Kbit, minimum order quantity: 50 (Allegion Part Number: 9651T)	7.21
AC-ING-CARD-APTIQ-XF7410	Proximity Card Clamshell (Allegion Part Number: XF7410)	3.22
AC-ING-CARD-APTIQ-XF7510	Proximity Card ISO Glossy White (Allegion Part Number: XF7510)	5.41
AC-ING-CARD-APTIQ-XF7510MS	Proximity and Magnetic Stripe Card ISO Glossy White (Allegion Part Number: XF7510MS)	6.23
AC-ING-CARD-APTIQ-XF8420	Schlage (formerly aptiQ™) Smart Card 2K byte/16k bit Clamshell (Allegion Part Number: XF8420)	6.72
AC-ING-CARD-APTIQ-XF8440	Schlage (formerly aptiQ™) Smart Card 4K byte/32k bit Clamshell (Allegion Part Number: XF8440)	7.59
AC-ING-CARD-APTIQ-XF8480	Schlage (formerly aptiQ™) Smart Card 8K byte/64k bit Clamshell (Allegion Part Number: XF8480)	9.29

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-ING-CARD-APTIQ-XF8520	Schlage (formerly aptiQ™) Smart Card 2K byte/16k bit ISO Glossy White (Allegion Part Number: XF8520)	7.32
AC-ING-CARD-APTIQ-XF8520M1	Schlage (formerly aptiQ™) Smart Card 2K byte/16k bit with Magnetic Stripe ISO Glossy White (Allegion Part Number: XF8520M1)	7.98
AC-ING-CARD-APTIQ-XF8540	Schlage (formerly aptiQ™) Smart Card 4K byte/32k bit ISO Glossy White (Allegion Part Number: XF8540)	8.25
AC-ING-CARD-APTIQ-XF8540M1	Schlage (formerly aptiQ™) Smart Card 4K byte/32k bit with Magnetic Stripe ISO Glossy White (Allegion Part Number: XF8540M1)	8.85
AC-ING-CARD-APTIQ-XF8580	Schlage (formerly aptiQ™) Smart Card 8K byte/64k bit ISO Glossy White (Allegion Part Number: XF8580)	9.83
AC-ING-CARD-APTIQ-XF8580M1	Schlage (formerly aptiQ™) Smart Card 8K byte/64k bit with Magnetic Stripe ISO Glossy White (Allegion Part Number: XF8580M1)	10.60
AC-ING-CARD-APTIQ-XF8720	Schlage (formerly Schlage (formerly aptiQ™)™) Smart Card 2K byte/16k bit PVC Patch (Allegion Part Number: XF8720)	6.67
AC-ING-CARD-APTIQ-XF8740	Schlage (formerly Schlage (formerly aptiQ™)™) Smart Card 4K byte/32k bit PVC Patch (Allegion Part Number: XF8740)	7.54
AC-ING-CARD-APTIQ-XF8780	Schlage (formerly Schlage (formerly aptiQ™)™) Smart Card 8K byte/64k bit PVC Patch (Allegion Part Number: XF8780)	9.07
AC-ING-CARD-APTIQ-XF8920	Proximity and Schlage (formerly aptiQ™) Smart Card Combo 2K byte/16k bit ISO Glossy White (Allegion Part Number: XF8920)	10.71
AC-ING-CARD-APTIQ-XF8940	Proximity and Schlage (formerly aptiQ™) Smart Card Combo 4K byte/32k bit ISO Glossy White (Allegion Part Number: XF8940)	11.69
AC-ING-CARD-APTIQ-XF8980	Proximity and Schlage (formerly aptiQ™) Smart Card Combo 8K byte/64k bit ISO Glossy White (Allegion Part Number: XF8980)	13.55
AC-ING-CARD-APTIQ-XF9420	MIFARE Smart Card 2.5k bit Clamshell (Allegion Part Number: XF9420)	4.10
AC-ING-CARD-APTIQ-XF9520	MIFARE Smart Card 2.5 k bit ISO Glossy White (Allegion Part Number: XF9520)	5.14
AC-ING-CARD-APTIQ-XF9520MS	MIFARE Smart Card 2.5 k bit with magnetic stripe ISO Glossy White (Allegion Part Number: XF9520MS)	5.93
AC-ING-CARD-APTIQ-XF9551	MIFARE Contactless Smart Card 1k byte/8k bit ISO Glossy White (Allegion Part Number: XF9551)	6.16
AC-ING-CARD-APTIQ-XF9551MS	MIFARE Contactless ISO Glossy Smart Card 1k byte/8k bit & mag stripe (Allegion Part Number: XF9551MS)	6.96
AC-ING-CARD-APTIQ-XF9558	MIFARE Contactless Smart Card 4k byte/32k bit ISO Glossy White (Allegion Part Number: XF9558)	8.63
AC-ING-CARD-APTIQ-XF9558MS	MIFARE Contactless ISO Glossy Smart Card 4k byte/32k bit and mag stripe (Allegion Part Number: XF9558MS)	9.51
AC-ING-CARD-APTIQ-XF9651	MIFARE Smart 1k bit (minimum order is 50) Keytag (Allegion Part Number: XF9651)	6.99
AC-ING-CARD-APTIQ-XF9751	MIFARE Smart Cards 1k byte/8k bit PVC Patch (Allegion Part Number: XF9751)	6.34
AC-ING-CARD-APTIQ-XF9758	MIFARE Smart Cards 4k byte/32k bit PVC Patch (Allegion Part Number: XF9758)	9.51
AC-ING-CARD-APTIQ-XF9951	Proximity and Contactless Smart Card Combo ISO Glossy White 1k byte/8k bit Card (Allegion Part Number: XF9951)	8.96
AC-ING-CARD-APTIQ-XF9958	Proximity and Contactless Smart Card Combo ISO Glossy White 4k byte/32k bit (Allegion Part Number: XF9958)	10.60
AC-ING-DISK-APTIQ-XF7010	Proximity Sticky Disk (35 mm Disk), minimum order quantity: 50 (Allegion Part Number: XF7010)	5.14
AC-ING-FOB-APTIQ-XF7610	Proximity Keyfob, minimum order quantity: 50 (Allegion Part Number: XF7610)	5.57
AC-SCH-CARD-2420	Allegion Schlage 13.56 MHz smart credential 2420, Clamshell, MIFARE DESFire EV2 ISO 14443, 2K byte/16Kbit, minimum order quantity: 100 (Allegion Part Number: 2420)	6.72
AC-SCH-CARD-2520	Allegion Schlage 13.56 MHz smart credential 2520, ISO glossy white printable composite Material, MIFARE DESFire EV2 ISO 14443, 2K byte/16Kbit, minimum order quantity: 100 (Allegion Part Number: 2520)	7.65
AC-SCH-CARD-2540	Allegion Schlage 13.56 MHz smart credential 2540, ISO glossy white printable composite Material, MIFARE DESFire EV2 ISO 14443, 4K byte/32Kbit, No Slot Punch, minimum order quantity: 100 (Allegion Part Number: 2540)	8.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-SCH-CARD-2540-SPH	Allegion Schlage 13.56 MHz smart credential 2540-SPH, ISO glossy white printable composite Material, MIFARE DESFire EV2 ISO 14443, 4K byte/32Kbit, Horizontal Slot Punch, minimum order quantity: 100 (Allegion Part Number: 2540-SPH)	8.39
AC-SCH-CARD-2540-SPV	Allegion Schlage 13.56 MHz smart credential 2540-SPV, ISO glossy white printable composite Material, MIFARE DESFire EV2 ISO 14443, 4K byte/32Kbit, Vertical Slot Punch, minimum order quantity: 100 (Allegion Part Number: 2540-SPV)	8.39
AC-SCH-CARD-2920	Allegion Schlage 125 kHz/13.56 MHz multi-technology credentials 2920, ISO glossy white printable composite Material, Proximity/MIFARE DESFire EV2 ISO 14443, 2K byte/8K bit, minimum order quantity: 100 (Allegion Part Number: 2920)	10.67
AC-SCH-CARD-8543	Schlage 13.56 MHz Smart credential ISO glossy white 4K byte/32k bit card (minimum order 100)	7.11
AC-SCH-CARD-8543M1	Schlage MIFARE DESFire EV3 4K byte/32K bit with Magnetic Stripe ISO Glossy White (minimum order 100)	7.27
AC-SCH-CARD-MT-8943	Schlage Multi-technology credential, 125 kHz + 13.56 MHz, Proximity and Schlage MIFARE DESFire EV3 4K byte/32K bit ISO Glossy White Card, No Slot Punch (Minimum order 100)	10.44
AC-SCH-FOB-2620T	Allegion Schlage 13.56 MHz smart credential 2620T, Thin keyfob, MIFARE DESFire EV2 ISO 14443, 2K byte/16K bit, minimum order quantity: 100 (Allegion Part Number: 2620T)	7.58
AC-SCH-FOB-8643T	Schlage 13.56 MHz Smart credential Thin keyfob 4K byte/32k bit card (minimum order 100)	7.44
AC-SCH-FOB-MT-8843T	Schlage Multi-technology credential, 125 kHz + 13.56 MHz, Proximity and Schlage MIFARE DESFire EV3 4K byte/32K bit, Thin keyfob, keyring hole (Minimum order 100)	11.19

Farpointe Data Credentials

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-FP-CARD-CONEKT-CSM-2P	CONEKT™ High-security ISO-style composite card	7.60
AC-FP-CARD-CSC-2	High-security clamshell-style card; MIFARE® DESFire® EV2	7.48
AC-FP-CARD-CSM-2S	CONEKT™ Credential High-security ISO-style composite card with HiCo (2750Oe) magnetic stripe	7.79
AC-FP-CARD-DC1-1	DC1-1 Delta Clamshell Contactless Smartcard - ISO14443-compliant, clamshell-style contactless smartcard card with a 1K-byte memory. Constructed of durable ABS, it is backed by a lifetime warranty. Memory of the model number DC4-1 is 4K-bytes (Minimum order is 50) (Farpointe Data Part Number: DC1-1)	4.67
AC-FP-CARD-DC4-1	DC4-1 Delta Clamshell Contactless Smartcard - ISO14443-compliant, clamshell-style contactless smartcard card with a 4K-byte memory. Constructed of durable ABS, it is backed by a lifetime warranty (Minimum order is 50) (Farpointe Data Part Number: DC4-1)	6.25
AC-FP-CARD-DE2	DE2 MIFARE® DESFire® EV1 SMARTCARD, Frequency: 13.56 MHz, Read Range: Up to 2.5 inches (64 mm) (Farpointe Data Part Number: DE2)	9.42
AC-FP-CARD-DM1-3	DM1-3 Delta ISO Contactless Smartcard - ISO14443-compliant, contactless smartcard card with a 1K-byte memory. Manufactured from glossy PVC, it is appropriate for dye sublimation imaging (ISO style) (Minimum order is 50) (Farpointe Data Part Number: DM1-3)	4.94
AC-FP-CARD-DM1-3S	DM1-3S Delta ISO Contactless Smartcard - ISO14443-compliant, contactless smartcard card with a 1K-byte memory. Manufactured from glossy PVC, it is appropriate for dye sublimation imaging (ISO style) - with a magnetic stripe (Minimum order is 50) (Farpointe Data Part Number: DM1-3S)	5.44
AC-FP-CARD-DM4-3	DM4-3 Delta ISO Contactless Smartcard - ISO14443-compliant, contactless smartcard card with a 4K-byte memory. Manufactured from glossy PVC, it is appropriate for dye sublimation imaging (ISO style) (Minimum order is 50) (Farpointe Data Part Number: DM4-3)	6.66
AC-FP-CARD-DM4-3S	DM4-3S Delta ISO Contactless Smartcard - ISO14443-compliant, contactless smartcard card with a 4K-byte memory. Manufactured from glossy PVC, it is appropriate for dye sublimation imaging (ISO style) - with a magnetic stripe (Minimum order is 50) (Farpointe Data Part Number: DM4-3S)	7.59
AC-FP-CARD-PSC-1-H		2.63

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	PSC-1 Standard Light Proximity Card - Clamshell style proximity card backed by a lifetime warranty (Minimum order is 50) (Farpointe Data Part Number: PSC-1-H)	
AC-FP-CARD-PSI-4-H	PSI-4 Image Technology Proximity Card - Thicker-format (0.046 inches (1.17 mm)) proximity card appropriate for dye sublimation imaging (Minimum order is 50) (Farpointe Data Part Number: PSI-4-H)	3.26
AC-FP-CARD-PSM-2P-H	PSM-2P Multi Technology Proximity Card - ISO-style multi technology proximity card appropriate for dye sublimation imaging (Minimum order is 50) (Farpointe Data Part Number: PSM-2P-H)	5.48
AC-FP-CARD-PSM-2S-H	PSM-2S Multi Technology Proximity Card - ISO-style multi technology style proximity card appropriate for dye sublimation imaging with a magnetic stripe (Minimum order is 50) (Farpointe Data Part Number: PSM-2S-H)	5.97
AC-FP-CONEKT-CMC-2-25	CONEKT Credentials, 2.4-GHz Mobile supporting BLE-enabled smartphones, 25 Pack with QR Code	180.54
AC-FP-FOB-CSK-2	High-security key fob-style tag; MIFARE® DESFire® EV2	8.58
AC-FP-FOB-DK1-3	DK1-3 Delta Keyfob Contactless Smartcard Credential - ISO14443-compliant key tag-style contactless smartcard credential with a 1K-byte memory. It is designed to be carried on a key ring, and includes a brass reinforcing eyelet (Minimum Order 50) (Farpointe Data Part Number: DK1-3)	8.02
AC-FP-FOB-DK4-3	DK4-3 Delta Keyfob Contactless Smartcard Credential - ISO14443-compliant key tag-style contactless smartcard credential with a 4K-byte memory. It is designed to be carried on a key ring, and includes a brass reinforcing eyelet (Minimum Order 50) (Farpointe Data Part Number: DK4-3)	11.42
AC-FP-MOB-CMC-2	CONEKT™ Credential 2.4-GHz Mobile credential supporting BLE-enabled smartphones	7.24
AC-FP-TAG-PDT-1-H	Model PDT-1 Proximity Disc Tag - Has an adhesive on one side that allows for the prox-enabling of a variety of non RFID devices, including ID credentials, cell phones and wallets. The PDT-1 offers a read range up to 3.5 inches (88.9 mm) when used with a P-500. Model P-PDT-1-H is 125 HID kHz compatible, while PDT-1-A is 125 kHz AWID compatible (Minimum order 50) (Farpointe Data Part Number: PDT-1-H)	3.66
AC-FP-TAG-PSK-3-H	PSK-3 Proximity Key Ring Tag - Small proximity tag designed to be carried on a key ring, includes a re-enforcing brass eyelet, and is backed by a lifetime warranty (Minimum order 50) (Farpointe Data Part Number: PSK-3-H)	6.07
AC-FP-TRANS-LONG-RANGE-WRT-2+D2	WRT-2+ Ranger Two Button Long Range Transmitter - 2-button clicker-type access credential, featuring both long range 433 MHz (upon button push) and MIFARE® DESFire® EV2 2K memory smartcard insert 13.56-MHz Smartcard protocols operation. (Farpointe Data Part Number: WRT-2+D2)	43.85
AC-FP-TRANS-LONG-RANGE-WRT-2+S1	Ranger® 433-MHz Long-Range Transmitters, 2-button, with 1K insert. (Farpointe Data Part Number: WRT-2+S1)	44.26
AC-FP-TRANS-LONG-RANGE-WRT-2+S4	Ranger® 433-MHz Long-Range Transmitters, 2-button, with 4K insert. (Farpointe Data Part Number: WRT-2+S4)	47.40
AC-FP-TRANS-LONG-RANGE-WRT-2M	Ranger® 433-MHz Long-Range Transmitters, Mini 2-button, no proximity insert. (Farpointe Data Part Number: WRT-2M)	26.94
AC-FP-TRANS-LONG-RANGE-WRT-4+S4	WRT-2+ Ranger Two Button Long Range Transmitter - 2-button clicker-type access credential, featuring both long range 433 MHz (upon button push) and w/ Farpointe 13.56-MHz 4K memory smartcard insert. (Farpointe Data Part Number: WRT-2+S4)	49.39
AC-FP-TRANS-LONG-RANGE-WRT-4+SI	Ranger® 433-MHz Long-Range Transmitters, 4-button, with 1K insert. (Farpointe Data Part Number: WRT-4+SI)	46.25
AC-FP-TRANS-WRT-2+H	WRT-2+ Ranger Two Button Long Range Transmitter - 2-button clicker-type access credential, featuring both long range 433 MHz (upon button push) and 125 kHz proximity operation. (Farpointe Data Part Number: WRT-2+H)	37.16
AC-FP-TRANS-WRT-4+H	WRT-4+ Ranger Four-Button Long Range Transmitter - 4-button clicker-type access credential, featuring both long range (upon button push) and proximity operation. (Farpointe Data Part Number: WRT-4+H)	38.08

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

Wireless Locks (Contact RSM for pricing)

Allegion Schlage (Contact RSM for pricing)

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-ALL-SCH-AD400-ANT400-REM-CEILING	Omni-Directional Remote Indoor/Outdoor Antenna Module. Includes Antenna, 15' Coax, Coax Whip. For indoor use with PIM400 and/or WRI400.(Allegion Part Number: ANT400-REM-CEILING)	441.55
AC-ALL-SCH-AD400-ANT400-REM-HALL	Bi-Directional Remote Indoor Antenna Module. Includes Antenna, 15' Coax, Coax Whip. For indoor use with PIM400 and/or WRI400.(Allegion Part Number: ANT400-REM-HALL)	628.77
AC-ALL-SCH-AD400-ANT400-REM-I/O+6DB	Omni-Directional Remote Indoor/Outdoor Antenna Module. Includes Antenna, 15' Coax, Coax Whip, Articulated Wall/Post Mounting Hardware. For indoor use with PIM400 and/or WRI400. Requires MGB+MCA5 Antenna Grounding Kit for outdoor applications.(Allegion Part Number: ANT400-REM-I/O+6db)	578.63
AC-ALL-SCH-AD400-MGB+MCA5	Antenna Grounding Kit (for outdoor mounting). Could be used with ANT400-REM-I/O, ANT400-REM-I/O+6DB, ANT400-REM-CEILING, ANT400-REM-HALL.(Allegion Part Number: MGB+MCA5)	207.98
AC-ALL-SCH-COM400L	Electronic Lock Communication Module Kit	399.74
AC-ALL-SCH-COM400P-626	Schlage COM400P Communication Module Kit, Satin chrome	399.74
AC-ALL-SCH-COM400P-643E	Schlage COM400P Communication Module Kit, Aged bronze	399.74
AC-ALL-SCH-ENGAGE-GWE	GWE — ENGAGE Gateway with RS-485 & IP (PoE) connectivity. Supports up to 10 ENGAGE enabled devices with Mercury Security' 1DR and 64DR (AC-MER-CONT-1DR and AC-MER-CONT-64DR Sold Separately) access control panels(Allegion Part Number: GWE – ENGAGE)	627.79
AC-ALL-SCH-PIB300-2D	Panel Interface Board (supports 2 doors)(Allegion Part Number: PIB300-2D)	531.09
AC-ALL-SCH-PIM400-1501-LC	900 MHz Panel Interface Module for 16 door intelligent controller (AC-MER-CONT-LP1501 Sold Separately) for AD Series wireless devices; powered by Mercury Security. Encrypted with AES-128 bit keys, Certifications: FCC Part 15, Industry Canada(IC), RoHS, UL294 Listed when connected to UL294 power supply, Dimensions: 10.43" X 7.28" X 3.79" (26.49cm X 18.49 cm X 9.63 cm), Weight 2.8 lbs (1.27 kg)(Allegion Part Number: PIM400-1501-LC)	1,936.44
AC-ALL-SCH-PIM400-485-RSI	900 MHz Panel Interface Module for 16 or 64 door intelligent controller (AC-MER-CONT-LP1501, AC-MER-CONT-LP1502, AC-MER-CONT-LP2500 and AC-MER-CONT-LP4502 Sold Separately) (Up to 16 wireless access devices such as AD-400 locks per PIM) for AD Series wireless devices; powered by Mercury Security. Certifications: NEMA 1, 4, 4X, 6; UL 294; FCC Part 15; Industry Canada (IC); RoHS, Dimensions (H x W x D): 6.3" x 3.2" x 2.2" (16.0 cm x 8.13 cm x 5.59 cm), Weight 1.25 lbs (.56 kg)(Allegion Part Number: PIM400-485-RSI)	1,611.91
AC-ALL-SCH-PIM400-TD2	Panel Interface Module (supports 2 doors) Wiegand (Data1/Data2) or magnetic stripe (Clock & Data) output. Includes Weatherproof Enclosure (7.1" x 7.1"), Internal Antenna with ability to add Remote Antenna. Requires 12 or 24 VDC power supply. Relay Board sold separately. (Allegion Part Number: PIM400-TD2)	935.34
AC-ALL-SCH-RLBD	Relay Board (for PIB300-2D or PIM400-TD2)(Allegion Part Number: RLBD)	268.80
AC-ALL-SCH-WPR400-MTK	Wireless Portable Reader with keypad (with Multi-Technology Reader Module) Handheld, battery operated unit with Multi-Technology(Allegion Part Number: WPR400-MTK)	2,252.71
AC-SCH-BATTERY-8B-626	AD-400 Eight (8) battery conversion kit in grey (Allegion Schlage Part #: 8B-626).	109.28
AC-SCH-COM300L-643E	Communication Module Kit for AD-300 Classroom/Storeroom (70) function. Compatible with Cylindrical, Mortise, Mortise with deadbolt, 993 exit trim chassis. Aged bronze finish.	369.65
AC-SCH-COM400L-626	Wireless AD-400 Communication Kit Module Cover with Indicator	398.48
AC-SCH-READ-MODULE-MT-626	AD-400 Multi-Technology reader module in grey (Allegion Part #: MT-626).	783.02

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-SCH-READ-MODULE-SI-626	AD-400 Smart Technology iClass compatible reader module in grey (Allegion Part #: SI-626).	908.79
AC-SCH-READ-MODULE-SIK-626	AD-400 Smart Technology iClass compatible reader + keypad module in grey (Allegion Part #: SIK-626).	972.64
AC-SCH-TK400	Wireless Test Kit, Pre-Installed Test Kit; Complete with WPR400-DT, PIM400-TD2, 593PI, Power Supply, Charger, Carrying Case.	1,906.54

ASSA ABLOY Aperio

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-AA-APA-10-PC	ASSA ABLOY Aperio Programming Application Tool Kit APA-10-PC, Includes USB Flash Drive, Programming Application Tool Software and License Files, Aperio Instructions (electronic files), Triton USB Radio Dongle (APD-10-USB), HID iCLASS/Prox Card	712.28
AC-AA-GEN5-AH20-HUB-AH20W14-NNNN	ASSA ABLOY Aperio® AH20 Standard Gen5 1 to 1 Wiegand Interface Communication Hub for or indoor use. The AH20 interfaces an single ASSA ABLOY Aperio door devices to the Access Control Manager system as a Wiegand interface to controllers and subpanels. Built in tamper switch for detection of removal from bracket. Integrated antenna with the option to mount an external antenna. Encrypted radio communication,.For standard electrical installation boxes. LED for status visualisation	290.09
AC-AA-GEN5-AH40-HUB-AH40IN2	ASSA ABLOY Aperio® AH40 Gen 5 1 to 64 Communication Hub for connection to Access Control Manager system via IP/Ethernet connection. Allows to connect up to 64 Aperio® devices on a single hub, Integrated antenna with the option to mount an external antenna, Encrypted radio communication, TCP/IP communication encrypted using TLS 1.1/1.2, Powered using Power over Ethernet (PoE) or external power supply, For standard electrical installation boxes, LED for status visualisation, Built in tamper switch. Detection of removal from bracket	506.23
AC-AA-HUB-EXT-10-ANT	ASSA ABLOY Aperio® hubs are certified for use with the ASSA ABLOY external (omnidirectional) antenna EXT-10-ANT. The external antenna may be used to obtain more even radio coverage (in the form of a doughnut) around the hub. Please note that the antenna does not extend the maximum range of the Aperio® hub. The Aperio® hubs are for indoor use only; Operating Temperature: 32°F (0 °C) to 113°F (45 °C) and Humidity: < 95% maximum (non-condensing).	78.39
AC-MER-AH30RN1-RC	ASSA ABLOY - Mercury Aperio Hub 1:8-with Avigilon Enablement SW(ASSA ABLOY Part Number: AH30RN1-RC)	461.49
AC-MER-APD-10-USB	ASSA ABLOY - USB Radio Dongle(ASSA ABLOY Part Number: APD-10-USB)	595.10

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

3rd Party Solutions

Visitor Management

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-HID-EL-96000-SVM10	SVM™ (main application) per workstation, includes Free Administrator™(HID Part Number: EL-96000-SVM10)	4,344.40
AC-HID-EL-96300-ADM10	Administrator™ (additional licenses) per workstation(HID Part Number: EL-96300-ADM10)	855.32
AC-HID-EL-97000-EKIOSK	EasyLobby® eKiosk™ Self Registration Software makes it fast and easy for visitors to register themselves upon arrival at a facility using a tablet computer. Runs on Windows®, an Apple® iPad® or an Android® tablet computer. Configurable self-registration screen can support any field including fields designated as required. Provides ability to display PDF or HTML file for visitors to review and acknowledge or agree to terms. Utilizes intuitive touch screen menu. Alerts employee being visited via email when visitor has completed self registration process and is checked-in. Enables badge to be printed upon check-in at the main guard station. Stores visitor record in central database.	3,481.91
AC-HID-EL-98000-EADV10	eAdvance™ (web pre-registration) per web server(HID Part Number: EL-98000-EADV10)	5,280.08
AC-HID-EL-ACI-AVIG	Access Control Integration - Access Control Manager from EasyLobby -Must also purchase Avigilon Rest License (Avigilon Part Number: AC-SW-LIC-REST)	5,172.02
AC-HID-EL-ACI-UPGRD	Access control integration upgrade to latest version(HID Part Number: EL-ACI-UPGRD)	4,242.57
AC-HID-EL-AST-ID150	AssureTec ID-150 (reads driver's license, data and photo capture) (COO: South Korea) (HID # EL-AST-ID150)	3,869.22
AC-HID-EL-AST-ID150A	AssureTec ID-150A (reads/authenticates driver's license, data and photo capture) (COO: South Korea) (HID # EL-AST-ID150A)	5,450.39
AC-HID-EL-AST-UPDATEA	AssureTec PRO software library updates for 1 year (data and authentication) (HID # EL-AST-UPDATEA)	1,236.38
AC-HID-EL-DESKO-ICON	The HID EasyLobby DESKO ICON Scanner's class leading scan technology, developed by DESKO, provides high-resolution and reflection free scans of ID's and passports under white light and IR. The ICON Scanner therefore provides excellent images for OCR data collection. (COO: Germany)	2,420.52
AC-HID-EL-DYMO-30856	DYMO 30856 non-adhesive badges (250)(HID Part Number: EL-DYMO-30856)	74.07
AC-HID-EL-DYMO-30911	DYMO 30911 adhesive self-expiring badges (250)(HID Part Number: EL-DYMO-30911)	126.97
AC-HID-EL-DYMO-450T	Dymo 450 Turbo Thermal Printer (B&W)(HID Part Number: EL-DYMO-450T)	600.64
AC-HID-EL-EADV-UPGRD	eAdvance software upgrade to latest version(HID Part Number: EL-EADV-UPGRD)	4,045.71
AC-HID-EL-K12-SVM	1 copy of SVM software, includes Free Administrator™ software (admin/reporting) Special bundle package for K-12 schools only (HID # EL-K12-SVM)(HID Part Number: EL-K12-SVM)	2,544.87
AC-HID-EL-SOS-K12	Sex offender screening service per year per system Special bundle package for K-12 schools only (HID # EL-SOS-K12)(HID Part Number: EL-SOS-K12)	905.43
AC-HID-EL-SS-R2	ACUANT SNAPSHELL R2 DRIVER'S LICENSE SCANNER (COO: Israel) (HID # EL-SS-R2)	2,662.44
AC-HID-EL-SSA-ACIS	A/C INTEGRATION ANNUAL MAINTENANCE PER COPY (INCLUDES UPGRADES AND UPDATES)	1,324.34
AC-HID-EL-SSA-EADVS	EADVANCE ANNUAL MAINTENANCE PER COPY (INCLUDES UPGRADES AND UPDATES)(HID Part Number: EL-SSA-EADVS)	1,323.94
AC-HID-EL-SSA-K12S	K12 ANNUAL SOFTWARE MAINTENANCE PLAN (FOR FREE UPDATES AND UPGRADES) = PER YEAR PER SYSTEM	488.13

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-EL-SSA-SVMS	SVM ANNUAL MAINTENANCE PER COPY (INCLUDES ALL UPDATES AND UPGRADES)(HID Part Number: EL-SSA-SVMS)	1,106.16
AC-HID-EL-SVM10-UPGRD	SVM software upgrade to SVM10(HID Part Number: EL-SVM10-UPGRD)	3,224.35
AC-HID-EL-TOP-1X5	Topaz SignatureGem LCD 1x5 SigPad (signature block only) (HID Part Number: EL-TOP-1X5)	1,025.28

HID pivCLASS

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-HID-PIVCLASS-00NHPTEK00088	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-20HNKS-03-0004XR	Signo PIV 20, Pigtal, Prox Enabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	384.18
AC-HID-PIVCLASS-20HNKS-03-00059X	Signo PIV 20, Pigtal, Prox Disabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	384.18
AC-HID-PIVCLASS-20HTKS-03-0004XR	Signo PIV 20, Terminal, Prox Enabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	384.18
AC-HID-PIVCLASS-20HTKS-03-00059X	Signo PIV 20, Terminal, Prox Disabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	384.18
AC-HID-PIVCLASS-20KHNS-03-0004XR	Signo PIV 20K, Keypad, Pigtal, Prox Enabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	610.74
AC-HID-PIVCLASS-20KHNS-03-00059X	Signo PIV 20K, Keypad, Pigtal, Prox Disabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	610.74
AC-HID-PIVCLASS-20KHTKS-03-0004XR	Signo PIV 20K, Keypad, Terminal, Prox Enabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	610.74
AC-HID-PIVCLASS-20KHTKS-03-00059X	Signo PIV 20K, Keypad, Terminal, Prox Disabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	610.74
AC-HID-PIVCLASS-40HNKS-03-0004XR	Signo PIV 40, Pigtal, Prox Enabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	394.03
AC-HID-PIVCLASS-40HNKS-03-00059X	Signo PIV 40, Pigtal, Prox Disabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	394.03
AC-HID-PIVCLASS-40HTKS-03-0004XR	Signo PIV 40, Terminal, Prox Enabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	394.03
AC-HID-PIVCLASS-40HTKS-03-00059X	Signo PIV 40, Terminal, Prox Disabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	394.03
AC-HID-PIVCLASS-40KHNS-03-0004XR	Signo PIV 40K, Keypad, Pigtal, Prox Enabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	610.74
AC-HID-PIVCLASS-40KHNS-03-00059X	Signo PIV 40K, Keypad, Pigtal, Prox Disabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	610.74
AC-HID-PIVCLASS-40KHTKS-03-0004XR	Signo PIV 40K, Keypad, Terminal, Prox Enabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	610.74
AC-HID-PIVCLASS-40KHTKS-03-00059X	Signo PIV 40K, Keypad, Terminal, Prox Disabled, HDX, 200Bit FASC-N with UUID 128Bit fallback	610.74
AC-HID-PIVCLASS-6132AKL	SPACER ACC KIT, PIVCLASS RDR, BLK, ERGO ANGLE, LEFT	21.73
AC-HID-PIVCLASS-900NHPNEK0000R	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	195.93
AC-HID-PIVCLASS-900NHPNEK00088	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHPNEK000UF	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V2, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	195.93
AC-HID-PIVCLASS-900NHPNEK0032Q	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHPNEK00336		195.93

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-900NHPNEKE032Q	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHPTEK0000R	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	195.93
AC-HID-PIVCLASS-900NHPTEK000UF	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V2, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	195.93
AC-HID-PIVCLASS-900NHPTEK0032Q	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHPTEK00336	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHPTEK00337	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHPTEK0036L	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V1, OPT TAMP, OPEN COLL, OSDP TAMP DISBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	195.93
AC-HID-PIVCLASS-900NHPTEKE036N	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, ELITE, A/V OFF, OSDP V1, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	195.93
AC-HID-PIVCLASS-900NHRNEK0000C	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK00018	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK0001T	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK0001Y	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK00032	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRS BCD, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK00038	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK0005W	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK00110	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK0012W	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK00220	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 128-BIT, FASCN + RMV OVRHD, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK00226	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH GRN, BZR OFF, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEK0032Y		195.93

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, IPM OFF, UART ON, WIEG OFF	
AC-HID-PIVCLASS-900NHRNEK0037D	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEKE000C	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, ELITE KEYS, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRNEKE001T	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, ELITE KEYS, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRTEK0000C	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRTEK00018	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRTEK0001T	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRTEK00038	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRTEK0003C	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900NHRTEK0032Y	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, IPM OFF, UART ON, WIEG OFF	195.93
AC-HID-PIVCLASS-900NHRTEKE000C	RDR, R10-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	195.93
AC-HID-PIVCLASS-900PHPNEK0000V	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPNEK0003Y	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPNEK000HA	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPNEK000UH	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V2, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPNEK0032U	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPNEK00332	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPNEK00335	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 64-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPNEK00338	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPNEK00339	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPNEKE000V		239.20

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	
AC-HID-PIVCLASS-900PHPNEKE003Y	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPNEKE00HA	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPNEKE032U	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPNEKE0332	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPNEKE0335	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 64-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPNEKE0338	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPNEKE0339	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPTEK0000V	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPTEK0003Y	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPTEK000HA	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPTEK000UH	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V2, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPTEK0032U	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPTEK00332	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPTEK00335	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 64-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPTEK00338	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPTEK00339	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPTEKE000V	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPTEKE003Y	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPTEKE00HA		239.20

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-900PHPTEKE032U	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPTEKE0332	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPTEKE0335	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 64-BIT, IPM OFF, UART OFF, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHPTEKE0338	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHPTEKE0339	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEK00004	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEK00005	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEK00006	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEK00007	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, IPM OFF, UART ON, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHRNEK00016	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEK0003U	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEK000HA	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEK000K2	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED ON, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200 BIT, PROX FSK, IPM OFF, UART OFF, WIEG ON, CSTM SEOS LEDS	239.20
AC-HID-PIVCLASS-900PHRNEK0012K	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, RVRS BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEK0037E	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEK00466	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, CSN SUPPRESSED, LED RED, FLSH GRN, BZR ON, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEKE0004	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEKE0005	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEKE0006	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEKE0007	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, IPM OFF, UART ON, WIEG OFF	239.20

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-900PHRNEKE00HA	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRNEKE037E	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEK00004	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEK00005	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEK00006	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEK00007	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, IPM OFF, UART ON, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHRTEK00016	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEK000HA	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEK0037E	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEK00466	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, CSN SUPPRESSED, LED RED, FLSH GRN, BZR ON, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEK0059B	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPN COL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON, PATH NY NJ	239.20
AC-HID-PIVCLASS-900PHRTEKE0004	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEKE0005	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEKE0006	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEKE0007	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, IPM OFF, UART ON, WIEG OFF	239.20
AC-HID-PIVCLASS-900PHRTEKE00HA	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, ELITE, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-900PHRTEKE037E	RDR, RP10-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	239.20
AC-HID-PIVCLASS-91000-MS	PAM Firmware Standard Maintenance & Support, STD M&S 8X5 M-F CST (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	59.51
AC-HID-PIVCLASS-91000BNNN	PAM, PIVCLASS (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	2,421.54
AC-HID-PIVCLASS-91000BNNNN	PAM, PIVCLASS, CCA ONLY, NO ENCLOSURE (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	2,077.75
AC-HID-PIVCLASS-920LHRNEK0001R		362.62

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RP40-H, PIVCLASS, SE E, LF CST, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-920LHRNEK0003Q	RDR, RP40-H, PIVCLASS, SE E, LF CST, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920LHRNEK0011P	RDR, RP40-H, PIVCLASS, SE E, LF CST, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920NHPNEK0000R	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	319.35
AC-HID-PIVCLASS-920NHPNEK00088	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHPNEK000MJ	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=50MS, FIPS 200-BIT, IPM OFF, UART ON, WIEG OFF	319.35
AC-HID-PIVCLASS-920NHPNEK000P1	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, IPM OFF	319.35
AC-HID-PIVCLASS-920NHPNEK0032Q	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHPNEK00330	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	319.35
AC-HID-PIVCLASS-920NHPNEK00336	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHPNEKE032Q	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHPTEK0000R	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	319.35
AC-HID-PIVCLASS-920NHPTEK00088	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHPTEK000P1	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, IPM OFF	319.35
AC-HID-PIVCLASS-920NHPTEK0032Q	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHPTEK00336	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHPTEK0036L	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V1, OPEN COLL, OSDP TAMP DISBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	319.35
AC-HID-PIVCLASS-920NHPTEK0036N	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, A/V OFF, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	319.35
AC-HID-PIVCLASS-920NHPTEKE036N	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, ELITE KEYS, A/V OFF, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	319.35
AC-HID-PIVCLASS-920NHRNEK0000C	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	319.35

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-920NHRNEK00018	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK0001T	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK0001Y	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK00032	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRS BCD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK00038	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK0005W	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK0007J	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 26-BIT CSN, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK00110	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK0012W	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK00220	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 128-BIT, FASCN + RMV OVRHD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK0032Y	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, IPM OFF, UART ON, WIEG OFF	319.35
AC-HID-PIVCLASS-920NHRNEK0037D	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRS BCD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK0043W	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, 14443A DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRNEK00578	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT,FASCN+RMV OVRHD+RMV PAR , IPM OFF	319.35
AC-HID-PIVCLASS-920NHRNEKE000C	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, ELITE KEYS, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEK0000C	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEK00018	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEK0001T	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEK00038	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEK0003C	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEK0007J	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT	319.35

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 26-BIT CSN, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-920NHRTEK000H9	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEK000Q6	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, A/V OFF, OPT TAMP, OPEN COLL, FIPS 58-BIT AMAG, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEK00220	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 128-BIT, FASCN + RMV OVRHD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEK0032Y	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, IPM OFF, UART ON, WIEG OFF	319.35
AC-HID-PIVCLASS-920NHRTEK0037D	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	319.35
AC-HID-PIVCLASS-920NHRTEKE032Y	RDR, R40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, IPM OFF, UART ON, WIEG OFF	256.02
AC-HID-PIVCLASS-920PHPNEK0000V	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	362.62
AC-HID-PIVCLASS-920PHPNEK0003Y	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHPNEK000P2	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, IPM OFF	362.62
AC-HID-PIVCLASS-920PHPNEK0032U	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHPNEK00332	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	362.62
AC-HID-PIVCLASS-920PHPNEK00338	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHPNEK00339	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHPNEKE0332	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	362.62
AC-HID-PIVCLASS-920PHPNEKE0338	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHPTEK0000V	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	362.62
AC-HID-PIVCLASS-920PHPTEK000HA	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHPTEK000P2	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, IPM OFF	362.62
AC-HID-PIVCLASS-920PHPTEK0032U	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHPTEK00332		362.62

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	
AC-HID-PIVCLASS-920PHPTEK00335	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 64-BIT, IPM OFF, UART OFF, WIEG OFF	362.62
AC-HID-PIVCLASS-920PHPTEK00338	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHPTEK00339	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHPTEK000V	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	362.62
AC-HID-PIVCLASS-920PHPTEKE003Y	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK00004	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK00005	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK00006	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK00007	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, IPM OFF, UART ON, WIEG OFF	362.62
AC-HID-PIVCLASS-920PHRNEK00016	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK0003U	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK0004A	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK0004V	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK0006T	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK0008U	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK00097	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 26-BIT CSN, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK000AA	RDR, RP40, PIVCLASS, SE E, LF CST, PROX GIC ONLY, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON, PROX PRIORITY	362.62
AC-HID-PIVCLASS-920PHRNEK000CV	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF CSTM, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 200-BIT, OPT TAMP OPN COLL, IPM OFF, UART OFF, WIEG ON, CSTM /FIPS/CAK/MIGR, LF ENBLD, PATH NY NJ	362.62
AC-HID-PIVCLASS-920PHRNEK000H4	RDR, RP40-H, PIVCLASS, SE E, LF CST, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 128-BIT, FASCN+RMVOVRHD+RMVPAR, IPM OFF, UART OFF, WIEG ON	362.62

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-920PHRNEK000HA	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK000MR	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 75-BIT, PROX PRIORITY, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK0012K	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRS BCD, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK00143	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF	362.62
AC-HID-PIVCLASS-920PHRNEK00157	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 14443A 32-BIT CSN, IPM OFF	362.62
AC-HID-PIVCLASS-920PHRNEK00202	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, IPM OFF	362.62
AC-HID-PIVCLASS-920PHRNEK00203	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH OFF, BZR OFF, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF	362.62
AC-HID-PIVCLASS-920PHRNEK0020A	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, C/D ON	362.62
AC-HID-PIVCLASS-920PHRNEK00245	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRS BCD, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK00365	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK0037E	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRS BCD, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK0043V	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, 14443A MIF 56-BIT CSN, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK00466	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF OFF, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK0046G	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEK00479	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF CSTM, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 200-BIT, OPT TAMP OPN COLL, IPM OFF, UART OFF, WIEG ON, CSTM STD/SIO/SEOS/FIPS/CAK/MIGR, LF ENBLD, PATH NY NJ	362.62
AC-HID-PIVCLASS-920PHRNEK0059A	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 58-BIT AMAG, IPM OFF, HID PROX ONLY, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRNEKE00005	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, ELITE KEYS, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRTEK00004	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRTEK00005	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRTEK00006	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRTEK00007	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, IPM OFF, UART ON, WIEG OFF	362.62
AC-HID-PIVCLASS-920PHRTEK0037E		362.62

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-920PHRTEK0043V	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, UART, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, 14443A MIF 56-BIT CSN, IPM OFF	362.62
AC-HID-PIVCLASS-920PHRTEK00449	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, UART, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART ON, UART CSTM, WIEG OFF	362.62
AC-HID-PIVCLASS-920PHRTEK00466	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF OFF, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-920PHRTEKE0005	RDR, RP40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	362.62
AC-HID-PIVCLASS-921NHPNEK0000T	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	557.29
AC-HID-PIVCLASS-921NHPNEK000UG	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, OSDP V2, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	557.29
AC-HID-PIVCLASS-921NHPNEK0019D	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHPNEK0032R	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHPNEK0033E	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHPNEKE032R	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHPTEK0000T	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	557.29
AC-HID-PIVCLASS-921NHPTEK000UG	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V2, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	557.29
AC-HID-PIVCLASS-921NHPTEK0013T	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM	557.29
AC-HID-PIVCLASS-921NHPTEK0019D	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHPTEK0032R	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHPTEK0033D	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 64-BIT, IPM OFF, UART OFF, WIEG OFF	557.29
AC-HID-PIVCLASS-921NHPTEK0033E	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHPTEK0036M		557.29

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V1, OPEN COLL, OSDP TAMP DISBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IP	
AC-HID-PIVCLASS-921NHPTEK0036V	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V1, OPEN COLL, OSDP TAMP DISBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, KPF, ASCII, BFFRD 1 KEY, IPM OFF, UART	557.29
AC-HID-PIVCLASS-921NHPTEKE013T	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, ELITE KEYS, A/V OFF, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, FIPS 200-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG	557.29
AC-HID-PIVCLASS-921NHRNEK0000C	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK00039	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK00044	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK0004K	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK0004M	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK00062	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK0006V	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 26-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK0008P	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK000Y5	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, DOR COMPL, BFFRD 1 KEY, NO PAR, 8 BIT-MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK0011K	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK00121	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 128-BIT, FASCN + RMV OVRHD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK00139	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK0013W	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEK0016Y	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT CSN, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF	557.29
AC-HID-PIVCLASS-921NHRNEK0024J	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-921NHRNEK0033A	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, ASCII, XMIT CMLPT, IPM OFF, UART ON, WIEG OFF	557.29
AC-HID-PIVCLASS-921NHRNEK0037F	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEKE004M	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, ELITE KEYS, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRNEKE0062	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, ELITE KEYS, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK00039	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK0004K	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK0004M	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK00054	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRS BCD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK00062	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK0006Q	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK0006V	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 26-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK00073	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK0008P	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK000NL	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT MSB CSN, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK000Q7	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, A/V OFF, OPT TAMP, OPEN COLL, FIPS 58-BIT AMAG, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8 BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK000Y5	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, DOR COMPL, BFFRD 1 KEY, NO PAR, 8 BIT-MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK0011G	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, 14443A 56-BIT CSN, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG	557.29
AC-HID-PIVCLASS-921NHRTEK0011J		557.29

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, KPF, BFFRD 1 KEY, PAR, 6-BIT MSG, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-921NHRTEK00121	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 128-BIT, FASCN + RMV OVRHD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK00123	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK0013W	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921NHRTEK0033A	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, ASCII, XMIT CMPLT, IPM OFF, UART ON, WIEG OFF	557.29
AC-HID-PIVCLASS-921NHRTEK0037F	RDR, RK40-H, PIVCLASS, SE E, LF OFF, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	557.29
AC-HID-PIVCLASS-921PHPNEK0000F	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHPNEK0004R	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHPNEK000HC	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHPNEK000R2	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 8-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHPNEK000UE	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, OSDP V2, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHPNEK0032N	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHPNEK0033G	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHPNEK0033H	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 64-BIT, IPM OFF, UART OFF, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHPNEK0033J	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHPNEK0033K	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHPNEKE000F	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHPNEKE033H		598.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 64-BIT, IPM OFF, UART OFF, WIEG OFF	
AC-HID-PIVCLASS-921PHPNEKE033K	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, FIG, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHPTEK0000F	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHPTEK000RY	RDR, RPK40-H, PIVCLASS, SE E, LF FSK ONLY, HF DIW/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON, SPAWAR	598.00
AC-HID-PIVCLASS-921PHPTEK000UE	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V2, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, IPM OFF, UART OFF, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHPTEK0032N	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHPTEK0033G	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, OSDP V1, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 75-BIT, IPM OFF, UART OFF, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHPTEK0033J	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHPTEKE032N	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0001U	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FL5H OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0002D	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0002G	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0002H	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0004V	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0004Y	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FL5H OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0005D	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FL5H GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0005P	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, FIG, BLK, STD-1, LED RED, FL5H	598.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-921PHRNEK0005T	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK00068	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0006F	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRS BCD, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK000CU	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF CST, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH GRN, BZR ON, OPT TMP/OPN COL, FIPS200-BIT, KPF BFRD 1 KEY, DOR CMP, NOPAR, 8-BIT, IPM OFF, UART OFF, WIEG ON, CSTM /FIPS/CAK/MIGR,LFENBD,PATHNJ	598.00
AC-HID-PIVCLASS-921PHRNEK000E7	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK,485FDX,PIG,BLK,STD-1, LED RED,FLSSH GRN,BZR ON,OPT TAMP, OC,CSN 32 BIT MSB,FIPS 75-BIT,BFFRD 1 KEY,DOR COMPL,NO PAR, 8-BIT,IPM OFF,UART ON,WIEG ON,PROX FSK PRIORITY	598.00
AC-HID-PIVCLASS-921PHRNEK000EF	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK,485FDX,PIG, BLK,STD-1, LED RED,FLSSH ON,BZR ON,OPT TAMP,OPN COL, FIPS 200-BIT,MIF/DES 56-BIT CSN,BFRD 1 KEY, DOR COMPL,NO PAR,8-BIT MSG,IPM OFF,UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK000HC	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK000K3	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED ON, FLSSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200 BIT, PROX FSK, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON, CSTM SEOS LEDS	598.00
AC-HID-PIVCLASS-921PHRNEK0010K	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF FIPS/CAK/MIGR, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS200-BIT, KPF BFRD 1 KEY, DOR CMP, NOPAR, 8-BIT, IPM OFF, UART OFF, WIEG ON, JFK	598.00
AC-HID-PIVCLASS-921PHRNEK0010N	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRS BCD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0011B	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0011R	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 26-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK00127	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0013F	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK00145	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF	598.00
AC-HID-PIVCLASS-921PHRNEK0015D		598.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH OFF, BZR OFF, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF	
AC-HID-PIVCLASS-921PHRNEK0020D	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRB BCD, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF	598.00
AC-HID-PIVCLASS-921PHRNEK0020R	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0020U	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRB BCD, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF	598.00
AC-HID-PIVCLASS-921PHRNEK0026H	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, ADD PAR, *E, #F, 6-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0026J	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, KPF, BFFRD 1 TO 5 KEYS, PAR, USER ENTRD FC, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0026L	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIE	598.00
AC-HID-PIVCLASS-921PHRNEK0026M	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0026W	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR OFF, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0026Y	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK00273	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK00274	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0032W	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0033B	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, ASCII, XMIT CMPLT, IPM OFF, UART ON, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHRNEK0037G	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, RVRB BCD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0043E	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH ON, BZR ON, OPT TAMP, OPN COL, FIPS 200-BIT, 14443A 56-BIT CSN, KPF, BFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0043G	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, MIF/DES 56-BIT	598.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-921PHRNEK0043T	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, 14443A MIF 56-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0044K	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 64-BIT, BCD, KPF, BFFRD 1 KEY, PAR, 8-BIT MSG, IPM OFF, UART OFF, WEIG ON	598.00
AC-HID-PIVCLASS-921PHRNEK00467	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF OFF, 485FDX, PIG, BLK, STD-1, CSN SURPRESSED, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0046F	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, , KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8 BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK00470	RDR, RPK40-H, PIVCLASS, SE E, LF CST, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED OFF, FL SH OFF, BZR ON, OPT TAMP, OPEN COLL, FIPS 200 BIT, KPF, BFFRD 1 KEY, DOR, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON, FSK, ASK, PSK ENABL	598.00
AC-HID-PIVCLASS-921PHRNEK0047A	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF CST, 485FDX, PIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TMP/OPN COL, FIPS200-BIT, KPF BFRD 1 KEY, DOR CMP, NOPAR, 8-BIT, IPM OFF, UART OFF, WIEG ON, CST STD/SIO/SEOS/FIPS/CAK/MIGR,LFENBD,PATHNJ	598.00
AC-HID-PIVCLASS-921PHRNEK0051T	RDR, RPK40-H, PIVCLASS, SE E, LF CST, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT , OC, FIPS 75-BIT, MIF/DES 56-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FSK PROX READ ONLY, IPM OFF, UART OFF	598.00
AC-HID-PIVCLASS-921PHRNEK0051V	RDR, RPK40-H, PIVCLASS, SE E, LF CST, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, FSK PROX READ ONLY, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0053Q	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON,CSN 32-BIT MSB, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEK0057D	RDR, RPK40-H, PIVCLASS,SE E,LF STD,HF STD/SIO/SEOS/FIPS/CAK,485FDX,PIG,BLK,STD-1,LED RED,FL SH GRN,BZR ON,OPT TAMP,OPEN COLL,FIPS 128-BIT,FASCN+RMV OVRHD+RMV PAR ,KPF,BFFRD 1 KEY,DOR COMPL,NO PAR 8-BIT MSG,IPM OFF	598.00
AC-HID-PIVCLASS-921PHRNEK00589	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 TO 5 KEYS, PAR, FC FIXED 96, 26-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEKE026V	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, ELITE KEYS, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, RVRS BCD, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRNEKE032W	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, PIG, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK0002D	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FL SH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK0002G	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FL SH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK000HC		598.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-921PHRTEK000Y6	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, DOR COMPL, BFFRD 1 KEY, NO PAR, 8 BIT-MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK00127	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 40-BIT, BCD, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK0020R	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK0032W	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK0033B	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, ASCII, XMIT CMPLT, IPM OFF, UART ON, WIEG OFF	598.00
AC-HID-PIVCLASS-921PHRTEK0037G	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK0043T	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, 14443A MIF 56-BIT CSN, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK0043U	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, 14443A MIF 56-BIT CSN, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF	598.00
AC-HID-PIVCLASS-921PHRTEK00467	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF OFF, 485FDX, TERM, BLK, STD-1, CSN SURPRESSED, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK00478	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF OFF, 485FDX, TERM, BLK, STD-1, CSN SURPRESSED, LED OFF, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEK0047A	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF CST, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TMP/OPN COL, FIPS200-BIT, KPF BFRD 1 KEY, DOR CMP, NOPAR, 8-BIT, IPM OFF, UART OFF, WIEG ON, CST STD/SIO/SEOS/FIPS/CAK/MIGR,LFENBD,PATHNJ	598.00
AC-HID-PIVCLASS-921PHRTEKE002G	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEKE00HC	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEKE020R	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEKE032W	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PHRTEKE033B	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, ASCII, XMIT CMPLT, IPM OFF, UART ON, WIEG OFF	598.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-921PHRTEKE037G	RDR, RPK40-H, PIVCLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	598.00
AC-HID-PIVCLASS-921PTNTEK0000B	RDR, RPK40, MULTICLASS, SE E, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, LED RED, FLSH GRN, BZR ON, KPF, ASCII, XMIT CMPLT PIN, LCD 1F, IPM OFF, UART ON, WIEG OFF	597.23
AC-HID-PIVCLASS-923NPPNEK0000L	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, RF SUPPR, 485HDX, FIG, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, FIPS 75-BIT, KPF, ASCII, BFFRD 1 KEY, LCD 1F, IPM OFF, UART OFF, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPNEK000HD	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPNEK000P3	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF	799.28
AC-HID-PIVCLASS-923NPPNEK0032T	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPNEK0033L	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPNEK0033M	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, OSDP V2, OPEN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPNEK0033N	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPNEK0033P	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPNEK0036H	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPNEK200KR	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-2, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, FIPS 75-BIT, KPF, ASCII, BFFRD 1 KEY, LCD 1F, IPM OFF, UART OFF, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPNEKE000U	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPNEKE00HD	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPNEKE032T	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPNEKE033L	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	799.28

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-923NPPNEKE033M	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, PIG, BLK, STD-1, OSDP V2,OPN COL,OSDP TAMP ENBLD,TEST KEYS,POLL=75MS,A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 64-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPNEKE033N	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPNEKE033P	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPNEKE036H	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPTEK0000L	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, RF SUPPR, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, FIPS 75-BIT, KPF, ASCII, BFFRD 1 KEY, LCD 1F, IPM OFF, UART OFF, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPTEK0000U	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1,OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS,POLL=75MS,A/V OFF,KPF, ASCII, BFFRD 1 KEY,FIPS 200-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPTEK0000HD	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPTEK0000P3	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF	799.28
AC-HID-PIVCLASS-923NPPTEK00032T	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPTEK00033L	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS,POLL=75MS,A/V OFF,KPF, ASCII, BFFRD 1 KEY,FIPS 75-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPTEK00033M	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK,STD-1,OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS, POLL=75MS,A/V OFF,KPF, ASCII, BFFRD 1 KEY,FIPS 64-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPTEK00033N	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPTEK00033P	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPTEK00036H	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPTEK200KR	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-2, A/V OFF,OSDP V2,OPT TAMP,OPEN COLL,OSDP TAMP ENBLD,TEST KEY, POLL=75MS,FIPS 75-BIT,KPF,ASCII,BFFRD 1 KEY, LCD 1F,IPM OFF,UART OFF,WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPTEKE000U	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1,OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS,POLL=75MS,A/V OFF,KPF, ASCII, BFFRD 1 KEY,FIPS 200-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPTEKE000HD		799.28

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-923NPPTKE032T	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPTKE033L	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPTKE033M	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPPTKE033N	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPTKE033P	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPPTKE036H	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG O	799.28
AC-HID-PIVCLASS-923NPRNEK0000Q	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEK000HD	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEK000Y7	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, DOR COMPL, BFFRD 1 KEY, NO PAR, 8 BIT-MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEK0032V	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPRNEK00333	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEK00334	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEK0037H	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEK00435	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, 14443 56-BIT MIFARE, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEK0052K	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, DESFIRE MIFARE CSN 56 BIT LSB, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPRNEK0057A		799.28

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF	
AC-HID-PIVCLASS-923NPRNEK0057K	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, DESFIRE MIFARE CSN 56 BIT MSB, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPRNEKE000Q	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, ELITE, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEKE00HD	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEKE032V	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPRNEKE0333	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEKE0334	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRNEKE037H	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEK0000Q	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEK000HD	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEK000Y7	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, DOR COMPL, BFFRD 1 KEY, NO PAR, 8 BIT-MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEK0032V	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPRTEK00333	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEK00334	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEK0037H	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG O	799.28
AC-HID-PIVCLASS-923NPRTEK00381	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1 WEIG, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 75-BIT, MIF/DES 56-BIT CSN, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEK005A9	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OC, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-923NPRTEKE000Q	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, ELITE, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEKE00HD	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEKE032V	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	799.28
AC-HID-PIVCLASS-923NPRTEKE0333	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEKE0334	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	799.28
AC-HID-PIVCLASS-923NPRTEKE037H	RDR, RKCL40-P, PIVCLASS, SE E, CONT LCD, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, IPM OFF, UART OFF, WIEG O	799.28
AC-HID-PIVCLASS-923PPPNEK0000G	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPNEK000HE	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPNEK000K5	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEY, POLL=75MS, FIPS 75-BIT, KPF, ASCII, BFFRD 1 KEY, LCD 1F, IPM OFF, UART OFF, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPNEK000P4	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, KPF, ASCII, XMIT CMPLT PIN, LCD 1F, IPM OFF	838.60
AC-HID-PIVCLASS-923PPPNEK0032P	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPNEK0033Q	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPNEK0033R	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPNEK0033T	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPNEK0033U	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPNEK0036J	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, LCD 1F, IPM OFF, UART OFF	838.60
AC-HID-PIVCLASS-923PPPNEKE000G		838.60

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK,STD-1,OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS,POLL=75MS,A/V OFF,KPF, ASCII, BFFRD 1 KEY,FIPS 200-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	
AC-HID-PIVCLASS-923PPPNEKE00HE	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPNEKE032P	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPNEKE033Q	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS,POLL=75MS,A/V OFF,KPF, ASCII, BFFRD 1 KEY,FIPS 75-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPNEKE033R	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS,POLL=75MS,A/V OFF,KPF, ASCII, BFFRD 1 KEY,FIPS 64-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPNEKE033T	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPNEKE033U	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPNEKE036J	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, LCD 0F, IPM OFF, UART OFF	838.60
AC-HID-PIVCLASS-923PPPTEK0000G	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK,STD-1,OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS,POLL=75MS,A/V OFF,KPF,BFRD 1 KEY,NO PAR,4-BIT MSG,FIPS 200-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPTEK000HE	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPTEK000K5	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI,485HDX,TERM, BLK,STD-1,A/V OFF,OSDP V2,OPT TAMP,OPEN COLL,OSDP TAMP ENBLD,TEST KEY,POLL=75MS,FIPS 75-BIT,KPF,ASCII,BFFRD 1 KEY,LCD 1F,IPM OFF,UART OFF,WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPTEK000P4	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, A/V OFF, OSDP V2, OPT TAMP, OPEN COLL, OSDP TAMP ENBLD, TEST KEYS, POLL=75MS, KPF, ASCII, XMIT CMLPT PIN, LCD 1F, IPM OFF	838.60
AC-HID-PIVCLASS-923PPPTEK000RW	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF FSK ONLY, HF DIW/FIPS/CAK, 485HDX, TERM, BLK, STD-1, LED RD, FLSH GN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG,FIPS 200-BIT,LCD 1F, IPM OF,URT OFF,WIEG ON,SPAWR	838.60
AC-HID-PIVCLASS-923PPPTEK0032P	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPTEK0033Q	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1,OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS,POLL=75MS,A/V OFF,KPF, ASCII, BFFRD 1 KEY,FIPS 75-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPTEK0033R	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1,OSDP V2,OPN COL,OSDP TAMP ENBLD,TST KEYS,POLL=75MS,A/V OFF,KPF, ASCII, BFFRD 1 KEY,FIPS 64-BIT,LCD 1F,IPM OFF,UART OFF,WIEG OFF	838.60

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-923PPPTKE0033T	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPTKE0033U	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPTKE0036J	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPTKE0000G	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPTKE000HE	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPTKE0032P	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPTKE0033Q	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPTKE0033R	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, OSDP V2, OPN COL, OSDP TAMP ENBLD, TST KEYS, POLL=75MS, A/V OFF, KPF, ASCII, BFFRD 1 KEY, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPPTKE0033T	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPTKE0033U	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPPTKE0036J	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, LCD 0F, IPM OFF, UART OF	838.60
AC-HID-PIVCLASS-923PPRNEK00008	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEK00009	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEK0000A	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEK0000B	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, ASCII, XMIT CMPLT PIN, LCD 1F, IPM OFF, UART ON, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPRNEK0000CC	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485HDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT, OPEN COLL, CSN 34-BIT MSB, FIPS 75-BIT, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEK0000HE	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED,	838.60

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-923PPRNEK000Y8	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, DOR COMPL, BFFRD 1 KEY, NO PAR, 8 BIT-MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEK0037J	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, LCD 0F, IPM OFF, UART OFF	838.60
AC-HID-PIVCLASS-923PPRNEK00427	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH OFF, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 40-BIT, BCD, LCD 0F, IPM OFF, UART OFF, WIEG	838.60
AC-HID-PIVCLASS-923PPRNEK0044M	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY-5, PAR, 26-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WEIG ON	838.60
AC-HID-PIVCLASS-923PPRNEK00474	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF 1 KEY DOR COMPL, NO PAR. 8 BIT, 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEK0047L	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT, OPEN COLL, FIPS 200 BIT, KPF, BFFRD 1 KEY, NO PAR, 4 BIT MSG, IPM OFF, UART OFF, WIEG ON, WIEG PULSE, 52 USEC	838.60
AC-HID-PIVCLASS-923PPRNEK00519	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEK0057M	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, FIPS 128-BIT, FASCN+RMV OVRHD+RMV PAR, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEKE0008	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEKE0009	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEKE000A	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEKE000B	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, ASCII, XMIT CMPLT PIN, LCD 1F, IPM OFF, UART ON, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPRNEKE0044M	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, ELITE, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, BFFRD 1 KEY- 5 KEYS, PAR, 26 BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEKE00HE	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRNEKE037J	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, PIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, LCD 0F, IPM OFF, UART OFF	838.60
AC-HID-PIVCLASS-923PPRTEK00008	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED,	838.60

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	
AC-HID-PIVCLASS-923PPRTEK00009	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK0000A	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK0000B	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, ASCII, XMIT CMPLT PIN, LCD 1F, IPM OFF, UART ON, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPRTEK000HE	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK000Y8	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, DOR COMPL, BFFRD 1 KEY, NO PAR, 8 BIT-MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK0037J	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, LCD 0F, IPM OFF, UART OF	838.60
AC-HID-PIVCLASS-923PPRTEK00382	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF BFFRD 1 KEY, NO PAR, 4 BIT MSG, FIPS 75 BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK00426	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT, FIPS 75-BIT 56 CSN, LCD 0F, IPM OFF, UART OFF, WIE	838.60
AC-HID-PIVCLASS-923PPRTEK00519	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, BFFRD 1 KEY, DOR COMPL, NO PAR, 8-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK00008	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 200-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK00009	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 75-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK0000A	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK0000B	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, ASCII, XMIT CMPLT PIN, LCD 1F, IPM OFF, UART ON, WIEG OFF	838.60
AC-HID-PIVCLASS-923PPRTEK000HE	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, ELITE, LED RED, FLSH GRN, BZR ON, FIPS 128-BIT REVERSED, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, LCD 1F, IPM OFF, UART OFF, WIEG ON	838.60
AC-HID-PIVCLASS-923PPRTEK037J	RDR, RPKCL40-P, PIVCLASS, SE E, CONT LCD, LF STD, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, OPT TAMP, OPEN COLL, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, FIPS 64-BIT REVERSE BCD, LCD 0F, IPM OFF, UART OF	838.60
AC-HID-PIVCLASS-924NPRNEK00504	RDR, RKCLB40-P, PIVCLASS, SE E, CONT LCD BIO, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	1,354.47
AC-HID-PIVCLASS-924NPRNEKE0504		1,354.47

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	RDR, RKCLB40-P, PIVCLASS, SE E, CONT LCD BIO, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, FIG, BLK, ELITE KEYS, STD-1, LED RED, FLSH GRN, BZR ON, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	
AC-HID-PIVCLASS-924NPRTEK00504	RDR, RKCLB40-P, PIVCLASS, SE E, CONT LCD BIO, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	1,354.47
AC-HID-PIVCLASS-924NPRTEK00504	RDR, RKCLB40-P, PIVCLASS, SE E, CONT LCD BIO, LF OFF, HF STD/SIO/SEOS/FIPS/CAK/PKI, 485FDX, TERM, BLK, ELITE KEYS, STD-1, LED RED, FLSH GRN, BZR ON, KPF, ASCII, XMIT CMPLT, LCD 1F, IPM OFF, UART ON, WIEG OFF	1,354.47
AC-HID-PIVCLASS-928NFNTEK000TE	RDR/ENROLLER, RKL40, ICLASS, SE E, HF STD BIO/SEOS BIO, LCD/BIO, WIEG, TERM, BLK, STD-1, LED RED, FLSH GRN, BZR ON, LCD 1F, KPF, BFFRD 1 KEY, NO PAR, 4-BIT MSG, IPM OFF, WPC MODEL RKCLB40	1,449.98
AC-HID-PIVCLASS-B920NHRNEK0032Y	PIVCLASS BUNDLE, TWO R40-H PIVCLASS REV E PIGTAIL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM)	2,615.26
AC-HID-PIVCLASS-B920NHRTEK0032Y	PIVCLASS BUNDLE, TWO R40-H PIVCLASS REV E TERMINAL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM), 032Y PIVCLASS CONFIG	2,615.26
AC-HID-PIVCLASS-B920PHRNEK00007	PIVCLASS BUNDLE, TWO RP40-H PIVCLASS REV E PIGTAIL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM), 0007 PIVCLASS CONFIG	2,715.90
AC-HID-PIVCLASS-B920PHRTEK00007	PIVCLASS BUNDLE, TWO RP40-H PIVCLASS REV E TERMINAL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM), 0007 PIVCLASS CONFIG	2,715.90
AC-HID-PIVCLASS-B923NPRNEK0032V	PIVCLASS BUNDLE, TWO RKCL40-P PIVCLASS REV E PIGTAIL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM)	3,441.13
AC-HID-PIVCLASS-B923NPRTEK0032V	PIVCLASS BUNDLE, TWO RKCL40-P PIVCLASS REV E TERMINAL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM), 032V PIVCLASS CONFIG	3,441.13
AC-HID-PIVCLASS-B923PPRNEK0000B	PIVCLASS BUNDLE, TWO RPKCL40-P PIVCLASS REV E PIGTAIL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM), 000B PIVCLASS CONFIG	3,542.91
AC-HID-PIVCLASS-B923PPRTEK0000B	PIVCLASS BUNDLE, TWO RPKCL40-P PIVCLASS REV E TERMINAL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM), 000B PIVCLASS CONFIG	3,542.91
AC-HID-PIVCLASS-B924NPRNEK00504	PIVCLASS BUNDLE, TWO RKCLB40-P PIVCLASS REV E PIGTAIL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM)	4,448.60
AC-HID-PIVCLASS-B924NPRTEK00504	PIVCLASS BUNDLE, TWO RKCLB40-P PIVCLASS REV E TERMINAL BLK RDRS & ONE M2000 PIVCLASS AUTHENTICATION MODULE (PAM)	4,448.60
AC-HID-PIVCLASS-E91000-MS	EMBEDDED AUTHENTICATION CONTROLLER, STD M&S 8X5 M-F CST (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	63.76
AC-HID-PIVCLASS-E920NHPNEK000P1	PIVCLASS BUNDLE, EMBEDDED AUTHENTICATION MODULE & TWO R40-H PIGTAIL READERS, FIRST YEAR EA MAINTENANCE AND SUPPORT INCLUDED	1,142.79
AC-HID-PIVCLASS-E920NHPTEK000P1	PIVCLASS BUNDLE, EMBEDDED AUTHENTICATION MODULE & TWO R40-H TERMINAL READERS, FIRST YEAR EA MAINTENANCE AND SUPPORT INCLUDED	1,142.79
AC-HID-PIVCLASS-E920PHPNEK000P2	PIVCLASS BUNDLE, EMBEDDED AUTHENTICATION MODULE & TWO RP40-H PIGTAIL READERS, FIRST YEAR EA MAINTENANCE AND SUPPORT INCLUDED	1,215.67
AC-HID-PIVCLASS-E920PHPTEK000P2	PIVCLASS BUNDLE, EMBEDDED AUTHENTICATION MODULE & TWO RP40-H TERMINAL READERS, FIRST YEAR EA MAINTENANCE AND SUPPORT INCLUDED	1,215.67
AC-HID-PIVCLASS-E923NPPNEK000P3	PIVCLASS BUNDLE, EMBEDDED AUTHENTICATION MODULE & TWO RKCL40-P PIGTAIL READERS, FIRST YEAR EA MAINTENANCE AND SUPPORT INCLUDED	2,084.34
AC-HID-PIVCLASS-E923NPPTEK000P3	PIVCLASS BUNDLE, EMBEDDED AUTHENTICATION MODULE & TWO RKCL40-P TERMINAL READERS, FIRST YEAR EA MAINTENANCE AND SUPPORT INCLUDED	2,084.34
AC-HID-PIVCLASS-E923PPPNEK000P4	PIVCLASS BUNDLE, EMBEDDED AUTHENTICATION MODULE & TWO RPKCL40-P PIGTAIL READERS, FIRST YEAR EA MAINTENANCE AND SUPPORT INCLUDED	2,157.24

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-E923PPPTK000P4	PIVCLASS BUNDLE, EMBEDDED AUTHENTICATION MODULE & TWO RPKCL40-P TERMINAL READERS, FIRST YEAR EA MAINTENANCE AND SUPPORT INCLUDED	2,157.24
AC-HID-PIVCLASS-EA-LICENSE2	TWO (2) EMBEDDED AUTHENTICATION LICENSES (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	533.46
AC-HID-PIVCLASS-PACS-SVC-18-00	PIVCLASS PACS SERVICE COMPONENT; AVIGILON ACM, DOWNLOAD (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	5.31
AC-HID-PIVCLASS-PVC-CM	PIVCLASS CERTIFICATE MANAGER, 1 LICENSE/PACS, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	15,708.00
AC-HID-PIVCLASS-PVC-CM-MS	CERTIFICATE MANAGER, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	2,457.79
AC-HID-PIVCLASS-PVC-CM-REDNT	PIVCLASS CERTIFICATE MANAGER, 1 LICENSE/PACS REDUNDANT, DOWNLOAD (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	7,854.00
AC-HID-PIVCLASS-PVC-CM-REDNT-MS	CERTIFICATE MANAGER, STD M&S 8X5 M-F CST, REDUNDANT (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	1,228.90
AC-HID-PIVCLASS-PVC-D/S	PIVCLASS VALIDATION WORKSTATION & DOCUMENTATION, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	2,688.72
AC-HID-PIVCLASS-PVC-D/S-MS	VALIDATION WORKSTATION STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	421.06
AC-HID-PIVCLASS-PVC-DTAIMP-18-00	PIVCLASS DATA IMPORT; AVIGILON ACM, DOWNLOAD (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	6,551.46
AC-HID-PIVCLASS-PVC-DTAIMP-MS	PIVCLASS DATA IMPORT, STD M&S 8X5 M-F CST (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	1,025.71
AC-HID-PIVCLASS-PVC-DTAIMP-REDNT-18-00	PIVCLASS DATA IMPORT - REDUNDANT; AVIGILON ACM, DOWNLOAD (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	3,276.24
AC-HID-PIVCLASS-PVC-DTAIMP-REDNT-MS	PIVCLASS DATA IMPORT - REDUNDANT, STD M&S 8X5 M-F CST (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	512.86
AC-HID-PIVCLASS-PVC-FXRDR	PIVCLASS READER SERVICES, SW & DOC, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	266.22
AC-HID-PIVCLASS-PVC-FXRDR-MS	READER SERVICES, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	41.62
AC-HID-PIVCLASS-PVC-FXRDR-REDNT	REDUNDANT PIVCLASS READER SERVICES, SW & DOC, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	133.62
AC-HID-PIVCLASS-PVC-FXRDR-REDNT-MS	REDUNDANT READER SERVICES, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	21.03
AC-HID-PIVCLASS-PVC-IDPUB1000		16,283.28

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	PIVCLASS ID PUBLISHER 1000, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	
AC-HID-PIVCLASS-PVC-IDPUB1000-MS	PIVCLASS ID PUBLISHER 1000, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	2,548.37
AC-HID-PIVCLASS-PVC-IDPUB1000-REDNT	REDUNDANT PIVCLASS ID PUBLISHER 1000, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	8,141.64
AC-HID-PIVCLASS-PVC-IDPUB1000-REDNT-MS	REDUNDANT PIVCLASS ID PUBLISHER 1000, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	1,274.17
AC-HID-PIVCLASS-PVC-IDPUB500	PIVCLASS ID PUBLISHER 500, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	8,065.14
AC-HID-PIVCLASS-PVC-IDPUB500-MS	PIVCLASS ID PUBLISHER 500, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	1,261.94
AC-HID-PIVCLASS-PVC-IDPUB500-REDNT	REDUNDANT PIVCLASS ID PUBLISHER 500, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	4,032.06
AC-HID-PIVCLASS-PVC-IDPUB500-REDNT-MS	REDUNDANT PIVCLASS ID PUBLISHER 500, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	631.58
AC-HID-PIVCLASS-PVC-IDPUBUNL	PIVCLASS ID PUBLISHER UNL, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	27,152.40
AC-HID-PIVCLASS-PVC-IDPUBUNL-MS	PIVCLASS ID PUBLISHER UNL, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	4,249.73
AC-HID-PIVCLASS-PVC-IDPUBUNL-REDNT	REDUNDANT PIVCLASS ID PUBLISHER UNL, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	13,576.20
AC-HID-PIVCLASS-PVC-IDPUBUNL-REDNT-MS	REDUNDANT PIVCLASS ID PUBLISHER UNL, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	2,124.85
AC-HID-PIVCLASS-PVC-MPX-CNSL	PIVCLASS MULTIPACS CONSOLE, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	15,702.90
AC-HID-PIVCLASS-PVC-MPX-CNSL-MS	PIVCLASS MULTIPACS CONSOLE, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	2,457.79
AC-HID-PIVCLASS-PVC-MPX-CNSL-REDNT	REDUNDANT PIVCLASS MULTIPACS CONSOLE, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	7,850.94
AC-HID-PIVCLASS-PVC-MPX-CNSL-REDNT-MS	REDUNDANT PIVCLASS MULTIPACS CONSOLE, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	1,228.90
AC-HID-PIVCLASS-PVC-MPX-CNX-18-00	PIVCLASS MULTIPACS CONNECTOR; AVIGILON ACM, DOWNLOAD (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	10,184.70
AC-HID-PIVCLASS-PVC-MPX-CNX-MS	PIVCLASS MULTIPACS CONNECTOR, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	1,593.65

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-HID-PIVCLASS-PVC-MPX-CNX-REDNT	REDUNDANT PIVCLASS MULTIPACS CONNECTOR; DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	5,092.86
AC-HID-PIVCLASS-PVC-MPX-CNX-REDNT-MS	REDUNDANT PIVCLASS MULTIPACS CONNECTOR, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	796.82
AC-HID-PIVCLASS-PVCAT-D	PIVCLASS VALIDATION WORKSTATION AUDIT TRAIL, DOWNLOAD, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	1,576.92
AC-HID-PIVCLASS-PVCAT-D-MS	VALIDATION WORKSTATION AUDIT TRAIL, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	247.25
AC-HID-PIVCLASS-PVCP-D/S-18-00	PIVCLASS REGISTRATION ENGINE; AVIGILON ACM, DOWNLOAD (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	13,068.24
AC-HID-PIVCLASS-PVCP-D/S-CPLG-18-00	PIVCLASS PACS PLUGIN CHANGE; AVIGILON ACM, DOWNLOAD (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	7,630.62
AC-HID-PIVCLASS-PVCP-D/S-MS	REGISTRATION ENGINE, STD M&S 8X5 M-F CST, CODEBENCH SUPPLIER (Requires pivCLASS Supplemental Ordering Information form with ALL orders found in the pivCLASS How To Order Guide https://www.hidglobal.com/documents/how-to-order)	2,045.30
AC-HID-USB-FINGERPRINT-RDR-MSO-1300E3-SNR-00058	HID SNR-00058 MSO-1300E3 USB FINGER PRINT SENSOR	602.75

Salto

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-SALTO-ADAPTER-RING-SP220418.38-IM	SALTO Mortise cylinder collar. B=3/8" (9.5mm) collar, Satin stainless steel (US32D) (Available only in the USA and Canada)	26.29
AC-SALTO-ADAPTER-RING-SP220495-14-IM	Adapter Ring, 1/4" key override depth spacer, satin stainless (Available only in the USA and Canada)	15.09
AC-SALTO-ADAPTER-RING-SP220495-18-IM	Adapter Ring, 1/8" key override depth spacer, satin stainless (Available only in the USA and Canada)	15.09
AC-SALTO-AELEMENT-AEB0IMBA3A8	AEElement elec Black Rdr BLE Mifare DESFire SVN, Standard Anthracite BB satin stainless trim (Available only in the USA and Canada)	547.93
AC-SALTO-AELEMENT-AEB0IPBA3A8	AEElement elec Black Rdr BLE Mifare DESFire SVN, Standard Anthracite BB polished ss trim (Available only in the USA and Canada)	578.66
AC-SALTO-AELEMENT-AEB1IMBA3A8	AEElement elec Black Rdr BLE Mifare DESFire SVN, Elec Privacy Anthracite BB satin stainless trim (Available only in the USA and Canada)	562.25
AC-SALTO-AELEMENT-AEB1IPBA3A8	AEElement elec Black Rdr BLE Mifare DESFire SVN, Elec Privacy Anthracite BB polished ss trim (Available only in the USA and Canada)	592.99
AC-SALTO-AELEMENT-AEJ1IMBA3A8	AEElement elec Black Rdr BLE HID iCLASS SVN, Elec Privacy Anthracite BB satin stainless trim (Available only in the USA and Canada)	518.20
AC-SALTO-AELEMENT-FUSION-READER-ANSI-AFB7PMB4A8	SALTO AEElement Fusion electronics. Includes split spindles that must be used with the AEElement handle set (Mortise lock and handles not included and must be ordered separately)(Available only in the USA and Canada)	679.35
AC-SALTO-AELEMENT-HANDLE-R1SJRIM080	SALTO J handle for AEElement handle set. Round rose. To be fitted with the split spindle provided with the AEElement electronics. 2 handles set. (Available only in the USA and Canada)	206.18
AC-SALTO-AELEMENT-HANDLE-R3SJRIM081	SALTO J handle for AEElement handle set. Round rose. To be fitted with the split spindle provided with the AEElement electronics. 2 handles set. (Available only in the USA and Canada)	253.09
AC-SALTO-AELEMENT-HANDLE-R3SWRPM081	SALTO W handle for AEElement handle set. Round rose. To be fitted with the split spindle provided with the AEElement electronics. 2 handles set. (Available only in the USA and Canada)	189.61
AC-SALTO-AELEMENT-MORTISE-LOCK-LA1T1770A24IMSRH	Mortise Lock AEElement ANSI, Door+Egress detectors RH stainless steel (Available only in the USA and Canada)	359.29

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-SALTO-AELEMEN-MORTISE-LOCK-LA1T1770F24IMSRH	SALTO AElemen Fusion mortise lock with dead bolt and panic function. Stainless steel (Available only in the USA and Canada)	366.45
AC-SALTO-AELEMEN-MORTISE-LOCKS-LA1T1770F74PMSRH	Mortise Lock AElemen ANSI, Door+Egress detectors RH satin brass (Available only in the USA and Canada)	383.41
AC-SALTO-AELEMEN-READER-ANSI-AEB0PMB3A8	SALTO AElemen electronics with ANSI mechanical privacy. Includes split spindles that must be used with the AElemen handle set (Mortise lock and handles not included and must be ordered separately) (Available only in the USA and Canada)	580.94
AC-SALTO-ASSEMBLY-TOOL-NEOXX-PADLOCK-SP226009	Assembly Tool Neoxx Padlock, (Available only in the USA and Canada)	31.10
AC-SALTO-BLUENET-BLACK-GATEWAYB3CUS	Wireless Gateway BLUEnet node black 12VDC xfmr, Ethernet supports upto 6 additional wired nodes (Available only in the USA and Canada)	753.36
AC-SALTO-BLUENET-WHITE-GATEWAYW3CUS	Wireless Gateway BLUEnet node white 12VDC xfmr, Ethernet supports upto 6 additional wired nodes (Available only in the USA and Canada)	753.36
AC-SALTO-CONTROL-UNIT-IP-CLEARCOVER-CU42E0TUS	Control Unit XS4 2.0 two rdr 6 in 4 out ethernet, expandable via RS485 12VDC xfmr encl clear cover (Available only in the USA and Canada)	1,363.91
AC-SALTO-CONTROL-UNIT-IP-GREYCOVER-CU42E0GUS	Control Unit XS4 2.0 two rdr 6 in 4 out ethernet, expandable via RS485 12VDC xfmr encl Grey cover (Available only in the USA and Canada)	1,363.91
AC-SALTO-CONTROL-UNIT-IP-NOCOVER-CU42E0US	Control Unit XS4 2.0 two rdr 6 in 4 out ethernet, expandable via RS485 12VDC xfmr No enclosure (Available only in the USA and Canada)	1,363.91
AC-SALTO-CONTROL-UNIT-RS485-CLEARCOVER-CU4200TUS	Control Unit XS4 2.0 two rdr 6 in 4 out RS485 aux, offline or exp of CU42Ex 12V xfmr encl Clear cover (Available only in the USA and Canada)	776.25
AC-SALTO-CONTROL-UNIT-RS485-GREYCOVER-CU4200GUS	Control Unit XS4 2.0 two rdr 6 in 4 out RS485 aux, offline or exp of CU42Ex 12V xfmr encl Grey cover (Available only in the USA and Canada)	776.25
AC-SALTO-CONTROL-UNIT-RS485-NOCOVER-CU4200US	Control Unit XS4 2.0 two rdr 6 in 4 out RS485 aux, offline or exp of CU42Ex 12VDC xfmr No enclosure (Available only in the USA and Canada)	776.25
AC-SALTO-COVER-PLATE-ANSI-WIDE-COPLE110IMCA	Cover Plate Pr ANSI wide cyl cartridge compatible, 13-53/64" H X 4-21/64" W satin stainless (Available only in the USA and Canada)	118.19
AC-SALTO-CREDENTIAL-BRACELET-WBM01KNL-5	SALTO proximity silicone Bracelets, MIFARE, 01K 1KBytes, Black, Large, Pack of 5 bracelets (Available only in the USA and Canada)	112.25
AC-SALTO-CREDENTIAL-BRACELET-WBM01KNM-5	SALTO proximity silicone Bracelets, MIFARE, 01K 1KBytes, Black, Medium, Pack of 5 bracelets (Available only in the USA and Canada)	112.25
AC-SALTO-CREDENTIAL-BRACELET-WBM01KNS-5	SALTO proximity silicone Bracelets, MIFARE, 01K 1KBytes, Black, Small, Pack of 5 bracelets (Available only in the USA and Canada)	112.25
AC-SALTO-CREDENTIAL-CARD-MIFARE-PCM04KB	SALTO Credential CR80 card dual technology, Mifare 4KB with magstripe pack of 50 (Available only in the USA and Canada)	314.29
AC-SALTO-CREDENTIAL-CONSTRUCTION-HID-PCH002C	Credential Construction Card HID iClass, testing and management prior to initialization (Available only in the USA and Canada)	36.93
AC-SALTO-CREDENTIAL-CONSTRUCTION-MIFARE-PCM01KC	Credential Construction Card Mifare, testing and management prior to initialization (Available only in the USA and Canada)	28.29
AC-SALTO-CREDENTIAL-CR80-CARD-HID-ICLASS-PCH004-50	Credential CR80 card printable white HID iClass, 32Kbs sammed for use with Salto standard codes, pack of 50 (Available only in the USA and Canada)	1,766.29
AC-SALTO-CREDENTIAL-CR80-CARD-MIFARE-PCD04KB-50	Credential CR80 card printable white Mifare 4KB, pack of 50 (Available only in the USA and Canada)	321.62
AC-SALTO-CREDENTIAL-CR80-CARD-MIFARE-PCM01KB-50	Credential CR80 card printable white Mifare 1KB pack of 50 (Available only in the USA and Canada)	256.13
AC-SALTO-CREDENTIAL-CR80-CARD-MIFARE-PCM04KBH-50	SALTO Credential CR80 card dual technology, Mifare 4KB with magstripe pack of 50 (Available only in the USA and Canada)	321.64
AC-SALTO-CREDENTIAL-FOB-DESFIRE-PFD04KB-10	Credential FOB blue with white center Salto logo, DESFire EV2 4KB pack of 10 (Available only in the USA and Canada)	101.23
AC-SALTO-CREDENTIAL-FOB-DESFIRE-PFD04KN-10	Credential FOB black with white center Salto logo, DESFire EV2 4KB pack of 10 (Available only in the USA and Canada)	101.25
AC-SALTO-CREDENTIAL-FOB-MIFARE-PFM04KB-10	Credential FOB blue with white center Salto logo, Mifare 4KB pack of 10 (Available only in the USA and Canada)	105.94
AC-SALTO-CREDENTIAL-FOB-SVN-BLUE-PFD04KBSVNKS-5	SVNKS SALTO KS + SVN compatible Tags - Blue - Pack of 5 (Available only in the USA and Canada)	90.75
AC-SALTO-CREDENTIAL-FOB-SVN-GREEN-PFD04KGSVNKS-5	SVNKS SALTO KS + SVN compatible Tags - Green - Pack of 5 (Available only in the USA and Canada)	90.75

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-SALTO-CREDENTIAL-FOB-SVN-RED-PFD04KRSVNKS-5	SVNKS SALTO KS + SVN compatible Tags - Red - Pack of 5 (Available only in the USA and Canada)	90.75
AC-SALTO-CREDENTIAL-FOB-SVN-SILVER-PFD04KSSVNKS-5	SVNKS SALTO KS + SVN compatible Tags - Silver - Pack of 5 (Available only in the USA and Canada)	90.75
AC-SALTO-CREDENTIAL-FOB-SVN-WHITE-PFD04KWSVNKS-5	SVNKS SALTO KS + SVN compatible Tags - White - Pack of 5 (Available only in the USA and Canada)	90.75
AC-SALTO-CYLINDRICAL-CARTRIDGE-ALIGNMENT-KIT-1848	Alignment Kit Cylindrical Cartridge, use with Ax6xx and LCxK cartridge combination (Available only in the USA and Canada)	15.70
AC-SALTO-CYLINDRICAL-CARTRIDGE-LOCK-LC1KC60IM	SALTO cylindrical latch grade 1. ANSI A156.2 grade1. model K. squared front plate. latch by lever either side. Auxiliar latch (anticard) deadlock the latch. Backset 50mm - 2 3/8. ASA strike, screws and dust box included. (Available only in the USA and Canada)	134.68
AC-SALTO-CYLINDRICAL-CARTRIDGE-LOCK-LC1KC70IM	Cylindrical Cartridge Lock ANSI Grade 2, 2-3/4" backset(std comm) satin stainless (Available only in the USA and Canada)	127.03
AC-SALTO-DEADBOLT-GEO-LD51C70CS	Deadbolt, single cylinder for use with GEO heavy duty deadbolt cylinder, 2 3/4" backset, standard operation, satin chromium finish (Available only in the USA and Canada)	207.16
AC-SALTO-DEADBOLT-NEO-LD51C60CS	Deadbolt less single cyl 2 3/8" backset requires eCylinder satin stainless (Available only in the USA and Canada)	225.43
AC-SALTO-DOOR-DETECTOR-ESCUTCHEON-RFDTCTS18W01	RFDTCT Door detector with plug connection for the SALTO wireles escutcheon, S For steel doors, 18 For wide body escutcheons (Available only in the USA and Canada)	54.50
AC-SALTO-EMERGENCY-POWER-SUPPLY-EPS100	Emergency Power Supply PPD connection cord, battery harness requires 4 AA batteries (Available only in the USA and Canada)	50.58
AC-SALTO-ENCODER-DESFIRE-EC904B0US	SALTO NCode - Proximity card encoder Mifare/DESFire. USB and Ethernet connections. DHCP addressing. Desktop reader capabilities (Bluetooth mobile keys not supported)(Available only in the USA and Canada)	1,039.30
AC-SALTO-ENCODER-DESFIRE-ECB04B0US	Encoder BLE DESFire Mifare ethernet, USB can be used as desktop reader (Available only in the USA and Canada)	980.24
AC-SALTO-ENCODER-HID-ECJ04B0US	Encoder BLE HID iClass ethernet, USB can be used as desktop reader (Available only in the USA and Canada)	980.24
AC-SALTO-EXPANSION-UNIT-RS485-NOCOVER-CU4EB8US	Expansion Unit XS4 2.0 4 in 8 out RS485 auxillary, exp of CU42xx 12VDC xfmr No enclosure (Available only in the USA and Canada)	670.68
AC-SALTO-GEO-INDOOR-PADLOCK-BLKRDR-G9P2148830CPBN	GEO Indoor Padlock Mifare DESFire SVN - Black Rdr shackle 8mm dia-30mm len polished chrome (Available only in the USA and Canada)	689.61
AC-SALTO-GEO-INDOOR-PADLOCK-BLKRDR-G9P2148860CPBN	GEO Indoor Padlock Mifare DESFire SVN - Black Rdr shackle 8mm dia-60mm len polished chrome (Available only in the USA and Canada)	689.61
AC-SALTO-GEO-INDOOR-PADLOCK-BLKRDR-G9P2148890CPBN	GEO Indoor Padlock Mifare DESFire SVN - Black Rdr shackle 8mm dia-90mm len polished chrome (Available only in the USA and Canada)	689.61
AC-SALTO-INSTALLATION-TOOL-NEO-SP220764	SALTO Geo installation tool (NOT NEO) (Available only in the USA and Canada)	9.24
AC-SALTO-INSTALLATION-TOOL-NEO-SP225542	SALTO Neo installation tool (Available only in the USA and Canada)	33.71
AC-SALTO-LOCKER-LOCK-DESFIRE-ANTHRASITE-LB050A30	Locker Lock XS4 BLE DESFire Mifare battery incl, 20-30mm door sandwich mount BioCote anthracite rdr (Available only in the USA and Canada)	433.57
AC-SALTO-LOCKER-LOCK-DESFIRE-WHITE-LB050M30	Locker Lock XS4 BLE DESFire Mifare battery incl, 20-30mm door sandwich mount BioCote white rdr rdr (Available only in the USA and Canada)	433.57
AC-SALTO-LOCKER-LOCK-HID-ANTHRACITE-LJ050A30	Locker Lock XS4 BLE HID iClass SEOS battery incl, 20-30mm door sandwich mount BioCote anthracite rdr (Available only in the USA and Canada)	433.57
AC-SALTO-LOCKER-LOCK-HID-WHITE-LJ050M30	Locker Lock XS4 BLE HID iClass SEOS battery incl, 20-30mm door sandwich mount BioCote white rdr rdr (Available only in the USA and Canada)	433.57
AC-SALTO-LOCKSET-PIN-SPO1047-325	Replacement Part: Single thumbturn knob for locks.(Available only in the USA and Canada)	97.57
AC-SALTO-MOBILE-USER-LICENSE-SPACE-OPT-0016-1	SALTO ProAccess SPACE, SPACE Mobile Users License (0016-1), included for first 12 months from software registration, billed annually thereafter - Requires Annual Subscription Renewal (0028-2) (Available only in the USA and Canada)	3.30
AC-SALTO-MORTISE-LOCK-LA1T0570A21IM8LH	Mortise Lock ANSI Grade 1 32mm faceplate, Door detector LH(field rev) satin stainless (Available only in the USA and Canada)	167.02
AC-SALTO-MORTISE-LOCK-LA1T0570A21IM8RH		167.02

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	Mortise Lock ANSI Grade 1 32mm faceplate, Door detector RH(field rev) satin stainless (Available only in the USA and Canada)	
AC-SALTO-MORTISE-LOCK-LA1T0770A22IMSLH	Mortise Lock AElement ANSI, Door+Egress detectors LH satin stainless (Available only in the USA and Canada)	338.88
AC-SALTO-MORTISE-LOCK-LA1T0770A22IMSLR	Mortise Lock AElement ANSI, Door+Egress detectors LHR satin stainless (Available only in the USA and Canada)	338.88
AC-SALTO-MORTISE-LOCK-LA1T0770A22IMSRH	Mortise Lock AElement ANSI, Door+Egress detectors RH satin stainless (Available only in the USA and Canada)	338.88
AC-SALTO-MORTISE-LOCK-LA1T0770A22IMSR	Mortise Lock AElement ANSI, Door+Egress detectors RHR satin stainless (Available only in the USA and Canada)	338.88
AC-SALTO-MORTISE-LOCK-LA1T0770A24IMSLH	Mortise Lock AElement ANSI, Privacy+Door+Egress detectors LH satin stainless (Available only in the USA and Canada)	338.88
AC-SALTO-MORTISE-LOCK-LA1T0770A24IMSLR	Mortise Lock AElement ANSI, Privacy+Door+Egress detectors LHR satin stainless (Available only in the USA and Canada)	338.88
AC-SALTO-MORTISE-LOCK-LA1T0770A24IMSRH	Mortise Lock AElement ANSI, Privacy+Door+Egress detectors RH satin stainless (Available only in the USA and Canada)	338.88
AC-SALTO-MORTISE-LOCK-LA1T0770A24IMSR	Mortise Lock AElement ANSI, Privacy+Door+Egress detectors RHR satin stainless (Available only in the USA and Canada)	338.88
AC-SALTO-MORTISE-LOCK-LA1T1570A21IM8LH	Mortise Lock Deadbolt ANSI Grade 1 32mm faceplate - Door detector LH (field rev) satin stainless (Available only in the USA and Canada)	177.08
AC-SALTO-MORTISE-LOCK-LA1T1570A21IM8RH	Mortise Lock Deadbolt ANSI Grade 1 32mm faceplate - Door detector RH(field rev) satin stainless (Available only in the USA and Canada)	176.56
AC-SALTO-MORTISE-LOCK-LA1T1570A71IM8R	SALTO Mortise Lock Deadbolt ANSI Grade 1 27mm faceplate, Door detector RH(field rev) satin stainless (Available only in the USA and Canada)	167.04
AC-SALTO-MORTISE-LOCK-LA1T3570A21IM8LH	SALTO Mortise Lock - ANSI with latch and automatic deadbolt. with panic function Auto-DB ANSI Grade 1 32mm faceplate Door detector LH(field rev) satin stainless (Available only in the USA and Canada)	298.53
AC-SALTO-MORTISE-LOCK-LA1T3570A21IM8RH	SALTO Mortise Lock - ANSI with latch and automatic deadbolt. with panic function Auto-DB ANSI Grade 1 32mm faceplate Door detector RH(field rev) satin stainless (Available only in the USA and Canada)	298.53
AC-SALTO-NEO-CAM-CYL-BLKRDR-NBCL119M40BCBA	Deadbolt, single cylinder for use with GEO heavy duty deadbolt cylinder, 2 3/4" backset, standard operation, satin chromium finish (Available only in the USA and Canada)	640.75
AC-SALTO-NEO-CAM-CYL-NBCL119M28BCBA	NEO Cam Cylinder BLE Mifare DESFire SVN, Black Rdr IP55 BioCote (Available only in the USA and Canada)	606.12
AC-SALTO-NEO-CAM-CYL-NBCL119M28BCBAR	NEO Cam Cylinder BLE Mifare DESFire SVN, Black Rdr IP66 BioCote (Available only in the USA and Canada)	634.14
AC-SALTO-NEO-CAM-CYL-NBCL119M28CPBA	NEO Cam Cylinder BLE Mifare DESFire SVN, Black Rdr IP55 polished chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-CAM-CYL-NBCL119M28CPBAR	NEO Cam Cylinder BLE Mifare DESFire SVN, Black Rdr IP66 polished chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-CAM-CYL-NBCL119M28CSBA	NEO Cam Cylinder BLE Mifare DESFire SVN, Black Rdr IP55 satin chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-CAM-CYL-NBCL119M28CSBAR	NEO Cam Cylinder BLE Mifare DESFire SVN, Black Rdr IP66 satin chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-CAM-CYL-NJCL119M28BCBA	NEO Cam Cylinder HID iClass SEOS SVN, Black Rdr IP55 BioCote (Available only in the USA and Canada)	606.12
AC-SALTO-NEO-CAM-CYL-NJCL119M28BCBAR	NEO Cam Cylinder HID iClass SEOS SVN, Black Rdr IP66 BioCote (Available only in the USA and Canada)	634.64
AC-SALTO-NEO-CAM-CYL-NJCL119M28CPBA	NEO Cam Cylinder HID iClass SEOS SVN, Black Rdr IP55 polished chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-CAM-CYL-NJCL119M28CPBAR	NEO Cam Cylinder HID iClass SEOS SVN, Black Rdr IP66 polished chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-CAM-CYL-NJCL119M28CSBA	NEO Cam Cylinder HID iClass SEOS SVN, Black Rdr IP55 satin chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-CAM-CYL-NJCL119M28CSBAR	NEO Cam Cylinder HID iClass SEOS SVN, Black Rdr IP66 satin chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-MORTISE-CYL-NBM1132N00BCBN	NEO Mortise Cylinder BLE Mifare DESFire SVN, Black Rdr 1-1/4" body length IP55 BioCote (Available only in the USA and Canada)	606.12
AC-SALTO-NEO-MORTISE-CYL-NBM1132N00BCBNR		634.64

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	NEO Mortise Cylinder BLE Mifare DESFire SVN, Black Rdr 1-1/4" body length IP66 BioCote (Available only in the USA and Canada)	
AC-SALTO-NEO-MORTISE-CYL-NBM1132N00CPBN	NEO Mortise Cylinder BLE Mifare DESFire SVN, Black Rdr 1-1/4" body length IP55 polished chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-MORTISE-CYL-NBM1132N00CPBNR	NEO Mortise Cylinder BLE Mifare DESFire SVN, Black Rdr 1-1/4" body length IP66 polished chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-MORTISE-CYL-NBM1132N00CSBN	NEO Mortise Cylinder BLE Mifare DESFire SVN, Black Rdr 1-1/4" body length IP55 satin chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-MORTISE-CYL-NBM1132N00CSBNR	NEO Mortise Cylinder BLE Mifare DESFire SVN, Black Rdr 1-1/4" body length IP66 satin chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-MORTISE-CYL-NBM1132N00NEBNR	SALTO NEO Mortise profile electronic cylinder Exterior cylinder, one knob, no thumbturn. (Can be initialized in SALTO SPACE or SALTO KS) (Available only in the USA and Canada)	569.95
AC-SALTO-NEO-MORTISE-CYL-NBM1135N00CSBNR	SALTO NEO Mortise profile electronic cylinder Exterior cylinder, one knob, no thumbturn - BLE DESFire MIFARE: Standard - standard length, standard cams, standard finish (Available only in the USA and Canada)	603.26
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00BCBN	NEO Mortise Cylinder HID iClass SEOS SVN, Black Rdr 1-1/4" body length IP55 BioCote (Available only in the USA and Canada)	606.12
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00BCBNR	NEO Mortise Cylinder HID iClass SEOS SVN, Black Rdr 1-1/4" body length IP66 BioCote (Available only in the USA and Canada)	634.64
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00CPBN	NEO Mortise Cylinder HID iClass SEOS SVN, Black Rdr 1-1/4" body length IP55 polished chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00CPBNR	NEO Mortise Cylinder HID iClass SEOS SVN, Black Rdr 1-1/4" body length IP66 polished chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00CSBN	NEO Mortise Cylinder HID iClass SEOS SVN, Black Rdr 1-1/4" body length IP55 satin chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-MORTISE-CYL-NJM1132N00CSBNR	NEO Mortise Cylinder HID iClass SEOS SVN, Black Rdr 1-1/4" body length IP66 satin chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-RIM-CYL-BLKRDR-NBB3151N00BCBN	SALTO NEO Rim Cylinder BLE Mifare DESFire SVN - Black Rdr Salto DB not incl IP55 BioCote (Available only in the USA and Canada)	640.75
AC-SALTO-NEO-RIM-CYL-BLKRDR-NBB3151N00BCBNR	SALTO NEO Rim Cylinder BLE Mifare DESFire SVN - Black Rdr Salto DB not incl IP66 BioCote (Available only in the USA and Canada)	670.92
AC-SALTO-NEO-SERVER-RACK-CYL-INDR-NBE9130N00NEBR	NEO Server Rack Cyl BLE Mifare DESFire SVN, Black Rdr 40mm long satin black (Available only in the USA and Canada)	663.16
AC-SALTO-NEO-SERVER-RACK-CYL-NJE9130N00NEBR	NEO Server Rack Cyl HID iClass SEOS SVN, Black Rdr 40mm long satin black (Available only in the USA and Canada)	663.16
AC-SALTO-NEO-SERVER-RACK-CYL-NJE9130N00NEBRR	NEO Server Rack Cyl HID iClass SEOS SVN, Black Rdr 40mm long satin black (Available only in the USA and Canada)	691.71
AC-SALTO-NEO-SERVER-RACK-CYL-OUTDR-NBE9130N00NEBRR	NEO Server Rack Cyl BLE Mifare DESFire SVN, Black Rdr 40mm long satin black (Available only in the USA and Canada)	569.00
AC-SALTO-NEO-US-RIM-CYL-NBB1100N00BCBN	NEO US Rim Cylinder BLE Mifare DESFire SVN, Black Rdr IP55 BioCote (Available only in the USA and Canada)	606.12
AC-SALTO-NEO-US-RIM-CYL-NBB1100N00BCBNR	NEO US Rim Cylinder BLE Mifare DESFire SVN, Black Rdr IP66 BioCote (Available only in the USA and Canada)	634.64
AC-SALTO-NEO-US-RIM-CYL-NBB1100N00CPBN	NEO US Rim Cylinder BLE Mifare DESFire SVN, Black Rdr IP55 polished chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-US-RIM-CYL-NBB1100N00CPBNR	NEO US Rim Cylinder BLE Mifare DESFire SVN, Black Rdr IP66 polished chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-US-RIM-CYL-NBB1100N00CSBN	NEO US Rim Cylinder BLE Mifare DESFire SVN, Black Rdr IP55 satin chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-US-RIM-CYL-NBB1100N00CSBNR	NEO US Rim Cylinder BLE Mifare DESFire SVN, Black Rdr IP66 satin chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-US-RIM-CYL-NBB3151N00CSBN	NEO Rim Cylinder BLE Mifare DESFire SVN Black Rdr Salto DB not incl IP55 satin chrome - SALTO NEO Heavy duty deadbolt electronic cylinder. To be used in combination with SALTO deadbolt LD51 or LD71series (Available only in the USA and Canada)	573.01
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00BCBN	NEO US Rim Cylinder HID iClass SEOS SVN, Black Rdr IP55 BioCote (Available only in the USA and Canada)	606.12
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00BCBNR	NEO US Rim Cylinder HID iClass SEOS SVN, Black Rdr IP66 BioCote (Available only in the USA and Canada)	634.64
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00CPBN	NEO US Rim Cylinder HID iClass SEOS SVN, Black Rdr IP55 polished chrome (Available only in the USA and Canada)	540.46

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-SALTO-NEO-US-RIM-CYL-NJB1100N00CPBNR	NEO US Rim Cylinder HID iClass SEOS SVN, Black Rdr IP66 polished chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00CSBN	NEO US Rim Cylinder HID iClass SEOS SVN, Black Rdr IP55 satin chrome (Available only in the USA and Canada)	540.46
AC-SALTO-NEO-US-RIM-CYL-NJB1100N00CSBNR	NEO US Rim Cylinder HID iClass SEOS SVN, Black Rdr IP66 satin chrome (Available only in the USA and Canada)	568.97
AC-SALTO-NEOXX-PADLOCK-DESFIRE-NBP4P60150CPB1	Neoxx Padlock BLE Mifare DESFire SVN Black - Removable shackle 11mm dia-60mm len IP66 chain (Available only in the USA and Canada)	1,065.06
AC-SALTO-NEOXX-PADLOCK-DESFIRE-NBP4R60150CPB0	Neoxx Padlock BLE Mifare DESFire SVN Black, Non-removable shackle 11mm dia-60mm len IP66 (Available only in the USA and Canada)	955.77
AC-SALTO-NEOXX-PADLOCK-HID-ICLASS-NJP4R60150CPB0	Neoxx Padlock HID iClass SEOS BLE SVN Black, Non-removable shackle 11mm dia-60mm len IP66 (Available only in the USA and Canada)	1,257.46
AC-SALTO-OUTDOOR-KIT-XS4-ESCUTCHEON-SP220475-6	Outdoor Kit, pair of gaskets for weather exposed, XS4 escutcheons, pack of 6 sets (Available only in the USA and Canada)	107.77
AC-SALTO-PORTABLE-PROGRAMMING-DEVICE-PPD800	Portable Programming Device NFC USB connection, 3 pin harness connector req 3 AAA batteries, incl (Available only in the USA and Canada)	881.77
AC-SALTO-PROACCESS-SPACE-SOFTWARE-SPACE-OPT-0032	SALTO ProAccess SPACE software SPACE-OPT-0032, SALTO event-alarms & communication module. Enables event alarms and also sends emails to the operators generated by the events. (Available only in the USA and Canada)	1,132.24
AC-SALTO-PROACCESS-SPACE-SOFTWARE-SPAONLINE	SALTO ProAccess SPACE, ProAccess SPACE Software Online SVN RF Lockdown, Event Stream Automatic Key Assignment Less Photo (Available only in the USA and Canada)	1,518.16
AC-SALTO-PROACCESS-SPACE-SOFTWARE-SPAPART	SALTO ProAccess SPACE software Partitional package that includes: - All the features included in the SALTO ProAccess SPACE ID System package - Partitional functionalities (department operator) (Available only in the USA and Canada)	3,886.08
AC-SALTO-PROACCESS-SPACE-STARTER-KIT-SPAONLABAB	SALTO Starter Kit - ProAccess SPACE Software - Online, standard readers, ANSI, black readers (Available only in the USA and Canada)	3,624.66
AC-SALTO-RFNET-BLACK-GATEWAYB2CUS	Wireless Gateway RFnet node black 12VDC xfmr, Ethernet supports upto 6 additional wired nodes (Available only in the USA and Canada)	753.36
AC-SALTO-RFNET-WHITE-GATEWAYW2CUS	Wireless Gateway RFnet node white 12VDC xfmr, Ethernet supports upto 6 additional wired nodes (Available only in the USA and Canada)	753.36
AC-SALTO-RIM-PB-PBF110033IM	Rim Panic Bar Device 33" length - Use w/KPB03 satin stainless (Available only in the USA and Canada)	1,304.77
AC-SALTO-RIM-PB-PBF110045IM	SALTO RIM Panic Bar Device. Stainless steel finish. Latchdeadlocking system. Max 1220mm wing width. Strike plate included. To be used with KPB03. Exit signal when bar is depressed included. (Available only in the USA and Canada)	1,308.57
AC-SALTO-SAMKIT9	Salto Authorization Module(SAM) DESFire EndUser, requires EC9xx application subject to approval, SAM Software Kit. Includes SAM Software, SAM card. (Available only in the USA and Canada)	6,087.17
AC-SALTO-SAMKITH	Salto Authorization Module(SAM) HID iClass EndUser, requires ECHxx application subject to approval, SAM Software Kit. Includes SAM Software, SAM card. (Available only in the USA and Canada)	6,087.17
AC-SALTO-SHACKLE-CHAIN-NEOXX-PADLOCK-SP226335	Shackle Chain collar attached 300mm length, For use with Neoxx Padlock, Padlock Not Included (Available only in the USA and Canada)	51.70
AC-SALTO-SHIP-OPTION-SPACE-OPT-0018	SALTO ProAccess SPACE, SPACE SHIP Interface Option (0018) (Available only in the USA and Canada)	427.15
AC-SALTO-SPACE-TRAINING-KIT-TR-SPACE-V1	Salto SPACE Training Kit (one user) (Available only in the USA and Canada)	5,818.50
AC-SALTO-SPACER-PLATE-SP226233.02-BM	Spacer Plate for door thickness 1-1/4" - 1-3/8" (30-35mm) (Available only in the USA and Canada)	19.57
AC-SALTO-STICKERS-SMARTCARD-PSM04K-20	Credential smart sticker 1" round white PVC Pack of 20 stickers Mifare 4KB pack of 20 (Available only in the USA and Canada)	204.67
AC-SALTO-THUMBTURN-SP01027-IM	Replacement Part: 25 Pack. Internal pin for lockset. (Available only in the USA and Canada)	29.41
AC-SALTO-UPDATER-KIT-UBOX42DBABTUS	The UBOX4000 offers a compact solution updater kit based on a SALTO Controller and a Wall Reader that permits to integrate with third party products. ANSI - North American - Single gang mount reader, Black, Transparent Cover, US version, Includes UBOX 42 controller in a case with translucent cover and black ANSI rectangular BLE Mifare DESFire reader. (Available only in the USA and Canada)	697.84
AC-SALTO-UPDATER-KIT-UBOX42DBMBTUS		697.84

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	The UBOX4000 offers a compact solution updaters kit based on a SALTO Controller and a Wall Reader that permits to integrate with third party products. Mullion - narrow reader, Black, Transparent Cover, US version, Includes UBOX 42 controller in a case with translucent cover and black mullion BLE Mifare DESFire reader. (Available only in the USA and Canada)	
AC-SALTO-WALL-READER-DESFIRE-BLACK-WRDB0A4B	Wall Reader ANSI XS4 2.0 BLE DESFire Mifare Black, series CU42xx controller req IP66 (Available only in the USA and Canada)	546.50
AC-SALTO-WALL-READER-DESFIRE-WHITE-WRDB0A4W	Wall Reader ANSI XS4 2.0 BLE DESFire Mifare White, series CU42xx controller req IP66 (Available only in the USA and Canada)	546.50
AC-SALTO-WALL-READER-ICLASS-BLACK-WRDJ0A4B	Wall Reader ANSI XS4 2.0 BLE HID iClass Black, series CU42xx controller req IP66 (Available only in the USA and Canada)	546.50
AC-SALTO-WALL-READER-ICLASS-WHITE-WRDJ0A4W	Wall Reader ANSI XS4 2.0 BLE HID iClass White, series CU42xx controller req IP66 (Available only in the USA and Canada)	546.50
AC-SALTO-WALL-READER-KEYPAD-DESFIRE-BLACK-WRDB0ABK	Wall Reader Keypad ANSI XS4 2.0 BLE DESFire Mifare, Black series CU42xx controller req IP66 (Available only in the USA and Canada)	739.10
AC-SALTO-WALL-READER-KEYPAD-DESFIRE-WHITE-WRDB0AWK	Wall Reader Keypad ANSI XS4 2.0 BLE DESFire Mifare, White series CU42xx controller req IP66 (Available only in the USA and Canada)	739.10
AC-SALTO-WALL-READER-KEYPAD-ICLASS-BLACK-WRDJ0ABK	Wall Reader Keypad ANSI XS4 2.0 BLE HID iClass, Black series CU42xx controller req IP66 (Available only in the USA and Canada)	739.10
AC-SALTO-WALL-READER-KEYPAD-ICLASS-WHITE-WRDJ0AWK	Wall Reader Keypad ANSI XS4 2.0 BLE HID iClass, White series CU42xx controller req IP66 (Available only in the USA and Canada)	739.10
AC-SALTO-WALL-READER-MULLION-DESFIRE-BLACK-WRDB0M4B	Wall Reader Mullion XS4 2.0 BLE DESFire Mifare, Black series CU42xx controller req IP66 (Available only in the USA and Canada)	546.50
AC-SALTO-WALL-READER-MULLION-DESFIRE-WHITE-WRDB0M4W	Wall Reader Mullion XS4 2.0 BLE DESFire Mifare, White series CU42xx controller req IP66 (Available only in the USA and Canada)	546.50
AC-SALTO-WALL-READER-MULLION-ICLASS-BLACK-WRDJ0M4B	Wall Reader Mullion XS4 2.0 BLE HID iClass, Black series CU42xx controller req IP66 (Available only in the USA and Canada)	546.50
AC-SALTO-WALL-READER-MULLION-ICLASS-WHITE-WRDJ0M4W	Wall Reader Mullion XS4 2.0 BLE HID iClass, White series CU42xx controller req IP66 (Available only in the USA and Canada)	546.50
AC-SALTO-WALL-READER-PANEL-MOUNT-DESFIRE-WRDB0P40	Wall Reader Panel Mount XS4 2.0 BLE DESFire Mifare, Incl stickers series CU42xx controller req IP66	546.50
AC-SALTO-WIRELESS-NODE-BLUENET-RFNODE3	Wireless Node BLUEnet white, Wired requires GATEWAYxx for operation (Available only in the USA and Canada)	144.01
AC-SALTO-WIRELESS-NODE-RFNET-RFNODE	Wireless Node RFnet white, Wired requires GATEWAYxx for operation (Available only in the USA and Canada)	144.01
AC-SALTO-WIRELESS-OPTION-BLUENET-SPACE-OPT-0033	SALTO ProAccess SPACE, SPACE BLUEnet Wireless Connection Option (0033), 1ea per Lockset (online) (Available only in the USA and Canada)	128.88
AC-SALTO-WIRELESS-OPTION-RF-SPACE-OPT-0021	SALTO ProAccess SPACE, SPACE Wireless Option (0021) enables RF (Available only in the USA and Canada)	101.86
AC-SALTO-WIRELESS-REPEATER-BLUENET-REPEATER03US	Wireless Repeater BLUEnet white, Wired requires GATEWAYx3 or RFNODE3 for operation (Available only in the USA and Canada)	144.01
AC-SALTO-XS4-ANSI-MINI-CB250N60BCB3	XS4 ANSI Mini BLE Mifare DESFire Black Rdr, Entrance N lever 2-3/8" backset BioCote (Available only in the USA and Canada)	828.51
AC-SALTO-XS4-ANSI-MINI-CB250N60CPB3	XS4 ANSI Mini BLE Mifare DESFire Black Rdr, Entrance N lever 2-3/8" backset polished chrome (Available only in the USA and Canada)	851.30
AC-SALTO-XS4-ANSI-MINI-CB250N60CSB3	XS4 ANSI Mini BLE Mifare DESFire Black Rdr, Entrance N lever 2-3/8" backset satin chrome (Available only in the USA and Canada)	828.51
AC-SALTO-XS4-ANSI-MINI-CB250N70CSB3	XS4 ANSI Mini BLE Mifare DESFire Black Rdr Entrance N lever 2-3/4" backset satin chrome (Available only in the USA and Canada)	875.84
AC-SALTO-XS4-ANSI-MINI-CB250N70CSB4	XS4 ANSI Mini BLE Mifare DESFire Black Rdr Entrance N lever 2-3/4" backset satin chrome (Available only in the USA and Canada)	875.84
AC-SALTO-XS4-ANSI-MINI-CB250R70CSB3	XS4 ANSI Mini BLE Mifare DESFire Black Rdr Entrance R lever 2-3/4" backset satin chrome (Available only in the USA and Canada)	875.84
AC-SALTO-XS4-ANSI-MINI-CB250R70NEB3	XS4 ANSI Mini BLE Mifare DESFire Black Rdr Entrance R lever 2-3/4" backset satin black (Available only in the USA and Canada)	927.13
AC-SALTO-XS4-ANSI-MINI-CB260N70CSB3	SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch, 2 handles, any type. Entrance Lock with key override. BLE Mifare DESFire: Standard - standard square spindles, finishes and handles.Mechanical cylinder not included. (Available only in the USA and Canada)	878.41
AC-SALTO-XS4-ANSI-MINI-CB260N70CSB4		878.44

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch, 2 handles, any type. Entrance Lock with key override. BLE Mifare DESFire: Standard - standard square spindles, finishes and handles. Mechanical cylinder not included. (Available only in the USA and Canada)	
AC-SALTO-XS4-ANSI-MINI-CB260N70DBB3	SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch, 2 handles, any type. Entrance Lock with key override. BLE Mifare DESFire: Standard - standard square spindles, finishes and handles. Mechanical cylinder not included. (Available only in the USA and Canada)	929.87
AC-SALTO-XS4-ANSI-MINI-CJ250N60BCB3	XS4 ANSI Mini BLE HID iClass Black Rdr, Entrance N lever 2-3/8" backset BioCote (Available only in the USA and Canada)	901.21
AC-SALTO-XS4-ANSI-MINI-CJ250N60CPB3	XS4 ANSI Mini BLE HID iClass Black Rdr, Entrance N lever 2-3/8" backset polished chrome (Available only in the USA and Canada)	851.30
AC-SALTO-XS4-ANSI-MINI-CJ250N60CSB3	XS4 ANSI Mini BLE HID iClass Black Rdr, Entrance N lever 2-3/8" backset satin chrome (Available only in the USA and Canada)	828.51
AC-SALTO-XS4-CABLE-SP01045-100	XS4 Original connection circuit cable. For XS4 Original with door thickness up to 100mm (Available only in the USA and Canada)	9.17
AC-SALTO-XS4-CREDENTIAL-UHF-WINDSHLD-TRPDR-PWU008B	SALTO Windshield transponder ISO-Format UHF 8 bytes for SALTO WRLUD readers. White neutral. UHF UID printed on the card. (Available only in the USA and Canada)	28.07
AC-SALTO-XS4-ESCUTCHEON-AB660J00IM38	XS4 Escutcheon BLE Mifare DESFire SVN, KO Entrance ANSI J lever satin stainless (Available only in the USA and Canada)	944.49
AC-SALTO-XS4-ESCUTCHEON-KEYPAD-ANSI-AB650G00IM38WK	SALTO XS4 Electronic Escutcheon Ax650, with keypad For ANSI mortise locks, 2 handles, any type. BLE DESFire Technology:Wireless - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,424.08
AC-SALTO-XS4-ESCUTCHEON-PB-AB656N00BC38W	XS4 Escutcheon BLE Mifare DESFire SVN - Privacy Button ANSI N lever BioCote (Available only in the USA and Canada)	1,293.95
AC-SALTO-XS4-ESCUTCHEON-AB650A00IM38	XS4 Escutcheon BLE Mifare DESFire SVN, Entrance ANSI A lever satin stainless (Available only in the USA and Canada)	918.14
AC-SALTO-XS4-ESCUTCHEON-AB650A00IM38W	XS4 Escutcheon BLE Mifare DESFire SVN RFnet, Entrance ANSI A lever satin stainless (Available only in the USA and Canada)	1,157.00
AC-SALTO-XS4-ESCUTCHEON-AB650W00IM38	XS4 Escutcheon BLE Mifare DESFire SVN, Entrance ANSI W lever satin stainless (Available only in the USA and Canada)	918.20
AC-SALTO-XS4-ESCUTCHEON-AB658N61IM48C	SALTO XS4 Electronic Escutcheon Ax658, For ANSI mortise locks, 2 handles, any type, inside thumbturn 90o, with connector for mortise lock with micro-switch. BLE Mifare Technology:Wireless convertible - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	937.67
AC-SALTO-XS4-ESCUTCHEON-AJ650A00IM38W	XS4 Escutcheon BLE HID iClass SVN, Entrance ANSI A lever satin stainless (Available only in the USA and Canada)	1,081.42
AC-SALTO-XS4-ESCUTCHEON-MIFAR-ANSI-PB-AB656N00IM38W	SALTO XS4 Escutcheon BLE Mifare DESFire SVN RFnet, Privacy Button ANSI N lever satin stainless (Available only in the USA and Canada)	1,157.05
AC-SALTO-XS4-MINI-ANSI-CB250G70CSB3	SALTO XS4 Mini ANSI Electronic Escutcheon Grade 1 cylindrical latch, 2 handles, any type. Entrance Lock. BLE Mifare DESFire: Standard - standard square spindles, finishes and handles. (Available only in the USA and Canada)	878.41
AC-SALTO-XS4-ONE-ESCUTCHEON-DEADLAT-EB756HDLIMB4MD5	SALTO XS4 ONE Electronic Escutcheon Ex756, 2 Handles, any type. Electronic "do not disturb" system. BLE Mifare DESFire: Standard - standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,332.71
AC-SALTO-XS4-OP-ESCUTCHEON-BIOCOTE-AM656N00BCB38	SALTO XS4 Original + Escutcheon BLE Mifare DESFire HSE SVN Privacy Button ANSI N lever BioCote BlueNet Capable (Available only in the USA and Canada)	1,129.98
AC-SALTO-XS4-OP-ESCUTCHEON-BIOCOTE-AM656N00BCB48	SALTO XS4 Original + Escutcheon BLE Mifare DESFire HSE SVN Privacy Button ANSI N lever BioCote BlueNet Capable (Available only in the USA and Canada)	1,129.98
AC-SALTO-XS4-OP-ESCUTCHEON-BIOCOTE-AM658N61BCB38	SALTO XS4 Original + Escutcheon BLE Mifare DESFire HSE SVN leadbolt ANSI N lever BioCote BlueNet Capable (Available only in the USA and Canada)	1,129.98
AC-SALTO-XS4-OP-ESCUTCHEON-BIOCOTE-AM658N62BCB38	SALTO XS4 Original + Escutcheon BLE Mifare DESFire HSE SVN leadbolt ANSI N lever BioCote BlueNet Capable (Available only in the USA and Canada)	1,129.98
AC-SALTO-XS4-OP-ESCUTCHEON-DC-KIT-SP01798-C8-4	SALTO XS4 Original + Escutcheon Door Thickness Change Kit (Available only in the USA and Canada)	14.89
AC-SALTO-XS4-OP-HALF-ESCUTCH-ANSI-AM660W00PMBH8E5		1,152.11

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	SALTO XS4 Electronic Half Escutcheon Ax660 for panic bar, 1 handle, any type, built in mechanical cylinder with audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	
AC-SALTO-XS4-OP-HALF-ESCUTCHEON-ANSI-AM650A00BCWH8	SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar, 1 handle, any type. Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles (Available only in the USA and Canada)	1,184.73
AC-SALTO-XS4-OP-HALF-ESCUTCHEON-ANSI-AM650A00IMBH8	SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar, 1 handle, any type. Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,107.69
AC-SALTO-XS4-OP-HALF-ESCUTCHEON-ANSI-AM650G00IMBH8	SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar, 1 handle, any type. Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,107.67
AC-SALTO-XS4-OP-HALF-ESCUTCHEON-ANSI-AM650G00IMBP8	SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar, 1 handle, any type for concealed rod panic bars. Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles.(Available only in the USA and Canada)	1,107.67
AC-SALTO-XS4-OP-HALF-ESCUTCHN-ANSI-AM650G00IMBH8E5	SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar, 1 handle, any type. Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,152.11
AC-SALTO-XS4-OP-HALF-ESCUTCHN-ANSI-AM650N00IMBH8E5	SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar, 1 handle, any type. Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,061.85
AC-SALTO-XS4-OP-HALF-ESCUTCHN-ANSI-AM660B00IMBH8E5	SALTO XS4 Electronic Half Escutcheon Ax660 for panic bar, 1 handle, any type, built in mechanical cylinder with audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,152.11
AC-SALTO-XS4-OP-HALF-ESCUTCHN-ANSI-AM660J00IMBH8	SALTO XS4 Original+ Half escutcheon ANSI - Electronic Half Escutcheon Ax660 for panic bar, 1 handle, any type, built in mechanical cylinder with audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. Mechanical cylinder not included. (Available only in the USA and Canada)	1,122.78
AC-SALTO-XS4-OP-HALF-ESCUTCHEON-ANSI-AM660N00IMBH8E5	XS4 Original+ Half escutcheon BLE Mifare DESFire HSE Black Rdr KO Entrance ANSI N lever satin ss, SALTO XS4 Electronic Half Escutcheon Ax660 for panic bar, 1 handle, any type, built in mechanical cylinder with audit . Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,152.11
AC-SALTO-XS4-OP-PANIC-BAR-BIOCOTE-AM650N00BCBH8	SALTO XS4 Original + Panic Bar Trim BLE Mifare DESFire HSE SVN RIM compatible ANSI N lever BioCote BlueNet Capable (Available only in the USA and Canada)	1,181.35
AC-SALTO-XS4-OP-PANIC-BAR-BIOCOTE-AM650N00BCBP8	SALTO XS4 Original + Panic Bar Trim BLE Mifare DESFire HSE SVN Con rod compatib ANSI N lever BioCote BlueNet Capable (Available only in the USA and Canada)	1,129.98
AC-SALTO-XS4-OP-PANIC-BAR-KIT-CR-KPP17IM	SALTO XS4 Original + PB Kit Corbin Russwin ED2500 & Yale 7100 SVN satin stainless (Available only in the USA and Canada)	355.96
AC-SALTO-XS4-OP-PANIC-BAR-KIT-DK-KPP55IM	SALTO XS4 Original + PB Kit Dorma Kabba SVN satin stainless (Available only in the USA and Canada)	355.96
AC-SALTO-XS4-OP-PANIC-BAR-KIT-DORMA-KPP19IM	SALTO XS4 Panic Bar Kit for versions of DORMA. (Available only in the USA and Canada)	329.02
AC-SALTO-XS4-OP-PANIC-BAR-KIT-SAR-KPP08IM	SALTO XS4 Original + PB Kit SARGENT 8888 SVN satin stainless (Available only in the USA and Canada)	355.96
AC-SALTO-XS4-OP-PANIC-BAR-KIT-SAR-KPP39IM	SALTO XS4 Panic Bar Kit for versions of SARGENT 8800 prior to 2002 (Available only in the USA and Canada)	329.02
AC-SALTO-XS4-OP-PANIC-BAR-KIT-VD-KPB03IM-U	Kit panic bars - UNIVERSAL - KPB Kit panic bars SALTO XS4 Panic Bar Kit for versions of VON DUPRIN Satin stainless steel UI-listed (Available only in the USA and Canada)	356.99
AC-SALTO-XS4-OP-PANIC-BAR-KIT-VD-KPP03IM	SALTO XS4 Original + PB Kit Salto PBF110 Von Duprin series 98 & 99 SVN satin stainless (Available only in the USA and Canada)	355.96
AC-SALTO-XS4-OP-PANIC-BAR-KIT-VD-KPP04IM	SALTO XS4 Original + PB Kit Von Duprin series 98/9927 & 98/9957 SVN satin stainless (Available only in the USA and Canada)	355.96
AC-SALTO-XS4-OP-PANIC-BAR-KIT-VD-KPP37IM	SALTO XS4 Panic Bar Kit for versions of VON DUPRIN. (Available only in the USA and Canada)	356.99
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00BCB38E5G	SALTO XS4 Electronic Escutcheon Ax650, For ANSI mortise locks, 2 handles, any type. Technology: Mifare + Bluetooth LE + HSE, finishes and handles. (Available only in the USA and Canada)	1,222.13
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB38E5G		1,055.39

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	SALTO XS4 Electronic Escutcheon Ax650, For ANSI mortise locks, 2 handles, any type. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB48E5G	SALTO XS4 Electronic Escutcheon Ax650, For ANSI mortise locks, 2 handles, any type. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,055.39
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650N00IMBH8	SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar, 1 handle, any type. Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,020.89
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM658A62IMB38E5G	SALTO XS4 Electronic Escutcheon Ax658, For ANSI mortise locks, 2 handles, any type, inside thumbturn 90°, with connector for mortise lock with micro-switch. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,055.39
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM658A62IMB48E5G	SALTO XS4 Electronic Escutcheon Ax658, For ANSI mortise locks, 2 handles, any type, inside thumbturn 90°, with connector for mortise lock with micro-switch. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,055.39
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM660U00IMB38E5G	SALTO XS4 Electronic Escutcheon Ax660, For ANSI mortise locks, 2 handles, any type, built in mechanical cylinder with audit housing, (mechanical cylinder not included, for technical specifications consult SALTO). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,055.39
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM666A00IMB48E5G	SALTO XS4 Electronic Escutcheon Ax666, For ANSI mortise locks, 2 handles, any type, electronic "do not disturb" system, built in mechanical cylinder with audit housing, (mechanical cylinder not included). Technology: Mifare + Bluetooth LE + HSE, finishes and handles. (Available only in the USA and Canada)	1,145.07
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM668U62IMB48E5G	SALTO XS4 Electronic Escutcheon Ax668, For ANSI mortise locks, 2 handles, any type, inside thumbturn 90°, with connector for mortise lock, built in mechanical cylinder with audit housing, (mechanical cylinder not included). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,055.39
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM660N00IMB48E5G	SALTO XS4 Electronic Escutcheon Ax660, For ANSI mortise locks, 2 handles, any type, built in mechanical cylinder with audit housing, (mechanical cylinder not included, for technical specifications consult SALTO). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,145.10
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB38	XS4 Original+ Wide Body Escutcheon - ANSI BLE Mifare DESFire HSE Black Rdr Entrance ANSI A lever satin ss (Available only in the USA and Canada)	1,056.20
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB48	SALTO XS4 Electronic Escutcheon Ax650, For ANSI mortise locks, 2 handles, any type. Technology: Mifare + Bluetooth LE + HSE, finishes and handles. (Available only in the USA and Canada)	1,056.20
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMB48G	SALTO XS4 Original+ Wide Body Escutcheon - ANSI - Electronic Escutcheon Ax650, For ANSI mortise locks, 2 handles, any type. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,100.67
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650A00IMBH8E5	SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar, 1 handle, any type. Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,061.85
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650G00IMB38E5	SALTO XS4 Electronic Escutcheon Ax650, For ANSI mortise locks, 2 handles, any type. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,100.67
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650N00IMB38	SALTO XS4 Electronic Escutcheon Ax650, For ANSI mortise locks, 2 handles, any type. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,056.18
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650N00IMB38E5	SALTO XS4 Original+ BLE Mifare DESFire HSE Black Rdr Entrance ANSI N lever satin ss, XS4 Original+ Wide Body Escutcheon - ANSI Electronic Escutcheon Ax650, For ANSI mortise locks, 2 handles, any type. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,100.67
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650W00IMB38	XS4 Original+ BLE Mifare DESFire HSE Black Rdr Entrance ANSI W lever satin ss (Available only in the USA and Canada)	1,053.12
AC-SALTO-XS4-OP-WB-ESCTCHEON-ANSI-AM650W00IMBH8	SALTO XS4 Electronic Half Escutcheon Ax650 for panic bar, 1 handle, any type. Technology: Mifare + Bluetooth LE + HSE and standard square spindles, finishes and handles. (Available only in the USA and Canada)	1,107.69

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM650W00NEB38	XS4 Original+ BLE Mifare DESFire HSE Black Rdr Entrance ANSI W lever blk chromium (Available only in the USA and Canada)	1,104.41
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM650W00NEB8	XS4 Original+ Half Escutcheon for Panic Bar BLE Mifare DESFire HSE Black Rdr Entrance ANSI W lever blk chromium (Available only in the USA and Canada)	1,155.73
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM656A00IMB48	XS4 Original+ BLE Mifare DESFire HSE Black Rdr Privacy Button ANSI A lever satin ss (Available only in the USA and Canada)	1,053.12
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM656A00IMB48G	SALTO XS4 Electronic Escutcheon Ax656, For ANSI mortise locks, 2 Handles, any type, Electronic "do not disturb" system. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,100.67
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM656N00IMB38	SALTO XS4 original+ Wide Body Electronic Escutcheon, For ANSI mortise locks, 2 Handles, any type, Electronic "do not disturb" system. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. XS4 Original+ BLE Mifare DESFire HSE Black Rdr Privacy Button ANSI N lever satin ss (Available only in the USA and Canada)	1,056.20
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM656N00IMB38G	SALTO XS4 Electronic Escutcheon Ax656, For ANSI mortise locks, 2 Handles, any type, Electronic "do not disturb" system. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,100.67
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM656W00IMB38	XS4 Original+ BLE Mifare DESFire HSE Black Rdr Privacy Button ANSI W lever satin ss (Available only in the USA and Canada)	1,053.12
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM658N62DBB38	SALTO XS4 original+ Wide Body Electronic Escutcheon, For ANSI mortise locks, 2 handles, any type, inside thumbturn 90°, with connector for mortise lock with micro-switch. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. XS4 Original+ BLE Mifare HSE Dark Bronze Black Rdr ANSI N lever (Available only in the USA and Canada)	1,107.67
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM658N62IMB38	XS4 Original+ BLE Mifare DESFire HSE Black Rdr Deadbolt ANSI N lever satin ss (Available only in the USA and Canada)	1,056.20
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM660A00IMB38E5	SALTO XS4 Electronic Escutcheon Ax660, For ANSI mortise locks, 2 handles, any type, built in mechanical cylinder with audit housing, (mechanical cylinder not included). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. XS4 Original+ BLE Mifare DESFire HSE Black Rdr KO Entrance ANSI A lever satin ss (Available only in the USA and Canada)	1,100.67
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM660A00IMB3SG	SALTO XS4 Electronic Escutcheon Ax660, For ANSI mortise locks, 2 handles, any type, built in mechanical cylinder with audit housing, (mechanical cylinder not included, for technical specifications consult SALTO). Technology: Mifare + Bluetooth LE + HSE - 8 mm split square spindle, finishes and handles. (Available only in the USA and Canada)	1,100.62
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM660J00IMB38	SALTO XS4 Electronic Escutcheon Ax660, For ANSI mortise locks, 2 handles, any type, built in mechanical cylinder with audit housing, (mechanical cylinder not included, for technical specifications consult SALTO). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,086.45
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM666A00IMB48G	SALTO XS4 Electronic Escutcheon Ax666, For ANSI mortise locks, 2 handles, any type, electronic "do not disturb" system, built in mechanical cylinder with audit housing, (mechanical cylinder not included). Technology: Mifare + Bluetooth LE + HSE, finishes and handles. (Available only in the USA and Canada)	1,100.63
AC-SALTO-XS4-OP-WB-ESCUTCHEON-ANSI-AM666N00BCB38	SALTO XS4 Electronic Escutcheon Ax666, For ANSI mortise locks, 2 handles, any type, electronic "do not disturb" system, built in mechanical cylinder with audit housing, (mechanical cylinder not included). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,133.25
AC-SALTO-XS4-OP-WB-ESCUTCHEONANSI-AM658N62IMB38E5G	SALTO XS4 Original+ Wide Body Escutcheon - ANSI - Electronic Escutcheon Ax658, For ANSI mortise locks, 2 handles, any type, inside thumbturn 90°, with connector for mortise lock with micro-switch. Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,145.37
AC-SALTO-XS4-OP-WB-ESCUTCHEONANSI-AM660A00IMB48E5G	SALTO XS4 Electronic Escutcheon Ax660, For ANSI mortise locks, 2 handles, any type, built in mechanical cylinder with audit housing, (mechanical cylinder not included, for technical specifications consult SALTO). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles.(Available only in the USA and Canada)	1,055.39
AC-SALTO-XS4-OP-WB-ESCUTCHEONANSI-AM668U61IMW38E5G	SALTO XS4 Electronic Escutcheon Ax668, For ANSI mortise locks, 2 handles, any type,inside thumbturn 90°, with connector for mortise lock, built in mechanical cylinder with audit housing,(mechanical cylinder not included). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles.(Available only in the USA and Canada)	1,055.39

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

AC-SALTO-XS4-OP-WB-ESCUTHEON-ANSI-AM660N00IMB38E5	XS4 Original+ BLE Mifare DESFire HSE Black Rdr KO Entrance ANSI N lever satin ss, SALTO XS4 Electronic Escutcheon Ax660, For ANSI mortise locks, 2 handles, any type, built in mechanical cylinder with audit housing, (mechanical cylinder not included). Technology: Mifare + Bluetooth LE + HSE - 8 mm square spindle, finishes and handles. (Available only in the USA and Canada)	1,100.67
AC-SALTO-XS4-PANIC-RIM-ANSI-BIOCOTE-AB650N00BCH8	XS4 Panic Bar Trim BLE Mifare DESFire SVN - RIM compatible ANSI N lever BioCote (Available only in the USA and Canada)	1,088.80
AC-SALTO-XS4-PANIC-RIM-ANSI-BIOCOTE-AB650N00BCH8W	XS4 Panic Bar Trim BLE Mifare DESFire SVN RFnet - RIM compatible ANSI N lever BioCote (Available only in the USA and Canada)	1,214.13
AC-SALTO-XS4-PB-KIT-CR-KPB17IM	XS4 PB Kit Corbin Russwin ED2500 & Yale 7100 - SVN satin stainless (Available only in the USA and Canada)	355.95
AC-SALTO-XS4-PB-KIT-SG-KPB08IM	XS4 PB Kit SARGENT 8888 - SVN satin stainless (Available only in the USA and Canada)	355.95
AC-SALTO-XS4-PB-KIT-SG-KPB08IMW	XS4 PB Kit SARGENT 8888 - SVN RFnet satin stainless (Available only in the USA and Canada)	487.19
AC-SALTO-XS4-PB-KIT-VD-KPB03IM	XS4 PB Kit Salto PBF110 Von Duprin series 98 & 99 - SVN satin stainless (Available only in the USA and Canada)	355.95
AC-SALTO-XS4-PB-KIT-VD-KPB04IM	XS4 PB Kit Von Duprin series 98/9927 & 98/9957 - SVN satin stainless (Available only in the USA and Canada)	355.95
AC-SALTO-XS4-PB-KIT-VONDUPRIN-98-99-KPB03IMW	SALTO KPB03XX.. Adapter Kit for Von Duprin 98/99 Panic Bar Single Point (Available only in the USA and Canada)	460.88
AC-SALTO-XS4-PB-MIFARE-RIM-EXIT-ANSI-AB650N00IMH8W	SALTO Mortise XS4 Panic Bar Trim BLE Mifare DESFire SVN RFnet, RIM compatible ANSI N lever satin stainless (Available only in the USA and Canada)	1,173.42
AC-SALTO-XS4-READER-UHF-LD-WRLUD24BUS	SALTO XS4 UHF Long Distance Reader. Up to 7 meters distance reading. To be used with CU42E0 controller. Needs a WRLUD-SIC1 to be connected to the CU. Mounting bracket included. Cable and WRLUD-SIC1 not included. (Available only in the USA and Canada)	4,144.63
AC-SALTO-XS4-UHF-LD-CONNECTION-CABLE-10M-WRLUD-C10	SALTO XS4 UHF Long Distance Reader 10 meters connection cable - 10m length Connection cable - 10m with 4 pin connector. (Available only in the USA and Canada)	220.60
AC-SALTO-XS4-UHF-LD-SIC-MODULE-CONVERTR-WRLUD-SIC1	SALTO XS4 UHF long Distance Reader SIC module LD Reader - CU42E0 Wiegand signal converter device. (Available only in the USA and Canada)	474.80

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

Professional Services

Onsite

MODEL NUMBER	DESCRIPTION	MSRP \$
PRO-ACM-ONSITE-8H	ACM Professional Services, 8 hours on-site consulting (Includes all travel costs), Contact ACM SE prior to Purchase	8,000.00

Remote

MODEL NUMBER	DESCRIPTION	MSRP \$
AC-PRO-HM-1024	One-time migration of field hardware data from a Mercury Security Hardware-based system of up to 1024 card readers to Avigilon ACM and includes controllers, reader interface modules, input modules, output modules, holidays, and schedules. PREREQUISITES: AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	54,900.00
AC-PRO-HM-2048	One-time migration of field hardware data from a Mercury Security Hardware-based system of up to 2048 card readers to Avigilon ACM and includes controllers, reader interface modules, input modules, output modules, holidays, and schedules. PREREQUISITES: AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	109,800.00
AC-PRO-HM-256	One-time migration of field hardware data from a Mercury Security Hardware-based system of up to 256 card readers to Avigilon ACM and includes controllers, reader interface modules, input modules, output modules, holidays, and schedules. PREREQUISITES: AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	13,800.00
AC-PRO-HM-512	One-time migration of field hardware data from a Mercury Security Hardware-based system of up to 512 card readers to Avigilon ACM and includes controllers, reader interface modules, input modules, output modules, holidays, and schedules. PREREQUISITES: AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	27,500.00
AC-PRO-MIG-LDAP	One-time migration of Identity data from a single LDAP-based data source into Avigilon ACM. Migrated data will include demographic information, images, tokens, and roles. PREREQUISITES: AC-SW-LIC-LDAP-6-P ACM LDAP collaboration licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	9,300.00
AC-PRO-MIG-ORCL	One-time migration of Identity data from a single Oracle data source into Avigilon ACM. Migrated data will include demographic information, images, tokens, and roles. PREREQUISITES: AC-SW-LIC-ORCL-6-P ACM Oracle collaboration licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	9,300.00
AC-PRO-MIG-SQL	One-time migration of Identity data from a single SQL data source into Avigilon ACM. Migrated data will include demographic information, images, tokens, and roles. PREREQUISITES: AC-SW-LIC-SQL-6-P ACM SQL collaboration licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	9,300.00
AC-PRO-MIGF-LDAP	One-time migration and filtering of Identity data from a single LDAP-based data source into Avigilon ACM. Migrated data will include demographic information, images, tokens, and roles. PREREQUISITES: AC-SW-LIC-LDAP-6-P ACM LDAP collaboration licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	12,400.00
AC-PRO-MIGF-ORCL	One-time migration and filtering of Identity data from a single Oracle data source into Avigilon ACM. Migrated data will include demographic	12,400.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").

	information, images, tokens, and roles. PREREQUISITES: AC-SW-LIC-ORCL-6-P ACM Oracle collaboration licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	
AC-PRO-MIGF-SQL	One-time migration and filtering of Identity data from a single SQL data source into Avigilon ACM. Migrated data will include demographic information, images, tokens, and roles. PREREQUISITES: AC-SW-LIC-SQL-6-P ACM SQL collaboration licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	12,400.00
AC-PRO-SYNC-AD-AZURE	On-going one-way inbound synchronization of Identity data from a single AzureAD data source into Avigilon ACM. Imported data will include demographic information, images, tokens, and roles. PREREQUISITES: Separate Windows-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	22,750.00
AC-PRO-SYNC-AD-GEN	On-going one-way inbound synchronization of Identity data from a single Generic AD data source into Avigilon ACM. Imported data will include demographic information, images, tokens, and roles. PREREQUISITES: Separate Windows-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	22,750.00
AC-PRO-SYNC-CUSTOM	Hourly Rate to configure on-going one-way inbound synchronization of Identity data from a single Custom Third-Party data source into Avigilon ACM. Imported data will include demographic information, images, tokens, and roles. PREREQUISITES: Separate Windows-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	100.00
AC-PRO-SYNC-LDAP	On-going one-way inbound synchronization of Identity data from a single LDAP data source into Avigilon ACM. Imported data will include demographic information, images, tokens, and roles. PREREQUISITES: Separate Windows-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	22,750.00
AC-PRO-SYNC-ORCL	On-going one-way inbound synchronization of Identity data from a single Oracle data source into Avigilon ACM. Imported data will include demographic information, images, tokens, and roles. PREREQUISITES: Separate Windows-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	22,750.00
AC-PRO-SYNC-SQL	On-going one-way inbound synchronization of Identity data from a single SQL data source into Avigilon ACM. Imported data will include demographic information, images, tokens, and roles. PREREQUISITES: Separate Windows-based server (virtual is acceptable) to host the synchronization service. AC-SW-LIC-REST-6-P ACM Rest API licensing is required and is not included. Service will be delivered remotely and requires remote access to the customers environment.	22,750.00
PRO-ACM-REMOTE-4H	ACM Professional Services, 4 hours remote consulting, Contact ACM SE prior to Purchase	2,500.00
PRO-ACM-REMOTE-8H	ACM Professional Services, 8 hours remote consulting, Contact ACM SE prior to Purchase	5,000.00

All prices are exclusive of taxes and freight. Motorola Solutions reserves the right to make changes to pricing and discount margins. All installation and use of Access Control Manager software is governed by its end user license agreement (EULA).

CONFIDENTIAL : The contents of this document are considered confidential and should not be posted on a public access website, made available for general public distribution, or otherwise shared with others without prior written authorization from Motorola Solutions Inc. ("Motorola Solutions").