

# C430-HDi

## ALPR CAMERA



### Features

- Dual-lane intelligent camera
- Dual 3MP Global Shutter sensor design
- 12mm-50mm ultra high-resolution lens
- Quad high-power integrated IR illuminator
- 130' (40m) operational range
- Optional HD CCTV Camera (ONVIF)
- IP67 for outdoor operation

### Benefits

- Provides multi-lane ALPR coverage, license plate capture and reads plus optional HD CCTV overview
- Flexible deployment options with telephoto lens
- Does not require additional external illuminators
- Additional situational awareness with optional ONVIF conformant HD CCTV camera providing a separate wide overview video stream
- Operates in severe weather conditions
- Reads License Plates at Night



The NDI Recognition Systems® C430-HDi ALPR camera with Infrared (IR) LED illumination options combine high-quality, dual-sensor capabilities with a motorized telephoto zoom lens to accurately capture license plate characteristics and color contrasts in a fixed, mobile, or portable system solution.

Powered by NDI's industry-leading TALON™ engine and backed with superior customer care and product training, the C430-HDi ALPR camera is an ideal ALPR solution for car park management, traffic management, speed enforcement, trafficking prevention and criminal investigations by law enforcement, government and commercial organizations worldwide.

The C430-HDi ALPR camera is designed to read varying license plate types and styles at distances of up to 130 feet (40m) and across Single or Dual-Lanes and consistently delivers high reliability and read accuracy in all weather conditions, day or night.

## Applications

- Dual-Lane or Single-Lane
- No External Processor
- Fixed Installation

|   |  |                                   |   |
|---|--|-----------------------------------|---|
| <b>Dimensions (WxDxH)</b>               | 245mm x 255mm x 125mm<br>(Bracket 60mm high)         | <b>Operating Voltage</b>          | DC: 24V to 48V or<br>PoE: IEEE 802.3bt Type 4 compliant |
| <b>Environmental Rating (IP)</b>        | IP67   | <b>Power Consumption</b>          | 45W Typical, 78W Max                                    |
| <b>Illumination</b>                     | Quad High-Power LEDs<br>810nm, 850nm or 940nm        | <b>Weight</b>                     | 7.7lbs / 3.5kg  |
| <b>Operating Temperature / Humidity</b> | -10 °C to +55 °C<br>100% Relative Humidity           | <b>Connections (Connectivity)</b> | LAN – 8-pin socket / Power - 4 pin socket               |
| <b>Lens</b>                             | 12mm - 50mm Telephoto (ANPR)<br>2.8mm - 8.5mm (CCTV) | <b>Customer Segment</b>           | Law Enforcement / Commercial                            |

NDI Recognition Systems, 105 E. State Road 434, Winter Springs, Florida 32708

Tel: 866 458 0426 | Fax: 321 441 1801 | Web: [www.ndi-rs.com](http://www.ndi-rs.com) | Email: [sales@ndi-rs.com](mailto:sales@ndi-rs.com)