



PRODUCT FEATURES & SPECIFICATIONS



FEATURES:

- Ⓞ 4G LTE CAT-12 Internal Cellular Modem
- Ⓞ FirstNet Capable
- Ⓞ Supports All Major US Carriers, Dual SIM Capability (AT&T, FirstNet, Verizon, US Cellular, Sprint)
- Ⓞ Dual WiFi: Hotspot around the vehicle
Access Point for high-speed offload
- Ⓞ Integrated Crash Sensor
- Ⓞ Integrated Battery Monitoring & Internal Temperature Sensor (for health monitoring)
- Ⓞ Optically Isolated Trigger Inputs & 1 Relay Output (5 total, 4.5V to 24V)
- Ⓞ Integrated Siren Trigger Interface
- Ⓞ Integrated On-Board Diagnostics: J1979 (ISO 15675-4), J1939 (The ISO 15675-4 was mandated in 2008 for all US cars: Is CAN interface)
- Ⓞ Under Voltage Warning / Shutdown
- Ⓞ Software Adjustable Shutdown Timer
- Ⓞ Integrated GPS with Antenna Detection Technology (for health monitoring)
- Ⓞ Remotely manage network configurations: Firewall, IPSec, Port Forwarding, Split networking, black and white list, bandwidth management

ROCKET IOT - XLE

Dimensions: 197mm (l) x 150mm (w) x 43mm (h)

Material: Cast Aluminum

Power: 9 - 24Vdc / 14W

Storage: 120GB Solid State Drive

Processor: Intel Dual Core Atom Processor, 1.33GHz

Memory: 2GB RAM, 1066 MT/s

Connectors: Color Coded, Water Tight, Locking

- 1 RED: Power and On-Board Diagnostics
- 2 DARK BLUE: 4 Ethernet (802.3af PoE 10/100Mb)
- 1 BLUE: 1Gb Ethernet
- 1 BLACK: Triggers (1 Ignition, 4 Programmable Inputs, 1 Siren, 1 Relay Output)
- 1 Radar Interface (RS-232)
- 1 USB 2.0 (optional)

RF Connectors

- 2 FME Cellular
- 2 RSPMA 2.4/5 GHz (WiFi 802.11 g/n/ac MIMO)
- 2 RSPMA 2.4/5 GHz (WiFi 802.11 g/n/ac MIMO)
- 1 SMA GPS

Environmental

- Temperature Range: -20° to 70° C
- IP-67 (submerge 1M for 30min w/ no water ingress)

Certifications

- FCC
- MIL-810G: Shock, Vibration & Temperature
- PTCRB

IN-CAR CAMERAS

Front Camera

- 2MP Full HD
- 30 FPS at 1080p (H.264)
- 0.1 LUX Minimum Illumination for Optimal Low Light Performance
- Auto Day / Night mode
- 3.7mm Lens (Wide Angle)
- Robust Low Profile Mounting

Back Seat

- 2MP Full HD
- 30 FPS at 1080p (H.264)
- 0 LUX Min Illumination
- Auto Day / Night mode
- Integrated Microphone
- 2.9mm Lens (Wide Angle)
- Robust Mounting Design