

OPTICOM™ 794 LED Emitter



DESCRIPTION

The Opticom 794 LED Emitter is a compact, lightweight, weather-resistant encoded signal device intended for use on priority vehicles. The Opticom 794 emitter consists of an LED array with an integral power supply and the required cables. Accessory switch devices are also available. The operation of the device may be customized through its interface software or remote coding unit.

The encoded signal pattern (composed of the individual vehicle class code and vehicle identification number) generated by the Opticom 794 emitter is determined after installation through the use of interface software or remote coding unit.

The Opticom 794 emitter, when installed on authorized service and maintenance vehicles, may also be configured to utilize the automated range-setting feature of Opticom 700 Series Phase Selectors and Opticom 400 Series Discriminators. This feature refines and simplifies individual intersection setup and maintenance techniques.

The Opticom 794 emitter separates precisely-timed pulses of infrared light at the base flash rate of approximately 10 or 14 Hz. It also interleaves programmed encoded pulses that carry the vehicle class and ID number information. These infrared pulses are sensed and processed by other Opticom Infrared system components to cause activation of the system.

The Opticom 794 emitter is capable of being programmed via the RC790 remote coding unit, eliminating any dependency on a computer. By simply pointing the RC790 at the Opticom 794

emitter, the user can communicate vehicle class and ID, visible LED, disable mode, diagnostics and default settings with just pushes of a button.

Description of Models

- Opticom 794H LED Emitter: High-priority emitter
- Opticom 794L LED Emitter: Low-priority emitter
- Opticom 794T LED Emitter: Low-priority emitter with reduced output for transit signal priority applications
- Opticom 794R Emitter: Range-setting emitter for high priority, low priority or probe frequency

FEATURES

- Discrete, penetrating infrared communication
 - Directional
 - Consistent, day and night transmission
 - All-weather performance
- Compact, single source system
- High- and low-priority operation as well as probe-frequency capability
- Encoded signal transmission
 - High priority: 10,000 discrete vehicle IDs (10 classes of vehicles and 1,000 individual codes available within each class)
 - Low priority: 10,000 discrete vehicle IDs (10 classes of vehicles and 1,000 individual codes available within each class)
- Remote range-setting capability
- RS485, J1708 serial interface
- Low power consumption

Global Traffic Technologies, LLC
7800 Third Street North
St. Paul, Minnesota 55128-5441
1-800-258-4610
651-789-7333
www.gtt.com

Global Traffic Technologies Canada, Inc.
157 Adelaide Street West, Suite 448
Toronto, ON M5H 4E7 Canada
1-800-258-4610

Global Traffic Technologies, LLC
1210 Parkview
Reading RG7 4TY
United Kingdom
+44 (0) 7999 908916

For complete warranty information
visit gtt.com. Please recycle. Printed in U.S.A.
© Global Traffic Technologies, LLC 2017.
All rights reserved. 79-1000-0377-0 (B)



GLOBAL TRAFFIC TECHNOLOGIES

OPTICOM™ 794 LED Emitter

- CE certified
- SAE J575, SAE J1455 compliant
- Improved installation flexibility
 - Mounts directly on vehicle
- Automatic emitter disable, indicated by slow flashing of the emitter switch's indicator light or emitter's visible LEDs
- Self-diagnostic with visual feedback through the switch's indicator light and visible LED indicator lights
- Cumulative flash counts available through the interface software or RC790 diagnostic mode

ACCESSORIES

- Switches
 - Rocker-type switch for knockout/panel mounting (with simple mounting bracket) (model 793B)
 - Three versions of fully enclosed pushbutton switches (with dashboard mounting bracket)
- On/Off only (model 793S)
- On/Off for high-priority, low-priority and probe frequency with range setting

- Automated range-setting control
- Bezel mount kit
- Programmable via interface software and/or RC790 remote coding unit

OPERATING PARAMETERS

Opticom 794 LED Emitter

High- or low-priority and probe-frequency operation selected by model and switch combination

- 10,000 vehicle codes available in high priority
- 10,000 vehicle codes available in low priority
- Automated range-setting feature
- Isolated power supply and emitter for positive or negative ground vehicle power system
- Less than 1 amp peak current draw
- Self-diagnostic
- Precisely controlled high-priority flash rate of 14 Hz
- Precisely controlled low-priority flash rate of 10 Hz
- Transmission range up to 2,500 feet (762 m)

- Electrical
 - Input Voltage: 10 to 32 VDC
 - Current: < 1 amp
- Environmental
 - Temperature: -30° F (-34° C) to +165° F (+74° C)
 - Relative Humidity: 5% to 95%

PHYSICAL DIMENSIONS

Opticom 794 LED Emitter

Depth: 2.25 in. (5 cm)

Width: 5.8 in. (14 cm)

Height: 3.7 in. (9 cm)

Model RC790 Remote Coding Unit

- LCD display and a keypad
- Operates on four AAA batteries

Length: 6.3 in. (16 cm)

Width: 3.7 in. (9.4 cm)

Thickness: 1.0 in. (2.5 cm)

Weight: 0.5 lb. (.2 kg)

	793S Switch	793B Switch	793R Switch	Customer-supplied switch
Opticom 794H Emitter	High Priority/Off	High Priority/Off	Not available	High Priority/Off
Opticom 794L Emitter	Low Priority/Off	Low Priority/Off	Not available	Low Priority/Off
Opticom 794T Emitter	Low Priority/Off	Low Priority/Off	Not available	Low Priority/Off
Opticom 794R Emitter	Not available	Not available	High and Low Priority/Off/Probe Frequency and Range Setting	Not available

