



Committed to the Cut.®

THE GRASSHOPPER COMPANY

Grasshopper MidMount 200V-G4 Series – Build Sheet

All Prices Are MSRP Eff 9/01/2023

• 534088 225VG4/52	\$10,610.00
• 534089 225VG4/61	\$10,830.00
• 534091 226VG4/52	\$10,820.00
• 534092 226VG4/61	\$11,040.00

Discount off MSRP for 200V-G4 Series Models: 12%

Freight/Setup Charges:

Standard Freight Charge *: \$480.00/mower
(Rate is for shipping to the 48 contiguous United States, does not include Alaska or Hawaii. Regional rates may vary, please inquire for pricing.)

Add: Implement Freight Charge *: \$210.00/implement
(Implements include but not limited to: AERA-vators, Sweepster Brooms, Grass Collectors, Cabs)

Add: Other Implement Freight Charge *: \$90.00/implement
(Other implements include but not limited to: snowthrowers, 72" decks, highlift mount kits, canopies)

Add: Special Handling Shielded Sprayers & Turbine Blowers: \$310.00/implement

Add: Mower Setup: \$150.00/mower

Add: Implement Setup: \$150.00/implement

* Freight charges are for mowers & implements ordered at the same time. Freight rates for implement only orders will be Price-On-Request. Stated freight rates are based on factory discretion. Other freight options are available, please inquire for pricing.

200V-G4 SERIES AIR-COOLED MIDMOUNT™

Take performance
to the next level.



LIMITED WARRANTY†

2 YEAR

— 800 HRS —

COMMERCIAL

LIMITED WARRANTY†

4 YEAR

— 800 HRS —

RESIDENTIAL

225V-G4

52 61

747 cc, V-twin, OHV
Kohler Confidant
gasoline engine

226V-G4

52 61

810 cc, V-twin, OHV
B&S Vanguard
gasoline engine

200V: Increase your productivity with speeds up to 9.0 mph and 5.00 acres per hour with a 61-inch cutting deck.*

9 MPH
5.00
ACRES PER HOUR*

Enjoy comfort, performance and durability with a compact 200V Series mower. An ergonomic design and integrated, multi-point suspension, coupled with the industry's most comfortable seat, lets you stay comfortably in control — even at faster mowing speeds.

200V-G4 models feature G4 Hydro-Gear ZT-4400 transmissions, which are self-contained, heavy-duty commercial transaxles that provide powerful, smooth response. Integrated cooling fans and 1-3/8-inch axles extend service life, and best-in-class transmission fluid change intervals reduce costs and maintenance time.

Grasshopper's intelligent design transfers more power to the cutting deck to maintain optimum blade tip speed and enhance cut quality.

Only two Access-Eze™ lubrication points cut maintenance time up to 95%.

5.5-inch deep decks designed for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple. Optional four-spindle 4XRD dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing.

The deep-cushioned, deluxe Premier Comfort seat features a coil-spring suspension and padded lumbar support with sliding 2-inch fore and aft adjustment for all-day comfort. Iso-mounting eliminates vibration even before it reaches the seat, and both padded seat and foldable armrests are covered in scuff-resistant, breathable CoolTemp Cordura® fabric, which dissipates heat and won't tear or crack with extended use.

QuikAjust Tilt™ steering levers with “no tools” adjustment provide a 9-inch range for maximum comfort and fit.

A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

The 6.5 gal/24.6L single-fill fuel tank under the seat lowers the center of gravity of the machine, providing traction and stability for an enhanced ride. Standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (see page 7)
- » 4X Rear Discharge™ decks (see page 5)
- » Down Discharge™ mulching packages (see page 5)
- » Side discharge control kit (see page 5)
- » Foot pedal extension kit for QuikAjust™ DropPin™ height adjustment
- » TrimAide™ anti-scalp roller kit — for 52-inch decks (see page 5)
- » Speed-Trimming™ heavy-duty anti-scalp roller kit — for 61-inch decks (see page 5)
- » Air Dam kit — for dry, dusty conditions (see page 7)
- » LED work lights — plug-in ready
- » Yellow beacon light
- » Sunshade Canopy — vinyl or aluminum
- » Custom Cordura® weather cover
- » GrassMax™ blade options (see page 6)
- » Heavy-duty, grass-grooming striping kit (see page 5)
- » Wide seat conversion kit
- » Extended levers for taller operators
- » Foldable ROPS with adjustable seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels
- » DuraFlex™ suspension forks
- » Edge-EZE™ edger



Optional DuraFlex™
Suspension Fork

AIR-COOLED 200V-G4 SERIES-SPECIFICATIONS

MODEL – CUTTING WIDTH	225V-G4 52	225V-G4 61	226V-G4 52	226V-G4 61
ENGINE				
Type/Displacement/Cylinders				
Kohler Confidant gasoline/45.6 cu. in. (747 cc)/V-twin	•	•		
B&S Vanguard – gasoline/49.4 cu. in. (810 cc)/v-twin			•	•
Lubrication System				
Pressure Lube, Filter				
Crankshaft				
Vertical				
Cooling System				
Air				
Fuel / Capacity				
Gasoline - unleaded / 6.5 U.S. Gal (24.6 L)	•	•	•	•
Air Cleaner				
Heavy-duty cyclonic air filter with QuadClean™ multi-stage air filtration	•	•		
Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management			•	•
Muffler				
Ultra-quiet, single, industrial type				
MOWING DECKS				
Construction (Robotic-welded steel)				
Double-layered 10-gauge plus 10-gauge formed-steel spindle plane 0.269 in. (6.83 mm) thick with 7-gauge skirts				
Spindle plane is 0.9 in. (22.86 mm) thick in stress zones; anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck				
Blades (MARBAIN®, 1/4-in.)				
(3) 18 in. (45.7 cm)	•		•	
(3) 21 in. (53.3 cm)		•		•
Spindle Assemblies				
Turned, ground and polished 2.5 cm (approx. 1 in.) outside diameter (O.D.) precision shaft; spindle head designed to eliminate fiber wrap; double bearings, non-greasable				
Spindle Housing				
8-in. (20.3 cm)-diameter machined aluminum housing with 6-bolt pattern				
Spindle Cones				
Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion				
QuikAdjust™ DropPin™ Height Adjustment				
Foot-controlled height adjustment pedal with pin				
Cutting Height Range				
1.0 – 4.5 in. (2.5 – 11.4 cm) in 1/4-inch increments				
Blade Drive				
Belt drive with single Kevlar V-belt & idler arm tensioning				
STARTER & ELECTRICAL SYSTEM				
Maintenance-Free Battery/Charging Capacity/Starter				
12 Volt/15 amp/solenoid shift	•	•		
12 Volt/16 amp/solenoid shift			•	•
Ignition				
Breakerless				
Interlock System				
Prevents engine start when PTO clutch is engaged or steering levers are in drive position; allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral				
ULTIMATE OPERATOR STATION™				
Premium Comfort Seat				
Iso-mounted, high-back, deep-cushioned, foam-padded Cordura®-covered, padded foldable arms, padded backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back; adjustable fore and aft				
Operator Protection				
ROPS with seat belt				
Suspension				
Roomy, iso-mounted footrest with Shock Impact Reduction System™ (SIRS™)				
Console-Mounted Instruments				
Low engine oil pressure, digital hour meter, parking brake indicator light, ignition switch, choke & push/pull PTO switch	•	•	•	•
Work Lights (Pre-wired)				
LED (optional)				

MODEL – CUTTING WIDTH	225V-G4 52	225V-G4 61	226V-G4 52	226V-G4 61
TRANSMISSION & STEERING				
Type				
Heavy-duty Hydro-Gear ZT-4400 hydrostatic transmissions with cooling fans; integrated transaxles with 12 cc piston pumps and 16 cc piston motors, gear reduction, internal disc brakes, and 1-3/8 inch axles	•	•	•	•
Filtration/Hydro Fluid				
Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals after 100-hour break in oil change				
Speed				
0 – 9.0 mph (0 – 14.5 kph) forward	•	•	•	•
0 – 6.0 mph (0 – 9.7 kph) reverse				
Turning Radius				
True zero degree, turns within own length with counter-rotating, independently powered drive wheels				
Steering				
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch comfort range that automatically return to neutral from either forward or reverse position				
Brakes				
Dynamic braking through hydrostatic transmission				
Parking Brake				
Internal disc brake in transmission				
TIRE SIZES				
Drive Wheels – Standard (5-bolt pattern)				
23 x 10.5-12 turf type, 4-ply rated	•	•	•	•
Front Casters				
13 x 6.5-6 rib tread, pneumatic with double-sealed bearings				
DIMENSIONS (Mower & Deck)				
Mulch Width/Length (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.)				
53.5 in. (135.9 cm)/76.0 in. (193.0 cm)	•		•	
62.5 in. (158.8 cm)/79.0 in. (200.7 cm)		•		•
Height (Seat back)				
46.0 in. (116.8 cm)				
Height (Seat cushion)				
30.0 in. (76.2 cm)				
Height (ROPS)				
68.0 in. (172.7 cm)				
Drive Tire Track Width (outside edge to outside edge)				
50.0 in. (127.0 cm)				
WEIGHT				
Uncrated (Mower & Deck)				
960 lbs. (435.4 kg)			•	
980 lbs. (444.5 kg)	•			
1030 lbs. (467.2 kg)				•
1050 lbs. (476.3 kg)		•		
Mulching Package (Package includes high-low mulching blades.)				
29 lbs. (13.2 kg)	•		•	
36 lbs. (16.3 kg)		•		•

• Standard ○ Option