



Committed to the Cut.®

THE GRASSHOPPER COMPANY

Grasshopper MidMount 300 Series – Build Sheet

All Prices Are MSRP Eff 9/01/2023

534172 329B/52	\$14,765.00
534177 329B/61	\$14,850.00
534183 335B/61	\$15,645.00
534184 335B/72	\$16,190.00
534171 329/52	\$18,435.00
534176 329/61	\$18,695.00
534181 329/72	\$19,195.00
534151 325D/52	\$19,040.00
534157 325D/61	\$19,300.00
534162 325D/72	\$19,765.00

Discount off MSRP for 300 Series Models: 23%

Freight/Setup Charges:

Standard Freight Charge *: \$480.00/mower
(Rate is for shipping to the 48 contiguous United States, does not include Alaska or Hawaii. Regional rates may vary, please inquire for pricing.)

Add: Implement Freight Charge *: \$210.00/implement
(Implements include but not limited to: AERA-vators, Sweepster Brooms, Grass Collectors, Cabs)

Add: Other Implement Freight Charge *: \$90.00/implement
(Other implements include but not limited to: snowthrowers, 72" decks, highlift mount kits, canopies)

Add: Special Handling Shielded Sprayers & Turbine Blowers: \$310.00/implement

Add: Mower Setup: \$150.00/mower

Add: Implement Setup: \$150.00/implement

* Freight charges are for mowers & implements ordered at the same time. Freight rates for implement only orders will be Price-On-Request. Stated freight rates are based on factory discretion. Other freight options are available, please inquire for pricing.

300 SERIES AIR-COOLED MIDMOUNT™

Unexpected power in
the straightaways

LIMITED WARRANTY†

3 YEAR
— UNLIMITED HRS —
COMMERCIAL

4 YEAR
— 800 HRS —
RESIDENTIAL

ComfortReach™ with “no tools”
2-in. adjustment range



3358
BIG BLOCK

61 72

993cc, V-twin OHV
Vanguard Big Block
air-cooled gasoline
engine

3298
BIG BLOCK

52 61

896cc, V-twin OHV
Vanguard Big Block
air-cooled gasoline
engine

► DuraMax® deck

Power, efficiency and economy – equipped with a heavy-duty, Vanguard Big Block engine, with horizontal crankshaft for longer performance life, giving you intense mowing power in a surprisingly compact design.

Robust, design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

5.5-inch deep DuraMax® decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar and coil-spring suspension provides all-day comfort. The adjustable cup holder makes it convenient to tote along your favorite beverage. Electronic fuel gauge/hour meter on the console is standard.

A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal/45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

Mowing speeds up to 10.5 MPH
and 6.88 acres/hr. based on
72" cutting width*
For more details, visit:
grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck (Pg. 11)
- » Speed-Trimming™ heavy-duty roller (61" and 72") (Pg. 8)
- » TrimAide™ Roller (52") (Pg. 8)
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks (Pg. 10)
- » LED work lights (Pg. 38)
- » QuikAjust Tilt™ steering levers with “no tools” 9-inch comfort range (Pg. 5)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters (Pg. 38)
- » Edge-EZE™ edger (Pg. 19)
- » Shielded sprayer (Pg. 19)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Filter minder (Pg. 38)
- » Side discharge control kit (Pg. 8)
- » Air Dam kit – for dry, dusty conditions (Pg. 17)

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements.
Models may be shown with optional equipment. *Actual results may vary. † See warranty card for details

AIR-COOLED 300 SERIES-SPECIFICATIONS

MODEL – CUTTING WIDTH	329B 52"	329B 61"	335B 61"	335B 72"
ENGINE				
Type/Displacement/Cylinders				
B&S Vanguard Big Block / 54.7 cu. in. (896 cc) / V-twin	•	•		
B&S Vanguard Big Block / 60.6 cu. in. (993 cc) / V-twin			•	•
Crankshaft / Cooling System				
Horizontal / Air	•	•	•	•
Fuel / Capacity				
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)	•	•	•	•
Air Cleaner				
Heavy-duty, remote-mounted engine air cleaner with replaceable element	•	•	•	•
DURAMAX® DECKS				
Construction (Robotic-welded steel)				
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	•	•	•	•
Blades (MARBAIN®, 1/4-in.)				
(3) 18 in. (45.7 cm) – high-lift blades standard	•			
(3) 21 in. (53.3 cm) – high-lift blades standard		•	•	
(3) 25 in. (63.5 cm) – high-lift blades standard				•
Sentry™ Spindle Assemblies				
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	•	•	•	•
Spindle Housing – 8-in. (20.3 cm)-diameter with 6-bolt pattern				
Machined aluminum	•	•	•	•
QuikAjust™ DropPin™ Height Adjustment				
Foot-controlled height adjustment pedal with pin	•	•	•	•
Cutting Height Range				
1.0 – 5.0 in. (2.5 – 12.7 cm)	•	•	•	•
Blade Drive				
Belt drive with single Kevlar® V-belt and idler arm tensioning	•	•	•	•
STARTER & ELECTRICAL SYSTEM				
Maintenance-Free Battery/Charging Capacity/Starter				
12 volt/20 amp/solenoid shift	•	•	•	•
Ignition				
Breakerless	•	•	•	•
Interlock System				
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	•	•	•	•
ULTIMATE OPERATOR STATION™				
Premium Comfort Seat				
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	•	•	•	•
Premier Suspension Seat	○	○	○	○
Operator Protection				
ROPS with seat belt	•	•	•	•
Suspension				
InFrame™ suspension with iso-mounted seat and footrest	•	•	•	•
Console-Mounted Instruments				
Low engine oil pressure and parking brake warning lights, combination electronic fuel gauge/hour meter, ignition and push/pull PTO switches. Choke integrated with throttle lever.	•	•	•	•
Work Lights (Pre-wired)				
LED	○	○	○	○

MODEL – CUTTING WIDTH	329B 52"	329B 61"	335B 61"	335B 72"
TRANSMISSION & STEERING				
Type				
Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 16 cc piston-type pumps and high-torque Parker wheel motors.	•	•	•	•
Filtration/Hydro Fluid				
7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.	•	•	•	•
Speed				
0 – 10.0 mph (0 – 16.1 kph) forward	•			
0 – 10.5 mph (0 – 16.9 kph) forward		•	•	•
0 – 6.0 mph (0 – 9.7 kph) reverse	•	•	•	•
Turning Radius				
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.	•	•	•	•
Steering				
One- or two-handed operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	•	•	•	•
Brakes				
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	•	•	•	•
Disc brakes	•	•	•	•
Clutch				
Heavy-duty electric MagStop blade clutch/brake	•	•	•	•
POWER UNIT TIRE SIZES				
Drive Wheels (4-ply rated): 23 x 10.5-12 turf	•			
Drive Wheels (4-ply rated): 24 x 12-12 turf		•	•	•
Drive Wheels (4-ply rated): 24 x 12-12 bar tread		○	○	○
Front Casters: 13 x 6.5-6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap	•	•	•	•
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS				
Mulch or 4XRD Width*/Length: 53.5 in. (135.9 cm) / 79.5 in. (201.9 cm)	•			
Mulch or 4XRD Width*/Length: 62.5 in. (158.8 cm) / 81.0 in. (205.7 cm)		•	•	
Mulch or 4XRD Width*/Length: 73.5 in. (186.7 cm) / 84.5 in. (214.6 cm)				•
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.				
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)	•	•	•	•
Height (ROPS): 70.0 in. (177.8 cm)	•	•	•	•
WEIGHT				
Uncrated*: 1140 lbs. (517.1 kg)	•			
Uncrated*: 1190 lbs. (539.8 kg)		•	•	
Uncrated*: 1280 lbs. (580.6 kg)				•
**Mulching package kit weights with high-low mulching blades: 52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs. (16.3 kg); 72-in. – 44 lbs. (20.0 kg)				

• Standard ○ Option



Featured Model 329B with 61-inch DuraMax® deck and optional bar tread tires

300 SERIES LIQUID-COOLED MIDMOUNT™

Torque and power
available on demand

LIMITED WARRANTY†
3 YEAR
— UNLIMITED HRS —
COMMERCIAL
4 YEAR
— 800 HRS —
RESIDENTIAL



ComfortReach™ with "no tools"
2-in. adjustment range

329

52 61 72

962cc, 3-cylinder,
MaxTorque™ gasoline
engine

3250

52 61 72

898cc, 3-cylinder,
MaxTorque™
Clean Diesel engine

● Standard deck ■ DuraMax® deck

Designed for fuel economy and extended service life for operating efficiency. Equipped with a 3-cylinder Kubota gasoline or EPA Tier 4 Final-compliant diesel engine, so you can tackle even the toughest jobs with the greatest of ease. The engine is mounted with horizontal crankshaft for longer performance life.

Robust, design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

5.5-inch deep DuraMax® decks with anviledged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar and coil-spring suspension provides all-day comfort. The adjustable cup holder makes it convenient to tote along your favorite beverage. Electronic fuel gauge/hour meter on the console is standard.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal / 45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

Mowing speeds up to 10.5 MPH
and 6.88 acres/hr. based on
72" cutting width*
For more details visit:
grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (Pg. 16)
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck (Pg. 11)
- » Speed-Trimming™ heavy-duty roller (61" and 72") (Pg. 8)
- » TrimAide™ Roller (52") (Pg. 8)
- » Hydraulic height adjustment (61" and 72") (Pg. 11)
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks (Pg. 10)
- » LED work lights (Pg. 38)
- » QuikAjust Tilt™ steering levers with "no tools" 9-inch comfort range (Pg. 5)
- » Taller steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat (Pg. 5)
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires (Pg. 38)
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Front Casters (Pg. 38)
- » Edge-EZE™ edger (Pg. 19)
- » Shielded sprayer (Pg. 19)
- » Aluminum or Vinyl Sunshade Canopy (Pg. 38)
- » Yellow beacon light (Pg. 21)
- » Filter minder (Pg. 38)
- » Radiator cleaning wand (Pg. 7)
- » Engine block heater
- » Side discharge control kit (Pg. 8)
- » Air Dam kit — for dry, dusty conditions (Pg. 17)

LIQUID-COOLED 300 SERIES-SPECIFICATIONS

MODEL – CUTTING WIDTH	325D 52"	325D 61"	325D 72"	329 52"	329 61"	329 72"
ENGINE						
Type/Displacement/Cylinders						
Kubota MaxTorque™ / 54.8 cu. in. (898 cc) / 3-cyl.	•	•	•			
Kubota MaxTorque™ / 58.7 cu. in. (962 cc) / 3-cyl.				•	•	•
Crankshaft/Cooling System						
Horizontal / Liquid	•	•	•	•	•	•
Fuel/Capacity						
Diesel - No. 2 / 12 U.S. Gal. (45.4 l)	•	•	•			
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)				•	•	•
Air Cleaner						
Heavy-duty, remote-mounted engine air cleaner with replaceable element	•	•	•	•	•	•
DECKS						
Construction (Robotic-welded steel)						
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	•	•	•	•	•	•
DuraMax® deck	•	•	•	•	•	•
Blades (MARBAIN®, 1/4-in.)						
(3) 18 in. (45.7 cm) – high-lift blades standard	•			•		
(3) 21 in. (53.3 cm) – high-lift blades standard		•			•	
(3) 25 in. (63.5 cm) – high-lift blades standard			•			•
Sentry™ Spindle Assemblies						
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	•	•	•	•	•	•
Spindle Housing – 8-in. (20.3 cm)-diameter with 6-bolt pattern						
Machined aluminum	•	•	•	•	•	•
QuikAjust™ DropPin™ Height Adjustment						
Foot-controlled height adjustment pedal with pin	•	•	•	•	•	•
Cutting Height Range						
1.0 – 5.0 in. (2.5 – 12.7 cm)	•	•	•	•	•	•
Blade Drive						
Belt drive with single Kevlar® V-belt and idler arm tensioning	•	•	•	•	•	•
STARTER & ELECTRICAL SYSTEM						
Maintenance-Free Battery/Charging Capacity/Starter						
12 volt/40 amp/solenoid shift	•	•	•	•	•	•
Ignition						
Breakerless				•	•	•
Diesel quick heat glow plug	•	•	•			
Interlock System						
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	•	•	•	•	•	•
ULTIMATE OPERATOR STATION™						
Premium Comfort Seat						
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	•	•	•	•	•	•
Premier Suspension Seat	○	○	○	○	○	○
Operator Protection						
ROPS with seat belt	•	•	•	•	•	•
Suspension						
InFrame™ suspension with iso-mounted seat and footrest	•	•	•	•	•	•
Console-Mounted Instruments						
Low engine oil pressure, combination electronic fuel gauge/hour meter, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, ignition and push/pull PTO switches.	•	•	•	•	•	•
Choke integrated with throttle lever				•	•	•
Glow plug	•	•	•			
Work Lights (Pre-wired)						
LED	○	○	○	○	○	○

MODEL – CUTTING WIDTH	325D 52"	325D 61"	325D 72"	329 52"	329 61"	329 72"
TRANSMISSION & STEERING						
Type						
Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 16 cc piston-type pumps and high-torque Parker wheel motors.	•	•	•	•	•	•
Filtration/Hydro Fluid						
7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.	•	•	•	•	•	•
Speed						
0 – 10 mph (0 – 16.1 kph) forward	•			•		
0 – 10.5 mph (0 – 16.9 kph) forward		•	•		•	•
0 – 6.0 mph (0 – 9.7 kph) reverse	•	•	•	•	•	•
Turning Radius						
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.	•	•	•	•	•	•
Steering						
One- or two-handed operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	•	•	•	•	•	•
Brakes						
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	•	•	•	•	•	•
Disc brakes	•	•	•	•	•	•
Clutch						
Heavy-duty electric MagStop blade clutch/brake	•	•	•	•	•	•
Temperature Sentry/high temperature clutch cut-out	•	•	•	•	•	•
POWER UNIT TIRE SIZES						
Drive Wheels (4-ply rated): 23 x 10.5-12 turf	•			•		
Drive Wheels (4-ply rated): 24 x 12-12 turf		•	•		•	•
Drive Wheels (4-ply rated): 24 x 12-12 bar tread		○	○		○	○
Front Casters: 13 x 6.5-6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap.	•	•	•	•	•	•
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS						
Mulch or 4XRD Width*/Length: 53.5 in. (135.9 cm) / 82.5 in. (209.6 cm)	•			•		
Mulch or 4XRD Width*/Length: 62.5 in. (158.8 cm) / 84.0 in. (213.4 cm)		•			•	
Mulch or 4XRD Width*/Length: 73.5 in. (186.7 cm) / 87.5 in. (222.3 cm)			•			•
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.						
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)	•	•	•	•	•	•
Height (ROPS): 69.5 in. (176.5 cm)	•	•	•		•	•
Height (ROPS): 70.0 in. (177.8 cm)				•		
WEIGHT						
Uncrated**: 1310 lbs. (594.2 kg)	•			•		
Uncrated**: 1360 lbs. (616.9 kg)		•			•	
Uncrated**: 1450 lbs. (657.7 kg)			•			•
**Mulching package kit weights with high-low mulching blades. 52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs. (16.3 kg); 72-in. – 44 lbs. (20.0 kg)						

• Standard ○ Option



Featured Model 329 with 72-inch DuraMax® deck