



Committed to the Cut.®

THE GRASSHOPPER COMPANY

Grasshopper MidMount 300G Series – Build Sheet

All Prices Are MSRP Eff 9/01/2023

534216 328G4/52	\$13,970.00
534217 328G4/61	\$14,265.00
534229 337G5/61	\$16,205.00
534230 337G5/72	\$16,720.00

Discount off MSRP for 300G Series Models: 23%

Freight/Setup Charges:

Standard Freight Charge *: \$480.00/mower
(Rate is for shipping to the 48 contiguous United States, does not include Alaska or Hawaii. Regional rates may vary, please inquire for pricing.)

Add: Implement Freight Charge *: \$210.00/implement
(Implements include but not limited to: AERA-vators, Sweepster Brooms, Grass Collectors, Cabs)

Add: Other Implement Freight Charge *: \$90.00/implement
(Other implements include but not limited to: snowthrowers, 72" decks, highlift mount kits, canopies)

Add: Special Handling Shielded Sprayers & Turbine Blowers: \$310.00/implement

Add: Mower Setup: \$150.00/mower

Add: Implement Setup: \$150.00/implement

* Freight charges are for mowers & implements ordered at the same time. Freight rates for implement only orders will be Price-On-Request. Stated freight rates are based on factory discretion. Other freight options are available, please inquire for pricing.

300G SERIES AIR-COOLED MIDMOUNT™

Powerful. Fuel Efficient.
Economical.



Model 337G5

LIMITED WARRANTY†

3 YEAR

— 64 – 1000 HOURS —
— 65 – 1250 HOURS —

COMMERCIAL

LIMITED WARRANTY†

4 YEAR

— 800 HRS —

RESIDENTIAL

Grasshopper 300G Series models are powered by Vanguard EFI engines, with closed-loop electronic fuel injection. EFI technology provides a wide range of benefits including better fuel economy, reliable hot and cold weather starts, reduced engine exhaust emissions and fewer fuel-related service issues.

Hydro-Gear transmissions feature self-contained, heavy-duty commercial transaxles that provide powerful, Grasshopper-smooth response, while integrated cooling fans and 1-3/8-inch axles extend service life. Enjoy best-in-class transmission fluid change intervals, reducing costs and maintenance.

5.5-inch-deep DuraMax® decks, with anvil-edged design for exceptional durability, easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple. Optional Mulching Kits and PowerVac™ Collection Systems are available.

The Premier Comfort Seat on the Model 328G4 model provides 2-inch fore and aft adjustment and is covered with breathable, CoolTemp Cordura® fabric that dissipates heat and will not tear or crack with extended use. Iso-mounting absorbs and reduces vibration before it reaches the seat. Coil-spring suspension and foldable, padded armrests add up to all-day comfort for the operator.

Model 337G5 model features a Premier Suspension (Grammer) Seat covered with exclusive CoolTemp Cordura®. This seat offers the ultimate in customized operator fit. It adjusts to the individual operator's weight and slides fore and aft. The backrest tilts and includes adjustable lumbar support. Adjustable, foldable, padded armrests complete the comfort features of this seat.

QuikAjust Tilt™ dual steering levers on both 300G models provide 9 inches of "no tools" adjustment for maximum comfort and fit while maintaining natural arm and wrist positions. The hydraulically dampened levers deliver smooth, responsive control and return to neutral when released from both forward and reverse.

A compact wheelbase provides a great power-to-size ratio for easy transport on trailers and through tighter spaces.

The 13.0 gal/49.2 L single-fill fuel tank located beneath the seat lowers the center of gravity, providing more traction and stability for an enhanced ride. The rear bumper protects the rear of the mower while preserving easy access and removal of the rear service shield.

328G4
EFI

52 61

810cc, V-Twin Vanguard, Delphi®-based closed-loop, Electronic Fuel Injection gasoline engine

337G5
EFI

61 72

993cc, V-Twin Vanguard, Delphi®-based closed-loop, Electronic Fuel Injection gasoline engine

Increase your productivity with speeds up to 11.0 mph and 7.20 acres per hour with a 72-inch cutting deck.*



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems (see page 8)
- » Down Discharge™ mulching packages (see page 7)
- » Speed-Trimming™ heavy-duty anti-scalp roller for 61" and 72" decks (see page 7)
- » TrimAide™ anti-scalp roller for 52" deck (see page 7)
- » DuraFlex™ suspension forks (see page 9)
- » LED work lights (Standard G5 models)
- » Extended steering levers
- » Big Boy wide-seat conversion kit
- » Premier Suspension Seat (see page 3) (Standard on G5 models)
- » Premium Comfort Seat (see page 3) (Standard on G4 models)
- » Footrest Riser (see page 3)
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® Airless Turf Tire (24 x 12-12) (see page 9)
- » Michelin® X® Tweel® Airless Front Tires (13 x 6.5-6) (see page 9)
- » Flat-proof front tires (see page 9)
- » Edge-EZE™ edger
- » Shielded sprayer
- » Sunshade Canopy (for ROPS) (see page 9)
- » Yellow beacon light
- » Filter minder (see page 9)
- » Side discharge control kit (see page 7)
- » Air Dam Kit (see page 8)

AIR-COOLED 300G SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	328G4 52	328G4 61	337G5 61	337G5 72
ENGINE				
Type/Displacement/Cylinders				
B&S Vanguard EFI/49.4 cu. in. (810cc)/V-twin	•	•		
B&S Vanguard EFI/60.6 cu. in. (993cc)/V-twin			•	•
Lubrication System				
Pressure Lube, Filter				
Crankshaft / Cooling System				
Vertical / Air				
Fuel / Capacity				
Gasoline - unleaded / 13 U.S. Gal (49.2 L)				
Air Cleaner				
Heavy-duty, cyclonic, remote-mounted engine dual cleaner with replaceable element				
Muffler				
Ultra-quiet, single, industrial type				
MOWING DECKS				
Construction (Robotic-welded steel)				
Double-layered 10-gauge plus 7-gauge formed steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts				
Spindle plane is 0.9 in. (22.86 mm) thick in stress zones; anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck (See Page 6 for thickness diagram)				
Blades (MARBAIN®, 1/4-in.)				
(3) 18 in. (45.7 cm)	•			
(3) 21 in. (53.3 cm)		•	•	
(3) 25 in. (63.5 cm)				•
Spindle Assemblies				
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) outside diameter (O.D.) shaft; spindle cone designed to eliminate fiber wrap; double bearings, non-greasable				
Spindle Housing				
8-in. (20.3 cm) diameter machined aluminum housing with 6-bolt pattern				
Spindle Cones				
Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion				
QuikAjust™ DropPin™ Height Adjustment				
Foot-controlled height adjustment pedal with pin				
Cutting Height Range				
1.0 – 5.0 in. (2.5 – 12.7 cm) in 1/4-inch increments				
Blade Drive				
Belt drive with single Kevlar V-belt & idler arm tensioning				
STARTER & ELECTRICAL SYSTEM				
Maintenance-Free Battery/Charging Capacity/Starter				
12 Volt/20 amp/solenoid shift				
Ignition				
Breakerless				
Interlock System				
Prevents engine start when PTO clutch is engaged or steering levers are in drive position; allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral				
ULTIMATE OPERATOR STATION™				
Operator Seat				
Premium Comfort Seat with sliding function	•	•	○	○
Premier Suspension (Grammer) Seat – slides fore and aft and adjusts to operator's size and weight	○	○	•	•
Operator Protection				
ROPS with seatbelt	•	•	•	•
Suspension				
Roomy, iso-mounted footrest with Shock Impact Reduction System™ (SIRS™)				
Console-Mounted Instruments				
Low engine oil pressure, combination electronic fuel gauge/hour meter, engine code light and parking brake warning light, ignition and push/pull PTO switches				
Work Lights (Pre-wired)				
LED	○	○	•	•

• Standard ○ Option

MODEL - CUTTING WIDTH	328G4 52	328G4 61	337G5 61	337G5 72
TRANSMISSION & STEERING				
Type				
Heavy-duty Hydro-Gear ZT-4400 hydrostatic transmissions with cooling fans; integrated transaxles with 12cc piston pumps and gear reduction, internal disc brakes, and 1-3/8 inch axles	•	•		
Heavy-duty Hydro-Gear ZT-5400 hydrostatic transmissions with cooling fans; integrated transaxles with 16cc piston pumps and gear reduction, internal disc brakes, and 1-3/8 inch axles			•	•
Filtration/Hydro Fluid				
Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals after 100-hour break in oil change				
Speed				
0 – 10.5 mph (0 – 16.9 kph) forward	•	•		
0 – 11.0 mph (0 – 17.7 kph) forward			•	•
0 – 6.0 mph (0 – 9.7 kph) reverse	•	•	•	•
Turning Radius				
True zero degree, turns within own length with counter-rotating, independently powered drive wheels				
Steering				
One- or two-handed operation with QuikAjust Tilt™ dual levers with 9-inch comfort range that automatically return to neutral from either forward or reverse position				
Brakes				
Dynamic braking through hydrostatic transmission				
Parking Brake				
Internal disc brake in transmission				
TIRE SIZES				
Drive Wheels – Standard (5-bolt pattern)				
24 x 12-12 turf type, 4-ply rated	•	•		
26 x 12-12 turf type, 6-ply rated			•	•
24 x 12-12 Airless Turf Tweel Drive Wheel	○	○	○	○
Front Casters				
13 x 6.5-6; rib tread, pneumatic with double-sealed bearings to protect from grass wrap				
13 x 6.5-6; Airless Tweel Caster Wheel	○	○	○	○
DIMENSIONS (Mower & Deck)				
Mulch Width/Length (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.)				
53.5 in. (135.9 cm)/84.0 in. (213.4 cm)	•			
62.5 in. (158.8 cm)/85.0 in. (215.9 cm)		•	•	
73.5 in. (186.7 cm)/89.0 in. (226.9 cm)				•
Height (Seat back)				
49.5 in. (125.7 cm)	•	•		
49.0 in. (124.5 cm)			•	•
Height (Seat cushion)				
33.0 in. (83.8 cm)	•	•		
35.0 in. (88.9 cm)			•	•
Height (ROPS)				
70.0 in. (177.8 cm)	•	•		
72.0 in. (182.9 cm)			•	•
Drive Tire Track Width (outside edge to outside edge)				
53.0 in. (134.6 cm)	•	•		
54.5 in. (138.4 cm)			•	•
WEIGHT*				
Uncrated: (Mower & Deck) 1140 lbs. (517.1 kg)	•			
Uncrated: (Mower & Deck) 1190 lbs. (539.8 kg)		•		
Uncrated: (Mower & Deck) 1260 lbs. (571.2 kg)			•	
Uncrated: (Mower & Deck) 1340 lbs. (607.8 kg)				•

*DuraMax® deck mulching package kit weights with high-low mulching blades:
52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs. (16.3 kg); 72-in. – 44 lbs. (20.0 kg)