



Committed to the Cut.®

# THE GRASSHOPPER COMPANY

## Grasshopper Stand-On SO26 Series – Build Sheet

All Prices Are MSRP Eff 9/01/2023

|                |             |
|----------------|-------------|
| 535150 SO26/52 | \$12,415.00 |
| 535160 SO26/61 | \$12,625.00 |

Discount off MSRP for Stand-On SO26 Series Models: 10%

### Freight/Setup Charges:

Standard Freight Charge \*: \$480.00/mower  
(Rate is for shipping to the 48 contiguous United States, does not include Alaska or Hawaii. Regional rates may vary, please inquire for pricing.)

Add: Implement Freight Charge \*: \$210.00/implement  
(Implements include but not limited to: AERA-vators, Sweepster Brooms, Grass Collectors, Cabs)

Add: Other Implement Freight Charge \*: \$90.00/implement  
(Other implements include but not limited to: snowthrowers, 72" decks, highlift mount kits, canopies)

Add: Mower Setup: \$150.00/mower

Add: Implement Setup: \$150.00/implement

\* Freight charges are for mowers & implements ordered at the same time. Freight rates for implement only orders will be Price-On-Request. Stated freight rates are based on factory discretion. Other freight options are available, please inquire for pricing.

# STAND-ON SERIES AIR-COOLED



Take your business  
to the next level.

LIMITED WARRANTY†  
**2 YEAR**  
—UNLIMITED HRS—  
COMMERCIAL



Stand-On 26-52

## STAND-ON 26

52 61

810 cc, V-Twin, OHV  
B&S Vanguard  
gasoline engine

Command Center tower features 4.5" of infinitely variable height adjustment, raising and lowering the control levers and pad to accommodate taller and shorter operators.



The Stand-On Series is designed for extreme operator proficiency and all-day ergonomic comfort. True ZeroTurn™ maneuverability, outstanding ease-of-use, effortless on/off and legendary Grasshopper cut quality combine to deliver superior performance.

### DURABILITY & LONGEVITY

T-Drive™ hydrostatic drive system features tandem pumps-in-reservoir, internal filtration and inline CoolFan™ coupled with Parker high-torque wheel motors design-matched to the engine HP for increased efficiency and simplified maintenance.

Extra-deep, 5.5-inch DuraMax® decks, with anvil-edged design for exceptional durability, deliver superior airflow for better cut quality. Cutting height is effortlessly raised and lowered thanks to the smooth motion of the hand-operated lever.

Engine, T-Drive™ pump and deck smoothly move as one when raising and lowering the cutting height position to keep the drive belt on a uniform horizontal plane for extended life and zero power loss. The service-friendly design includes removable guards and easy access to grease points and filters.

Fleet managers will appreciate the commonality of parts between Stand-On models and the rest of the Grasshopper product line.

### COMFORT & ERGONOMICS

The wide anti-slip platform is equipped with coil-spring suspension and dampeners, insulating the operator from vibrations, for a smooth, shock-reducing, floating-action ride and minimal bouncing.

The Command Center tower features an extra-wide, extra-thick pad with embroidered Grasshopper logo.

The Command Center tower provides 4.5 inches of adjustable range and is positioned to provide a panoramic view of the mowing environment and easy reach of all switches, levers and controls, including a deep phone/accessory tray with USB charging ports.

### TRACTION & CONTROL

Hydraulically dampened control levers that also provide responsive and effortless maneuvering—including one-hand operation—and return to neutral when released from forward and reverse. Adjustable grip bar accommodates larger and smaller reaches of different operators.

The compact wheelbase provides an incredible power-to-size ratio. Easily fit more units on trailers and maneuver through tighter spaces.

Every Grasshopper mower is designed with a low center of gravity for optimal traction and stability. The centralized location of the engine, T-Drive™ pump and dual fuel tanks on Stand-On models lowers the overall center of gravity, and a total fuel capacity of 9.25 gal/35.0 L reduces the need for frequent refueling.

Increase your productivity with speeds  
up to 9.5 mph and 5.27 acres per hour  
with a 61-inch cutting deck.\*



### OPTIONS

- » Down Discharge™ mulching packages
- » TrimAide™ anti-scalp roller for 52" deck
- » Michelin® X® Tweel® Airless Front Tires (13 x 6.5-6)
- » Speed-Trimming™ heavy-duty anti-scalp roller for 61" decks
- » Flat-proof front tires
- » Side discharge control kit
- » Filter minder
- » Air Dam Kit

Models may be shown with optional equipment. \*Actual results may vary. † See warranty card for details

# STAND-ON SERIES-SPECIFICATIONS

| MODEL – CUTTING WIDTH  | STAND-ON<br>52 | STAND-ON<br>61 |
|--|----------------|----------------|
| <b>ENGINE</b>  |                |                |
| <b>Type/Displacement/Cylinders</b>   |                |                |
| B&S Vanguard/49.4 cu. in. (810cc)/V-Twin   | •              | •              |
| <b>Lubrication System</b>  |                |                |
| Pressure Lube, Filter  |                |                |
| <b>Crankshaft / Cooling System</b>   |                |                |
| Vertical   |                |                |
| <b>Cooling System</b>  |                |                |
| Air  |                |                |
| <b>Fuel / Capacity</b>   |                |                |
| Gasoline - unleaded / 9.25 U.S. Gal. (35.0 l) total fuel capacity – twin tanks with fuel selector  |                |                |
| <b>Air Cleaner</b>   |                |                |
| Heavy-duty, cyclonic, remote-mounted engine dual cleaner with replaceable element  |                |                |
| <b>Muffler</b>   |                |                |
| Ultra-quiet, single, industrial type   |                |                |
| <b>DURAMAX® DECKS</b>  |                |                |
| <b>Construction (Robotic-welded steel)</b>   |                |                |
| Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones; anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck. |                |                |
| <b>Blades (MARBAIN®, 1/4-in.)</b>  |                |                |
| (3) 18 in. (45.7 cm)   | •              |                |
| (3) 21 in. (53.3 cm)   |                | •              |
| <b>Spindle Assemblies</b>  |                |                |
| Sentry™ Spindle System, 2.5 cm (approx. 1 in.) outside diameter (O.D.) shaft; double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.  |                |                |
| <b>Spindle Housing</b>   |                |                |
| 8-in. (20.3 cm)-diameter machined aluminum housing with 6-bolt pattern   |                |                |
| <b>Spindle Cones</b>   |                |                |
| Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion   |                |                |
| <b>QuikAdjust™ Height Adjustment</b>   |                |                |
| Hand-controlled height adjustment lever with lock/release button   |                |                |
| <b>Cutting Height Range</b>  |                |                |
| 1.0 – 5.5 in. (2.5 – 12.7 cm) in 1/4-inch increments   |                |                |
| <b>Blade Drive</b>   |                |                |
| Belt drive with single Kevlar V-belt & idler arm tensioning  |                |                |
| <b>STARTER &amp; ELECTRICAL SYSTEM</b>   |                |                |
| <b>Maintenance-Free Battery/Charging Capacity/Starter</b>  |                |                |
| 12 Volt/16 amp/solenoid shift  |                |                |
| <b>Ignition</b>  |                |                |
| Breakerless  |                |                |
| <b>Interlock System</b>  |                |                |
| Prevents engine start when PTO clutch is engaged or steering levers are in drive position; allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are returned to neutral  |                |                |
| <b>ULTIMATE OPERATOR STATION™</b>  |                |                |
| <b>Operator Platform</b>   |                |                |
| Wide anti-slip platform with dampers; extra-thick pad with logo  |                |                |
| <b>Suspension</b>  |                |                |
| Coil spring suspension with dampening  |                |                |
| <b>Console-Mounted Instruments (Command Center)</b>  |                |                |
| Low engine oil pressure, hour meter, phone/accessory tray with USB charging ports, parking brake indicator light, ignition switch, choke & push/pull PTO switch  |                |                |
| <b>Work Lights</b>   |                |                |
| LED  | •              | •              |

| MODEL – CUTTING WIDTH   | STAND-ON<br>52 | STAND-ON<br>61 |
|---|----------------|----------------|
| <b>TRANSMISSION &amp; STEERING</b>  |                |                |
| <b>Type</b>   |                |                |
| T-Drive™ hydrostatic transmission with tandem 12cc Parker pumps-in-reservoir, in-line CoolFan™ for cooling efficiency, and design-matched Parker high-torque wheel motors |                |                |
| <b>Filtration/Hydro Fluid</b>   |                |                |
| Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals                      |                |                |
| <b>Speed</b>  |                |                |
| 0 – 9.5 mph (0 – 15.3 kph) forward  |                |                |
| 0 – 5.0 mph (0 – 8.0 kph) reverse   |                |                |
| <b>Turning Radius</b>   |                |                |
| True zero degree, turns within own length with counter-rotating, independently powered drive wheels   |                |                |
| <b>Steering</b>   |                |                |
| One- or two-handed operation with dual levers that automatically return to neutral from either forward or reverse position  |                |                |
| <b>Brakes</b>   |                |                |
| Dynamic braking through hydrostatic transmission  |                |                |
| <b>Parking Brake</b>  |                |                |
| Manual lever through linkage to bar in tire (compression) brake   |                |                |
| <b>TIRE SIZES</b>   |                |                |
| <b>Drive Wheels – Standard (5-bolt pattern)</b>   |                |                |
| 23 x 10.5-12, 350 Mag OTR, 4-ply rated  |                |                |
| <b>Front Casters</b>  |                |                |
| 13 x 6.5-6; rib tread, pneumatic with double-sealed bearings to protect from grass wrap   |                |                |
| 13 x 6.5-6; Airless Tweel Caster Wheel  | ○              | ○              |
| <b>DIMENSIONS (Mower &amp; Deck)</b>  |                |                |
| <b>Mulch Width/Length</b> (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.)    |                |                |
| 53.0 in. (134.6 cm)/73.0 in. (185.4 cm)   | •              |                |
| 62.0 in. (157.5 cm)/75.3 in. (191.3 cm)   |                | •              |
| <b>Height (Command Center – Tower Up)</b>   |                |                |
| 50.0 in. (127.0 cm)   |                |                |
| <b>Height (Command Center – Tower Down)</b>   |                |                |
| 45.5 in. (115.6 cm)   |                |                |
| <b>Drive Tire Track Width (outside edge to outside edge)</b>  |                |                |
| 50.5 in. (128.3 cm)   |                |                |
| <b>WEIGHT</b>   |                |                |
| Uncrated*: (Mower & Deck) 1080 lbs. (489.9 kg)  | •              |                |
| Uncrated*: (Mower & Deck) 1120 lbs. (508.0 kg)  |                | •              |

\*DuraMax® deck mulching package kit weights with high-low mulching blades:  
52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs (16.3 kg).

• Standard ○ Option