

PACKAGE ARRANGEMENT (1)		Discount to apply 25%
Product	Approx. Weight	List Price
DX180LC-5-US40	19,900.00 KG	196,382.32 USD

DX180LC-5 BASE MACHINE W/O BUCKET 17' (5.2M) BOOM 8' 6" (2.6 M) ARM 9' 6" (2900 mm) DOZER 27.6" (700 mm) TRIPLE GROUSER SHOE 7,055 LBS (3.2 METRIC TON) COUNTERWEIGHT

ONE AND TWO WAY AUXILIARY PIPING TO END OF THE ARM WITH ONE WAY FLOW

OPTIONAL EQUIPMENT - Factory Installed (17)			Discount to apply 20%
Option	CODE	Description	List Price
TRACK SHOE	800	31.5" (800 MM) TRIPLE GROUSER SHOE	1,413.17 USD
TRACK SHOE	900	35.4" (900 MM) TRIPLE GROUSER SHOE	2,968.41 USD
LOCK VALVE	LOB	BOOM LOCK VALVE	1,950.67 USD
ROTATING PIPING(PERO)	PER	ROTATE CIRCUIT PIPING	6,360.88 USD
ONE & TWO WAY PIPING	PE3	ONE & TWO WAY PILOT PIPING	6,360.88 USD
STRAIGHT TRAVEL	STT	STRAIGHT TRAVEL	763.31 USD
RAIN SHIELD	RAI	CAB RAIN SHIELD	283.06 USD
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	2,756.38 USD
CABIN FRONT GUARD	FUL	UPPER AND LOWER FRONT WINDOW GUA	ARD 1,187.37 USD
ADDITIONAL WORK LAMP	2LA	2 ADDITIONAL WORKING LAMPS	720.90 USD
ADDITIONAL WORK LAMP	6LA	6 ADDITIONAL WORKING LAMPS	1,441.80 USD
LOWER WIPER	LOW	LOWER WIPER	254.43 USD
ROTATING BEACON	ROB	ROTATING BEACON	466.46 USD
Water Separator	WIH	WATER SEPARATOR WITH HEATER	720.90 USD
ENGINE COOLANT HEATER	110	110 V PLUG HEATER	196.13 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	3,710.52 USD
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	406.04 USD



Attachments - [Dealer Installed (21)		
Attachment	Description	Approx. Weight	List Price
5000033	TRIMBLE EARTHWORKS 2D MACHINE GUIDANCE; INDICATE KIT; w/ INSTALL, CALIBRATION	50.00	24,000.00 USD
AT200-060	*Non-Cancelable* 0.75 CU. YD. 60" ANGLE TILT DITCHING BUCKET (WITH BOLT-ON EDGE)	1,750.00	12,824.06 USD
DC200-048	0.97 CU. YD. 48" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,195.00	5,062.88 USD
DC200-060	1.22 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,507.79 USD
DC200-072	1.34 CU. YD. 72" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,859.68 USD
HD18-024	0.50 CU. YD. 24" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,095.00	5,788.45 USD
HD18-030	0.68 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,190.00	7,128.80 USD
HD18-036	0.86 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,338.00	6,585.24 USD
HD18-042	1.04 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,448.00	6,896.40 USD
HD18-048	1.22 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,584.00	7,427.08 USD
HDC180-060	1.58 CU. YD. 60" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	1,887.00	8,865.21 USD
HT-18DM3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1,012.00	7,992.35 USD
HT-18DM4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	1,050.00	7,992.35 USD
HT-18QC3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1,100.00	8,212.15 USD
HT-18QC4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1,130.00	8,896.22 USD
QC-80H3G3-318	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX180/DX190	628.00	7,723.95 USD
SD18-024	0.50 CU. YD. 24" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,151.00	7,265.72 USD
SD18-030	0.68 CU. YD. 30" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,264.00	7,745.08 USD
SD18-036	0.86 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,417.00	8,207.90 USD
SD18-042	1.04 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,531.00	8,839.94 USD
SD18-048	1.22 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,681.00	9,462.32 USD

STANDARD EQUIPMENT FOR BASE MACHINE (8)



Item	Description
Engine	"Perkins 1204F: 4-Cycle Water Cooled Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with Diesel Exhaust Fluid 131HP(SAE J1995) Gross Flywheel Horsepower @ 2000 rpm Displacement: 269cu.in., 4 Cylinder Bore 105mm Diameter x 127mm Stroke Torque: 391ft. lbs @ 1,400 rpm High Idle 2000 j¾ 25rpm, Low Idle 900 j¾ 10 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control"
Hydraulic	"Pilot Operated Control Valves, (9) Spools Main Pump: Swash Plate Axial Piston Type, Pressure Setting 4694 psi normal / 4978 psi boost 2 X 40gpm Pilot Circuit, Gear Type Pump Swing Motor, Axial Piston Type Swing Speed Control up to 10.52RPM Maximum Swing Torque 46,653 ft.lbs. Spring Set, Hydraulic-released Brakes Travel Motor: Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.0 mph 1.8 mph Maximum Tractive Force 45,195 ft.lbs. in low speed In-Shoe Design, Oil Disc Parking Brake Cross Sensing Pump Control for Fuel Saving Four Operating Modes, Four Power Modes One-way Auxiliary Hydraulics Adjustable Auxiliary Flow and Pressure up to 10 presets Computer-aided Pump Power Control e-EPOS (Electronic Power Optimizing System) Controller"
Cabin	"Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Controlled Air Conditioner with Heat 7"" Multi-function Color LCD Monitor Panel Rear & Side View Camera Cigarette Lighter Door Locks Front Windshield Wiper with Washer Radio: MP3 Stereo with CD Player Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Glass Antenna Safety Lock Lever Seat: Heated Air Suspension with Seat Belt (2 Wide) Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Skylight Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Sliding Side Windows Front Window Air Defroster Travel Pedals with Hand Levers Emergency Breakout Tool



	12V Power Socket Height Adjustable Control Stands Joystick Lever with 3 Switches, Two Button and One Rotate Cup Holder Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Operation Modes: Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Flow Rate Control Auto Idle Select Button 4 Display Selection Buttons Rear View Camera Button Jog Switch to Control Monitor"
Electrical	"Alternator: 24 V,85 amp Batteries: (2) 12 V, 100amp, 900CCA Starter: 24 V x 4.5 KW Lights: Halogen Working Light (2) Machine, (2) Boom Electric Horn Hour Meter"
Display Monitor and Warnings	"Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF Level Multi-function Display for: Engine RPM Battery Voltage Front and Rear Hydraulic Pump Pressure ECO Gauge Hydraulic Oil Overheating Warning Fuel Shortage Warning Air Cleaner Clogging Warning Pilot Filter Clogging Warning Pilot Filter Clogging Warning Digital Clock Engine Check Warning Light Engine Oil Pressure Warning Light Charge Warning Light Charge Warning Light Coolant Temperature Warning Light Work Light Indicator Light Work Light Indicator Light Water in the Fuel Warning Symbol SCR Failure Warning Symbol"
Undercarriage	"Track Guards and Chains with Adjusters Track Rollers: (2) Upper, (7) Lower Each Side Triple Grouser Shoes, 45 Each Side"
Other	"Joystick Pattern Change Valve Centralized Lube Points Large Handrail Punched Metal Anti-slip Plates Engine Restart Prevention System Self-Diagnostic System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc at the Bucket Pivot Vandalism Protection (All panels and fill points lockable) GPS 3 Year Subscription"



"DX170LC-5-US20 MAIN PIN SIZE CHANGE

SERIAL NUMBER BREAK:

Attachment SERIAL NO. $001001 \sim 001522 = 71MM PIN$

SERIAL NO. 001523 ~ = 80MM PIN



PACKAGE ARRANGEMENT (1)		Discount to apply 25%
Product	Approx. Weight	List Price
DX180LC-5-US60	17,800.00 KG	180,170.82 USD

DX180LC-5 BASE MACHINE W/O BUCKET NARROW TRACK 17' (5.2M) BOOM 8' 6" (2.6 M) ARM 23.6" (600 mm) TRIPLE GROUSER SHOES 7,055 LBS (3.2 METRIC TON) COUNTERWEIGHT

ONE AND TWO WAY AUXILIARY PIPING TO END OF THE ARM WITH ONE WAY FLOW

OPTIONAL EQUIPMENT - Factory Installed (16)		Discount to apply 20%	
Option	CODE	Description	List Price
TRACK SHOE	500	19.7" (500 MM) TRIPLE GROUSER SHOE	-629.00 USD
LOCK VALVE	LOB	BOOM LOCK VALVE	1,950.67 USD
ROTATING PIPING(PERO)	PER	ROTATE CIRCUIT PIPING	6,360.88 USD
ONE & TWO WAY PIPING	PE3	ONE & TWO WAY PILOT PIPING	6,360.88 USD
STRAIGHT TRAVEL	STT	STRAIGHT TRAVEL	763.31 USD
RAIN SHIELD	RAI	CAB RAIN SHIELD	283.06 USD
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	2,756.38 USD
CABIN FRONT GUARD	FUL	UPPER AND LOWER FRONT WINDOW GU	ARD 1,187.37 USD
ADDITIONAL WORK LAMP	2LA	2 ADDITIONAL WORKING LAMPS	720.90 USD
ADDITIONAL WORK LAMP	6LA	6 ADDITIONAL WORKING LAMPS	1,441.80 USD
LOWER WIPER	LOW	LOWER WIPER	254.43 USD
ROTATING BEACON	ROB	ROTATING BEACON	466.46 USD
Water Separator	WIH	WATER SEPARATOR WITH HEATER	720.90 USD
ENGINE COOLANT HEATER	110	110 V PLUG HEATER	196.13 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	3,710.52 USD
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	406.04 USD

Attachments - Dealer Installed (21)



Attachment	Description	Approx. Weight	List Price
5000033	TRIMBLE EARTHWORKS 2D MACHINE GUIDANCE; INDICATE KIT; w/ INSTALL, CALIBRATION	50.00	24,000.00 USD
AT200-060	*Non-Cancelable* 0.75 CU. YD. 60" ANGLE TILT DITCHING BUCKET (WITH BOLT-ON EDGE)	1,750.00	12,824.06 USD
DC200-048	0.97 CU. YD. 48" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,195.00	5,062.88 USD
DC200-060	1.22 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,507.79 USD
DC200-072	1.34 CU. YD. 72" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,859.68 USD
HD18-024	0.50 CU. YD. 24" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,095.00	5,788.45 USD
HD18-030	0.68 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,190.00	7,128.80 USD
HD18-036	0.86 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,338.00	6,585.24 USD
HD18-042	1.04 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,448.00	6,896.40 USD
HD18-048	1.22 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,584.00	7,427.08 USD
HDC180-060	1.58 CU. YD. 60" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	1,887.00	8,865.21 USD
HT-18DM3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1,012.00	7,992.35 USD
HT-18DM4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	1,050.00	7,992.35 USD
HT-18QC3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1,100.00	8,212.15 USD
HT-18QC4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1,130.00	8,896.22 USD
QC-80H3G3-318	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX180/DX190	628.00	7,723.95 USD
SD18-024	0.50 CU. YD. 24" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,151.00	7,265.72 USD
SD18-030	0.68 CU. YD. 30" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,264.00	7,745.08 USD
SD18-036	0.86 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,417.00	8,207.90 USD
SD18-042	1.04 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,531.00	8,839.94 USD
SD18-048	1.22 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,681.00	9,462.32 USD

STANDARD EQUIPMENT FOR BASE MACHINE (8)	
Item	Description



Engine	"Perkins 1204F: 4-Cycle Water Cooled Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with Diesel Exhaust Fluid 131HP(SAE J1995) Gross Flywheel Horsepower @ 2000 rpm Displacement: 269cu.in., 4 Cylinder Bore 105mm Diameter x 127mm Stroke Torque: 391ft. lbs @ 1,400 rpm High Idle 2000 ¡¾ 25rpm, Low Idle 900 ¡¾ 10 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control"
Hydraulic	"Pilot Operated Control Valves, (9) Spools Main Pump: Swash Plate Axial Piston Type, Pressure Setting 4694 psi normal / 4978 psi boost 2 X 40gpm Pilot Circuit, Gear Type Pump Swing Motor, Axial Piston Type Swing Speed Control up to 10.52RPM Maximum Swing Torque 46,653 ft.lbs. Spring Set, Hydraulic-released Brakes Travel Motor: Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.0 mph 1.8 mph Maximum Tractive Force 45,195 ft.lbs. in low speed In-Shoe Design, Oil Disc Parking Brake Cross Sensing Pump Control for Fuel Saving Four Operating Modes, Four Power Modes One-way Auxiliary Hydraulics Adjustable Auxiliary Flow and Pressure up to 10 presets Computer-aided Pump Power Control e-EPOS (Electronic Power Optimizing System) Controller"
Cabin	"Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Controlled Air Conditioner with Heat 7" Multi-function Color LCD Monitor Panel Rear & Side View Camera Cigarette Lighter Door Locks Front Windshield Wiper with Washer Radio: MP3 Stereo with CD Player Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Glass Antenna Safety Lock Lever Seat: Heated Air Suspension with Seat Belt (2 Wide) Reclining, Height Adjustable Adjustable Arm Rests Silding Control Console Skylight Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Sliding Side Windows Front Window Air Defroster Travel Pedals with Hand Levers Emergency Breakout Tool Lunch Box with insulation 12V Power Socket Height Adjustable Control Stands Joystick Lever with 3 Switches, Two Button and One Rotate



	Cup Holder Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Operation Modes: Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Flow Rate Control Auto Idle Select Button 4 Display Selection Buttons Rear View Camera Button Jog Switch to Control Monitor"
Electrical	"Alternator: 24 V,85 amp Batteries: (2) 12 V, 100amp, 900CCA Starter: 24 V x 4.5 KW Lights: Halogen Working Light (2) Machine, (2) Boom Electric Horn Hour Meter"
Display Monitor and Warnings	"Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF Level Multi-function Display for: Engine RPM Battery Voltage Front and Rear Hydraulic Pump Pressure ECO Gauge Hydraulic Oil Overheating Warning Fuel Shortage Warning Air Cleaner Clogging Warning Pilot Filter Clogging Warning Pilot Filter Clogging Warning Digital Clock Engine Check Warning Light Engine Oil Pressure Warning Light Charge Warning Light Charge Warning Light Charge Warning Light Charge Indicator Light Work Light Indicator Light Water in the Fuel Warning Light DEF Low Level Warning Symbol SCR Failure Warning Symbol"
Undercarriage	"Track Guards and Chains with Adjusters Track Rollers: (2) Upper, (7) Lower Each Side Triple Grouser Shoes, 45 Each Side"
Other	"Joystick Pattern Change Valve Centralized Lube Points Large Handrail Punched Metal Anti-slip Plates Engine Restart Prevention System Self-Diagnostic System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc at the Bucket Pivot Vandalism Protection (All panels and fill points lockable) GPS 3 Year Subscription"



"DX170LC-5-US20 MAIN PIN SIZE CHANGE

SERIAL NUMBER BREAK:

Attachment SERIAL NO. $001001 \sim 001522 = 71MM PIN$

SERIAL NO. 001523 ~ = 80MM PIN



PACKAGE ARRANGEMENT (1)		Discount to apply 25%
Product	Approx. Weight	List Price
DX180LC-5-US20	18,300.00 KG	180,568.50 USD

DX180LC-5 BASE MACHINE W/O BUCKET
17' (5.2M) BOOM
8' 6" (2.6 M) ARM
27.6" (700 mm) TRIPLE GROUSER SHOE
7,055 LBS (3.2 METRIC TON) COUNTERWEIGHT
ONE AND TWO WAY AUXILIARY PIPING TO END OF THE ARM WITH ONE WAY FLOW

OPTIONAL EQUIPMENT - Factory Installed (17)			Discount to apply 20%	
Option	CODE	Description	List Price	
TRACK SHOE	800	31.5" (800 MM) TRIPLE GROUSER SHOE	1,413.17 USD	
TRACK SHOE	900	35.4" (900 MM) TRIPLE GROUSER SHOE	2,968.41 USD	
LOCK VALVE	LOB	BOOM LOCK VALVE	1,950.67 USD	
ROTATING PIPING(PERO)	PER	ROTATE CIRCUIT PIPING	6,360.88 USD	
ONE & TWO WAY PIPING	PE3	ONE & TWO WAY PILOT PIPING	6,360.88 USD	
STRAIGHT TRAVEL	STT	STRAIGHT TRAVEL	763.31 USD	
RAIN SHIELD	RAI	CAB RAIN SHIELD	283.06 USD	
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	2,756.38 USD	
CABIN FRONT GUARD	FUL	UPPER AND LOWER FRONT WINDOW GUAR	D 1,187.37 USD	
ADDITIONAL WORK LAMP	2LA	2 ADDITIONAL WORKING LAMPS	720.90 USD	
ADDITIONAL WORK LAMP	6LA	6 ADDITIONAL WORKING LAMPS	1,441.80 USD	
LOWER WIPER	LOW	LOWER WIPER	254.43 USD	
ROTATING BEACON	ROB	ROTATING BEACON	466.46 USD	
Water Separator	WIH	WATER SEPARATOR WITH HEATER	720.90 USD	
ENGINE COOLANT HEATER	110	110 V PLUG HEATER	196.13 USD	
AIR COMPRESSOR	ACO	AIR COMPRESSOR	3,710.52 USD	
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	406.04 USD	



Attachments - [Dealer Installed (21)		
Attachment	Description	Approx. Weight	List Price
5000033	TRIMBLE EARTHWORKS 2D MACHINE GUIDANCE; INDICATE KIT; w/ INSTALL, CALIBRATION	50.00	24,000.00 USD
AT200-060	*Non-Cancelable* 0.75 CU. YD. 60" ANGLE TILT DITCHING BUCKET (WITH BOLT-ON EDGE)	1,750.00	12,824.06 USD
DC200-048	0.97 CU. YD. 48" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,195.00	5,062.88 USD
DC200-060	1.22 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,507.79 USD
DC200-072	1.34 CU. YD. 72" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,859.68 USD
HD18-024	0.50 CU. YD. 24" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,095.00	5,788.45 USD
HD18-030	0.68 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,190.00	7,128.80 USD
HD18-036	0.86 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,338.00	6,585.24 USD
HD18-042	1.04 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,448.00	6,896.40 USD
HD18-048	1.22 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,584.00	7,427.08 USD
HDC180-060	1.58 CU. YD. 60" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	1,887.00	8,865.21 USD
HT-18DM3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1,012.00	7,992.35 USD
HT-18DM4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	1,050.00	7,992.35 USD
HT-18QC3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1,100.00	8,212.15 USD
HT-18QC4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1,130.00	8,896.22 USD
QC-80H3G3-318	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX180/DX190	628.00	7,723.95 USD
SD18-024	0.50 CU. YD. 24" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,151.00	7,265.72 USD
SD18-030	0.68 CU. YD. 30" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,264.00	7,745.08 USD
SD18-036	0.86 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,417.00	8,207.90 USD
SD18-042	1.04 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,531.00	8,839.94 USD
SD18-048	1.22 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,681.00	9,462.32 USD

STANDARD EQUIPMENT FOR BASE MACHINE (8)



Item	Description
Engine	"Perkins 1204F: 4-Cycle Water Cooled Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with Diesel Exhaust Fluid 131HP(SAE J1995) Gross Flywheel Horsepower @ 2000 rpm Displacement: 269cu.in., 4 Cylinder Bore 105mm Diameter x 127mm Stroke Torque: 391ft. lbs @ 1,400 rpm High Idle 2000 j¾ 25rpm, Low Idle 900 j¾ 10 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control"
Hydraulic	"Pilot Operated Control Valves, (9) Spools Main Pump: Swash Plate Axial Piston Type, Pressure Setting 4694 psi normal / 4978 psi boost 2 X 40gpm Pilot Circuit, Gear Type Pump Swing Motor, Axial Piston Type Swing Speed Control up to 10.52RPM Maximum Swing Torque 46,653 ft.lbs. Spring Set, Hydraulic-released Brakes Travel Motor: Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.0 mph 1.8 mph Maximum Tractive Force 45,195 ft.lbs. in low speed In-Shoe Design, Oil Disc Parking Brake Cross Sensing Pump Control for Fuel Saving Four Operating Modes, Four Power Modes One-way Auxiliary Hydraulics Adjustable Auxiliary Flow and Pressure up to 10 presets Computer-aided Pump Power Control e-EPOS (Electronic Power Optimizing System) Controller"
Cabin	"Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Controlled Air Conditioner with Heat 7"" Multi-function Color LCD Monitor Panel Rear & Side View Camera Cigarette Lighter Door Locks Front Windshield Wiper with Washer Radio: MP3 Stereo with CD Player Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Glass Antenna Safety Lock Lever Seat: Heated Air Suspension with Seat Belt (2 Wide) Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Skylight Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Sliding Side Windows Front Window Air Defroster Travel Pedals with Hand Levers Emergency Breakout Tool



	12V Power Socket Height Adjustable Control Stands Joystick Lever with 3 Switches, Two Button and One Rotate Cup Holder Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Operation Modes: Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Flow Rate Control Auto Idle Select Button 4 Display Selection Buttons Rear View Camera Button Jog Switch to Control Monitor"
Electrical	"Alternator: 24 V,85 amp Batteries: (2) 12 V, 100amp, 900CCA Starter: 24 V x 4.5 KW Lights: Halogen Working Light (2) Machine, (2) Boom Electric Horn Hour Meter"
Display Monitor and Warnings	"Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF Level Multi-function Display for: Engine RPM Battery Voltage Front and Rear Hydraulic Pump Pressure ECO Gauge Hydraulic Oil Overheating Warning Fuel Shortage Warning Air Cleaner Clogging Warning Pilot Filter Clogging Warning Pilot Filter Clogging Warning Digital Clock Engine Oil Pressure Warning Light Engine Oil Pressure Warning Light Charge Warning Light Preheat Indicator Light Work Light Indicator Light Work Light Indicator Light Water in the Fuel Warning Light DEF Low Level Warning Symbol SCR Failure Warning Symbol"
Undercarriage	"Track Guards and Chains with Adjusters Track Rollers: (2) Upper, (7) Lower Each Side Triple Grouser Shoes, 45 Each Side"
Other	"Joystick Pattern Change Valve Centralized Lube Points Large Handrail Punched Metal Anti-slip Plates Engine Restart Prevention System Self-Diagnostic System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc at the Bucket Pivot Vandalism Protection (All panels and fill points lockable) GPS 3 Year Subscription"



"DX170LC-5-US20 MAIN PIN SIZE CHANGE

SERIAL NUMBER BREAK:

Attachment SERIAL NO. $001001 \sim 001522 = 71MM PIN$

SERIAL NO. 001523 ~ = 80MM PIN



Product Approx. Weight List Price Discount to apply 25%

DX180LC-5-US30 18,600.00 KG 181,848.39 USD

DX180LC-5 BASE MACHINE W/O BUCKET 17' (5.2M) BOOM

10' 2" (3.1M) ARM

31.5" (800 mm) TRIPLE GROUSER SHOE

7,055 LBS (3.2 METRIC TON) COUNTERWEIGHT

ONE AND TWO WAY AUXILIARY PIPING TO END OF THE ARM WITH ONE WAY FLOW

OPTIONAL EQUIPMENT - Factory Installed (17)			Discount to apply 20%
Option	CODE	Description	List Price
TRACK SHOE	700	27.6" (700 MM) TRIPLE GROUSER SHOE	-853.00 USD
TRACK SHOE	900	35.4" (900 MM) TRIPLE GROUSER SHOE	1,555.24 USD
LOCK VALVE	LOB	BOOM LOCK VALVE	1,950.67 USD
ROTATING PIPING(PERO)	PER	ROTATE CIRCUIT PIPING	6,360.88 USD
ONE & TWO WAY PIPING	PE3	ONE & TWO WAY PILOT PIPING	6,360.88 USD
STRAIGHT TRAVEL	STT	STRAIGHT TRAVEL	763.31 USD
RAIN SHIELD	RAI	CAB RAIN SHIELD	283.06 USD
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	2,756.38 USD
CABIN FRONT GUARD	FUL	UPPER AND LOWER FRONT WINDOW GUARD	1,187.37 USD
ADDITIONAL WORK LAMP	2LA	2 ADDITIONAL WORKING LAMPS	720.90 USD
ADDITIONAL WORK LAMP	6LA	6 ADDITIONAL WORKING LAMPS	1,441.80 USD
LOWER WIPER	LOW	LOWER WIPER	254.43 USD
ROTATING BEACON	ROB	ROTATING BEACON	466.46 USD
Water Separator	WIH	WATER SEPARATOR WITH HEATER	720.90 USD
ENGINE COOLANT HEATER	110	110 V PLUG HEATER	196.13 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	3,710.52 USD
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	406.04 USD



Attachment	Description	Approx. Weight	List Price
5000033	TRIMBLE EARTHWORKS 2D MACHINE GUIDANCE; INDICATE KIT; w/ INSTALL, CALIBRATION	50.00	24,000.00 USD
AT200-060	*Non-Cancelable* 0.75 CU. YD. 60" ANGLE TILT DITCHING BUCKET (WITH BOLT-ON EDGE)	1,750.00	12,824.06 USD
DC200-048	0.97 CU. YD. 48" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,195.00	5,062.88 USD
DC200-060	1.22 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,507.79 USD
DC200-072	1.34 CU. YD. 72" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,859.68 USD
HD18-024	0.50 CU. YD. 24" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,095.00	5,788.45 USD
HD18-030	0.68 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,190.00	7,128.80 USD
HD18-036	0.86 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,338.00	6,585.24 USD
HD18-042	1.04 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,448.00	6,896.40 USD
HD18-048	1.22 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,584.00	7,427.08 USD
HDC180-060	1.58 CU. YD. 60" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	1,887.00	8,865.21 USD
HT-18DM3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1,012.00	7,992.35 USD
HT-18DM4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	1,050.00	7,992.35 USD
HT-18QC3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1,100.00	8,212.15 USD
HT-18QC4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1,130.00	8,896.22 USD
QC-80H3G3-318	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX180/DX190	628.00	7,723.95 USD
SD18-024	0.50 CU. YD. 24" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,151.00	7,265.72 USD
SD18-030	0.68 CU. YD. 30" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,264.00	7,745.08 USD
SD18-036	0.86 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,417.00	8,207.90 USD
SD18-042	1.04 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,531.00	8,839.94 USD
SD18-048	1.22 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,681.00	9,462.32 USD

STANDARD EQUIPMENT FOR BASE MACHINE (8)



Item	Description
Engine	"Perkins 1204F: 4-Cycle Water Cooled Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with Diesel Exhaust Fluid 131HP(SAE J1995) Gross Flywheel Horsepower @ 2000 rpm Displacement: 269cu.in., 4 Cylinder Bore 105mm Diameter x 127mm Stroke Torque: 391ft. lbs @ 1,400 rpm High Idle 2000 j¾ 25rpm, Low Idle 900 j¾ 10 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control"
Hydraulic	"Pilot Operated Control Valves, (9) Spools Main Pump: Swash Plate Axial Piston Type, Pressure Setting 4694 psi normal / 4978 psi boost 2 X 40gpm Pilot Circuit, Gear Type Pump Swing Motor, Axial Piston Type Swing Speed Control up to 10.52RPM Maximum Swing Torque 46,653 ft.lbs. Spring Set, Hydraulic-released Brakes Travel Motor: Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.0 mph 1.8 mph Maximum Tractive Force 45,195 ft.lbs. in low speed In-Shoe Design, Oil Disc Parking Brake Cross Sensing Pump Control for Fuel Saving Four Operating Modes, Four Power Modes One-way Auxiliary Hydraulics Adjustable Auxiliary Flow and Pressure up to 10 presets Computer-aided Pump Power Control e-EPOS (Electronic Power Optimizing System) Controller"
Cabin	"Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Controlled Air Conditioner with Heat 7"" Multi-function Color LCD Monitor Panel Rear & Side View Camera Cigarette Lighter Door Locks Front Windshield Wiper with Washer Radio: MP3 Stereo with CD Player Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Glass Antenna Safety Lock Lever Seat: Heated Air Suspension with Seat Belt (2 Wide) Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Skylight Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Sliding Side Windows Front Window Air Defroster Travel Pedals with Hand Levers Emergency Breakout Tool



	12V Power Socket Height Adjustable Control Stands Joystick Lever with 3 Switches, Two Button and One Rotate Cup Holder Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Operation Modes: Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Flow Rate Control Auto Idle Select Button 4 Display Selection Buttons Rear View Camera Button Jog Switch to Control Monitor"
Electrical	"Alternator: 24 V,85 amp Batteries: (2) 12 V, 100amp, 900CCA Starter: 24 V x 4.5 KW Lights: Halogen Working Light (2) Machine, (2) Boom Electric Horn Hour Meter"
Display Monitor and Warnings	"Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF Level Multi-function Display for: Engine RPM Battery Voltage Front and Rear Hydraulic Pump Pressure ECO Gauge Hydraulic Oil Overheating Warning Fuel Shortage Warning Air Cleaner Clogging Warning Pilot Filter Clogging Warning Pilot Filter Clogging Warning Digital Clock Engine Oil Pressure Warning Light Engine Oil Pressure Warning Light Charge Warning Light Preheat Indicator Light Work Light Indicator Light Work Light Indicator Light Water in the Fuel Warning Light DEF Low Level Warning Symbol SCR Failure Warning Symbol"
Undercarriage	"Track Guards and Chains with Adjusters Track Rollers: (2) Upper, (7) Lower Each Side Triple Grouser Shoes, 45 Each Side"
Other	"Joystick Pattern Change Valve Centralized Lube Points Large Handrail Punched Metal Anti-slip Plates Engine Restart Prevention System Self-Diagnostic System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc at the Bucket Pivot Vandalism Protection (All panels and fill points lockable) GPS 3 Year Subscription"



"DX170LC-5-US20 MAIN PIN SIZE CHANGE

SERIAL NUMBER BREAK:

Attachment SERIAL NO. $001001 \sim 001522 = 71MM PIN$

SERIAL NO. 001523 ~ = 80MM PIN