

PACKAGE ARRANGEMENT (1)		Discount to apply 25%	
Product	Approx. Weight	List Price	
DX235LCR-7-US40	25,100.00 KG	256,421.87 USD	
DX235LCR-7 BASE MACHINE W/DOZER BLADE AND NO BUCKET 18' 8" (5.7 M) MONO BOOM 7' 10" (2.4 M) ARM 24" (600 mm) TRIPLE GROUSER SHOE 16,280 LBS (7.4 METRIC TON) COUNTERWEIGHT ONE <(>&<)> TWO WAY AUX. PIPING TO END OF ARM			

OPTIONAL EQUIPMENT - Factory Installed (21)			Discount to apply 20%	
Option	CODE	Description	List Price	
ARM	029	2.9m Arm	850.00 USD	
BREAKER FILTER	BRF	Breaker Filter	425.00 USD	
CLAMSHELL PIPING	CLA	Clamshell	300.00 USD	
LOCK VALVE	LBA	Boom & Arm Lock Valve	1,700.00 USD	
LOCK VALVE	LOB	Boom Lock Valve	1,150.00 USD	
ROTATING PIPING(PERO)	PER	Rotating Piping (PERO)	3,180.55 USD	
ONE & TWO WAY PIPING	OEP	One Way with Electric Pedal	5,210.88 USD	
ONE & TWO WAY PIPING	PE3	Two Way with Pedal	6,360.88 USD	
STRAIGHT TRAVEL	STT	Straight Travel	300.00 USD	
HEATING & COOLING SEAT	HCS	Heating & Cooling Seat	725.00 USD	
MICROPHONE	MIC	Microphone	600.00 USD	
RAIN SHIELD	RAI	Rain Shield	175.00 USD	
CAMERA	AVC	Around View Camera	3,450.00 USD	
CABIN FRONT GUARD	FUL	Upper and Lower Guard	475.00 USD	
CABIN FRONT GUARD	LOW	Lower Guard Only	275.00 USD	
FOGS GUARD	FOG	FOGS	2,600.00 USD	
ADDITIONAL WORK LAMP	6LE	6 ADDITIONAL WORKING LAMP(LED)	862.50 USD	
ADDITIONAL WORK LAMP	4LE	4 ADDITIONAL WORKING LAMP(LED)	575.00 USD	





ROTATING BEACON	ROB	Rotating Beacon	200.00 USD
Water Separator	WIH	Water Separator with Heater	300.00 USD
FUEL FILLER PUMP	FIL	Fuel Filler Pump	375.00 USD

Attachments - Dealer Installed (29)			
Attachment	Description	Approx. Weight	List Price
230104-03482	1.41 CU. YD. 48" HEAVY DUTY BUCKET (FACTORY BUCKET)	2,205.00	6,003.72 USD
230104-03516	1.20 CU. YD. 42" HEAVY DUTY BUCKET (FACTORY BUCKET)	1,962.00	5,751.53 USD
230104-03517	0.99 CU. YD. 36" HEAVY DUTY BUCKET (FACTORY BUCKET)	1,665.00	5,211.20 USD
5000033	TRIMBLE EARTHWORKS 2D MACHINE GUIDANCE; INDICATE KIT; w/ INSTALL, CALIBRATION	50.00	24,000.00 USD
AT200-060	*Non-Cancelable* 0.75 CU. YD. 60" ANGLE TILT DITCHING BUCKET (WITH BOLT-ON EDGE)	1,750.00	12,824.06 USD
DC200-048	0.97 CU. YD. 48" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,195.00	5,062.88 USD
DC200-060	1.22 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,507.79 USD
DC200-072	1.34 CU. YD. 72" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	1,395.00	5,859.68 USD
HD22-024	0.55 CU. YD. 24" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,394.00	7,976.33 USD
HD22-030	0.74 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,566.00	9,432.92 USD
HD22-036	0.94 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,747.00	7,556.52 USD
HD22-042	1.14 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,893.00	8,097.41 USD
HD22-048	1.34 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,074.00	8,711.00 USD
HDC200-060	1.95 CU. YD. 60" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	2,370.00	10,452.14 USD
HDC200-066	2.16 CU. YD. 66" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	2,554.00	10,990.84 USD
HT-22DM3T	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1,150.00	10,518.49 USD
HT-22DM4T	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	1,150.00	10,518.49 USD
HT-22QC3T	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1,150.00	10,811.54 USD
HT-22QC4T	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1,150.00	10,811.54 USD



PL-22DM3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1,307.00	12,883.22 USD
PL-22DM4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	1,307.00	12,883.22 USD
PL-22QC3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1,415.00	13,270.97 USD
PL-22QC4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1,415.00	13,270.97 USD
QC-80H1G3-319	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX210/DX225/DX235	721.00	9,984.35 USD
SD22-024	0.55 CU. YD. 24" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,424.00	8,678.01 USD
SD22-030	0.74 CU. YD. 30" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,586.00	8,695.01 USD
SD22-036	0.94 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,774.00	10,928.01 USD
SD22-042	1.14 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,919.00	10,984.70 USD
SD22-048	1.34 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,097.00	12,247.13 USD
			,

STANDARD EQUIPMENT FOR BASE MACHINE (7)		
Item	Description	
Engine	Doosan DL06V; 5.9L 4-Cycle Water Cooled, Turbocharged and Intercooled T4f Emission Compliant with EGR Electronically Controlled Common Rail Direct Injected T4f Emissions: Diesel Oxidation Catalyst + DPF + Selective Catalytic Reduction with Ammonia Oxidation Catalytic 189 hp (141 kW) @ 1900 rpm (SAE J1995) Gross Flywheel Horsepower 170 HP(SAE J1349) Net @ 1900 rpm Displacement: 359 in3 (5890cc), 4 Cylinder Bore 3.94 in (100mm) Diameter x 4.92 in (125mm) Stroke Torque: 593 ft. lbs (82 kgf-m) @ 1,400 rpm High Idle 2000 ± 25 rpm, Low Idle 800 ± 10 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control Engine Derate and Shutdown if failure in Emission Control System Engine Overheat and Low Oil Pressure Prevention System	
Hydraulic	 Pilot Operated Control Valves, (9) Spools Main Pump: Tandem Variable Axial Piston Type, Flow: 2 x [59 gpm (222 Lpm)]; Pressure Setting 4978 psi normal / 5263 psi boost Pilot Circuit, Gear Type Pump; Flow: 7 gpm (26 Lpm) Swing Motor, Axial Piston Type driving a 2-stage planetary gearbox to maximize torque Swing Maximum Speed: 11.5 RPM Fine Swing Control Maximum Swing Torque 69,625 lbf-ft. (9,626 kgf-m) Spring Set, Hydraulic-released Brakes Travel Motors: 2 x Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.6 mph/2.0 mph Maximum Tractive Force 64,375 lbf. (29,200 kgf) in low speed In-Shoe Design, Oil Disc Parking Brake 	



One way/two way Auxiliary Hydraulics with 2-pump flow Smart Hydraulic Logic to prioritize flow to hydraulic attachments like a molcher or a grinder Working Mode for Tilt-Rotator Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets Door Locks Front Windshield Panto Wiper with Washer 8' Multi-function Color LCD Touch Screen Monitor Aerial, Side & Rear View Camera with dedicated LCD display Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: Engine Speed Control Dial Jog Switch for monitor display control Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Inteiligent Floating Boom (optional) Engine After Treatment System Switch Wiper Control Panel Safety Lock Lever Ergonomic Leatherlike Operator Seat: Ergonomic Leatherlike Operator Seat: Safey Lock Lever Cab 3-Stage Climate Control des Seat (cgitical) Air Suspension with Seat Belt (2' Wide)	
Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets Door Locks Front Windshield Panto Wiper with Washer 8" Multi-function Color LCD Touch Screen Monitor Aerial, Side & Rear View Camera with dedicated LCD display Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: Engine Speed Control Dial Jog Switch for monitor display control Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch Breaker, Power-up, Shear Switch Intelligent Floating Boom (optional) Engine After Treatment System Switch Wiper Control Panel Safety Lock Lever Cab 2-Stage Heated Seat (standard) Air Suspension with Seat Belt (2" Wide)	
Adjustable bottom cushion Lumbar Support Adjustment Adjustable Headrest Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Height Adjustable Panels Skylight Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Sliding Side Windows Front Window Air Defroster Travel Pedals with Hand Levers Emergency Exit Glass Breaking Tool Quick Coupler Switch Joystick Lever with 3 Switches, Two Button and One Rotate Front and Rear Cup Holders Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Sun Screens for Top Hatch, Front Windshield and Rear Window	
Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity Power Mode Select Button (P+,P,S,E)	
Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Electronic Power Optimizing System Cross Sensing Pump Control	
Machine Status Display with Integrated Self Diagnostics System Adjustable LCD Color Display Auto Idle Control System plus One Touch Deceleration Button on Joystick	
Engine Speed Control Dial Power Boost Control Button on Joystick	
Electrical/Electronic Control Limp Home Mode Control Switch Proximity Alarm Warning System Proportional control for auxiliary hydraulics via roll switch on both joysticks	
Adjustable Auxiliary Flow and Pressure up to 10 presets Alternator: 24 V, 100 amp Batteries: (2) 12 V, 100AmpH, 900CCA	



	Starter: 24 V x 6 KW Engine Emergency Stop Switch accessible from ground level Panto Wiper to cover the entire front windshield window LED Lights: Working Light (2) Machine, (2) Boom Smart Ignition Switch Key for remote control of engine start/stop and door lock/unlock Electric Horn Hour Meter
Display Monitor and Warnings	Main Warning Lamp Warning Symbol Indicator for: Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, GSM antenna failure, Satelite antenna failure, Check machine, Stop engine Digital Clock Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF (AdBlue®) Level Multi-function Touch Screen Display for: Funcion Symbol Indicator (Power Boost, Auxiliary Hydraulic Pedal/Joystick Selector, Travel Speed, Work Light, Intelligent Floating Boom, ISO/BHL Pattern Control, Fine Swing Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth) Favorite Button Indicator Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info) Main Information Indicator Power Mode Selector Button Indicator (Power+, Power, Standard, Economy) Power Mode Indicator Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear) Auto Idle Indicator Menu Selector Button
Undercarriage	Track Guards and Chains with Adjusters Track Rollers: (2) Upper, (9) Lower Each Side Triple Grouser Shoes, 49 Each Side
Other	Joystick Pattern Change Valve Centralized Lube Points Large Access Handrail to upper deck Steel Casted Lift Bracket integrated with Idler Linkage Punched Metal Anti-slip Plates Engine Restart Prevention System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc on both sides of bucket arm end Vandalism Protection (All panels and fill points lockable) Telematics: 3 Yr Free Cellular Subscription - 3.0 Global (Cell Only)