

CAMERA

CABIN FRONT GUARD

SRC

FUL



PACKAGE ARRANGEMENT (1)

Discount to apply 25%

20%

1,450.00 USD

500.00 USD

 Product
 Approx. Weight
 List Price

 DX300LC-7-US10
 29,330.00 KG
 266,182.81 USD

 DX300LC-7 BASE MACHINE W/O ATTACHMENTS NO BOOM <(>&<)> NO ARM
 VO ATTACHMENTS

31.5" (800 mm) TRIPLE GROUSER SHOES 13,890 LBS (6.3 METRIC TON) COUNTERWEIGHT

OPTIONAL EQUIPMENT - Factory Installed (27)			Discount to apply 20
Option	CODE	Description	List Price
MICROPHONE	MIC	Microphone	1,050.00 USD
RAIN SHIELD	RAI	CAB RAIN SHIELD	175.00 USD
ENGINE COOLANT HEATER	110	110V Plug Heater	240.00 USD
ENGINE COOLANT HEATER	220	220V Plug Heater	240.00 USD
PRE CLEANER	DRY	Dry Type Pre Cleaner	400.00 USD
PRE CLEANER	OWC	Oil Washed Pre Cleaner	1,725.00 USD
BOOM FLOATING PIPING	BFL	Boom Floating Piping	1,350.00 USD
BREAKER FILTER	BRF	Breaker Filter	450.00 USD
LEVER PATTERN CHANGE	LEV	Lever Pattern Change	200.00 USD
STRAIGHT TRAVEL	STT	Straight Travel Pedal	300.00 USD
AIR COMPRESSOR	ACO	Air Compressor	3,710.00 USD
SIDE PROTECTOR & CATWALK	PRO	Side Protector	1,675.00 USD
FUEL FILLER PUMP	FIL	Fuel Filler Pump	400.00 USD
SHOE CASE	SHC	Shoe Case	75.00 USD
BODY LAMP TYPE	HAL	Halogen Type Lamps	150.00 USD
BODY LAMP TYPE	LED	LED Type Lamps	1,025.00 USD
CAMERA	AVC	Around View Camera	4,250.00 USD

Side & Rear View Camera

Upper and Lower Guard

Price Page



FOGS GUARD	FOG	Falling Object Guarding	2,725.00 USD
ADDITIONAL WORK LAMP	6LE	6 Additional Working Lamps (LED)	862.50 USD
ADDITIONAL WORK LAMP	4LE	4 Additiona Working Lamps (LED)	575.00 USD
ROTATING BEACON	ROB	Rotating Beacon	200.00 USD
TRACK SHOE	600	600mm TG Shoe	-3,500.00 USD
TRACK SHOE	60D	600mm Double Grouser Shoe	-3,500.00 USD
TRACK SHOE	700	700mm TG Shoe	-1,750.00 USD
TRACK SHOE	900	35.4" (900 mm) TG Shoe	2,650.00 USD

Attachments - Dealer Installed			
Attachment	Description	Approx. Weight List	Price

STANDARD EQUIPMENT FOR BASE MACHINE (7)		
Item	Description	
Engine	Doosan DL08V; 7.6L Wastegate Turbocharged and Intercooled T4f Emission Compliant Electronically Controlled Common Rail Direct Injected T4f Emissions: Diesel Oxidation Catalyst + Cooled EGR + Selective Catalytic Reduction with Diesel Exhaust Fluid 271 hp (202 kW) @ 1800 rpm (SAE J1995) Gross Flywheel Horsepower 199 HP(SAE J1349) Net @ 1800 rpm Displacement: 466 in3 (7,640cc), 6 Cylinder Bore 4.25 in (108mm) Diameter x 5.47 in (139mm) Stroke Torque: 940 ft. lbs (130 kgf-m) @ 1,400 rpm High Idle 1900 ± 25 rpm, Low Idle 800 ± 10 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control Engine Derate and Shutdown if failure in Emission Control System Engine Overheat and Low Oil Pressure Prevention System	
Hydraulics	 Pilot Operated Control Valves, (9) Spools Main Pump: Tandem Variable Axial Piston Type, Flow: 2 x 66 gpm; Pressure Setting 4978 psi normal / 5263 psi boost Pilot Circuit, Gear Type Pump; Flow: 7 gpm (26 Lpm) Swing Motor, Axial Piston Type driving a 2-stage planetary gearbox to maximize torque Swing Maximum Speed: 9.7 RPM Fine Swing Control Maximum Swing Torque 87,787 lbf-ft. (12,137 kgf-m) Spring Set, Hydraulic-released Brakes Travel Motors: 2 x Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.4 mph/2.0 mph Maximum Tractive Force 77,162 lbf. (35,000 kgf) in low speed In-Shoe Design, Oil Disc Parking Brake 	



	One way/two way Auviliary Hydraulice with 2 nump flow
	One way/two way Auxiliary Hydraulics with 2-pump flow Smart Hydraulic Logic to prioritize flow to hydraulic attachments like a molcher or a grinder
	Working Mode for Tilt-Rotator
Cab	Working Mode for Tilt-Rotator Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets Door Locks Front Windshield Panto Wiper with Washer 8' Multi-function Color LCD Touch Screen Monitor Aerial, Side & Rear View Camera with dedicated LCD display Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: Engine Speed Control Dial Jog Switch for monitor display control Auxiliary Mode Switch Breaker, Power-up, Shear Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Intelligent Floating Boom (optional) Engine After Treatment System Switch Wiper Control Panel Safety Look Laver Ergonomic Leatherlike Operator Seat: 3-Stage Climate Controlide seat (optional) 2-Stage Heated Set (standard) Ari suspension with Seat Belt (2" Wide) Adjustable Arm Rests Silding Control Console Height Adjustable Pan
	Sun Screens for Top Hatch, Front Windshield and Rear Window
	Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Electronic Power Optimizing System Cross Sensing Pump Control Machine Status Display with Integrated Self Diagnostics System
Electrical/Electronic Control System	Adjustable LCD Color Display Auto Idle Control System plus One Touch Deceleration Button on Joystick Engine Speed Control Dial Power Boost Control Button on Joystick Limp Home Mode Control Switch Proximity Alarm Warning System Proportional control for auxiliary hydraulics via roll switch on both joysticks Adjustable Auxiliary Flow and Pressure up to 10 presets Alternator: 24 V, 80 amp Batteries: (2) 12 V, 150AmpH, 950CCA



	Starter: 24 V x 6 KW Engine Emergency Stop Switch accessible from ground level Panto Wiper to cover the entire front windshield window LED Lights: Working Light (2) Machine, (2) Boom Smart Ignition Switch Key for remote control of engine start/stop and door lock/unlock Electric Horn Hour Meter
Display Monitor and Warnings	Main Warning Lamp Warning Symbol Indicator for: Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, GSM antenna failure, Satelite antenna failure, Check machine, Stop engine Digital Clock Alarm Buzzer for: Engine Colant Temperature Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF (AdBlue®) Level Multi-function Touch Screen Display for: Funcion Symbol Indicator (Power Boost, Auxiliary Hydraulic Pedal/Joystick Selector, Travel Speed, Work Light, Intelligent Floating Boom, ISO/BHL Pattern Control, Fine Swing Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth) Favorite Button Indicator Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info) Main Information Indicator Power Mode Selector Button Indicator (Power+, Power, Standard, Economy) Power Mode Indicator Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear) Audio Display Auto Idle Indicator
Undercarriage	Track Guards and Chains with Adjusters Track Rollers: (2) Upper, (9) Lower Each Side Triple Grouser Shoes, 48 Each Side
Other	Joystick Pattern Change Valve Centralized Lube Points Large Access Handrail to upper deck Steel Casted Lift Bracket integrated with Idler Linkage Punched Metal Anti-slip Plates Engine Restart Prevention System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc on both sides of bucket arm end Vandalism Protection (All panels and fill points lockable) Telematics: 3 Yr Free Cellular Subscription - 3.0 Global (Cell Only)