

PACKAGE ARRANGEMENT (1)		Discount to apply 25%
Product	Approx. Weight	List Price
DX350LC-7-US10	36,000.00 KG	317,171.90 USD
DX350LC-7 BASE MACHINE W/O BOOM, ARM AND BUCKET NO BOOM NO ARM INCLUDES BOOM CYLINDER 31.5" (800 mm) TRIPLE GROUSER SHOES 15,653 LBS (7.1 METRIC TON) COUNTERWEIGHT ONE WAY AUX FLOW		

OPTIONAL EQUIPMENT - Factory Installed (18)			Discount to apply 20%
Option	CODE	Description	List Price
RAIN SHIELD	RAI	CAB RAIN SHIELD	283.06 USD
ENGINE COOLANT HEATER	110	110 V PLUG HEATER	196.13 USD
PRE CLEANER	OWC	OIL BATH AIR CLEANER	3,200.00 USD
BOOM FLOATING PIPING	BFL	BOOM FLOATING PIPING	1,350.00 USD
BREAKER FILTER	BRF	BREAKER FILTER	450.00 USD
ROTATING PIPING(PERO)	PER	BUCKET TILT/ROTATING PIPING	6,360.88 USD
ONE & TWO WAY PIPING	PE3	ONE & TWO WAY PILOT CONTROL WITH PEDAL	6,360.88 USD
STRAIGHT TRAVEL	STT	STRAIGHT TRAVEL	763.31 USD
AIR COMPRESSOR	ACO	ELECTRICAL AIR COMPRESSOR	2,650.00 USD
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	406.04 USD
CAMERA	AVC	AVM (AROUND VIEW CAMERA) WITH MONITOR	4,800.00 USD
CABIN FRONT GUARD	FUL	UPPER AND LOWER FRONT WINDOW GUARD	1,187.37 USD
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	2,756.38 USD
ADDITIONAL WORK LAMP	4LE	4 ADDITIONAL LED WORKING LAMPS	575.00 USD
ADDITIONAL WORK LAMP	6LE	6 ADDITIONAL LED WORKING LAMPS	862.50 USD
ROTATING BEACON	ROB	ROTATING BEACON	466.46 USD
TRACK SHOE	700	27.6" (700 MM) TRIPLE GROUSER SHOE	-1,013.00 USD
TRACK SHOE	900	35.4" (900 MM) TRIPLE GROUSER SHOE	1,855.26 USD

Attachments - Dealer Installed

Attachment	Description	Approx. Weight	List Price

STANDARD EQUIPMENT FOR BASE MACHINE (7)

Item	Description
Engine	<p>"DL08-LEE03: 4-Cyclewater-Cooled Turbo Charged (Variable Geometry Turbo) Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with Diesel Exhaust Fluid 286HP(SAE J1995) Gross Flywheel Horsepower @ 1800 rpm Displacement: 466 cu.in., 6 Cylinder Bore 4.25" (108 mm) Diameter x 5.47" (139 mm) Stroke Torque: 940ft. lbs @ 1,300 rpm High Idle 1900 $\frac{3}{4}$ 25rpm, Low Idle 800 $\frac{3}{4}$ 10 rpm Auto Idle System Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Three Stage Air Intake Filtering with Large Capacity Double Element Air Cleaner and Evacuate Electronic Engine Speed Control Engine Overheat and Low Oil Pressure Prevention System "</p>
Hydraulic	<p>"Pilot Operated Control Valves, (9) Spools Main Pump: Tandem Variable Axial Piston Type, Pressure Setting 4978 psi normal / 5263 psi boost Pump flow: 2 X 92 gpm Pilot Circuit, Gear Type Pump Swing Motor, Axial Piston Type Swing Speed Control up to 9.5 RPM Maximum Swing Torque 107,483 ft.lbs. Spring Set, Hydraulic-released Brakes Travel Motor: Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.5 mph / 2.1 mph Maximum Tractive Force 83,555 ft.lbs. in low speed In-Shoe Design, Oil Disc Parking Brake One-way/two way Auxiliary Hydraulics with 2-pump flow "</p>
	<p>"Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets 8" Multi-function Color LCD Touch Screen Monitor Door Locks Front Windshield Panto Wiper with Washer Digital Bluetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: Engine Speed Control Dial Jog Switch for monitor display control Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Intelligent Floating Boom (optional) Engine After Treatment System Switch Wiper Control Panel Safety Lock Lever "</p>

Cab	<p>Ergonomic Leatherlike Operator Seat: Integrated Heater and Air Conditioner Air Suspension with Seat Belt (2" Wide) Adjustable bottom cushion Lumbar Support Adjustment Adjustable Headrest Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Height Adjustable Panels Skylight Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Door Sliding Windows Front Window Air Defroster Travel Pedals with Hand Levers Emergency Exit Glass Breaking Tool Fully insulated Lunch Box Compartment Quick Coupler Switch Joystick Lever with 3 Switches, Two Button and One Rotate Front and Rear Cup Holders Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Sun Screens for Top Hatch, Front Windshield and Rear Window "</p>
Electrical/Electronic Control System	<p>"Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Electronic Power Optimizing System Cross Sensing Pump Control Machine Status Display with Integrated Self Diagnostics System Adjustable LCD Color Display Incorporated Camera Views Auto Idle Control System plus One Touch Deceleration Button on Joystick Engine Speed Control Dial Power Boost Control Button on Joystick Limp Home Mode Control Switch Proximity Alarm Warning System Proportional control for auxiliary hydraulics via roll switch on both joysticks Adjustable Auxiliary Flow and Pressure up to 10 presets Alternator: 24 V, 100 amp Batteries: (2) 12 V, 200 AmpH, 950 CCA Starter: 24 V x 6 KW Engine Emergency Stop Switch Panto Wiper to cover the entire front windshield window LED Lights: Working Light (2) Machine, (2) Boom Smart Ignition Switch Key for remote control of engine start/stop and fdoor lock/unlock Electric Horn Hour Meter "</p>
	<p>"Main Warning Lamp Warning Symbol Indicator for: Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, GSM antenna failure, Satellite antenna failure, Check machine, Stop engine "</p>

Display Monitor and Warnings	<p>Digital Clock</p> <p>Alarm Buzzer for:</p> <ul style="list-style-type: none"> Engine Oil Pressure Coolant Temperature <p>Electronic Monitor for:</p> <ul style="list-style-type: none"> Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF (AdBlue®) Level <p>Multi-function Touch Screen Display for:</p> <p>Function Symbol Indicator (Power Boost, Auxiliary Hydraulic Pedal/Joystick Selector, Travel Speed, Work Light, Intelligent Floating Boom, ISO/BHL Pattern Control, Fine Swing)</p> <p>Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth)</p> <p>Favorite Button Indicator</p> <p>Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info)</p> <p>Main Information Indicator</p> <p>Power Mode Selector Button Indicator (Power+, Power, Standard, Economy)</p> <p>Power Mode Indicator</p> <p>Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear)</p> <p>Audio Display</p> <p>Auto Idle Indicator</p> <p>Menu Selector Button</p> <p>"</p>
Undercarriage	<p>"Track Guards and Chains with Adjusters</p> <p>2 pairs of standard track guides per side</p> <p>Track Rollers: (2) Upper, (9) Lower Each Side</p> <p>31.5" (800 mm) Triple Grouser Shoes, 48 Each Side</p> <p>"</p>
Other	<p>"Joystick Pattern Change Valve</p> <p>Centralized Lube Points</p> <p>Large Handrail</p> <p>Punched Metal Anti-slip Plates</p> <p>Engine Restart Prevention System</p> <p>Self-Diagnostic System</p> <p>Manuals, Parts and Operator's</p> <p>Ultra-hard Wear-resistant Disc at the Bucket Pivot</p> <p>Vandalism Protection (All panels and fill points lockable)</p> <p>GPS 3 Year Subscription</p> <p>"</p>