



PACKAGE ARRANGEMENT (1)

Discount to apply 25%

Product

Approx. Weight

List Price

DX350LC-7-US20

36,000.00 KG

357,721.50 USD

DX350LC-7 BASE MACHINE W/O BUCKET 21' 4" (6.5 M) BOOM 10' 6" (3.2 M) ARM 31.5" (800 mm) TRIPLE GROUSER SHOES 15,653 LBS (7.1 METRIC TON) COUNTERWEIGHT ONE AND TWO WAY AUXILIARY PIPING TO END OF THE ARM WITH ONE WAY FLOW

OPTIONAL EQUIPMENT - Factory Installed (18)		Discount to apply 20%	
CODE	Description	List Price	
RAI	CAB RAIN SHIELD	283.06 USD	
110	110 V PLUG HEATER	196.13 USD	
OWC	OIL BATH AIR CLEANER	3,200.00 USD	
BFL	BOOM FLOATING PIPING	1,350.00 USD	
BRF	BREAKER FILTER	450.00 USD	
PER	BUCKET TILT/ROTATING PIPING	6,360.88 USD	
PE3	ONE & TWO WAY PILOT CONTROL WITH PED	AL 6,360.88 USD	
STT	STRAIGHT TRAVEL	763.31 USD	
ACO	ELECTRICAL AIR COMPRESSOR	2,650.00 USD	
FIL	FUEL FILLER PUMP	406.04 USD	
AVC	AVM (AROUND VIEW CAMERA) WITH MONITO	0R 4,800.00 USD	
FUL	UPPER AND LOWER FRONT WINDOW GUAR	D 1,187.37 USD	
FOG	FOG (FALLING OBJECT GUARD)	2,756.38 USD	
4LE	4 ADDITIONAL LED WORKING LAMPS	575.00 USD	
6LE	6 ADDITIONAL LED WORKING LAMPS	862.50 USD	
ROB	ROTATING BEACON	466.46 USD	
700	27.6" (700 MM) TRIPLE GROUSER SHOE	-1,013.00 USD	
900	35.4" (900 MM) TRIPLE GROUSER SHOE	1,855.26 USD	
	CODE RAI 110 OWC BFL BRF PER PE3 STT ACO FIL AVC FUL FOG 4LE 6LE ROB 700	CODE Description RAI CAB RAIN SHIELD 110 110 V PLUG HEATER OWC OIL BATH AIR CLEANER BFL BOOM FLOATING PIPING BRF BREAKER FILTER PER BUCKET TILT/ROTATING PIPING PE3 ONE & TWO WAY PILOT CONTROL WITH PED STT STRAIGHT TRAVEL ACO ELECTRICAL AIR COMPRESSOR FIL FUEL FILLER PUMP AVC AVM (AROUND VIEW CAMERA) WITH MONITOR FUL UPPER AND LOWER FRONT WINDOW GUARD FOG FOG (FALLING OBJECT GUARD) 4LE 4 ADDITIONAL LED WORKING LAMPS 6LE 6 ADDITIONAL LED WORKING LAMPS ROB ROTATING BEACON	

Attachments - Dealer Installed (21)			
Attachment	Description	Approx. Weight	List Price
DC350-060	1.28 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	2,117.00	6,120.74 USD
DC350-072	1.55 CU. YD. 72" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	2,496.00	6,951.66 USD
HD35-027	0.88 CU. YD. 26" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,125.00	8,848.96 USD
HD35-030	1.07 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	0.00	11,693.58 USD
HD35-036	1.37 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	0.00	12,655.28 USD
HD35-048	1.96 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,651.00	12,772.03 USD
HD35-054	2.27 CU. YD. 54" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,326.00	13,872.76 USD
HD35-060	2.58 CU. YD. 60" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,600.00	14,954.91 USD
HDC350-072	3.17 CU. YD. 72" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	3,980.00	16,042.14 USD
HT-35DM-048	MAIN PIN THUMB; HYDRAULIC; 5 TINE; FOR 48" BUCKET; USED WITH BUCKET	1.00	10,632.81 USD
HT-35DM-054	MAIN PIN THUMB; HYDRAULIC; 5 TINE; FOR 54" BUCKET; USED WITH BUCKET	1.00	11,908.74 USD
HT-35DM-060	MAIN PIN THUMB; HYDRAULIC; 5 TINE; FOR 60" BUCKET; USED WITH BUCKET	1.00	16,747.06 USD
HT-35QC-048	HYD. MAIN PIN THUMB; 4 TINE; FOR 48" BUCKET; USED WITH COUPLER	1.00	16,747.06 USD
HT-35QC-054	HYD. MAIN PIN THUMB; 4 TINE; FOR 54" BUCKET; USED WITH COUPLER	1.00	16,747.06 USD
HT-35QC-060	HYD. MAIN PIN THUMB; 5 TINE; FOR 60" BUCKET; USED WITH COUPLER	1.00	16,747.06 USD
PL-35QC-060	HYD. PRO LINK THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1.00	18,711.66 USD
QC-100H1G3-321	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX350	1,512.00	11,544.31 USD
SD35-036	1.37 CU. YD. 46" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,715.00	13,692.46 USD
SD35-048	1.96 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,200.00	15,530.32 USD
SD35-054	2.27 CU. YD. 54" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,401.00	17,194.09 USD
SD35-060	2.58 CU. YD. 60" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,675.00	18,615.78 USD



STANDARD EQUIPMENT FOR BASE MACHINE (7) Item Description "DL08-LEE03: 4-Cyclewater-Cooled Turbo Charged (Variable Geometry Turbo) Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with **Diesel Exhaust Fluid** 286HP(SAE J1995) Gross Flywheel Horsepower @ 1800 rpm Displacement: 466 cu.in., 6 Cylinder Bore 4.25"" (108 mm) Diameter x 5.47"" (139 mm) Stroke Torque: 940ft. lbs @ 1,300 rpm Engine High Idle 1900 ; 3/4 25rpm, Low Idle 800 ; 3/4 10 rpm Auto Idle System Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Three Stage Air Intake Filtering with Large Capacity Double Element Air Cleaner and Evacuate **Electronic Engine Speed Control** Engine Overheat and Low Oil Pressure Prevention System "Pilot Operated Control Valves, (9) Spools Main Pump: Tandem Variable Axial Piston Type, Pressure Setting 4978 psi normal / 5263 psi boost Pump flow: 2 X 92 gpm Pilot Circuit, Gear Type Pump Swing Motor, Axial Piston Type Swing Speed Control up to 9.5 RPM Maximum Swing Torque 107,483 ft.lbs. Hydraulic Spring Set, Hydraulic-released Brakes Travel Motor: Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.5 mph / 2.1 mph Maximum Tractive Force 83,555 ft.lbs. in low speed In-Shoe Design, Oil Disc Parking Brake One-way/two way Auxiliary Hydraulics with 2-pump flow "Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets 8"" Multi-function Color LCD Touch Screen Monitor Door Locks Front Windshield Panto Wiper with Washer Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: **Engine Speed Control Dial** Jog Switch for monitor display control Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Intelligent Floating Boom (optional) Engine After Treatment System Switch Wiper Control Panel Safety Lock Lever Ergonomic Leatherlike Operator Seat: Integrated Heater and Air Conditioner Air Suspension with Seat Belt (2"" Wide) Cab Adjustable bottom cushion Lumbar Support Adjustment Adjustable Headrest Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Height Adjustable Panels Skylight



	Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Door Sliding Windows Front Window Air Defroster Travel Pedals with Hand Levers Emergency Exit Glass Breaking Tool Fully insolated Lunch Box Compartment Quick Coupler Switch Joystick Lever with 3 Switches, Two Button and One Rotate Front and Rear Cup Holders Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Sun Screens for Top Hatch, Front Windshield and Rear Window
Electrical/Electronic Control System	 "Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Electronic Power Optimizing System Cross Sensing Pump Control Machine Status Display with Integrated Self Diagnostics System Adjustable LCD Color Display Incorporated Camera Views Auto Idle Control System plus One Touch Deceleration Button on Joystick Engine Speed Control Dial Power Boost Control Button on Joystick Limp Home Mode Control Switch Proportional control for auxiliary hydraulics via roll switch on both joysticks Adjustable Auxiliary Flow and Pressure up to 10 presets Alternator: 24 V, 100 amp Batteries: (2) 12 V, 200 AmpH, 950 CCA Starter: 24 V x 6 KW Engine Emergency Stop Switch Panto Wiper to cover the entire front windshield window LED Lights: Working Light (2) Machine, (2) Boom Smart Ignition Switch Key for remote control of engine start/stop and fdoor lock/unlock Electric Horn Hour Meter
	"Main Warning Lamp Warning Symbol Indicator for: Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, GSM antenna failure, Satelite antenna failure, Check machine, Stop engine
Display Monitor and Warnings	Digital Clock Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF (AdBlue¢ç) Level Multi-function Touch Screen Display for: Euncion Symbol Indicator (Power Boost Auxiliary Hydraulic Pedal/Joystick Selector Travel Speed



	Work Light, Intelligent Floating Boom, ISO/BHL Pattern Control, Fine Swing
	Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth)
	Favorite Button Indicator Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info) Main Information Indicator Power Mode Selector Button Indicator (Power+, Power, Standard, Economy) Power Mode Indicator Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear) Audio Display Auto Idle Indicator Menu Selector Button
Undercarriage	"Track Guards and Chains with Adjusters 2 pairs of standard track guides per side Track Rollers: (2) Upper, (9) Lower Each Side 31.5"" (800 mm) Triple Grouser Shoes, 48 Each Side
Other	"Joystick Pattern Change Valve Centralized Lube Points Large Handrail Punched Metal Anti-slip Plates Engine Restart Prevention System Self-Diagnostic System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc at the Bucket Pivot Vandalism Protection (All panels and fill points lockable) GPS 3 Year Subscription





PACKAGE ARRANGEMENT (1)

Discount to apply 25%

21' 4" (6.5 M) BOOM 13' 0" (3.95 M) ARM 33.5" (850 mm) TRIPLE GROUSER SHOES 15,653 LBS (7.1 METRIC TON) COUNTERWEIGHT ONE AND TWO WAY AUXILIARY PIPING TO END OF THE ARM WITH ONE WAY FLOW

OPTIONAL EQUIPMENT - Factory Installed (19)			Discount to apply 20%	
Option	CODE	Description	List Price	
RAIN SHIELD	RAI	CAB RAIN SHIELD	283.06 USD	
ENGINE COOLANT HEATER	110	110 V PLUG HEATER	196.13 USD	
PRE CLEANER	OWC	OIL BATH AIR CLEANER	3,200.00 USD	
BOOM FLOATING PIPING	BFL	BOOM FLOATING PIPING	1,350.00 USD	
BREAKER FILTER	BRF	BREAKER FILTER	450.00 USD	
ROTATING PIPING(PERO)	PER	BUCKET TILT/ROTATING PIPING	6,360.88 USD	
ONE & TWO WAY PIPING	PE3	ONE & TWO WAY PILOT CONTROL WITH PEI	DAL 6,360.88 USD	
STRAIGHT TRAVEL	STT	STRAIGHT TRAVEL	763.31 USD	
AIR COMPRESSOR	ACO	ELECTRICAL AIR COMPRESSOR	2,650.00 USD	
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	406.04 USD	
CAMERA	AVC	AVM (AROUND VIEW CAMERA) WITH MONIT	OR 4,800.00 USD	
CABIN FRONT GUARD	FUL	UPPER AND LOWER FRONT WINDOW GUAF	RD 1,187.37 USD	
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	2,756.38 USD	
ADDITIONAL WORK LAMP	4LE	4 ADDITIONAL LED WORKING LAMPS	575.00 USD	
ADDITIONAL WORK LAMP	6LE	6 ADDITIONAL LED WORKING LAMPS	862.50 USD	
ROTATING BEACON	ROB	ROTATING BEACON	466.46 USD	
TRACK SHOE	700	27.6" (700 MM) TRIPLE GROUSER SHOE	-2,792.00 USD	
TRACK SHOE	800	31.5" (800 MM) TRIPLE GROUSER SHOE	-488.00 USD	





TRACK SHOE

900

35.4" (900 MM) TRIPLE GROUSER SHOE

457.98 USD

Attachments - Dealer Installed (21)			
Attachment	Description	Approx. Weight	List Price
DC350-060	1.28 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	2,117.00	6,120.74 USD
DC350-072	1.55 CU. YD. 72" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	2,496.00	6,951.66 USD
HD35-027	0.88 CU. YD. 26" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,125.00	8,848.96 USD
HD35-030	1.07 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	0.00	11,693.58 USD
HD35-036	1.37 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	0.00	12,655.28 USD
HD35-048	1.96 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,651.00	12,772.03 USD
HD35-054	2.27 CU. YD. 54" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,326.00	13,872.76 USD
HD35-060	2.58 CU. YD. 60" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,600.00	14,954.91 USD
HDC350-072	3.17 CU. YD. 72" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	3,980.00	16,042.14 USD
HT-35DM-048	MAIN PIN THUMB; HYDRAULIC; 5 TINE; FOR 48" BUCKET; USED WITH BUCKET	1.00	10,632.81 USD
HT-35DM-054	MAIN PIN THUMB; HYDRAULIC; 5 TINE; FOR 54" BUCKET; USED WITH BUCKET	1.00	11,908.74 USD
HT-35DM-060	MAIN PIN THUMB; HYDRAULIC; 5 TINE; FOR 60" BUCKET; USED WITH BUCKET	1.00	16,747.06 USD
HT-35QC-048	HYD. MAIN PIN THUMB; 4 TINE; FOR 48" BUCKET; USED WITH COUPLER	1.00	16,747.06 USD
HT-35QC-054	HYD. MAIN PIN THUMB; 4 TINE; FOR 54" BUCKET; USED WITH COUPLER	1.00	16,747.06 USD
HT-35QC-060	HYD. MAIN PIN THUMB; 5 TINE; FOR 60" BUCKET; USED WITH COUPLER	1.00	16,747.06 USD
PL-35QC-060	HYD. PRO LINK THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1.00	18,711.66 USD
QC-100H1G3-321	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX350	1,512.00	11,544.31 USD
SD35-036	1.37 CU. YD. 46" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	2,715.00	13,692.46 USD
SD35-048	1.96 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,200.00	15,530.32 USD
SD35-054	2.27 CU. YD. 54" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,401.00	17,194.09 USD
SD35-060	2.58 CU. YD. 60" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	3,675.00	18,615.78 USD



STANDARD EQUIPMENT FOR BASE MACHINE (7) Item Description "DL08-LEE03: 4-Cyclewater-Cooled Turbo Charged (Variable Geometry Turbo) Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with **Diesel Exhaust Fluid** 286HP(SAE J1995) Gross Flywheel Horsepower @ 1800 rpm Displacement: 466 cu.in., 6 Cylinder Bore 4.25"" (108 mm) Diameter x 5.47"" (139 mm) Stroke Torque: 940ft. lbs @ 1,300 rpm Engine High Idle 1900 ; 3/4 25rpm, Low Idle 800 ; 3/4 10 rpm Auto Idle System Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Three Stage Air Intake Filtering with Large Capacity Double Element Air Cleaner and Evacuate Electronic Engine Speed Control Engine Overheat and Low Oil Pressure Prevention System "Pilot Operated Control Valves, (9) Spools Main Pump: Tandem Variable Axial Piston Type, Pressure Setting 4978 psi normal / 5263 psi boost Pump flow: 2 X 92 gpm Pilot Circuit, Gear Type Pump Swing Motor, Axial Piston Type Swing Speed Control up to 9.5 RPM Maximum Swing Torque 107,483 ft.lbs. Hydraulic Spring Set, Hydraulic-released Brakes Travel Motor: Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.5 mph / 2.1 mph Maximum Tractive Force 83,555 ft.lbs. in low speed In-Shoe Design, Oil Disc Parking Brake One-way/two way Auxiliary Hydraulics with 2-pump flow "Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets 8"" Multi-function Color LCD Touch Screen Monitor Door Locks Front Windshield Panto Wiper with Washer Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: **Engine Speed Control Dial** Jog Switch for monitor display control Auxiliary Mode Switch Engine Emergency Stop Switch Work Light Switch **Travel Speed Selector Switch** Breaker, Power-up, Shear Switch Intelligent Floating Boom (optional) Engine After Treatment System Switch Wiper Control Panel Safety Lock Lever Ergonomic Leatherlike Operator Seat: Integrated Heater and Air Conditioner Air Suspension with Seat Belt (2"" Wide) Cab Adjustable bottom cushion Lumbar Support Adjustment Adjustable Headrest Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console



Price Page

[
	Height Adjustable Panels
	Skylight
	Pull Up Type Front Window with Storage Behind Seet
	Removable Lower Front Window with Storage Behind Seat
	Door Sliding Windows
	Front Window Air Defroster
	Travel Pedals with Hand Levers
	Emergency Exit Glass Breaking Tool
	Fully insolated Lunch Box Compartment
	Quick Coupler Switch
	Joystick Lever with 3 Switches, Two Button and One Rotate
	Front and Rear Cup Holders
	Room Light
	Serial Communication Port for Laptop PC Interface (DMS)
	Viscous Cab Mounts
	Sun Screens for Top Hatch, Front Windshield and Rear Window "
	"Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and
	productivity
	Power Mode Select Button (P+,P,S,E)
	Work Mode Selector Button (Excavation, Lifting, Breaker and Shear)
	Electronic Power Optimizing System
	Cross Sensing Pump Control
	Machine Status Display with Integrated Self Diagnostics System
	Adjustable LCD Color Display
	Incorporated Camera Views
	Auto Idle Control System plus One Touch Deceleration Button on Joystick
	Engine Speed Control Dial
Electrical/Electronic Control	Power Boost Control Button on Joystick
	Limp Home Mode Control Switch
System	Proximity Alarm Warning System
	Proportional control for auxiliary hydraulics via roll switch on both joysticks
	Adjustable Auxiliary Flow and Pressure up to 10 presets
	Alternator: 24 V, 100 amp
	Batteries: (2) 12 V, 200 AmpH, 950 CCA
	Starter: 24 V x 6 KW
	Engine Emergency Stop Switch
	Panto Wiper to cover the entire front windshield window
	LED Lights: Working Light (2) Machine, (2) Boom
	Smart Ignition Switch Key for remote control of engine start/stop and fdoor lock/unlock
	Electric Horn
	Hour Meter
	"Main Warning Lamp Warning Symbol Indicator for:
	Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil
	temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low
	DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR
	valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS
	failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF
	pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS
	antenna failure, GSM antenna failure, Satelite antenna failure, Check machine, Stop engine
	Digital Clock
	Alarm Buzzer for:
	Alarm Buzzer for: Engine Oil Pressure
	Alarm Buzzer for: Engine Oil Pressure Coolant Temperature
	Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for:
Display Monitor and Warnings	Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge
Display Monitor and Warnings	Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge
Display Monitor and Warnings	Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge



	Multi-function Touch Screen Display for: Funcion Symbol Indicator (Power Boost, Auxiliary Hydraulic Pedal/Joystick Selector, Travel Speed, Work Light, Intelligent Floating Boom, ISO/BHL Pattern Control, Fine Swing Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth)
	Favorite Button Indicator Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info) Main Information Indicator Power Mode Selector Button Indicator (Power+, Power, Standard, Economy) Power Mode Indicator Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear) Audio Display Auto Idle Indicator Menu Selector Button
Undercarriage	"Track Guards and Chains with Adjusters 2 pairs of standard track guides per side Track Rollers: (2) Upper, (9) Lower Each Side 31.5"" (800 mm) Triple Grouser Shoes, 48 Each Side "
Other	"Joystick Pattern Change Valve Centralized Lube Points Large Handrail Punched Metal Anti-slip Plates Engine Restart Prevention System Self-Diagnostic System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc at the Bucket Pivot Vandalism Protection (All panels and fill points lockable) GPS 3 Year Subscription