PACKAGE ARRANGEMENT (1)		Discount to apply 25%	
Product	Approx. Weight	List Price	
DX530LC-5K-US10	50,500.00 KG	488,201.09 USD	
DX530LC-5K BASE MACHINE W/O BUCKET NO BOOM NO ARM INCLUDES BOOM CYLINDERS 36" (900mm) TRIPLE GROUSER SHOES 24,420 lb (11.1 METRIC TON) COUNTERWEIGHT 11' 9" (3.57m) RETRACTABLE UNDERCARRIAGE ONE WAY AUXILIARY HYDRAULIC FLOW			

OPTIONAL EQUIPMENT - Factory Installed (34)		Discount to apply 20%	
Option	CODE	Description	List Price
TRACK GUARD	FUL	Full Track Guard	2,150.00 USD
TRACK SHOE	800	800mm Shoe	-1,675.00 USD
TRACK SHOE	750	750mm Shoe	-2,500.00 USD
TRACK SHOE	60D	600mm Double Grouser Shoe	-5,000.00 USD
TRACK SHOE	600	600mm Shoe	-5,000.00 USD
BOOM FLOATING PIPING	WOL	Boom Floating Piping without B	1,275.00 USD
BREAKER FILTER	BRF	Breaker Filter	425.00 USD
LOCK VALVE	LBA	Boom & Arm Lock Valve	1,700.00 USD
LOCK VALVE	LOB	Boom Lock Valve	1,150.00 USD
ONE & TWO WAY PIPING	ONE	Mono One Way	950.00 USD
ONE & TWO WAY PIPING	PE3	Mono Two Way with Pedal	6,360.88 USD
STRAIGHT TRAVEL	STT	Straight Travel	300.00 USD
HEATING & COOLING SEAT	HCS	Heating & Cooling Seat	975.00 USD
MICROPHONE	MIC	Microphone	1,000.00 USD
RAIN SHIELD	RAI	Rain Shield	175.00 USD
ALARM	TRA	Alarm for Travel Only	-50.00 USD
CAMERA	RVC	Rear View Camera	-700.00 USD
CABIN FRONT GUARD	FUL	Up <del>p</del> ချွေချော့ရ ြစုဃူer Guard	475.00 USD

CABIN FRONT GUARD	LOW	Lower Guard Only	275.00 USD
FOGS GUARD	FOG	FOGS	2,600.00 USD
FOGS GUARD	TOP	Top Guard	575.00 USD
ADDITIONAL WORK LAMP	2LA	2 Additional Working Lamp(HAL)	275.00 USD
ADDITIONAL WORK LAMP	6LA	6 Additional Working Lamp(HAL)	962.50 USD
LOWER WIPER	LOW	Lower Wiper	100.00 USD
OVERLOAD WARNING DEVICE	OWD	Overload Warning Device	100.00 USD
ROTATING BEACON	ROB	Rotating Beacon	200.00 USD
ENGINE COOLANT HEATER	110	110V Plug Heater	225.00 USD
PRE CLEANER	OWC	Oil Washed Pre Cleaner	2,675.00 USD
AIR COMPRESSOR	ACO	Air Compressor	4,575.00 USD
AUTO GREASING UNIT	AGU	Auto Greasing Unit	5,700.00 USD
FUEL FILLER PUMP	FIL	Fuel Filler Pump	375.00 USD
SHOE CASE	SHC	Shoe Case	75.00 USD
ADDITIONAL 12V SOCKET	12V	Additional 12V Socket	300.00 USD
UNDER COVER	HED	Heavy Duty Under Cover	300.00 USD

Attachments - Dealer Installed			
Attachment	Description	Approx. Weight	List Price

STANDARD EQUIPMENT FOR BASE MACHINE (6)	
Item	Description
Engine	DC13 Scania engine; 4-Cyclewater-Cooled Turbo Charged (Variable Geometry Turbo) Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with Diesel Exhaust Fluid 283kW (379 HP) (SAE J1995) Gross Flywheel Horsepower @ 1800 rpm Displacement: 466 cu.in. (12,700 cc), 6 Cylinder Bore 5.12" (130 mm) Diameter x 6.30" (160 mm) Stroke Torque: 1,302 ft. Lbs (180 kgf-m) @ 1,300 rpm High Idle 1900 ± 25rpm, Low Idle 750 ± 25 rpm Auto Idle System Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank

	Three Stage Air Intake Filtering with Large Capacity Double Element Air Cleaner and Evacuate Electronic Engine Speed Control Engine Overheat and Low Oil Pressure Prevention System
Hydraulic	Pilot Operated Control Valves, (9) Spools Main Pump: Tandem Variable Axial Piston Type, Pressure Setting 4978 psi normal / 5263 psi boost Pump flow: 2 X [107 gpm (405 lpm)] Pilot Circuit, Gear Type Pump Swing Motor, Axial Piston Type Swing Speed Control up to 9.2 RPM Maximum Swing Torque 145,600 ft.lbs. (20,130 kgf-m) Spring Set, Hydraulic-released Brakes Travel Motor: Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.5 mph / 2.1 mph Maximum Tractive Force 83,555 ft.lbs. in low speed In-Shoe Design, Oil Disc Parking Brake One-way/two way Auxiliary Hydraulics with 2-pump flow
Electrical/Electronic Control System	Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Electronic Power Optimizing System Cross Sensing Pump Control Machine Status Display with Integrated Self Diagnostics System Adjustable LCD Color Display Incorporated Camera Views Auto Idle Control System plus One Touch Deceleration Button on Joystick Engine Speed Control Dial Power Boost Control Button on Joystick Limp Home Mode Control Switch Proximity Alarm Warning System Proportional control for auxiliary hydraulics via roll switch on both joysticks Adjustable Auxiliary Flow and Pressure up to 10 presets Alternator: 28 V, 100 amp Batteries: (2) 12 V, 200 AmpH, 1300 CCA Starter: 24 V x 6 KW Engine Emergency Stop Switch Panto Wiper to cover the entire front windshield window Standard Halogen Type Lighting; 2 Working lights on machine and 2 on boom Optional LED Type Lights Smart Ignition Switch Key for remote control of engine start/stop and door lock/unlock Electric Horn Hour Meter
Undercarriage	Track Guards and Chains with Adjusters 3 sets of track guides per side Track Rollers: (3) Upper, (9) Lower Each Side 36" (900 mm) Triple Grouser Shoes, 53 Each Side
Other	Joystick Pattern Change Valve Centralized Lube Points Large Handrail Punched Metal Anti-slip Plates Engine Restart Prevention System Self-Diagnostic System Operator's Manual Ultra-hard Wear-resistant Disc at the Bucket Pivot Vandalism Protection (All panels and fill points lockable) GPS 3 Year Subscription - 3.0 GLOBAL DUAL(SAT+CELL)
	Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets 8" Multi-function Color LCD Touch Screen Monitor Door Locks Front Windshield Panto Wiper with Washer Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On 1995 witch, Control Volume, Channel Select

Eng

Switches:

**Engine Speed Control Dial** 

Jog Switch for monitor display control

**Auxiliary Mode Switch** 

Engine Emergency Stop Switch

Work Light Switch

Travel Speed Selector Switch Breaker, Power-up, Shear Switch Intelligent Floating Boom (optional) Engine After Treatment System Switch

Wiper Control Panel

Safety Lock Lever

Ergonomic Leatherlike Operator Seat: Integrated Heater and Air Conditioner Air Suspension with Seat Belt (2" Wide)

Adjustable bottom cushion Lumbar Support Adjustment

Adjustable Headrest

Reclining, Height Adjustable

Adjustable Arm Rests
Sliding Control Console
Height Adjustable Panels

Skylight

Pull Up Type Front Window

Removable Lower Front Window with Storage Behind Seat

Door Sliding Windows
Front Window Air Defroster
Travel Pedals with Hand Levers
Emergency Exit Glass Breaking Tool
Fully insolated Lunch Box Compartment

**Quick Coupler Switch** 

Joystick Lever with 3 Switches, Two Button and One Rotate

Front and Rear Cup Holders

Room Light

Serial Communication Port for Laptop PC Interface (DMS)

Viscous Cab Mounts

Sun Screens for Top Hatch, Front Windshield and Rear Window

Cab