

PACKAGE ARRANGEMENT (1)		Discount to apply 25%
Product	Approx. Weight	List Price
DX800LC-7-US10	80,000.00 KG	783,596.45 USD
DX800LC-7 BASE MACHINE W/O BOOM, ARM AND BUCKET NO BOOM NO ARM INCLUDES BOOM CYLINDERS 35.4" (900 mm) DOUBLE GROUSER SHOES 23,589 LBS (10.7 METRIC TON) COUNTERWEIGHT ONE WAY AUX FLOW		

OPTIONAL EQUIPMENT - Factory Installed (15)			Discount to apply 20%
Option	CODE	Description	List Price
REMOVAL COUNTERWEIGHT	RCW	REMOVABLE COUNTERWEIGHT	27,705.18 USD
RAIN SHIELD	RAI	CAB RAIN SHIELD	283.06 USD
ONE & TWO WAY PIPING	PE3	ONE & TWO WAY PILOT PIPING	6,360.88 USD
STRAIGHT TRAVEL	STT	STRAIGHT TRAVEL	763.31 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	3,710.52 USD
AUTO GREASING UNIT	AGU	AUTO GREASING SYSTEM	5,830.81 USD
FUEL FILLER PUMP	FIL	FUEL FILLER PUMP	406.04 USD
CAMERA	AVC	AROUND VIEW CAMERA	3,741.70 USD
CABIN FRONT GUARD	FUL	UPPER AND LOWER FRONT WINDOW GUARD	1,186.95 USD
FOGS GUARD	FOG	FOG (FALLING OBJECT GUARD)	2,756.38 USD
ADDITIONAL WORK LAMP	6LE	6 ADDITIONAL WORKING LAMPS (LED)	1,662.98 USD
ADDITIONAL WORK LAMP	2LE	2 ADDITIONAL WORKING LAMPS (LED)	935.42 USD
ROTATING BEACON	ROB	ROTATING BEACON	466.46 USD
TRACK SHOE	65D	25.6" (650 MM) DOUBLE GROUSER SHOE	-2,667.00 USD
TRACK SHOE	75D	29.5" (750 MM) DOUBLE GROUSER SHOE	-1,333.00 USD

Attachments - Dealer Installed			
Attachment	Description	Approx. Weight	List Price

STANDARD EQUIPMENT FOR BASE MACHINE (7)

Item	Description
Engine	<p>"Perkins 2506J: Turbocharged Water Cooled Mechanical Electronic Unit Injector System (MEUI) T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Diesel Particulate Filter + Selective Catalytic Reduction with Diesel Exhaust Fluid 539HP (ISO 14396) Gross Flywheel Horsepower @ 2,100 rpm Displacement: 928 cu.in., 6 Cylinder Bore 137mm Diameter x 171mm Stroke Torque: 1821ft. lbs @ 1,400 rpm High Idle 1900 $\frac{3}{4}$ 10rpm, Low Idle 900 $\frac{3}{4}$ 10 rpm Auto Idle System Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control Engine Overheat and Low Oil Pressure Prevention System"</p>
Hydraulic	<p>"Pilot Operated Control Valves, (10) Spools Main Pump: Tandem Axial Piston Type, Pressure Setting 4975psi 2 X 133 gpm Pilot Circuit, Gear Type Pump Swing Motor, Axial Piston Type Swing Speed Control up to 7.5 RPM Maximum Swing Torque 228,563 ft.lbs. Spring Set, Hydraulic-released Brakes Travel Motor: Axial Piston Type (High, Low, Auto) Travel Speed (High/Low): 3.0 mph / 1.9 mph Maximum Tractive Force 155793 ft.lbs. in low speed In-Shoe Design, Oil Disc Parking Brake Cross Sensing Pump Control for Fuel Saving Four Operating Modes, Four Power Modes One-way Auxiliary Hydraulics Adjustable Auxiliary Flow and Pressure up to 10 presets Computer-aided Pump Power Control e-EPOS (Electronic Power Optimizing System) Controller"</p>
	<p>"Steel, All Weather Sound Suppressed Fully Automatic Controlled Air Conditioner with Heat 8" Touch Screen Color LCD Monitor Panel Rear View Camera Cigarette Lighter Door Locks Front Windshield Wiper with Washer Radio: MP3 Stereo with CD Player Switches: Smart Key Push Start Ignition Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Swing Priority Switch Reversing Fan Switch DPF Regeneration Switch Auxiliary Mode Switch Glass Antenna Safety Lock Lever Seat: 2 Stage Heated Air Suspension with Seat Belt (2 Wide) Reclining, Height Adjustable</p>

Cab	Adjustable Arm Rests Sliding Control Console Skylight Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Sliding Side Windows Front Window Air Defroster Travel Pedals with Hand Levers Emergency Breakout Tool Lunch Box with insulation 12V Power Socket Height Adjustable Control Stands Joystick Lever with Three Buttons Cup Holder LED Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts Operation Modes: Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Flow Rate Control Auto Idle Select Button 4 Display Selection Buttons Rear View Camera Button Jog Switch to Control Monitor"
Electrical	"Alternator: 24 V, 115 amp Batteries: (2) 12 V, 200 amp Starter: 24 V x 9 KW Lights: LED Working Light (6) Machine, (2) Boom Electric Horn Hour Meter"
Display Monitor and Warnings	"Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF Level DPF Soot Level Indicator Multi-function Display for: Engine RPM Radio Control Display Battery Warning Power Mode Selector Button Power Mode Indicator Hydraulic Oil Overheating Warning Fuel Shortage Warning Air Cleaner Clogging Warning Fuel Filter Clogging Warning Return Filter Clogging Warning Digital Clock Engine Check Warning Light Engine Oil Pressure Warning Light Coolant Temperature Warning Light Work Light Indicator Light Regeneration Notification Water in the Fuel Warning Light DEF Low Level Warning Symbol SCR Failure Warning Symbol"
Undercarriage	"Track Guards and Chains with Adjusters Track Rollers: (3) Upper, (8) Lower Each Side Double Grouser Shoes, 48 Each Side"

Other	"Joystick Pattern Change Valve Centralized Lube Points Headlamp Delay (Escort Lamp) Lamp Indicator on DEF Tank Large Handrail Punched Metal Anti-slip Plates Engine Restart Prevention System Self-Diagnostic System Manuals, Parts and Operator's Ultra-hard Wear-resistant Disc at the Bucket Pivot Vandalism Protection (All panels and fill points lockable) Telematics Unlimited Access with No Contracts & No Fees"
-------	--