

PACKAGE ARRANGEMENT (1)		Discount to apply 20%
Product	Approx. Weight	List Price
DX27Z-7-US20	2,900.00 KG	44,481.68 USD
"The Tier 4 compliant DX27Z-7 is configured with a 3' 6" (1.1 M) arm. NOTE: Attachment not included. Standard dozer blade and standard boom swing improves productivity. 11.8" (300 mm) Rubber Tracks are standard. 2-way Flow Auxiliary Hydraulics 5.7" Display Monitor Bluetooth Audio QC Piping Thumb Ready Arm"		

OPTIONAL EQUIPMENT - Factory Installed (5)			Discount to apply 20%
Option	CODE	Description	List Price
ONE & TWO WAY PIPING	PE3	TWO WAY WITH PEDAL	-355.00 USD
ALARM	TRA	ALARM FOR TRAVEL	250.00 USD
CAMERA	RVC	REAR VIEW CAMERA	275.00 USD
ADDITIONAL WORK LAMP	LED	ADDITIONAL WORK LAMP	175.00 USD
ROTATING BEACON	ROB	ROTATING BEACON	325.00 USD

Attachments - Dealer Installed (12)			
Attachment	Description	Approx. Weight	List Price
DC03-36	36" PIN-ON DITCHING BUCKET; 5.20 CU. FT. CAPACITY	1.00	1,783.80 USD
HD03-12	12" HEAVY DUTY PIN ON BUCKET; 1.45 CU. FT. CAPACITY	1.00	1,448.45 USD
HD03-18	18" HEAVY DUTY PIN ON BUCKET; 2.00 CU. FT. CAPACITY	1.00	1,640.88 USD
HD03-24	24" HEAVY DUTY PIN ON BUCKET; 3.53 CU. FT. CAPACITY	1.00	1,838.54 USD
HT-03DM	HYDRAULIC THUMB; 2 TINE; COMPATIBLE W/ MANUAL QUICKHITCH COUPLER/PIN ON BUCKETS	1.00	4,083.39 USD
HT-03QC	HYDRAULIC THUMB; 2 TINE; USED WITH HYDRAULIC QUICK COUPLER (PIN GRABBER)	1.00	4,083.39 USD
QC35-40H1LE-9416	HYDRAULIC QUICK COUPLER (PIN GRABBER); INCLUDES SOFT PINS, JUMPER HOSE ONLY	77.00	3,500.78 USD
QH-03	QUICKHITCH QUICK COUPLER; MANUAL	1.00	1,117.33 USD
QH03-12	12" QUICKHITCH GP BUCKET; 1.57 CU. FT. CAPACITY	1.00	876.61 USD

QH03-18	18" QUICKHITCH GP BUCKET; 2.74 CU. FT. CAPACITY	1.00	989.13 USD
QH03-24	24" QUICKHITCH GP BUCKET; 3.94 CU. FT. CAPACITY	1.00	1,123.51 USD
QH03GB	QUICK HITCH QUICK COUPLER; MANUAL	1.00	1,117.33 USD

STANDARD EQUIPMENT FOR BASE MACHINE (6)

Item	Description
Engine	"D1.8 Doosan engine High Pressure Common Rail Tier 4 Compliance without aid of DPF 25 HP Gross @ 2,200 rpm Max. Torque 72 ft. lbs @ 1,600 rpm Auto Idle Auto preheat cold start assist High Idle 2350 rpm MAX, Low Idle 1300 \pm 25 rpm Alternator: 12 V, 90 Amp. Battery: 12V Battery, 540 CCA @ 0 \pm F (-18 \pm C) Starter: 12 Volt, 1.7 Kw"
Hydraulic	"Control Valve: (10) Spools, closed center, individually compensated Main Pump: Load Sensing, torque limiting, variable displacement piston pump with gear pump (36.6 US gpm) Pressure Setting (3,553 PSI) Auxiliary Hydraulics Flow (24 gpm) Swing Motor: Axial Piston Type, with planetary reduction Swing Speed Control up to 10 RPM Swing Brake Travel Motors: Axial Piston, 2-Speed Travel Speed (High/Low), 2.7 mph / 1.6 mph Travel Brake Load Sensing System 2-Way Auxiliary Flow "
Cab	"ROPS Certified Air Conditioner (Enclosed Cab ONLY) AM/FM Stereo + Bluetooth (Enclosed Cab ONLY) Power Socket, 12V Cab Door Lock (Enclosed Cab ONLY) Front Windshield Wiper with Washer (Enclosed Cab ONLY) Safety Glass, Tinted (Enclosed Cab ONLY) Controls - Safety Lock Lever Seat: Deluxe Cloth Seat with Seat Belt (Enclosed Cab ONLY) Deluxe Vinyl Seat with Seat Belt (Canopy ONLY) Fully Adjustable Arm Rests Suspension Slide-up Front Window (Enclosed Cab ONLY) Sliding Side Windows (Enclosed Cab ONLY) Travel Control: Hand Levers/Foot pedals Emergency Breakout Tool (Enclosed Cab ONLY) "
	"Horn Lights: (1) Cabin, (1) Boom Alarm Buzzer for: Engine Overheat Engine Oil Pressure Electronic Monitor for: Air Filter Restriction Indicator Auto-Idle Indicator

Electrical	Auxiliary Flow Mode Indicator Clock - Day & Time Engine Check Warning Light Engine Oil Pressure Light Engine Temperature Gauge Fuel Gauge with low fuel indicator Hour Meter Pre-Heat (cold start assist) Indicator Two Speed Travel Indicator Light "
Undercarriage	"Track Adjusters Track Rollers: (1) Upper, (4) Lower each side 15.7 inch (400 mm) Rubber Tracks "
Other	"Dozer Blade Pattern Selector Valve Air Cleaner (Dual Filter) Joystick Lever, Dozer (High/Low Travel Speed Switch) Swing Boom (Left: 60 Degrees, Right: 53 Degrees) Auto-Shift, Two Speed Travel Fingertip Auxiliary Hydraulics & Boom Swing Password Protection System Rubber Tracks "