PACKAGE ARRANGEMENT (1)		Discount to apply 23%
Product	Approx. Weight	List Price
DX35Z-7-US30	3,500.00 KG	48,231.56 USD

"The Tier 4 compliant DX35Z-7 is configured with a 4' 3"" (1.3 M) arm.

NOTE: Attachment not included.

Standard dozer blade and standard boom swing improves productivity.

11.8" (300 mm) Rubber Tracks are standard.

2-way Flow Auxiliary Hydraulics (i.e. clamp control) increases

versatility. 5.7" Display Monitor

QC Piping

Thumb Ready Arm"

OPTIONAL EQUIPMENT - Factory Installed (4)		Discount to apply 20%	
Option	CODE	Description	List Price
ONE & TWO WAY PIPING	PE3	MONO TWO WAY WITH PEDAL	-355.00 USD
ALARM	TRA	ALARM FOR TRAVEL	250.00 USD
ADDITIONAL WORK LAMP	LED	ADDITIONAL WORKING LAMP(LED)	175.00 USD
ROTATING BEACON	ROB	ROTATING BEACON	325.00 USD

Attachments - Dealer Installed (11)				
Attachment	Description	Approx. Weight	List Price	
DC03-36	36" PIN-ON DITCHING BUCKET; 5.20 CU. FT. CAPACITY	1.00	1,783.80 USD	
HD03-12	12" HEAVY DUTY PIN ON BUCKET; 1.45 CU. FT. CAPACITY	1.00	1,448.45 USD	
HD03-18	18" HEAVY DUTY PIN ON BUCKET; 2.00 CU. FT. CAPACITY	1.00	1,640.88 USD	
HD03-24	24" HEAVY DUTY PIN ON BUCKET; 3.53 CU. FT. CAPACITY	1.00	1,838.54 USD	
HT-03DM	HYDRAULIC THUMB; 2 TINE; COMPATIBLE W/ MANUAL QUICKHITCH COUPLER/PIN ON BUCKETS	1.00	4,083.39 USD	
HT-03QC	HYDRAULIC THUMB; 2 TINE; USED WITH HYDRAULIC QUICK COUPLER (PIN GRABBER)	1.00	4,083.39 USD	
QC35-40H1LE-9416	HYDRAULIC QUICK COUPLER (PIN GRABBER); INCLUDES SOFT PINS, JUMPER HOSE ONLY	77.00	3,500.78 USD	
QH-03	QUICKHITCH QUICK COUPLER; MANUAL	1.00	1,117.33 USD	
QH03-12	12" QUICKHITCH GP BUCKET; 1.57 CU. FT. CAPACITY	1.00	876.61 USD	
QH03-18	18" QUICKHITCH GP BUCKET; 2.74 CU. FT. CAPACITY Page 1 of 3	1.00	989.13 USD	

QH03-24 24" QUICKHITCH GP BUCKET; 3.94 CU. FT. CAPACITY 1.00 1,123.51 USD

Item	Description
Engine	"DN1.7 Turbo Doosan engine High Pressure Common Rail Tier 4 Compliance without aid of DPF 25 HP Gross @ 2,200 rpm Max. Torque 72 ft. lbs @ 1,600 rpm Auto Idle Auto preheat cold start assist High Idle 2350 rpm MAX, Low Idle 1300 j¾ 25 rpm Alternator: 12 V, 90 Amp. Battery: 12V Battery, 540 CCA @ 0jÆ F (-18jÆ C) Starter: 12 Volt, 1.7 Kw
Hydraulic	"Control Valve: (10) Spools, closed center, individually compensated Main Pump: Load Sensing, torque limiting, variable displacement piston pump with gear pump (36.6 US gpm) Pressure Setting (3,553 PSI) Auxiliary Hydraulics Flow (24 gpm) Swing Motor: Axial Piston Type, with planetary reduction Swing Speed Control up to 10 RPM Swing Brake Travel Motors: Axial Piston, 2-Speed Travel Speed (High/Low), 2.7 mph / 1.6 mph Travel Brake 2-Way Auxiliary Flow
Cab	"ROPS Certified Air Conditioner (Enclosed Cab ONLY) AM/FM Stereo + Bluetooth (Enclosed Cab ONLY) Power Socket, 12V Cab Door Lock (Enclosed Cab ONLY) Front Windshield Wiper with Washer (Enclosed Cab ONLY) Safety Glass, Tinted (Enclosed Cab ONLY) Controls - Safety Lock Lever Seat: Deluxe Cloth Seat with Seat Belt (Enclosed Cab ONLY) Deluxe Vinyl Seat with Seat Belt (Canopy ONLY) Fully Adjustable Arm Rests Suspension Slide-up Front Window (Enclosed Cab ONLY) Sliding Side Windows (Enclosed Cab ONLY) Travel Control: Hand Levers/Foot pedals Emergency Breakout Tool (Enclosed Cab ONLY) "
Electrical	"Horn Lights: (1) Cabin, (1) Boom Alarm Buzzer for: Engine Overheat Engine Oil Pressure Electronic Monitor for: Air Filter Restriction Indicator Auto-Idle Indicator Auxiliary Flow Mode Indicator Clock - Day & Time Engine Check Warning Light Engine Oil Pressure Light Engine Temperature Gage2 of 3

	Fuel Gauge with low fuel indicator Hour Meter Pre-Heat (cold start assist) Indicator Two Speed Travel Indicator Light
Undercarriage	"Track Adjusters Track Rollers: (1) Upper, (4) Lower each side 15.7 inch (400 mm) Rubber Tracks
Other	"Dozer Blade Pattern Selector Valve Air Cleaner (Dual Filter) Joystick Lever, Dozer (High/Low Travel Speed Switch) Swing Boom (Left: 60 Degrees, Right: 53 Degrees) Auto-Shift, Two Speed Travel Fingertip Auxiliary Hydraulics & Boom Swing Password Protection System Rubber Tracks