

PACKAGE ARRANGEMENT (1)

Product	Approx. Weight	List Price
DX50Z-7-US20	5,150.00 KG	74,928.54 USD
<p>"The Tier 4 compliant DX50Z-7 is configured with a 4' 9" (1.45 M) thumb ready arm. NOTE: Attachment not included. Standard dozer blade and standard boom swing improves productivity. 15.7" (400 mm) Rubber Tracks are standard. 2-way Flow Auxiliary Hydraulics (i.e. clamp control) increases versatility. 5.7" Display Monitor Bluetooth Audio QC Piping"</p>		

OPTIONAL EQUIPMENT - Factory Installed (5)

Option	CODE	Description	List Price
Gauge Panel(H)	80D	8" DIGITAL TOUCH SCREEN PANEL	1,146.88 USD
CAMERA	RVC	Rear View Camera (Not Selectable)	450.56 USD
ADDITIONAL WORK LAMP	LED	Additional Working Lamp (LED)	143.36 USD
REAR LAMP	RLA	Rear Lamp	143.36 USD
ROTATING BEACON	ROB	Rotating Beacon	266.24 USD

Attachments - Dealer Installed (12)

Attachment	Description	Approx. Weight	List Price
DC05-48	48" PIN ON DITCHING BUCKET; 10.63 CU. FT. CAPACITY	1.00	3,111.72 USD
HD05-12	12" HEAVY DUTY PIN ON BUCKET; 1.45 CU. FT. CAPACITY	1.00	1,887.84 USD
HD05-18	18" HEAVY DUTY PIN ON BUCKET; 2.00 CU. FT. CAPACITY	1.00	2,095.63 USD
HD05-24	24" HEAVY DUTY PIN-ONBUCKET; 3.53 CU. FT. CAPACITY	1.00	2,671.03 USD
HD05-36	36" HEAVY DUTY PIN ON BUCKET; 8.69 CU. FT. CAPACITY	1.00	3,287.64 USD
HT-05DM	HYDRAULIC THUMB; 2 TINE; COMPATIBLE W/ MANUAL QUICKHITCH COUPLER/PIN ON BUCKETS	1.00	4,155.59 USD
HT-05QC	HYDRAULIC THUMB; 2 TINE; USED WITH HYDRAULIC QUICK COUPLER (PIN GRABBER)	1.00	4,137.98 USD
QC45-50H1G4-9136	HYDRAULIC QUICK COUPLER (PIN GRABBER); INCLUDES SOFT PINS, JUMPER HOSE ONLY	1.00	4,464.61 USD
QH-05	QUICKHITCH QUICK COUPLER; MANUAL	1.00	1,173.18 USD

QH05-12	12" GENERAL PURPOSE QUICKHITCH BUCKET; 1.96 CU. FT. CAPACITY	1.00	943.81 USD
QH05-18	18" GENERAL PURPOSE QUICKHITCH BUCKET; 3.43 CU. FT. CAPACITY	1.00	1,036.00 USD
QH05-24	24" GENERAL PURPOSE QUICKHITCH BUCKET; 4.99 CU. FT. CAPACITY	1.00	1,146.92 USD

STANDARD EQUIPMENT FOR BASE MACHINE (6)

Item	Description
Engine	"D18 Turbo High Pressure Common Rail Tier 4 Compliance without aid of DPF 48.8 HP Gross @ 2,200 rpm Max. Torque 133 ft. lbs @ 1,600 rpm Auto Idle Auto preheat cold start assist High Idle 2200 rpm MAX, Low Idle 1150 ¼ 25 rpm Alternator: 12 V, 90 Amp. Battery: 12V Battery, 540 CCA @ 0jÆ F (-18jÆ C) Starter: 12 Volt, 2.7 Kw"
Hydraulic	"Control Valve: (9) Spools, closed center, individually compensated Main Pump: Load Sensing, torque limiting, variable displacement piston pump with gear pump (36.6 US gpm) Pressure Setting (3,553 PSI) Auxiliary Hydraulics Flow (24 gpm) Swing Motor: Axial Piston Type, with planetary reduction Swing Speed Control up to 10 RPM Swing Brake Travel Motors: Axial Piston, 2-Speed Travel Speed (High/Low), 2.7 mph / 1.6 mph Travel Brake Load Sensing System 2-Way Auxiliary Flow"
Cab	"ROPS Certified Air Conditioner (Enclosed Cab ONLY) AM/FM Stereo + Bluetooth (Enclosed Cab ONLY) Power Socket, 12V Cab Door Lock (Enclosed Cab ONLY) Front Windshield Wiper with Washer (Enclosed Cab ONLY) Safety Glass, Tinted (Enclosed Cab ONLY) Controls - Safety Lock Lever Seat: Deluxe Cloth Seat with Seat Belt (Enclosed Cab ONLY) Deluxe Vinyl Seat with Seat Belt (Canopy ONLY) Fully Adjustable Arm Rests Suspension Slide-up Front Window (Enclosed Cab ONLY) Sliding Side Windows (Enclosed Cab ONLY) Travel Control: Hand Levers/Foot pedals Emergency Breakout Tool (Enclosed Cab ONLY)"
	"ROPS Certified Air Conditioner (Enclosed Cab ONLY) AM/FM Stereo + Bluetooth (Enclosed Cab ONLY) Power Socket, 12V Cab Door Lock (Enclosed Cab ONLY) Front Windshield Wiper with Washer (Enclosed Cab ONLY) Safety Glass, Tinted (Enclosed Cab ONLY)"

<p>Electrical</p>	<p>Controls - Safety Lock Lever Seat: Deluxe Cloth Seat with Seat Belt (Enclosed Cab ONLY) Deluxe Vinyl Seat with Seat Belt (Canopy ONLY) Fully Adjustable Arm Rests Suspension Slide-up Front Window (Enclosed Cab ONLY) Sliding Side Windows (Enclosed Cab ONLY) Travel Control: Hand Levers/Foot pedals Emergency Breakout Tool (Enclosed Cab ONLY)"</p>
<p>Undercarriage</p>	<p>"Track Adjusters Track Rollers: (1) Upper, (4) Lower each side 15.7 inch (400 mm) Rubber Tracks"</p>
<p>Other</p>	<p>"Dozer Blade Pattern Selector Valve Air Cleaner (Dual Filter) Joystick Lever, Dozer (High/Low Travel Speed Switch) Swing Boom (Left: 60 Degrees, Right: 53 Degrees) Auto-Shift, Two Speed Travel Fingertip Auxiliary Hydraulics & Boom Swing Password Protection System Rubber Tracks"</p>