

PACKAGE ARRANGEMENT (1)		Discount to apply 23%
Product	Approx. Weight	List Price
DX55R-7-US30	5,300.00 KG	71,212.92 USD
"The Tier 4 compliant DX55R-7 is configured with a 5' 3" (1.6 M) arm. NOTE: Attachment not included. Standard dozer blade and standard boom swing improves productivity. 15.7" (400 mm) Rubber Tracks are standard. 2-way Flow Auxiliary Hydraulics (i.e. clamp control) increases versatility. 5.7" Display Monitor QC Piping"		

OPTIONAL EQUIPMENT - Factory Installed (3)			Discount to apply 20%
Option	CODE	Description	List Price
ADDITIONAL WORK LAMP	LED	Additional Working Lamp (LED)	143.36 USD
REAR LAMP	RLA	Rear Lamp	143.36 USD
ROTATING BEACON	ROB	Rotating Beacon	266.24 USD

Attachments - Dealer Installed (12)			
Attachment	Description	Approx. Weight	List Price
DC05-48	48" PIN ON DITCHING BUCKET; 10.63 CU. FT. CAPACITY	1.00	3,111.72 USD
HD05-12	12" HEAVY DUTY PIN ON BUCKET; 1.45 CU. FT. CAPACITY	1.00	1,887.84 USD
HD05-18	18" HEAVY DUTY PIN ON BUCKET; 2.00 CU. FT. CAPACITY	1.00	2,095.63 USD
HD05-24	24" HEAVY DUTY PIN-ONBUCKET; 3.53 CU. FT. CAPACITY	1.00	2,671.03 USD
HD05-36	36" HEAVY DUTY PIN ON BUCKET; 8.69 CU. FT. CAPACITY	1.00	3,287.64 USD
HT-05DM	HYDRAULIC THUMB; 2 TINE; COMPATIBLE W/ MANUAL QUICKHITCH COUPLER/PIN ON BUCKETS	1.00	4,155.59 USD
HT-05QC	HYDRAULIC THUMB; 2 TINE; USED WITH HYDRAULIC QUICK COUPLER (PIN GRABBER)	1.00	4,137.98 USD
QC45-50H1G4-9136	HYDRAULIC QUICK COUPLER (PIN GRABBER); INCLUDES SOFT PINS, JUMPER HOSE ONLY	1.00	4,464.61 USD
QH-05	QUICKHITCH QUICK COUPLER; MANUAL	1.00	1,173.18 USD
QH05-12	12" GENERAL PURPOSE QUICKHITCH BUCKET; 1.96 CU. FT. CAPACITY	1.00	943.81 USD
QH05-18	18" GENERAL PURPOSE QUICKHITCH BUCKET; 3.43 CU. FT. CAPACITY	1.00	1,036.00 USD

QH05-24	24" GENERAL PURPOSE QUICKHITCH BUCKET; 4.99 CU. FT. CAPACITY	1.00	1,146.92 USD
---------	--	------	--------------

STANDARD EQUIPMENT FOR BASE MACHINE (6)

Item	Description
Engine	"D18 Turbo High Pressure Common Rail Tier 4 Compliance without aid of DPF 48.8 HP Gross @ 2,200 rpm Max. Torque 133 ft. lbs @ 1,600 rpm Auto Idle Auto preheat cold start assist High Idle 2200 rpm MAX, Low Idle 1150 \pm 25 rpm Alternator: 12 V, 90 Amp. Battery: 12V Battery, 540 CCA @ 0 \pm F (-18 \pm C) Starter: 12 Volt, 2.7 Kw"
Hydraulic	"Control Valve: (9) Spools, closed center, individually compensated Main Pump: Load Sensing, torque limiting, variable displacement piston pump with gear pump (36.6 US gpm) Pressure Setting (3,553 PSI) Auxiliary Hydraulics Flow (24 gpm) Swing Motor: Axial Piston Type, with planetary reduction Swing Speed Control up to 10 RPM Swing Brake Travel Motors: Axial Piston, 2-Speed Travel Speed (High/Low), 2.7 mph / 1.6 mph Travel Brake Load Sensing System 2-Way Auxiliary Flow"
Cab	"ROPS Certified Air Conditioner (Enclosed Cab ONLY) AM/FM Stereo + Bluetooth (Enclosed Cab ONLY) Power Socket, 12V Cab Door Lock (Enclosed Cab ONLY) Front Windshield Wiper with Washer (Enclosed Cab ONLY) Safety Glass, Tinted (Enclosed Cab ONLY) Controls - Safety Lock Lever Seat: Deluxe Cloth Seat with Seat Belt (Enclosed Cab ONLY) Deluxe Vinyl Seat with Seat Belt (Canopy ONLY) Fully Adjustable Arm Rests Suspension Slide-up Front Window (Enclosed Cab ONLY) Sliding Side Windows (Enclosed Cab ONLY) Travel Control: Hand Levers/Foot pedals Emergency Breakout Tool (Enclosed Cab ONLY)"
Electrical	"ROPS Certified Air Conditioner (Enclosed Cab ONLY) AM/FM Stereo + Bluetooth (Enclosed Cab ONLY) Power Socket, 12V Cab Door Lock (Enclosed Cab ONLY) Front Windshield Wiper with Washer (Enclosed Cab ONLY) Safety Glass, Tinted (Enclosed Cab ONLY) Controls - Safety Lock Lever Seat: Deluxe Cloth Seat with Seat Belt (Enclosed Cab ONLY) Deluxe Vinyl Seat with Seat Belt (Canopy ONLY) Fully Adjustable Arm Rests Suspension Slide-up Front Window (Enclosed Cab ONLY) Sliding Side Windows (Enclosed Cab ONLY)"

	Travel Control: Hand Levers/Foot pedals Emergency Breakout Tool (Enclosed Cab ONLY)"
Undercarriage	"Track Adjusters Track Rollers: (1) Upper, (4) Lower each side 15.7 inch (400 mm) Rubber Tracks"
Other	"Dozer Blade Pattern Selector Valve Air Cleaner (Dual Filter) Joystick Lever, Dozer (High/Low Travel Speed Switch) Swing Boom (Left: 60 Degrees, Right: 53 Degrees) Auto-Shift, Two Speed Travel Fingertip Auxiliary Hydraulics & Boom Swing Password Protection System Rubber Tracks"