PACKAGE ARRANGEMENT (1)		Discount to apply 25%
Product	Approx. Weight	List Price
DX140W-7-US30	17,000.00 KG	215,084.51 USD

DX140W-7 BASE MACHINE W/O BUCKET
14' 5" (4.4 M) MONO BOOM
6' 11" (2.1 M) ARM
FRONT AND REAR INDEPENDENT OUTRIGGERS W/O CRADLE
ONE AND TWO WAY AUX. PIPING PLUS SLOPE/ROTATING PIPING TO END OF ARM
TWIN TIRES 10.0-20-16PR

OPTIONAL EQUIPMENT - Factory Installed (21)		Discount to apply 20%	
Option	CODE	Description	List Price
FENDER	SFD	Fender	2,075.00 USD
TIRE	10A	10.0-20-14PR	-300.00 USD
TIRE	18C	18.0-19.5-20PR	1,800.00 USD
CLAMSHELL PIPING	CLA	Clamshell	300.00 USD
LOCK VALVE	LBA	Boom & Arm Lock Valve	1,150.00 USD
LOCK VALVE	LOB	Boom Lock Valve	750.00 USD
HEATING & COOLING SEAT	HCS	Heating & Cooling Seat	750.00 USD
RAIN SHIELD	RAI	Rain Shield	175.00 USD
MICROPHONE	MIC	Microphone	1,000.00 USD
CAMERA	AVC	Around View Camera	4,300.00 USD
CAMERA	RVA	Rear View AVM Ready	75.00 USD
FOGS GUARD	FOG	FOGS	2,600.00 USD
CABIN FRONT GUARD	FUL	Upper and Lower GuarD	475.00 USD
CABIN FRONT GUARD	LOW	Lower Guard Only	275.00 USD
ADDITIONAL WORK LAMP	6LE	6 ADDITIONAL WORKING LAMP(LED)	1,425.00 USD
ADDITIONAL WORK LAMP	4LE	4 ADDITIONAL WORKING LAMP(LED)	1,125.00 USD
ROTATING BEACON	ROB	Rotating Beacon	200.00 USD
Water Separator	WIH	Water Separator with Heater	300.00 USD

AIR COMPRESSOR	ACO	Air Compressor	2,825.00 USD
FUEL FILLER PUMP	FIL	Fuel Filler Pump	375.00 USD
JOYSTICK STEERING	JST	JOYSTICK STEERING	3,575.00 USD

Attachments -	Dealer Installed (26)		
Attachment	Description	Approx. Weight	List Price
230104-03480	0.68 CU. YD. 36" HEAVY DUTY BUCKET (FACTORY BUCKET)	1,146.00	3,583.47 USD
230104-03510	0.41 CU. YD. 24" HEAVY DUTY BUCKET (FACTORY BUCKET)	882.00	3,017.33 USD
230104-03513	0.88 CU. YD. 42" HEAVY DUTY BUCKET (FACTORY BUCKET)	1,279.00	4,064.47 USD
AT140-060	*Non-Cancelable* 0.75 CU. YD. 60" ANGLE TILT DITCHING BUCKET (WITH BOLT-ON EDGE)	1,350.00	20,416.28 USD
DC140-048	0.63 CU. YD. 48" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	820.00	5,169.32 USD
DC140-060	0.80 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	985.00	5,998.10 USD
HD14-024	0.44 CU. YD. 24" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	901.00	5,670.45 USD
HD14-030	0.59 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,001.00	5,953.81 USD
HD14-036	0.75 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,129.00	6,454.99 USD
HD14-042	0.91 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,222.00	6,759.59 USD
HD14-048	1.06 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,338.00	7,352.71 USD
HDC140-060	1.38 CU. YD. 60" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	1,620.00	10,174.20 USD
HT-14DM3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	720.00	11,325.60 USD
HT-14DM4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	750.00	11,325.60 USD
HT-14QC3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	770.00	11,644.09 USD
HT-14QC4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	805.00	11,644.09 USD
PL-14DM3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1.00	14,837.23 USD
PL-14DM4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	1.00	14,837.23 USD
PL-14QC3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1.00	15,284.76 USD

PL-14QC4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1.00	17,781.67 USD
QC-65H1G3-317	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX140	404.00	7,414.26 USD
SD14-024	0.44 CU. YD. 24" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	931.00	7,915.29 USD
SD14-030	0.59 CU. YD. 30" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,035.00	7,540.53 USD
SD14-036	0.75 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,154.00	8,173.11 USD
SD14-042	0.91 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,248.00	8,540.89 USD
SD14-048	1.06 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,367.00	8,928.69 USD

STANDARD EQUIPMEN	IT FOR BASE MACHINE (6)
Item	Description
Engine	Doosan DL06P: Variable Geometry Turbo Charged Air to Air Intercooler Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with Diesel Exhaust Fluid 137 HP(ISO 14396)/102 kW Gross Flywheel Horsepower @ 2000 rpm 129 HP(SAE J1349)/96.3 kW Net @ 2000 rpm Displacement: 359cu.in., 6 Cylinder Bore 3.94" (100mm) Diameter x 4.92" (125mm) Stroke Torque: 593ft. Lbs (82 kgf-m) @ 1,400 rpm High Idle 1900 ± 50 rpm, Low Idle 800 ± 50 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control Engine Overheat and Low Oil Pressure Prevention System
Hydraulic, Transmission & Steering	Pilot Operated Control Valves, (10) Spools Main Pump: Tandem Variable Axial Piston Type, Flow: 2 x 44 gpm; Pressure Setting 4975 psi Pilot Circuit, Gear Type Pump; Flow: 7 gpm Swing Motor, Axial Piston Type driving a 2-stage planetary gearbox to maximize torque Swing Maximum Speed: 12 RPM Fine Swing Control Maximum Swing Torque 27,100 ft.lbs. Spring Set, Hydraulic-released Brakes Drive Train: A Bent Axial Pistion motor in combination with a 2 speed Power Shift Gear Box to deliver 17,860 pounds of force Maximum speed of 22 mph on the road; 6 mph off road and creeping speed of 2 mph Axle oscillation without fenders: +/- 8° Twin wheel 10.0-20-16PR Minimum turning radius of 21 feet One way/two way Auxiliary Hydraulics with 2-pump flow Smart Hydraulic Logic to prioritize flow to hydraulic attachments like a molcher or a grinder Working Mode for Tilt-Rotator
	Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets Door Locks Front Windshield Panto Wiper with Washer 8" Multi-function Color LCD 1966 1 Streen Monitor

Aerial, Side & Rear View Camera with dedicated LCD display Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration Audio Control Panel On/Off Switch, Control Volume, Channel Select Switches: **Engine Speed Control Dial** Jog Switch for monitor display control **Auxiliary Mode Switch** Engine Emergency Stop Switch Work Light Switch Travel Speed Selector Switch Breaker, Power-up, Shear Switch Engine After Treatment System Switch Wiper Control Panel Safety Lock Lever Ergonomic Leatherlike Operator Seat: Integrated Heater and Air Conditioner Cab Air Suspension with Seat Belt (2" Wide) Adjustable bottom cushion Lumbar Support Adjustment Adjustable Headrest Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Height Adjustable Panels Skylight Pull Up Type Front Window Removable Lower Front Window with Storage Behind Seat Sliding Side Windows Front Window Air Defroster Travel Pedals with Hand Levers **Emergency Exit Glass Breaking Tool** Fully insolated Lunch Box Compartment **Quick Coupler Switch** Joystick Lever with 3 Switches, Two Button and One Rotate Front and Rear Cup Holders Room Light Serial Communication Port for Laptop PC Interface (DMS) Viscous Cab Mounts with Spring reinforcement Sun Screens for Top Hatch, Front Windshield and Rear Window Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity Power Mode Select Button (P+,P,S,E) Work Mode Selector Button (Excavation, Lifting, Breaker and Shear) Electronic Power Optimizing System Cross Sensing Pump Control Machine Status Display with Integrated Self Diagnostics System Adjustable LCD Color Display Auto Idle Control System plus One Touch Deceleration Button on Joystick **Engine Speed Control Dial** Power Boost Control Button on Joystick Electrical/Electronic Control Limp Home Mode Control Switch Proximity Alarm Warning System (option) System Proportional control for auxiliary hydraulics via roll switch on both joysticks Adjustable Auxiliary Flow and Pressure up to 10 presets Alternator: 24 V, 80 amp Batteries: (2) 12 V, 150AmpH, 950CCA Starter: 24 V x 6 KW Engine Emergency Stop Switch Panto Wiper to cover the entire front windshield window LED Lights: Working Light (2) Machine, (2) Boom Smart Ignition Switch Key for remote control of engine start/stop and fdoor lock/unlock Electric Horn

Hour Meter

Main Warning Lamp

Warning Symbol Indicator for:

Battery, Engine oil pressur 2aQeo4aof 5verheated, Engine, Stop engine, Low fuel level, Hydraulic oil

temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, GSM antenna failure, Satelite antenna failure, Check machine, Stop engine

Digital Clock
Alarm Buzzer for:
Engine Oil Pressure
Coolant Temperature

Electronic Monitor for:

Display Monitor and Warnings

Engine Coolant Temperature Gauge

Fuel Gauge

Hydraulic Oil Temperature Gauge

DEF (AdBlue®) Level

Multi-function Touch Screen Display for:

Funcion Symbol Indicator (Power Boost, Auxiliary Hydraulic Pedal/Joystick Selector, Travel Speed,

Work Light, ISO/BHL Pattern Control, Fine Swing

Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth)

Favorite Button Indicator

Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info)

Main Information Indicator

Power Mode Selector Button Indicator (Power+, Power, Standard, Economy)

Travel Speed Indicator Power Mode Indicator

Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear)

Audio Display Auto Idle Indicator Menu Selector Button

Joystick Pattern Change Valve

Centralized Lube Points

Large Handrail

Steel Casted Lift Bracket integrated with Idler Linkage

Punched Metal Anti-slip Plates Engine Restart Prevention System Manuals, Parts and Operator's

Cab prepared with Vandalism Guard Hooks

GPS 3 Year Subscription

Page 5 of 5

Other

PACKAGE ARRANGEMENT (1) Disc		Discount to apply 25%
Product	Approx. Weight	List Price
DX140W-7-US40	17,000.00 KG	221,852.96 USD

DX140W-7 BASE MACHINE W/O BUCKET
16' 4" (5.0 M) ARTICULATED BOOM
6' 11" (2.1 M) ARM
FRONT DOZER BLADE AND INDEPENDENT REAR OUTRIGGERS
ONE AND TWO WAY AUX. PIPING PLUS SLOPE/ROTATING PIPING TO END OF ARM
TWIN TIRES 10.0-20-16PR

OPTIONAL EQUIPMENT - Factory Installed (23)			Discount to apply 20%
Option	CODE	Description	List Price
ARM	A25	2.5m Arm; Articulated	50.00 USD
FENDER	SFD	Fender	2,075.00 USD
TIRE	10A	10.0-20-14PR	-300.00 USD
TIRE	18C	18.0-19.5-20PR	1,800.00 USD
CLAMSHELL PIPING	CLA	Clamshell	300.00 USD
LOCK VALVE	LBA	Boom & Arm Lock Valve	1,150.00 USD
LOCK VALVE	LOB	Boom Lock Valve	750.00 USD
HEATING & COOLING SEAT	HCS	Heating & Cooling Seat	750.00 USD
RAIN SHIELD	RAI	Rain Shield	175.00 USD
MICROPHONE	MIC	Microphone	1,000.00 USD
CAMERA	AVB	Boom and Around View Camera	5,275.00 USD
CAMERA	AVC	Around View Camera	4,300.00 USD
CAMERA	RVA	Rear View AVM Ready	75.00 USD
FOGS GUARD	FOG	FOGS	2,600.00 USD
CABIN FRONT GUARD	FUL	Upper and Lower GuarD	475.00 USD
CABIN FRONT GUARD	LOW	Lower Guard Only	275.00 USD
ADDITIONAL WORK LAMP	6LE	6 ADDITIONAL WORKING LAMP(LED)	1,425.00 USD
ADDITIONAL WORK LAMP	4LE	4 ADDITIONAL WORKING LAMP(LED)	1,125.00 USD

ROTATING BEACON	ROB	Rotating Beacon	200.00 USD
Water Separator	WIH	Water Separator with Heater	300.00 USD
AIR COMPRESSOR	ACO	Air Compressor	2,825.00 USD
FUEL FILLER PUMP	FIL	Fuel Filler Pump	375.00 USD
JOYSTICK STEERING	JST	JOYSTICK STEERING	3,575.00 USD

Attachments -	Dealer Installed (26)		
Attachment	Description	Approx. Weight	List Price
230104-03480	0.68 CU. YD. 36" HEAVY DUTY BUCKET (FACTORY BUCKET)	1,146.00	3,583.47 USD
230104-03510	0.41 CU. YD. 24" HEAVY DUTY BUCKET (FACTORY BUCKET)	882.00	3,017.33 USD
230104-03513	0.88 CU. YD. 42" HEAVY DUTY BUCKET (FACTORY BUCKET)	1,279.00	4,064.47 USD
AT140-060	*Non-Cancelable* 0.75 CU. YD. 60" ANGLE TILT DITCHING BUCKET (WITH BOLT-ON EDGE)	1,350.00	20,416.28 USD
DC140-048	0.63 CU. YD. 48" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	820.00	5,169.32 USD
DC140-060	0.80 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	985.00	5,998.10 USD
HD14-024	0.44 CU. YD. 24" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	901.00	5,670.45 USD
HD14-030	0.59 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,001.00	5,953.81 USD
HD14-036	0.75 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,129.00	6,454.99 USD
HD14-042	0.91 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,222.00	6,759.59 USD
HD14-048	1.06 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,338.00	7,352.71 USD
HDC140-060	1.38 CU. YD. 60" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	1,620.00	10,174.20 USD
HT-14DM3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	720.00	11,325.60 USD
HT-14DM4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	750.00	11,325.60 USD
HT-14QC3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	770.00	11,644.09 USD
HT-14QC4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	805.00	11,644.09 USD
PL-14DM3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1.00	14,837.23 USD
PL-14DM4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET Page 2 of 5	1.00	14,837.23 USD

PL-14QC3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1.00	15,284.76 USD
PL-14QC4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1.00	17,781.67 USD
QC-65H1G3-317	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX140	404.00	7,414.26 USD
SD14-024	0.44 CU. YD. 24" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	931.00	7,915.29 USD
SD14-030	0.59 CU. YD. 30" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,035.00	7,540.53 USD
SD14-036	0.75 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,154.00	8,173.11 USD
SD14-042	0.91 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,248.00	8,540.89 USD
SD14-048	1.06 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,367.00	8,928.69 USD
L			

STANDARD EQUIPMEN	STANDARD EQUIPMENT FOR BASE MACHINE (6)		
Item	Description		
Engine	Doosan DL06P: Variable Geometry Turbo Charged Air to Air Intercooler Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with Diesel Exhaust Fluid 137 HP(ISO 14396)/102 kW Gross Flywheel Horsepower @ 2000 rpm 129 HP(SAE J1349)/96.3 kW Net @ 2000 rpm Displacement: 359cu.in., 6 Cylinder Bore 3.94" (100mm) Diameter x 4.92" (125mm) Stroke Torque: 593ft. Lbs (82 kgf-m) @ 1,400 rpm High Idle 1900 ± 50 rpm, Low Idle 800 ± 50 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control Engine Overheat and Low Oil Pressure Prevention System		
Hydraulic, Transmission & Steering	Pilot Operated Control Valves, (10) Spools Main Pump: Tandem Variable Axial Piston Type, Flow: 2 x 44 gpm; Pressure Setting 4975 psi Pilot Circuit, Gear Type Pump; Flow: 7 gpm Swing Motor, Axial Piston Type driving a 2-stage planetary gearbox to maximize torque Swing Maximum Speed: 12 RPM Fine Swing Control Maximum Swing Torque 27,100 ft.lbs. Spring Set, Hydraulic-released Brakes Drive Train: A Bent Axial Pistion motor in combination with a 2 speed Power Shift Gear Box to deliver 17,860 pounds of force Maximum speed of 22 mph on the road; 6 mph off road and creeping speed of 2 mph Axle oscillation without fenders: +/- 8° Twin wheel 10.0-20-16PR Minimum turning radius of 21 feet One way/two way Auxiliary Hydraulics with 2-pump flow Smart Hydraulic Logic to prioritize flow to hydraulic attachments like a molcher or a grinder Working Mode for Tilt-Rotator		
	Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Sockets 2 of 5		

Door Locks

Front Windshield Panto Wiper with Washer

8" Multi-function Color LCD Touch Screen Monitor

Aerial, Side & Rear View Camera with dedicated LCD display

Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration

Audio Control Panel On/Off Switch, Control Volume, Channel Select

Switches:

Engine Speed Control Dial

Jog Switch for monitor display control

Auxiliary Mode Switch

Engine Emergency Stop Switch

Work Light Switch

Travel Speed Selector Switch Breaker, Power-up, Shear Switch Engine After Treatment System Switch

Wiper Control Panel

Safety Lock Lever

Ergonomic Leatherlike Operator Seat: Integrated Heater and Air Conditioner Air Suspension with Seat Belt (2" Wide)

Adjustable bottom cushion Lumbar Support Adjustment

Adjustable Headrest

Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Height Adjustable Panels

Skylight

Pull Up Type Front Window

Removable Lower Front Window with Storage Behind Seat

Sliding Side Windows
Front Window Air Defroster
Travel Pedals with Hand Levers
Emergency Exit Glass Breaking Tool
Fully insolated Lunch Box Compartment

Quick Coupler Switch

Joystick Lever with 3 Switches, Two Button and One Rotate

Front and Rear Cup Holders

Room Light

Serial Communication Port for Laptop PC Interface (DMS)

Viscous Cab Mounts with Spring reinforcement

Sun Screens for Top Hatch, Front Windshield and Rear Window

Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity

Power Mode Select Button (P+,P,S,E)

Work Mode Selector Button (Excavation, Lifting, Breaker and Shear)

Electronic Power Optimizing System
Cross Sensing Pump Control

Machine Status Display with Integrated Self Diagnostics System

Adjustable LCD Color Display

Auto Idle Control System plus One Touch Deceleration Button on Joystick

Engine Speed Control Dial

Power Boost Control Button on Joystick Limp Home Mode Control Switch

Proximity Alarm Warning System (option)
Proportional control for auxiliary hydraulics via roll switch on both joysticks

Adjustable Auxiliary Flow and Pressure up to 10 presets

Alternator: 24 V, 80 amp

Batteries: (2) 12 V, 150AmpH, 950CCA

Starter: 24 V x 6 KW

Engine Emergency Stop Switch

Panto Wiper to cover the entire front windshield window LED Lights: Working Light (2) Machine, (2) Boom

Smart Ignition Switch Key for remote control of engine start/stop and fdoor lock/unlock

Electric Horn Hour Meter

Page 4 of 5

Cab

Electrical/Electronic Control

System

Display Monitor and Warnings

Main Warning Lamp

Warning Symbol Indicator for:

Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, GSM antenna failure, Satelite antenna failure, Check machine, Stop engine

Digital Clock

Alarm Buzzer for:

Engine Oil Pressure Coolant Temperature

Electronic Monitor for:

Engine Coolant Temperature Gauge

Fuel Gauge

Hydraulic Oil Temperature Gauge

DEF (AdBlue®) Level

Multi-function Touch Screen Display for:

Funcion Symbol Indicator (Power Boost, Auxiliary Hydraulic Pedal/Joystick Selector, Travel Speed, Work Light, ISO/BHL Pattern Control, Fine Swing

Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth)

Favorite Button Indicator

Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info)

Main Information Indicator

Power Mode Selector Button Indicator (Power+, Power, Standard, Economy)

Travel Speed Indicator Power Mode Indicator

Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear)

Audio Display
Auto Idle Indicator
Menu Selector Button

Joystick Pattern Change Valve

Centralized Lube Points

Large Handrail

Steel Casted Lift Bracket integrated with Idler Linkage

Punched Metal Anti-slip Plates Engine Restart Prevention System Manuals, Parts and Operator's

Cab prepared with Vandalism Guard Hooks

GPS 3 Year Subscription

Other

Page 5 of 5

PACKAGE ARRANGEMENT (1)		Discount to apply 25%
Product	Approx. Weight	List Price
DX140W-7-US50	17,000.00 KG	223,931.08 USD

DX140W-7 BASE MACHINE W/O BUCKET
16' 4" (5.0 M) ARTICULATED BOOM
6' 11" (2.1 M) ARM
FRONT AND REAR INDEPENDENT OUTRIGGERS W/O CRADLE
ONE AND TWO WAY AUX. PIPING PLUS SLOPE/ROTATING PIPING TO END OF ARM
TWIN TIRES 10.0-20-16PR

OPTIONAL EQUIPMENT - Factory Installed (23)		Discount to apply 20%	
Option	CODE	Description	List Price
ARM	A25	2.5m Arm; Articulated	50.00 USD
FENDER	SFD	Fender	2,075.00 USD
TIRE	10A	10.0-20-14PR	-300.00 USD
TIRE	18C	18.0-19.5-20PR	1,800.00 USD
CLAMSHELL PIPING	CLA	Clamshell	300.00 USD
LOCK VALVE	LBA	Boom & Arm Lock Valve	1,150.00 USD
LOCK VALVE	LOB	Boom Lock Valve	750.00 USD
HEATING & COOLING SEAT	HCS	Heating & Cooling Seat	750.00 USD
RAIN SHIELD	RAI	Rain Shield	175.00 USD
MICROPHONE	MIC	Microphone	1,000.00 USD
CAMERA	AVB	Boom and Around View Camera	5,275.00 USD
CAMERA	AVC	Around View Camera	4,300.00 USD
CAMERA	RVA	Rear View AVM Ready	75.00 USD
FOGS GUARD	FOG	FOGS	2,600.00 USD
CABIN FRONT GUARD	FUL	Upper and Lower GuarD	475.00 USD
CABIN FRONT GUARD	LOW	Lower Guard Only	275.00 USD
ADDITIONAL WORK LAMP	6LE	6 ADDITIONAL WORKING LAMP(LED)	1,425.00 USD
ADDITIONAL WORK LAMP	4LE	4 ADDITIONAL WORKING LAMP(LED)	1,125.00 USD

ROTATING BEACON	ROB	Rotating Beacon	200.00 USD
Water Separator	WIH	Water Separator with Heater	300.00 USD
AIR COMPRESSOR	ACO	Air Compressor	2,825.00 USD
FUEL FILLER PUMP	FIL	Fuel Filler Pump	375.00 USD
JOYSTICK STEERING	JST	JOYSTICK STEERING	3,575.00 USD

Attachments -	Dealer Installed (26)		
Attachment	Description	Approx. Weight	List Price
230104-03480	0.68 CU. YD. 36" HEAVY DUTY BUCKET (FACTORY BUCKET)	1,146.00	3,583.47 USD
230104-03510	0.41 CU. YD. 24" HEAVY DUTY BUCKET (FACTORY BUCKET)	882.00	3,017.33 USD
230104-03513	0.88 CU. YD. 42" HEAVY DUTY BUCKET (FACTORY BUCKET)	1,279.00	4,064.47 USD
AT140-060	*Non-Cancelable* 0.75 CU. YD. 60" ANGLE TILT DITCHING BUCKET (WITH BOLT-ON EDGE)	1,350.00	20,416.28 USD
DC140-048	0.63 CU. YD. 48" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	820.00	5,169.32 USD
DC140-060	0.80 CU. YD. 60" DITCH CLEANING BUCKET (WITH BOLT-ON EDGE)	985.00	5,998.10 USD
HD14-024	0.44 CU. YD. 24" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	901.00	5,670.45 USD
HD14-030	0.59 CU. YD. 30" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,001.00	5,953.81 USD
HD14-036	0.75 CU. YD. 36" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,129.00	6,454.99 USD
HD14-042	0.91 CU. YD. 42" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,222.00	6,759.59 USD
HD14-048	1.06 CU. YD. 48" HEAVY DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,338.00	7,352.71 USD
HDC140-060	1.38 CU. YD. 60" HD DITCH CLEAN UP BUCKET (WITH BOLT-ON EDGE)	1,620.00	10,174.20 USD
HT-14DM3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	720.00	11,325.60 USD
HT-14DM4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET	750.00	11,325.60 USD
HT-14QC3T-A	HYD. MAIN PIN THUMB; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	770.00	11,644.09 USD
HT-14QC4T-A	HYD. MAIN PIN THUMB; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	805.00	11,644.09 USD
PL-14DM3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH BUCKET	1.00	14,837.23 USD
PL-14DM4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH BUCKET Page 2 of 5	1.00	14,837.23 USD

PL-14QC3T	PRO LINK THUMB; HYDRAULIC; 3 TINE; FOR 30"; 48" BUCKET; USED WITH COUPLER	1.00	15,284.76 USD
PL-14QC4T	PRO LINK THUMB; HYDRAULIC; 4 TINE; FOR 36"; 42" BUCKET; USED WITH COUPLER	1.00	17,781.67 USD
QC-65H1G3-317	HYD. QUICK COUPLER (INCLUDES SOFT PINS, JUMPER HOSE ONLY) FOR DX140	404.00	7,414.26 USD
SD14-024	0.44 CU. YD. 24" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	931.00	7,915.29 USD
SD14-030	0.59 CU. YD. 30" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,035.00	7,540.53 USD
SD14-036	0.75 CU. YD. 36" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,154.00	8,173.11 USD
SD14-042	0.91 CU. YD. 42" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,248.00	8,540.89 USD
SD14-048	1.06 CU. YD. 48" SEVERE DUTY BUCKET (INCLUDES WEAR SHROUDS)	1,367.00	8,928.69 USD
L			

STANDARD EQUIPMENT FOR BASE MACHINE (6)		
Item	Description	
Engine	Doosan DL06P: Variable Geometry Turbo Charged Air to Air Intercooler Electronically Controlled Common Rail Direct Injected T4: Cooled Exhaust Gas Recirculation + Diesel Oxidation Catalyst + Selective Catalytic Reduction with Diesel Exhaust Fluid 137 HP(ISO 14396)/102 kW Gross Flywheel Horsepower @ 2000 rpm 129 HP(SAE J1349)/96.3 kW Net @ 2000 rpm Displacement: 359cu.in., 6 Cylinder Bore 3.94" (100mm) Diameter x 4.92" (125mm) Stroke Torque: 593ft. Lbs (82 kgf-m) @ 1,400 rpm High Idle 1900 ± 50 rpm, Low Idle 800 ± 50 rpm Auto Idle System Auto Shut Down Equipped with the Fuel Pre-filter with Water Separator Radiator Reserve Tank Large Capacity Double Element Air Cleaner with Evacuate Electronic Engine Speed Control Engine Overheat and Low Oil Pressure Prevention System	
Hydraulic, Transmission & Steering	Pilot Operated Control Valves, (10) Spools Main Pump: Tandem Variable Axial Piston Type, Flow: 2 x 44 gpm; Pressure Setting 4975 psi Pilot Circuit, Gear Type Pump; Flow: 7 gpm Swing Motor, Axial Piston Type driving a 2-stage planetary gearbox to maximize torque Swing Maximum Speed: 12 RPM Fine Swing Control Maximum Swing Torque 27,100 ft.lbs. Spring Set, Hydraulic-released Brakes Drive Train: A Bent Axial Pistion motor in combination with a 2 speed Power Shift Gear Box to deliver 17,860 pounds of force Maximum speed of 22 mph on the road; 6 mph off road and creeping speed of 2 mph Axle oscillation without fenders: +/- 8° Twin wheel 10.0-20-16PR Minimum turning radius of 21 feet One way/two way Auxiliary Hydraulics with 2-pump flow Smart Hydraulic Logic to prioritize flow to hydraulic attachments like a molcher or a grinder Working Mode for Tilt-Rotator	
	Steel, All Weather Sound Suppressed ROPS Type Fully Automatic Heater and Air Conditioner with Radian Energy Photo Sensor 12V and 24V Power Socketsage 3 of 5	

Door Locks

Front Windshield Panto Wiper with Washer

8" Multi-function Color LCD Touch Screen Monitor

Aerial, Side & Rear View Camera with dedicated LCD display

Digital Blutetooth Audio Broadcasting MP3 Radio with Cell Phone integration

Audio Control Panel On/Off Switch, Control Volume, Channel Select

Switches:

Engine Speed Control Dial

Jog Switch for monitor display control

Auxiliary Mode Switch

Engine Emergency Stop Switch

Work Light Switch

Travel Speed Selector Switch Breaker, Power-up, Shear Switch Engine After Treatment System Switch

Wiper Control Panel

Safety Lock Lever

Ergonomic Leatherlike Operator Seat: Integrated Heater and Air Conditioner Air Suspension with Seat Belt (2" Wide)

Adjustable bottom cushion Lumbar Support Adjustment

Adjustable Headrest

Reclining, Height Adjustable Adjustable Arm Rests Sliding Control Console Height Adjustable Panels

Skylight

Pull Up Type Front Window

Removable Lower Front Window with Storage Behind Seat

Sliding Side Windows
Front Window Air Defroster
Travel Pedals with Hand Levers
Emergency Exit Glass Breaking Tool
Fully insolated Lunch Box Compartment

Quick Coupler Switch

Joystick Lever with 3 Switches, Two Button and One Rotate

Front and Rear Cup Holders

Room Light

Serial Communication Port for Laptop PC Interface (DMS)

Viscous Cab Mounts with Spring reinforcement

Sun Screens for Top Hatch, Front Windshield and Rear Window

Advanced Mechatronics with Power Mode Control System to maximize machine efficiency and productivity

Power Mode Select Button (P+,P,S,E)

Work Mode Selector Button (Excavation, Lifting, Breaker and Shear)

Electronic Power Optimizing System
Cross Sensing Pump Control

Machine Status Display with Integrated Self Diagnostics System

Adjustable LCD Color Display

Auto Idle Control System plus One Touch Deceleration Button on Joystick

Engine Speed Control Dial

Power Boost Control Button on Joystick Limp Home Mode Control Switch

Proximity Alarm Warning System (option)
Proportional control for auxiliary hydraulics via roll switch on both joysticks

Adjustable Auxiliary Flow and Pressure up to 10 presets

Alternator: 24 V, 80 amp

Batteries: (2) 12 V, 150AmpH, 950CCA

Starter: 24 V x 6 KW

Engine Emergency Stop Switch

Panto Wiper to cover the entire front windshield window LED Lights: Working Light (2) Machine, (2) Boom

Smart Ignition Switch Key for remote control of engine start/stop and fdoor lock/unlock

Electric Horn Hour Meter

Page 4 of 5

Cab

Electrical/Electronic Control

System

Display Monitor and Warnings

Main Warning Lamp

Warning Symbol Indicator for:

Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil temp, Fuel System, Air cleaner clogged, Machine lift overload, Quick Coupler, Regen request, Low DEF level, Problem in SCR, VBO angle sensor failure, VBO joystick pressure sensor failure, EPPR valve failure, AGS, clogged Fuel filter, Ultrasonic sensor, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, No smart key, Failed to detect smart key, Low battery smart key, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, GSM antenna failure, Satelite antenna failure, Check machine, Stop engine

Digital Clock

Alarm Buzzer for:

Engine Oil Pressure Coolant Temperature

Electronic Monitor for:

Engine Coolant Temperature Gauge

Fuel Gauge

Hydraulic Oil Temperature Gauge

DEF (AdBlue®) Level

Multi-function Touch Screen Display for:

Funcion Symbol Indicator (Power Boost, Auxiliary Hydraulic Pedal/Joystick Selector, Travel Speed, Work Light, ISO/BHL Pattern Control, Fine Swing

Indicator Display (USB, Auto Shutdown, ACC, Auto Warm Up, Joystic One-touch, VBO Limp Home Mode, Engine Preheat, EPOS/ECU/EPOS-ECU, Reverse Fan On, Mirror Heater, Bluetooth)

Favorite Button Indicator

Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info)

Main Information Indicator

Power Mode Selector Button Indicator (Power+, Power, Standard, Economy)

Travel Speed Indicator Power Mode Indicator

Auxiliary Hydraulics Selector Button (Unidirectional-Hammer or Bi-directional-Shear)

Audio Display
Auto Idle Indicator
Menu Selector Button

Joystick Pattern Change Valve

Centralized Lube Points

Large Handrail

Steel Casted Lift Bracket integrated with Idler Linkage

Punched Metal Anti-slip Plates Engine Restart Prevention System Manuals, Parts and Operator's

Cab prepared with Vandalism Guard Hooks

GPS 3 Year Subscription

Other

Page 5 of 5