

PACKAGE ARRANGEMENT (1)		
Product	Approx. Weight	List Price
DD100-US10	10,280.00 KG	166,859.07 USD
DD100 BASE MACHINE WITH XL TRACK 2.8 CUBIC YARD BLADE CAPACITY (SAE) 8' 11" BLADE WIDTH 20" GROUSER WIDTH INCLUDES RIPPER PIPPING		

OPTIONAL EQUIPMENT - Factory Installed (9)			
Option	CODE	Description	List Price
SMART MG/MC READY KIT	TRB	TRIMBLE READY KIT	57.71 USD
SMART CONTROL SYSTEM	DAC	DOZING ASSIST CONTROL SYSTEM (2D)	2,206.15 USD
ALARM	ALL	ALARM FOR ALL	65.40 USD
FIRE EXTINGUISHER AND HELMET	OFB	FIRE EXTINGUISHER BRACKET ONLY	19.24 USD
ADDITIONAL WORK LAMP	2LE	2 ADDITIONAL WORKING LAMP (LED)	550.10 USD
ROTATING BEACON	ROB	ROTATING BEACON	128.87 USD
TRACK GUARD	FUL	FULL TRACK GUARD	1,540.64 USD
REAR ATTACHMENT	RIP	RIPPER	7,699.39 USD
REAR ATTACHMENT	TDB	TOWING DRAW BAR	423.15 USD

Attachments - Dealer Installed			
Attachment	Description	Approx. Weight	List Price

STANDARD EQUIPMENT FOR BASE MACHINE (7)	
Item	Description
ENGINE	ENGINE SUFFIX: G2 DM03-LED00 ENGINE NAME: D34 TIER4 FINAL 122 HP @ 2200 rpm (SAE J1995, GROSS) 530 N.m @ 1,400 rpm VARIABLE GEOMETRY TURBOCHARGER COMMON RAIL DIRECT INJECTION DISPLACEMENT : 3,409 cc, 4 CYLINDER BORE DIA. & STROKE : 130mm x 140mm

	<p>AFTERTREATMENT: DOC+SCR HIGH IDLE SPEED : 2,300 rpm LOW IDLE SPEED : 900 rpm</p>
HYDRAULIC	<p>ELECTRICALLY CONTROLLED MAIN CONTROL VALVES, (4) SPOOLS MAIN PUMP: VARIABLE DISPLACEMENT AXIAL PISTON PUMP 103.5 LPM, 250 BAR FAN PUMP: FIXED DISPLACEMENT GEAR PUMP 61.4 LPM TRAVEL PUMP: SWASH PLATE, AXIAL PISTON, 2 X 149 LPM TRAVEL MOTOR: 2 X 288 LPM TRAVEL SPEED: 9 KPH TRACTION FORCE: 16 TON</p>
CAB	<p>ROPS CERTIFIED FULLY AUTOMATIC HEATER AND AIR CONDITIONER 12V POWER SOCKETS AND USB CHARGER FRONT, REAR, LEFT/RIGHT WIPER WITH WASHER 8" MULTI-FUNCTION COLOR LCD TOUCH SCREEN MONITOR REAR VIEW CAMERA BLUETOOTH AUDIO BROADCASTING WITH CELL PHONE INTEGRATION SWITCHES: ENGINE SPEED CONTROL DIAL ENGINE EMERGENCY START SWITCH ENGINE EMERGENCY STOP SWITCH ENGINE AFTER TREATMENT SYSTEM SWITCH ERGONOMIC OPERATOR SEAT: HEATED SEAT EMERGENCY EXIT GLASS BREAKING TOOL</p>
Electrical/Electronic Control System	<p>Machine Status Display with Integrated Self Diagnostics System Adjustable LCD Color Display Engine Speed Control Dial Alternator: 24 V, 80 amp Batteries: (2) 12 V, 150AH, 950CCA Starter: 24 V x 5 kW Electric Horn Hour Meter</p>
Display Monitor and Warnings	<p>Main Warning Lamp Warning Symbol Indicator for: Battery, Engine oil pressure, Coolant overheated, Engine, Stop engine, Low fuel level, Hydraulic oil temp, Fuel System, Air cleaner clogged, Regen request, Low DEF level, Problem in SCR, Clogged Fuel filter,, Engine RPM and starting restriction or TMS failure, Coolant level, Seat belt, DEF pressure, Hydraulic return filter clogged, Regen prohibited, Regeneration active, Manual regen, GPS antenna failure, Check machine, Stop engine Digital Clock Alarm Buzzer for: Engine Oil Pressure Coolant Temperature Electronic Monitor for: Engine Coolant Temperature Gauge Fuel Gauge Hydraulic Oil Temperature Gauge DEF (AdBlue®) Level Multi-function Touch Screen Display for: Function Symbol Indicator Indicator Display (USB, Auto Shutdown, Reverse Fan On, Bluetooth) Main Information Selector Button (Reset Trip, Trip Info, Soot Level, PM Service Info) Main Information Indicator Audio Display Auto Idle Indicator Menu Selector Button</p>
Undercarriage	<p>SEALED AND LUBRICATED TYPE LINKAGE Track Rollers: (1) Upper, (7) Lower Each Side SINGLE GROUSER SHOES, 40 EACH SIDE</p>
Other	<p>GPS 3 Year Subscription</p>