

PACKAGE ARRANGEMENT (1)		
Product	Approx. Weight	List Price
DL320-7-US10	19,727.00 KG	269,126.21 USD
DL320-7-US10 Base Machine With Standard Front Differentials - Limited Slip Different Without Bucket Steel Cab with Integrated ROPS/F0 Tires: 23.5R25,L3, Triangle Air Suspension Seat Thumb Wheel Joystick Transmission: 4F / 3R Torque Con Transparent Bucket Technology Rear view camera 3.0 Telematics Radio	ial Front / Rear DPS	

OPTIONAL EQUIPMENT	- Factory Insta	alled (18)	
Option	CODE	Description	List Price
ADDITIONAL COUNTERWEIGHT	400	882LB ADDITIONAL COUNTERWEIGHT	3,005.95 USD
CABIN HANDRAIL(TOP)	HDR	CABIN TOP HANDRAIL	514.56 USD
ENGINE COOLANT HEATER	110	110V PLUG HEATER	514.56 USD
EMERGENCY STEER	ESS	EMERGENCY STEER / SECONDARY STEERING	2,117.12 USD
LOAD ISOLATION SYSTEM	LIH	HYDRAULIC LOAD ISOLATION SYSTEM	4,505.60 USD
Additional Brake Pedal	ABP	ADDITIONAL BRAKE PEDAL	99.84 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	2,803.20 USD
MIRROR	ADE	ADJUSTABLE MIRROR, REMOTE ELECTRIC	1,886.72 USD
NOISE KIT	NOF	NOISE KIT WITH FRONT	1,774.08 USD
Weighing System	WEI	DOOSAN INTEGRATED WEIGHING SYSTEM	1,344.00 USD
HEAD LAMP	LED	WORK LIGHTS 2 FRONT	399.36 USD
HEAD LAMP	4L4	WORK LIGHTS 4 FRONT AND 4 REAR	925.00 USD
HEAD LAMP	6L6	WORK LIGHTS 6 FRONT AND 6 REAR	1,497.50 USD
ROOF COVER	RFC	CAB ROOF COVER	1,144.32 USD
ROTATING BEACON	ROB	ROTATING BEACON	171.52 USD





CAMERA	AVC	AROUND VIEW CAMERA W/BACKUP SENSOR	2,565.00 USD
FENDER	FUL	REAR FULL FNDR W/FNT FNDR, FNT FNDR HAS MUD GUARD AND RUBBER PROTECTOR	3,320.32 USD
FENDER	RPF	STEEL FRONT FENDER W/RUBBER PROTECTOR	972.80 USD

Attachments - Dealer Installed (22)			
Attachment	Description	Approx. Weight	List Price
186-1760D	AUTO LUBRICATON SYSTEM	0.00	6,807.84 USD
7203954	PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE; 72 IN. TINE LENGTH	2,891.00	16,746.74 USD
225063	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 72 IN. TINE LENGTH	2,830.00	15,224.30 USD
235385	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 96 IN. TINE LENGTH	3,112.00	19,183.20 USD
7235387	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 84 IN. TINE LENGTH	2,969.00	17,965.48 USD
7235389	PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE; 96 IN. TINE LENGTH	3,171.00	21,101.53 USD
7235391	PALLET FORKS - JRB QC; 106IN WIDE CARRIAGE; 84IN TINE LENGTH	3,028.00	19,762.03 USD
7273853	GPBKT; 114IN 4.0YD; JRB QC; BOCE	3,299.00	17,945.14 USD
7273854	GPBKT; 114IN 4.0YD; JRB QC; BOT	3,519.00	21,108.37 USD
7273855	GPBKT; 114IN 4.0YD; ISO QC; BOCE	3,328.00	17,945.14 USD
7273856	GPBKT; 114IN 4.0YD; ISO QC; BOT	3,550.00	17,365.88 USD
7273889	GPBKT; 120IN 4.5YD; PIN ON; BOCE	3,784.00	19,915.79 USD
7273890	GPBKT; 120IN 4.5YD; PIN ON; BOT	3,970.00	23,079.06 USD
7273891	GPBKT; 120IN 4.5YD; JRB QC; BOCE	3,506.00	18,919.38 USD
7273892	GPBKT; 120IN 4.5YD; JRB QC; BOT	3,691.00	22,082.65 USD
7273893	GPBKT; 120IN 4.5YD; ISO QC; BOCE	3,497.00	18,919.38 USD
7273894	GPBKT; 120IN 4.5YD; ISO QC; BOT	3,682.00	18,068.72 USD
7389868	GRAPPLE BKT; 120IN 3.50YD; JRB QC; BOCE	4,947.00	27,954.25 USD
7389869	GRAPPLE BKT; 120IN 3.50YD; ISO QC; BOCE	4,924.00	21,617.96 USD
389870	GRAPPLE BKT; 120IN 3.75YD; PIN ON; BOCE	5,368.00	23,779.75 USD



DEVELON

QC-DL0007

QC-DL0008

QUICK COUPLER, JRB 418 STYLE (Standard Lift)

QUICK COUPLER, ISO STYLE (Standard Lift)

1,233.00

1,445.00

12,000.00 USD

11,065.00 USD

STANDARD EQUIPMENT FOR BASE MACHINE (12) Item Description Doosan DL08: Turbo Charged, Air to Air Intercooled, T4 Electronically Controlled Common Rail Direct Injected 446 cu.in., 6 Cylinder 271 SAE Gross Flywheel Horsepower @ 1,800 RPM ENGINE: Air Cleaner: Dry Type (Double Stage) Engine Self Diagnostic System Reversible Fan Driven by Hydraulic Fan Motor Auto Idle Variable Displacement Axial Piston Pump Closed-Center (LS) Hydraulic Systems with Variable Pumps, Pilot Control with Float Spool, 2 Spools 3rd Valve with Lines & Control (lines terminate at boom base) HYDRAULIC SYSTEM: Automatic Boom / Lift - Kick-Out (Set and Adjust from inside the cab) Automatic Return-to-Dig Position (Adjustable Electro-Magnetic) Accumulator for Emergency Pilot System Dual Pedal Braking system 4 Wheel Outboard Wet Disc Brakes with Separate Front & Rear Circuits Accumulator for Emergency Stopping Parking Brake: Spring Apply Hydraulic Release, sliding caliper disc brake on the face of the BRAKE SYSTEM: transmission Heavy Duty Brakes, Increase brake force 6 Disc Wet Load Sensing Type with a Flow Amplifier and a Priority Valve 40 Degree Articulation, Full Hydraulic Power Steering Steering Cylinder Cushion Valve STEERING: Tilt and Telescopic Steering Wheel Electric Joystick Steering US50 / US51 Air Conditioner Heater & Defroster Double Filtered Air Cab **Combination Lever Rear View Camera** Accelerator Pedal Transmission Lever Rear Hinged & Locking Doors (Both sides) / Right side is emergency access door Switches: Transmission Shift Switch (Manual, Auto 1-4 and Auto 2-4) Economy Mode Switch (Power, Normal & Economy Modes) Headlight Switch Front Work Light Switch Rear Work Light Switch Rear Wiper Switch CAB ROPS/FOPS Pilot Cutoff Switch Parking Brake Switch Transmission Cutoff Switch Mirror Heater Switch **Reverse Fan Switch Display Screen Control Switch Display Screen Selector Switch** Hazard Warning Light Switch Boom Kick Out Switch Side View Mirrors with Heat Tintod Page 3 of 5

	Fully Adjustable Air Suspension Seat with Heat
	Seat Belt (2 Wide)
	Sliding Door Windows (Left Side)
TRANSMISSION / AXLES:	Full Automatic Power Shift 4 Forward & 3 Reverse Speeds, with Torque Converter; US10, US11, US20, US21 5 Forward & 3 Reverse Speeds, with Lock Up Torque Converter; US50, US51 Differentials - US10 / US20 / US50 = Limited slip front and rear Differentials - US11 / US21 / US51, Hydraulic locking front with open rear Self Adjusting Brake Disc Clearance Torque Converter, Fixed Wheel Stator Electrical T/M Clutch Disconnect with Service Brake T/M Down Shift on Shift Control and Joy Stick Control Transmission Oil Level Gauge
ELECTRICAL:	Alternator, 80 Amp., 28 Volt Batteries, (2) 12 Volt, 200 Amp, 1300 CCA Starter, 24 Volt 6 KW Horn Key Fob; Entry and starting Lights: (2) Front Headlights with High / Low Beams (2) Stop Lights. Tail Lights & Directional Indicators (2) Front Floodlights (LED) (4) Rear Floodlights (2 roof mounted, 2 mounted in rear grill Alarm Buzzer for: Transmission Overheat Engine Oil Pressure Coolant Temperature Electronic Monitoring & Display for: Fuel Level Gauge Engine Coolant Temperature Gauge Transmission Ott Temperature Gauge Transmission Ott Temperature Gauge Transmission Ott Temperature Gauge Transmission Actual Gear Transmission Actual Gear Transmission Actual Gear Transmission Gear Select Preheat Indicator Light Air Cleaner Warning Light Multi Function Gauge Total Time of Operation Left Tum Signal Right Tum Signal Right Tum Signal Hazard Warning Light Mirror Heater Light Brake Fuid Pressure Warning Engine Oil Pressure Warning Engine Oil Pressure Warning Engine Warning Water in Fuel Warnings DEF Low Level Warning SCR Failure Warning Back-Up Alarm
TIRES:	23.5R25,L3,Triangle
	Single Lever Control with FRADE Hattons





OTHER STANDARD EQUIPMENT:	Air Cleaner with Pre-cleaner Engine Side Covers Boom / Float Drawbar and Pin Neutral Safety Start System Muffler Fenders, Front & Rear Ladders & Service Platforms Manuals, Parts & Operator's Remote Drain Ports	
OPERATING WEIGHT:	41,502 lbs	
AUTO LUBE/GREASE SYSTEM (NOT STANDARD EQUIPMENT)	Auto Lube (SKF / Lincoln): Listed under Dealer Installed Options, price is the kit only (186-1760D) Installation Options: 1. By your dealership, install video included. Install cost, based on your labor rate. First time install should take about 2 days. Once familiar with install, about a day 2. At NACUP (Savannah), by our SKF vendor, Air and Hydraulics (AHE), \$2,200-\$2800 Kit comes with pump bracket but modification is required, for factory fit, order pump bracket and front valve bracket from parts. Part #'s are as follows 110406-07214A Pump Bracket 1 ea 110406-05501 Front Valve Bracket 1 ea \$05090666 Bolt 4 ea \$05090666 Bolt 4 ea \$0508166 Bolt 4 ea \$2	
LOADRITE SCALE SYSTEM (NOT STANDARD EQUIPMENT)	Loadrite Scales: Order is placed through Doosan PO cut to Loadrite. Loadrite will coordinate with your dealership for installation. Install will be done at your dealership or at customer location. Price is inclusive of Install, Calibration and Customer training. Warranty is covered by Loadrite	