

PACKAGE ARRANGEMENT (1)			
Product	Approx. Weight	List Price	
DL380-7-US10	20,349.00 KG	297,369.66 USD	
DL380-7-US10 Base Machine With Standard Front Differentials - Limited Slip Different Without Bucket Steel Cab with Integrated ROPS/F0 Tires: 23.5R25,L3, Triangle Air Suspension Seat Thumb Wheel Joystick Transmission: 4F / 3R Torque Cor Transparent Bucket Technology Rear View Camera 3.0 Telematics Radio	ial Front / Rear OPS		

OPTIONAL EQUIPMENT	- Factory Insta	alled (18)	
Option	CODE	Description	List Price
ADDITIONAL COUNTERWEIGHT	400	882LB ADDITIONAL COUNTERWEIGHT	3,005.95 USD
CABIN HANDRAIL(TOP)	HDR	CABIN TOP HANDRAIL	514.56 USD
ENGINE COOLANT HEATER	110	110V PLUG HEATER	514.56 USD
EMERGENCY STEER	ESS	EMERGENCY STEER / SECONDARY STEERING	2,117.12 USD
LOAD ISOLATION SYSTEM	LIH	HYDRAULIC LOAD ISOLATION SYSTEM	4,505.60 USD
Additional Brake Pedal	ABP	ADDITIONAL BRAKE PEDAL	99.84 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	2,803.20 USD
MIRROR	ADE	ADJUSTABLE MIRROR, REMOTE ELECTRIC	1,886.72 USD
NOISE KIT	NOF	NOISE KIT WITH FRONT	1,774.08 USD
Weighing System	WEI	DOOSAN INTEGRATED WEIGHING SYSTEM	1,344.00 USD
HEAD LAMP	LED	WORK LIGHTS 2 FRONT	399.36 USD
HEAD LAMP	4L4	WORK LIGHTS 4 FRONT AND 4 REAR	925.00 USD
HEAD LAMP	6L6	WORK LIGHTS 6 FRONT AND 6 REAR 1,497.50 US	
ROOF COVER	RFC	CAB ROOF COVER 1,144.32 USD	
ROTATING BEACON	ROB	ROTATING BEACON	171.52 USD





CAMERA	AVC	AROUND VIEW CAMERA W/BACKUP SENSOR	2,565.00 USD
FENDER	FUL	REAR FULL FNDR W/FNT FNDR, FNT FNDR HAS MUD GUARD AND RUBBER PROTECTOR	3,320.32 USD
FENDER	RPF	FRONT FENDER WITH RUBBER PROTECTOR	972.80 USD

Attachments -	Dealer Installed (18)		
Attachment	Description	Approx. Weight	List Price
186-1760D	AUTO LUBRICATON SYSTEM	0.00	6,807.84 USD
7203954	PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE; 72 IN. TINE LENGTH	2,891.00	16,746.74 USD
7225063	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 72 IN. TINE LENGTH	2,830.00	15,224.30 USD
7235385	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 96 IN. TINE LENGTH	3,112.00	19,183.20 USD
7235387	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 84 IN. TINE LENGTH	2,969.00	17,965.48 USD
7235389	PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE; 96 IN. TINE LENGTH	3,171.00	21,101.53 USD
7235391	PALLET FORKS - JRB QC; 106IN WIDE CARRIAGE; 84IN TINE LENGTH	3,028.00	19,762.03 USD
7273889	GPBKT; 120IN 4.5YD; PIN ON; BOCE	3,784.00	19,915.79 USD
7273890	GPBKT; 120IN 4.5YD; PIN ON; BOT	3,970.00	23,079.06 USD
7273891	GPBKT; 120IN 4.5YD; JRB QC; BOCE	3,506.00	18,919.38 USD
7273892	GPBKT; 120IN 4.5YD; JRB QC; BOT	3,691.00	22,082.65 USD
7273893	GPBKT; 120IN 4.5YD; ISO QC; BOCE	3,497.00	18,919.38 USD
7273894	GPBKT; 120IN 4.5YD; ISO QC; BOT	3,682.00	18,068.72 USD
7389868	GRAPPLE BKT; 120IN 3.50YD; JRB QC; BOCE	4,947.00	27,954.25 USD
7389869	GRAPPLE BKT; 120IN 3.50YD; ISO QC; BOCE	4,924.00	21,617.96 USD
7389870	GRAPPLE BKT; 120IN 3.75YD; PIN ON; BOCE	5,368.00	23,779.75 USD
QC-DL0009	QUICK COUPLER, JRB 418 STYLE (Standard Lift)	1,450.00	11,228.10 USD
QC-DL0010	QUICK COUPLER, ISO STYLE (Standard Lift)	1,233.00	12,811.18 USD

## **STANDARD EQUIPMENT FOR BASE MACHINE (12)**

ltem

Description



ENGINE:	Doosan DL08: Turbo Charged, Air to Air Intercooled, T4 Electronically Controlled Common Rail Direct Injected 446 cu.in., 6 Cylinder 271 SAE Gross Flywheel Horsepower @ 1,800 RPM Air Cleaner: Dry Type (Double Stage) Engine Self Diagnostic System Reversible Fan Driven by Hydraulic Fan Motor Auto Idle
HYDRAULIC SYSTEM:	Variable Displacement Axial Piston Pump Closed-Center (LS) Hydraulic Systems with Variable Pumps, Pilot Control with Float Spool, 2 Spools 3rd Valve with Lines & Control (lines terminate at boom base) Automatic Boom / Lift - Kick-Out (Set and Adjust from inside the cab) Automatic Return-to-Dig Position (Adjustable Electro-Magnetic) Accumulator for Emergency Pilot System
BRAKE SYSTEM:	Dual Pedal Braking system 4 Wheel Outboard Wet Disc Brakes with Separate Front & Rear Circuits Accumulator for Emergency Stopping Parking Brake: Spring Apply Hydraulic Release, sliding caliper disc brake on the face of the transmission Heavy Duty Brakes, Increase brake force 6 Disc Wet
STEERING:	Load Sensing Type with a Flow Amplifier and a Priority Valve 40 Degree Articulation, Full Hydraulic Power Steering Steering Cylinder Cushion Valve Tilt and Telescopic Steering Wheel Electric Joystick Steering US50 / US51
CAB ROPS/FOPS	"Air Conditioner Heater & Defroster Double Filtered Air Cab Combination Lever Rear View Camera Accelerator Pedal Transmission Lever Rear Hinged & Locking Doors (Both sides) / Right side is emergency access door Switches: Transmission Shift Switch (Manual, Auto 1-4 and Auto 2-4) Economy Mode Switch (Power, Normal & Economy Modes) Headlight Switch Front Work Light Switch Rear Work Light Switch Rear Work Light Switch Rear Work Switch Parking Brake Switch Transmission Cutoff Switch Mirror Heater Switch Display Screen Control Switch Display Screen Control Switch Hazard Warning Light Switch Boom Kick Out Switch Side View Mirrors with Heat Safety Glass, Tinted Fully Adjustable Air Suspension Seat with Heat Seat Belt (2 Wide) Sliding Door Windows (Left Side)"
TRANSMISSION / AXLES:	"Full Automatic Power Shift 4 Forward & 3 Reverse Speeds, with Torque Converter; US10, US11, US20, US21 5 Forward & 3 Reverse Speeds, with Lock Up Torque Converter; US50, US51 Differentials - US10 / US20 / US50 = Limited slip front and rear Differentials - US11 / US21 / US51, Hydraulic locking front with open rear Self Adjusting Brake Disc Clearance Torque Converter, Fixed Wheel Stator Electrical T/M Clutch Discomaget with Service Brake



Transmission Oil Level Gauge         Very Fob: Entry and starting         Lights:         (2) Fort Headights with High / Low Beams         (2) Fort Headights (2 food mounded 2 mounded in rear grill         Alama         Transmission Overheat         Engine Oil Prossure         Colont Temperature Gauge         DEF Level Gauge         DEF Level Gauge         DEF Level Gauge         DE Ford Colant Temperature Gauge         Transmission Actual Gear         Transmission Gare Gauge Moning Light         Art Cleaner Cloging Woning Light         Art Cleaner Cloging Woning Light         Right Tum and Hazard Warning Light         Right Deressing Symbol         Can black Up Mining Light         Right Deressing Woning Light				
Batteries, (2) 12 Volt, 200 Amp, 1300 CCA         Starter, 24 Volt 6 KW         Hom         Key Fob; Entry and starting         Lights.         (2) Front Floadights with High / Low Beams         (2) Front Floadights (2 food mounted, 2 mounted in rear grill         Alam Buzzer for:         Transmission Ourhead         Engine Oil Pressure         Coolent Temperature Gauge         Def Level Coolent Hoadights (2 food mounted, 2 mounted in rear grill         Alam Buzzer for:         Transmission Out Temperature Gauge         Def Level Coolent Temperature Gauge         Transmission Actual Gear         Transmission Actual Gear		T/M Down Shift on Shift Control and Joy Stick Control Transmission Oil Level Gauge"		
OTHER STANDARD       Single Lever Control with FNR Control Buttons         OTHER STANDARD       Engine Side Covers         Boom / Float       Drawbar and Pin         Neutral Safety Start System       Muffler         Fenders, Front & Rear       Ladders & Service Platforms         Manuals, Parts & Operator's       Remote Drain Ports"         OPERATING WEIGHT:       41,502 lbs	ELECTRICAL:	*Alternator, 80 Amp., 28 Vol Batteries, (2) 12 Volt, 200 Amp, 1300 CCA Starter, 24 Volt 6 KW Hom Key Fob; Entry and starting Lights: (2) Front Headlights with High / Low Beams (2) Stop Lights, Tail Lights & Directional Indicators (2) Front Floodlights (LED) (4) Rear Floodlights (2 roof mounted, 2 mounted in rear grill Alarm Buzzer for: Transmission Overheat Engine Oil Pressure Coolant Temperature Betertonic Monitoring & Display for: Fuel Level Gauge DEF Level Gauge DEF Level Gauge DEF Level Gauge Transmission Oil Temperature Gauge Speedometer Tachometer ECO Bar Transmission Actual Gear Transmission Actual Gear Transmission Gear Select Preheat Indicator Light Air Cleaner Cloging Warning Light Multi Function Gauge (can display one of the following at a time) Trip Meter Battery Voltage Total Time of Operation Left Turn and Hazard Warning Light High Beam Indicator Light Right Turn and Hazard Warning Light High Beam Indicator Light Arking Theer Selectr Indicator Light Arking Tachometer Battery Voltage Total Time of Operation Left Turn and Hazard Warning Light High Beam Indicator Light Parking Brake Indicator Light Parking Brake Indicator Light Miror Heater Indicator Light Arking Turn and Hazard Warning Light High Beam Indicator Light Parking Brake Indicator Light Parking Brake Indicator Light Parking Brake Indicator Light Parking Brake Indicator Light Miror Heater Indicator Light Parking Brake Indicator Light Parking Brake Indicator Light Parking Brake Indicator Light Parking Brake Indicator Light Charge Warning Symbol Engine Warning Symbol DEF Low Level Warning Symbol DEF Low Level Warning Symbol		
OTHER STANDARD EQUIPMENT:Air Čleaner with Pre-cleaner Engine Side Covers Boom / Float Drawbar and Pin Neutral Safety Start System Muffler Fenders, Front & Rear Ladders & Service Platforms Manuals, Parts & Operator's Remote Drain Ports"OPERATING WEIGHT:41,502 lbs	TIRES:	23.5R25,L3,Triangle		
		Air Cleaner with Pre-cleaner Engine Side Covers Boom / Float Drawbar and Pin Neutral Safety Start System Muffler Fenders, Front & Rear Ladders & Service Platforms Manuals, Parts & Operator's		
	OPERATING WEIGHT:	41,502 lbs Page 4 of 5		



Price F	Page
---------	------

	Installation Options: 1. By your dealer should take about 2 days. Once fa 2. At NACUP (Sa	rship, install video includ miliar with install, about avannah), by our SKF ve o bracket but modificatio parts.	ealer Installed Options, price is the kit only (186-1760D). ded. Install cost, based on your labor rate. First time install t a day endor, Air and Hydraulics (AHE), \$2,200-\$2800 on is required, for factory fit, order pump bracket and front 1 ea 1 ea 3 ea 4 ea 3 ea 4 ea 4 ea 4 ea 4 ea
	S5010503 120804-00078	Washer Washer	4 ea 4 ea
	Approximate cost fo		
AUTO LUBE/GREASE SYSTEM (NOT STANDARD EQUIPMENT)	<ul> <li>Auto Lube (SKF / Lincoln): Listed under Dealer Installed Options, price is the kit only (186-1760D) Installation Options:</li> <li>By your dealership, install video included. Install cost, based on your labor rate. First time install should take about 2 days. Once familiar with install, about a day</li> <li>At NACUP (Savannah), by our SKF vendor, Air and Hydraulics (AHE), \$2,200-\$2800</li> </ul>		
	Kit comes with pump valve bracket from p Part #'s are as follow	oarts.	on is required, for factory fit, order pump bracket and front
	110406-07214A		1 ea
	110406-05501	Front Valve Bracket	1 ea
	S05090666	Bolt	3 ea
	S0509066	Bolt	4 ea
	S5010513	Washer	3 ea
	S5102503	Washer	4 ea
	S0558166	Bolt	4 ea
	S5010503	Washer	4 ea
	120804-00078	Washer	4 ea
	Approximate cost fo	r above parts \$72"	
LOADRITE SCALE SYSTEM (NOT STANDARD EQUIPMENT	Loadrite Scales: Order is placed through Doosan PO cut to Loadrite. Loadrite will coordinate with your dealership for installation. Install will be done at your dealership or at customer location. Price is inclusive of Install, Calibration and Customer training. Warranty is covered by Loadrite"		