PACKA	GE A	ARRAN	IGEMENT	(1)

Product Approx. Weight **List Price** DL380-7-US20 20,349.00 KG 307,007.92 USD

DL380-7-US20

Base Machine With High Lift Front

Differentials - Limited Slip Differential Front / Rear

Additional Counterweight

Without Bucket

Steel Cab with Integrated ROPS/FOPS Tires: 23.5R25,L3, Triangle

Air Suspension Seat

Thumb Wheel Joystick
Transmission: 4F / 3R Torque Converter

Transparent Bucket Technology

Rear View Camera

Radio

OPTIONAL EQUIPMENT - Factory Installed (18)			
Option	CODE	Description	List Price
ADDITIONAL COUNTERWEIGHT	400	882LB ADDITIONAL COUNTERWEIGHT	3,005.95 USD
CABIN HANDRAIL(TOP)	HDR	CABIN TOP HANDRAIL	514.56 USD
ENGINE COOLANT HEATER	110	110V PLUG HEATER	514.56 USD
EMERGENCY STEER	ESS	EMERGENCY STEER / SECONDARY STEERING	2,117.12 USD
LOAD ISOLATION SYSTEM	LIH	HYDRAULIC LOAD ISOLATION SYSTEM	4,505.60 USD
Additional Brake Pedal	ABP	ADDITIONAL BRAKE PEDAL	99.84 USD
AIR COMPRESSOR	ACO	AIR COMPRESSOR	2,803.20 USD
MIRROR	ADE	ADJUSTABLE MIRROR, REMOTE ELECTRIC	1,886.72 USD
NOISE KIT	NOF	NOISE KIT WITH FRONT	1,774.08 USD
Weighing System	WEI	DOOSAN INTEGRATED WEIGHING SYSTEM	1,344.00 USD
TIRE	CR3	23.5R25,L5,BRI,VSDL	19,801.60 USD
TIRE	CR8	23.5R25 brigestone VJT L3	10,050.56 USD
HEAD LAMP	LED	WORK LIGHTS 2 FRONT	399.36 USD
ROOF COVER	RFC	CAB ROOF COVER	1,144.32 USD
ROTATING BEACON	ROB	ROTATING BEACON	171.52 USD
		Page 1 of 5	

CAMERA	AVC	AROUND VIEW CAMERA W/BACKUP SENSOR	2,565.00 USD
FENDER	FUL	REAR FULL FNDR W/FNT FNDR, FNT FNDR HAS MUD GUARD AND RUBBER PROTECTOR	3,320.32 USD
FENDER	RPF	FRONT FENDER WITH RUBBER PROTECTOR	972.80 USD

Attachments - Dealer Installed (18)				
Attachment	Description	Approx. Weight	List Price	
186-1760D	AUTO LUBRICATON SYSTEM	0.00	6,807.84 USD	
7203954	PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE; 72 IN. TINE LENGTH	2,891.00	16,746.74 USD	
7225063	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 72 IN. TINE LENGTH	2,830.00	15,224.30 USD	
7235385	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 96 IN. TINE LENGTH	3,112.00	19,183.20 USD	
7235387	PALLET FORKS - ISO QC; 106 IN. WIDE CARRIAGE; 84 IN. TINE LENGTH	2,969.00	17,965.48 USD	
7235389	PALLET FORKS - JRB QC; 106 IN. WIDE CARRIAGE; 96 IN. TINE LENGTH	3,171.00	21,101.53 USD	
7235391	PALLET FORKS - JRB QC; 106IN WIDE CARRIAGE; 84IN TINE LENGTH	3,028.00	19,762.03 USD	
7273889	GPBKT; 120IN 4.5YD; PIN ON; BOCE	3,784.00	19,915.79 USD	
7273890	GPBKT; 120IN 4.5YD; PIN ON; BOT	3,970.00	23,079.06 USD	
7273891	GPBKT; 120IN 4.5YD; JRB QC; BOCE	3,506.00	18,919.38 USD	
7273892	GPBKT; 120IN 4.5YD; JRB QC; BOT	3,691.00	22,082.65 USD	
7273893	GPBKT; 120IN 4.5YD; ISO QC; BOCE	3,497.00	18,919.38 USD	
7273894	GPBKT; 120IN 4.5YD; ISO QC; BOT	3,682.00	18,068.72 USD	
7389868	GRAPPLE BKT; 120IN 3.50YD; JRB QC; BOCE	4,947.00	27,954.25 USD	
7389869	GRAPPLE BKT; 120IN 3.50YD; ISO QC; BOCE	4,924.00	21,617.96 USD	
7389870	GRAPPLE BKT; 120IN 3.75YD; PIN ON; BOCE	5,368.00	23,779.75 USD	
QC-DLHL11	QUICK COUPLER, JRB 418 STYLE (High Lift)	1,450.00	12,336.18 USD	
QC-DLHL12	QUICK COUPLER, ISO STYLE (High Lift)	1,233.00	13,111.20 USD	

STANDARD EQUIPMENT FOR BASE MACHINE (12)

Item Description

Page 2 of 5

ENGINE:	Doosan DL08: Turbo Charged, Air to Air Intercooled, T4 Electronically Controlled Common Rail Direct Injected 446 cu.in., 6 Cylinder 271 SAE Gross Flywheel Horsepower @ 1,800 RPM Air Cleaner: Dry Type (Double Stage) Engine Self Diagnostic System Reversible Fan Driven by Hydraulic Fan Motor Auto Idle
HYDRAULIC SYSTEM:	Variable Displacement Axial Piston Pump Closed-Center (LS) Hydraulic Systems with Variable Pumps, Pilot Control with Float Spool, 2 Spools 3rd Valve with Lines & Control (lines terminate at boom base) Automatic Boom / Lift - Kick-Out (Set and Adjust from inside the cab) Automatic Return-to-Dig Position (Adjustable Electro-Magnetic) Accumulator for Emergency Pilot System
BRAKE SYSTEM:	Dual Pedal Braking system 4 Wheel Outboard Wet Disc Brakes with Separate Front & Rear Circuits Accumulator for Emergency Stopping Parking Brake: Spring Apply Hydraulic Release, sliding caliper disc brake on the face of the transmission Heavy Duty Brakes, Increase brake force 6 Disc Wet
STEERING:	Load Sensing Type with a Flow Amplifier and a Priority Valve 40 Degree Articulation, Full Hydraulic Power Steering Steering Cylinder Cushion Valve Tilt and Telescopic Steering Wheel Electric Joystick Steering US50 / US51
CAB ROPS/FOPS	"Air Conditioner Heater & Defroster Double Filtered Air Cab Combination Lever Rear View Camera Accelerator Pedal Transmission Lever Rear Hinged & Locking Doors (Both sides) / Right side is emergency access door Switches: Transmission Shift Switch (Manual, Auto 1-4 and Auto 2-4) Economy Mode Switch (Power, Normal & Economy Modes) Headlight Switch Front Work Light Switch Rear Work Light Switch Rear Wiper Switch Pilot Cutoff Switch Parking Brake Switch Transmission Cutoff Switch Mirror Heater Switch Display Screen Control Switch Display Screen Selector Switch Boom Kick Out Switch Side View Mirrors with Heat Safety Glass, Tinted Fully Adjustable Air Suspension Seat with Heat Seat Belt (2 Wide) Sliding Door Windows (Left Side)"
TRANSMISSION / AXLES:	"Full Automatic Power Shift 4 Forward & 3 Reverse Speeds, with Torque Converter; US10, US11, US20, US21 5 Forward & 3 Reverse Speeds, with Lock Up Torque Converter; US50, US51 Differentials - US10 / US20 / US50 = Limited slip front and rear Differentials - US11 / US21 / US51, Hydraulic locking front with open rear Self Adjusting Brake Disc Clearance Torque Converter, Fixed Wheel Stator Electrical T/M Clutch Discoppaget with Service Brake

TM Down Shift on Shift Control and Joy Stick Control Transmission Dit Level Gauge *Alternator, 90 Amp., 28 Volt Batteries, (2) 12 Volt, 200 Amp., 1300 CCA Stator, 24 Volt 6 KW Horn Key Fob: Entry and starting Lights Lights		
"Alternator, 80 Amp., 28 Volt Batteries, (2) 112 Volt, 200 Amp., 1300 CCA Section 12 Volt 6 KW Hom AV Fob: Entry and starting Lights: (2) Front Headlights with High / Low Beams (2) Stop Lights, Tall Lights & Directional Indicators (2) Front Floodlights (LED) August 12 American 12		
Single Lever Control with FNR Control Buttons Air Cleaner with Pre-cleaner Engine Side Covers Boom / Float Drawbar and Pin Neutral Safety Start System Muffler Fenders, Front & Rear Ladders & Service Platforms Manuals, Parts & Operator's Remote Drain Ports" OPERATING WEIGHT: 41,502 lbs	ELECTRICAL:	"Alternator, 80 Amp., 28 Volt Batteries, (2) 12 Volt, 200 Amp, 1300 CCA Starter, 24 Volt 6 KW Horn Key Fob; Entry and starting Lights: (2) Front Headlights with High / Low Beams (2) Stop Lights, Tail Lights & Directional Indicators (2) Front Floodlights (LED) (4) Rear Floodlights (LED) (4) Rear Floodlights (2 roof mounted, 2 mounted in rear grill Alarm Buzzer for: Transmission Overheat Engine Oil Pressure Coolant Temperature Electronic Monitoring & Display for: Fuel Level Gauge DEF Level Gauge DEF Level Gauge Engine Coolant Temperature Gauge Transmission Oil Temperature Gauge Speedometer ECO Bar Transmission Actual Gear Transmission Actual Gear Transmission Gear Select Preheat Indicator Light Air Cleaner Clogging Warning Light Multi Function Gauge (can display one of the following at a time) Tip Meter Battery Voltage Total Time of Operation Left Turn and Hazard Warning Light Right Turn and Hazard Warning Light Right Turn and Hazard Warning Light Roys Turn Hazard Warning Light Roys Ean Indicator Light More Heater Indicator Light Reverse Fan Indicator Light Reverse Fan Indicator Light Parking Brake Indicator Light Parking Brake Indicator Light F/R (Forward/Reverse) Selector Indicator Light Brake Fluid Pressure Warning Symbol Engine Oil Pressure Warning Symbol Engine Warning Symbol Engine Warning Symbol DEF Low Level Warning Symbol SCR Failure Warning Symbol
Air Cleaner with Pre-cleaner Engine Side Covers Boom / Float Drawbar and Pin Neutral Safety Start System Muffler Fenders, Front & Rear Ladders & Service Platforms Manuals, Parts & Operator's Remote Drain Ports" OPERATING WEIGHT: 41,502 lbs	TIRES:	23.5R25,L3,Triangle
,		Air Cleaner with Pre-cleaner Engine Side Covers Boom / Float Drawbar and Pin Neutral Safety Start System Muffler Fenders, Front & Rear Ladders & Service Platforms Manuals, Parts & Operator's
1 tun. = 10 t	OPERATING WEIGHT:	41,502 lbs Page 4 of 5

"Auto Lube (SKF / Lincoln): Listed under Dealer Installed Options, price is the kit only (186-1760D). Installation Options:

1. By your dealership, install video included. Install cost, based on your labor rate. First time install should take about 2

days. Once familiar with install, about a day

2. At NACUP (Savannah), by our SKF vendor, Air and Hydraulics (AHE), \$2,200-\$2800

Kit comes with pump bracket but modification is required, for factory fit, order pump bracket and front valve bracket from parts.

110406-07214A	Pump Bracket	1 ea
110406-05501	Front Valve Bracket	1 ea
S05090666	Bolt	3 ea
S0509066	Bolt	4 ea
S5010513	Washer	3 ea
S5102503	Washer	4 ea
S0558166	Bolt	4 ea
S5010503	Washer	4 ea
120804-00078	Washer	4 ea

Approximate cost for above parts \$72"

AUTO LUBE/GREASE SYSTEM (NOT STANDARD EQUIPMENT)

Auto Lube (SKF / Lincoln): Listed under Dealer Installed Options, price is the kit only (186-1760D) Installation Options:

- 1. By your dealership, install video included. Install cost, based on your labor rate. First time install should take about 2 days. Once familiar with install, about a day
- 2. At NACUP (Savannah), by our SKF vendor, Air and Hydraulics (AHE), \$2,200-\$2800

Kit comes with pump bracket but modification is required, for factory fit, order pump bracket and front valve bracket from parts.

Part #'s are as follows

110406-07214A 110406-05501	Pump Bracket Front Valve Bracket	1 ea 1 ea
S05090666	Bolt	3 ea
S0509066	Bolt	4 ea
S5010513 S5102503	Washer Washer	3 ea 4 ea
S0558166	Bolt	4 ea
S5010503 120804-00078	Washer Washer	4 ea 4 ea

Approximate cost for above parts \$72"

Loadrite Scales:

Order is placed through Doosan

ALE SYSTEM PO cut to Loadrite.

LOADRITE SCALE SYSTEM (NOT STANDARD EQUIPMENT

Loadrite will coordinate with your dealership for installation. Install will be done at your dealership or at customer location. Price is inclusive of Install, Calibration and Customer training. Warranty is covered by Loadrite"