# Q SERIES ROLLOUT CART

## Delivering both Quality and Quantity in every truckload.

Get the industry-leading truckload capacity you want with the product integrity you've come to trust. The Q Cart from SSI SCHAEFER delivers the quality that your customers expect, while offering municipalities and haulers more carts in every truckload.

SCHAFER

schaeferwaste.com



### **BODY / BAR**

- Non-slip, textured finish on corners for grabber traction
- Injection molded for maximum strength and durability
- One-piece high-density polyethylene (HDPE) construction
- Built-in flexibility
- Reinforced wall thickness in critical wear areas
- Externally housed lift bar for water-tight leak-proof body
- Rotating retention bar for less stress on cart body



LIDS

BODY

INTERIOR

## **UPPER ATTACHMENT**

- Integrated, reinforced upper attachment for semi-automated lifters
- Highly durable, in-molded bar supports
- Meets all ANSI standards

## LIDS / HANDLES

- Solid lid axle with a robust 3-point attachment
- Overlapping lid design with integral moisture barrier lip
- Inside dripping rim to seal in odors •
- 270° lid opening
- Ergonomically designed hand grips for easy push and pull motion
- Smooth surface with no protrusions
- Two ergonomic lift handles for easy opening



## WHEELS & AXLES

- 3/4" solid axle of tempered, rolled, and Zinc Chromate steel
- Quick release durable HDPE wheel for ease of disassembly and easy rolling motion
- Lubricated maintenance-free bearings
- Rubber wheels optional



## BOTTOM

- Angled bottom for easy tilting
- Dual 3/8" wear strip for longer life

#### **Proud supporters of:**

#### www.schaeferwaste.com

Schaefer Plastics North America, LLC. 10301 Westlake Drive Charlotte, NC 28273 Phone 855-900-CART ©2022 SSI SCHAEFER. Release 12/2022 EN



## **OUTSIDE DIMENSIONS**

	1	2	3	4	5		
Order #	TOTAL HEIGHT	BODY HEIGHT	WIDTH	DEPTH	WHEEL DIAMETER	LOAD RATING↓	TRUCKLOAD QUANTITY
USD 26Q	26.4	35.8	19.8	26.0	8	91 lbs.	1,144
USD 35Q	36.5	36.0	19.7	26.3	8	126 lbs.	1,456
USD 95Q	43.2	41.8	28.0	32.1	10 or 12	333 lbs.	793

ANSI Z245.30 and ANSI Z245.60 Approved. ISO 9001 Certified. Truckload quantity based on 53' trailer. Measurements in inches

#### **INJECTION MOLDED MANUFACTURING, MANAGED ASSEMBLY & DISTRIBUTION,** AND SERVICE VERIFICATION

## **COLORS, MARKINGS, & OPTIONS**

- Available in an array of standard colors. Custom colors available upon request with minimum quantities.
- Smooth surface for hot stamping on lid and body
- Customizable in-mold labeling (IML) on lid



## MANUFACTURING LOCATIONS

- Charlotte, North Carolina •
- Lodi, California •







## National Waste & Recycling Association