

Technical sheet :

M 40-4 ST5



 **MANITOU**
HANDLING YOUR WORLD

	Technical characteristics		Imperial
1.1	Manufacturer		MANITOU
1.2	Model Name		M 40-4 ST5
1.3	Power source		Diesel
1.4	Operator type		Sitting
1.5	Max. capacity	Q	8818 lb
1.6	Load centre of gravity	c	20 in
1.8	Load distance, centre of drive axle to fork	x	30 in
1.9	Wheelbase	y	83 in
	Weight		
2.1	Service weight		15355 lb
2.2	Weight on front axle (laden) / rear axle (laden)		19864 lb / 4310 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		5787 lb / 9568 lb
	Wheels		
3.1	Tyres type		Pneumatic
3.2	Dimensions of front wheels		18-22,5 MPT-06
3.3	Dimensions of rear wheels		340/80 R18 XMCL
3.5	Number of front wheels / rear wheels		2 / 2
3.5.2	Number of drive wheels		4
3.6	Front wheel gauge	b10	64 in
3.7	Rear wheel gauge	b11	69 in
	Dimensions		
4.7	Height of overhead guard (cabin) / Overall height of low overhead guard (Buggie version)	h6 / h6*	98 in / 98 in
4.8	Seat height/stand height	h7	57 in
4.19	Overall length	l1	191 in
4.20	Length to face of forks	l2	144 in
4.21	Overall width	b1	82 in
4.22	Forks section x width x length	s / e / l	2 in x 6 in / 47 in
4.23	Fork carriage ISO 2328 (class/form) A/B		3A
4.24	Fork carriage width	b3	66 in
4.31	Ground clearance below mast	m1	12 in
4.32	Ground clearance at centre of wheelbase	m2	17 in
4.33	Aisle width for 1000 x 1200 pallet widthways	Ast	265 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	265 in
4.35	Turning radius	Wa	180 in
	Performances		
5.1	Travel speed (laden / unladen)		6 mi/h / 14 mi/h
5.2	Lifting speed (laden / unladen)		1 ft/s / 1 ft/s
5.3	Lowering speed (laden / unladen)		2 ft/s / 1 ft/s
5.5	Drawbar pull (Laden / Unladen)		11000 daN / 6600 daN
5.10	Service brake		Hydraulic
	Engine		
7.1	Engine brand / model		Deutz / TCD 2,9
7.2	Engine power according to ISO 1585		55 kW
7.3	Rated speed		2300 rpm
7.4	Number of cylinders / Capacity of cylinders		4 - 178 in³
	Miscellaneous		
8.2	Working hydraulic pressure for attachments		3046 PSI
8.3	Oil flow rate for attachments		26 US gpm
8.4	Sound level at the driver's ear according to DIN 12 053		76 dB

M 40-4 ST5 - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 30	FVD 33	FVD 35	FVD 37	FVD 40	FVD 45	FVD 50
h1 - Height mast lowered *	in	8' 3"	8' 9"	9' 1"	9' 5"	9' 11"	10' 9"	11' 7"
h4 - Height mast extended *	in	13' 4"	14' 4"	15'	15' 8"	16' 8"	18' 3"	19' 11"
h3 - Max. lifting height	in	9' 10"	10' 10"	11' 6"	12' 2"	13' 1"	14' 9"	16' 5"
α / β - Mast inclination (front / rear)	°	15 / 15	15 / 15	15 / 15	15 / 15	15 / 15	15 / 15	15 / 15
Residual capacity at max height	lb	8818.49	8818.49	8818.49	8818.49	8818.49		
Residual capacity without attachment (Off road load chart)	lb	8818.49	8818.49	8818.49	8818.49	8818.49		
Residual capacity with hooked-on side shift (Off road load chart)	lb	8818.49	8818.49	8818.49	8818.49	8818.49		
Height at max capacity	in	9' 10"	10' 10"	11' 6"	12' 2"	13' 1"		
Height at max capacity with hooked-on sideshift	in	9' 10"	10' 10"	11' 6"	12' 2"	13' 1"		

Free Lift Triplex (FLT)		FLT 37	FLT 40	FLT 43	FLT 45	FLT 47	FLT 50	FLT 55
h1 - Height mast lowered *	in	7' 5"	7' 9"	8' 1"	8' 4"	8' 7"	8' 11"	9' 5"
h2 - Free lift	in	4' 1"	4' 5"	4' 9"	5'	5' 3"	5' 7"	6' 1"
h4 - Height mast extended *	in	15' 8"	16' 8"	17' 7"	18' 3"	18' 11"	19' 11"	21' 7"
h3 - Max. lifting height	in	12' 2"	13' 1"	14' 1"	14' 9"	15' 5"	16' 5"	18' 1"
α / β - Mast inclination (front / rear)	°	15 / 15	15 / 15	15 / 15	15 / 15	15 / 15	10 / 15	10 / 15
Residual capacity at max height	lb	8818.49	8818.49	8818.49	8818.49			
Residual capacity without attachment (Off road load chart)	lb	8818.49	8818.49	8818.49	8818.49			
Residual capacity with hooked-on side shift (Off road load chart)	lb				8377.57	6613.87		4409.25
Height at max capacity	in	12' 2"	13' 1"	14' 1"	14' 9"			
Height at max capacity with hooked-on sideshift	in				13' 1"	13' 9"		13' 9"

Full Visibility Triplex (FVT)		FLT 60
h1 - Height mast lowered *	in	10'
h2 - Free lift	in	6' 8"
h4 - Height mast extended *	in	23' 2"
h3 - Max. lifting height	in	19' 8"
α / β - Mast inclination (front / rear)	°	10 / 15



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes