



TECHNICAL DATA

MASSES

Max. operating mass	1,100 lbs
Transport mass	485 lbs

DIMENSIONS

Length, max	6.6 ft
Transport dimensions (LxWxH)	5.5 x 3.2 x 3.6 ft
Working width, max.	39.4 in
Working width, min.	9.8 in

MATERIAL HOPPER

Capacity	40 gal
----------	--------

PROPULSION

Max. working speed	1.1 mph
Transport speed, max	2.1 mph

ENGINE

Manufacturer/Model	Honda GXV 160
Emissions according to	EPA
Rated power	3.20 kW
Type	Air cooled gasoline
Number of cylinders	1
Fuel tank capacity	0.5 gal

DRIVE SYSTEM

Drive system	Hydrostatic
--------------	-------------

UNDERCARRIAGE

Front wheels (Qty x W x D)	2x hydrostatically driven wheels, 15.7 in diameter
Rear wheels	1x swivel castor wheel, 10 in diameter

STANDARD EQUIPMENT

- Two hydrostatically driven wheels and a swivel castor wheel
- Forward and reverse drive controls at operator handle
- Layer thickness control with independent left and right hydraulic cylinders
- Operating width control with hydraulically controlled hatches
- Screed heated with exhaust gas recovery
- Hopper container
- Parking brake

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.