



CONFIGURATION

Chassis	ProView 6x4 (Wide) ASL
----------------	------------------------

STANDARD SPECIFICATION

Vehicle Overview	
Drive Hand	DS (Steering Box on Left)
GVWR	62,000 lb
Wheelbase	230"
Engine	Cummins L9 360HP (Current Spec)
Gearbox	Allison 3000RDS
Fuel Tank	70 US Gallons
Cab Seating	Driver +1

WHEELS, TYRES & SUSPENSION

Axle	Design Weight	Suspension	Tires
Axle 1	20,000 lbs	Front Steel Suspension 5655001	315/80 R 22.5 5656001
Axle 2	44,000 lbs	Drive Axle 1 Suspension Hendrickson HN460 5661001	315/80 R 22.5 5662001
Axle 3		Drive Axle 1 Suspension Hendrickson HN460 5661001	315/80 R 22.5 5665001



STANDARD EQUIPMENT – CHASSIS

- Low Entry Cab with Single Hi-Vis Step Entry (16" Step Height)	- Flat, Unobstructed Walkthrough Cab Floor - Washable
- Cummins L9 360 HP, 6 Cyl. 8.9L in-Line Diesel	- LED Headlamps, low and high
	- LED Daytime Running Lights
- Cromwell Blended Steel Cab	- Mechanically Operated Hydraulic Cab Tilt
- DPF and SCR Treatment for EPA Compliance	- Rear of Cab Vertically Mounted Exhaust
- Electronic Fuel Injection	- Brake Pad Wear Lining Sensors
- Enhanced Converter Load Reduction (ECLR)	- Engine Immobiliser
- 4 Wheel Park Brake	- Red 3 Point Inertia Seatbelts
- Adjustable Air Suspended Driver's Seat, Armrest	- Storage Net for Documents
- 4 x Split Coat Hooks, Accommodates 8 Coats	- Oddments Tray in Doors
- 2x Half Width Sun Blinds	- Driver/Passenger Door LED Red Strip Marker
- In Dash 12V Power Supply Socket	- Electric Heated Mirrors
- Electric Windows	- Knorr Bremse Bendix Disc Brakes All Round
- Emergency Brake Signal	- 10 Gallon DEF Reservoir
- 70 Gallon Fuel Tank Anti-Siphon, Anti-Spill & Lockable Cap	- Anderson Socket
- 12v Electrical System	- 3x 185 amp/hour Batteries, 1000 CCA Capacity Each
- 320A Alternator	- RP170 Connectivity
- J1939 CAN Integrated	- Traction Enhancement
- Air Conditioning	- Flat Cab Roof with Compliant Marker Lights
- Cruise Control	- Battery Isolator on Battery Box with Power On/Off LED Light
- Engine Hour Meter Within Display Unit with Clock	- Rail Section 13.66" x 3.74" x 3/8"
- Pressed Steel Channel Frame, Bolted Construction	- Differential Lock
- Frame RBM 3,290,000	



FITTED EQUIPMENT – CHASSIS

Option No.	Option Name
5650001	USA
5652001	6x4
5653001	Wide Track
5634001	GVW 62000 lbs
5633004	Wheelbase 230 inches
5654007	Cummins L9 360HP (Current Spec)
5638001	Allison 3000RDS Gearbox
5636001	Fuel Type Diesel
5671001	70 US Gallon Fuel Tank
5655001	Front Steel Suspension
5661001	Drive Axle 1 Suspension Hendrickson HN460
5664001	Drive Axle 2 Suspension Hendrickson HN460
5669002	Tyre Manufacturer Cooper
5657003	Front Axle Tread Pattern Roadmaster R230 WH
5663004	Drive Axle 1 Tread Pattern Roadmaster R230 WH
5666004	Drive Axle 2 Tread Pattern Roadmaster R230 WH
5656001	Front Tire Size 315/80 R 22.5
5662001	Drive Tire 1 Size 315/80 R 22.5
5665001	Drive Tire 2 Size 315/80 R 22.5
5734001	Steel Wheels
5-1089-0001	White Coloured Wheels
5635002	Dual Steer (Steering Box on Left)
5637001	Individual Crew Seat. Heated, Air Suspended Crew Seat - 6 Way adjustable. Armrest and Seatbelts
5674001	English only Labels
5673001	English only Documents
5061002	Window in Cab Rear Panel (Centre)
5024002	Air Conditioning
5267001	Instrument Cluster Language 1 (English)
5799001	English Only Labels
5796002	Individual Air Tank Drains
5020003	Inter + Cross Axle Diff Lock
5-1091-0001	Standard Rear Overhang

WARRANTY

Description
2 Year

TRAINING

Description
No Training