

**Prepared For :**  
Kaylyn Mitman  
NC SHERIFFS ASSOCIATION  
PO BOX 20049  
RALEIGH, NC 27619  
UNITED STATES  
Phone : 919-459-6471

**Prepared by:**  
Todd Lenhart  
PIEDMONT TRUCK CENTER, INC.  
412 SOUTH REGIONAL ROAD  
GREENSBORO, NC 27409  
Phone :3366682401

*A proposal for*  
**NC SHERIFFS ASSOCIATION**

*Prepared by*  
**PIEDMONT TRUCK CENTER, INC.**

*Todd Lenhart*

*April 19, 2023*

**Western Star 47X**



Components shown may not reflect all spec'd options and are not to scale

SPECIFICATION PROPOSAL

Description
Price Level
WST 47X/49X PRL-27X (EFF:MY24 ORDERS)
Data Version
SPECPRO21 DATA RELEASE VER 038
Vehicle Configuration
WESTERN STAR 47X
2024 MODEL YEAR SPECIFIED
SET BACK AXLE - TRUCK
TRAILER TOWING PROVISION AT END OF FRAME WITH SAE J560
LH PRIMARY STEERING LOCATION
General Service
TRUCK/TRAILER CONFIGURATION
DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)
CONSTRUCTION SERVICE
GOVERNMENT BUSINESS SEGMENT
DIRT/SAND/ROCK COMMODITY
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS
MAXIMUM 8% EXPECTED GRADE
SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE
WESTERN STAR VOCATIONAL WARRANTY
EXPECTED FRONT AXLE(S) LOAD 12000.0 lbs
EXPECTED REAR DRIVE AXLE(S) LOAD 40000.0 lbs
EXPECTED GROSS VEHICLE WEIGHT CAPACITY 52000.0 lbs

**Prepared For :**  
Kaylyn Mitman  
NC SHERIFFS ASSOCIATION  
PO BOX 20049  
RALEIGH, NC 27619  
UNITED STATES  
Phone : 919-459-6471

**Prepared by:**  
Todd Lenhart  
PIEDMONT TRUCK CENTER, INC.  
412 SOUTH REGIONAL ROAD  
GREENSBORO, NC 27409  
Phone :3366682401

#### Description

EXPECTED GROSS COMBINATION WEIGHT 52000.0 lbs

#### Truck Service

END DUMP BODY

GODWIN MANUFACTURING COMPANY

#### Engine

CUM L9 300 HP @ 2200 RPM; 2200 GOV RPM, 860 LB-FT  
@ 1200 RPM

#### Electronic Parameters

75 MPH ROAD SPEED LIMIT

#### Engine Equipment

2010 EPA/CARB/GHG21 CONFIGURATION

NO 2008 CARB EMISSION CERTIFICATION

STANDARD OIL PAN

ENGINE MOUNTED OIL CHECK AND FILL

SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR  
CLEANER

DR 12V 160 AMP 28-SI QUADRAMOUNT PAD  
ALTERNATOR WITH REMOTE BATTERY VOLT SENSE

(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA,  
555RC, THREADED STUD BATTERIES

BATTERY BOX WITH ALUMINUM COVER MOUNTED  
SHORT SIDE TO RAIL

SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK  
OF CAB

WIRE GROUND RETURN FOR BATTERY CABLES WITH  
ADDITIONAL FRAME GROUND RETURN

UNPOLISHED ALUMINUM WST BATTERY BOX COVER

CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR  
WITH INTERNAL SAFETY VALVE

ELECTRONIC ENGINE INTEGRAL SHUTDOWN  
PROTECTION SYSTEM

CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE  
GEOMETRY TURBO ON/OFF WITH BRAKE LAMPS

RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL  
AFTERTREATMENT SYSTEM ASSEMBLY WITH RH

Description
HORIZONTAL TAILPIPE
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH
STANDARD EXHAUST SYSTEM LENGTH
RH STANDARD HORIZONTAL TAILPIPE
8 GALLON DIESEL EXHAUST FLUID TANK
UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER
LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION
STANDARD DIESEL EXHAUST FLUID TANK CAP
AIR POWERED ON/OFF ENGINE FAN CLUTCH
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED
DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR
CUMMINS SPIN ON FUEL FILTER
FULL FLOW OIL FILTER
1400 SQUARE INCH VOCATIONAL RADIATOR
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT
RADIATOR DRAIN VALVE
LOWER RADIATOR GUARD
NO REPTO, EXTENDED FLYWHEEL HOUSING, CUML9 REQUIRED FOR PACKAGING
ELECTRIC GRID AIR INTAKE WARMER
DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH
Transmission

Description
EATON FULLER FRO-16210C TRANSMISSION
Transmission Equipment
QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP
EATON ADVANTAGE 15-1/2 INCH SELF ADJUSTING CLUTCH
TORQUE LIMITING CLUTCH BRAKE
ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING
HYDRAULIC CLUTCH CONTROL
ALUMINUM CLUTCH HOUSING
NO PTO MOUNTING LOCATION SPECIFIED
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN
PAINTED SHIFT LEVER, SOLID LINKAGE
AIR TO OIL TRANSMISSION COOLER
SYNTHETIC TRANSMISSION LUBE
Front Axle and Equipment
DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE
CONMET PRESET PLUS PREMIUM ALUMINUM FRONT HUBS
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
NON-ASBESTOS FRONT BRAKE LINING
CONMET CAST IRON FRONT BRAKE DRUMS
FRONT BRAKE DUST SHIELDS
FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS

Description
SINGLE POWER STEERING GEAR, BENDIX, 12-13.3K
2 QUART SEE THROUGH POWER STEERING RESERVOIR
CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE
Front Suspension
12,000# DUAL TAPERLEAF FRONT SUSPENSION
MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION
FRONT SHOCK ABSORBERS
Rear Axle and Equipment
MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE
CONMET PRESET PLUS PREMIUM ALUMINUM REAR HUBS
4.11 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING
MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES
MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES
(1) INTERAXLE LOCK VALVE FOR TANDEM DRIVE AXLES
INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH
MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
NON-ASBESTOS REAR BRAKE LINING
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)
GUNITE CAST IRON REAR BRAKE DRUMS
REAR BRAKE DUST SHIELDS
REAR OIL SEALS
WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS

Description
HALDEX AUTOMATIC REAR SLACK ADJUSTERS
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE
STANDARD REAR AXLE BREATHER(S)

Rear Suspension
TUFTRAC GEN2 40,000# REAR SPRING SUSPENSION
9.5 INCH NOMINAL RIDE HEIGHT (460MM GLOBAL REFERENCE HEIGHT)
AXLE CLAMPING GROUP
55 INCH AXLE SPACING
FORE/AFT AND TRANSVERSE CONTROL RODS
REAR SHOCK ABSORBERS - TWO AXLES (TANDEM)

Brake System
WABCO 6S/4M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE
WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE
WABCO OIL COALESCING FILTER FOR AIR DRYER
AIR DRYER MOUNTED UNDER HOOD
STEEL AIR BRAKE RESERVOIRS
PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections
AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS
PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME

Description
Wheelbase & Frame
5275MM (208 INCH) WHEELBASE
9.5MM X 89.0MM X 304.0MM STEEL FRAME (0.37X3.50X11.97 INCH) 120 KSI
1825MM (72 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 71 INCH TO 80 INCH
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) 142.52 in
CALC'D FRAME LENGTH - OVERALL 324.73 in
FRAME HEIGHT TOP FRONT UNLADEN 41.12 in
FRAME HEIGHT TOP FRONT LADEN 39.15 in
FRAME HEIGHT TOP REAR UNLADEN 42.96 in
FRAME HEIGHT TOP REAR LADEN 41.65 in
SQUARE END OF FRAME
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD CAST ALUMINUM CROSSMEMBER BACK OF TRANSMISSION
STANDARD CAST ALUMINUM MIDSHIP
STANDARD CAST ALUMINUM REARMOST CROSSMEMBER
STANDARD SUSPENSION CROSSMEMBER
CAST ALUMINUM REAR SUSPENSION CROSSMEMBER
Chassis Equipment
UNPOLISHED ALUMINUM WST EQUIPMENT COVERS
BRIGHT STEEL 1/8 INCH VOCATIONAL BUMPER
REMOVABLE FRONT TOW/RECOVERY DEVICE,STORED ON CHASSIS FRAME
BUMPER MOUNTING FOR SINGLE LICENSE PLATE
HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS



Description
EXTERIOR HARNESSSES WRAPPED IN ABRASION TAPE
Fuel Tanks
80 GALLON/302 LITER ALUMINUM FUEL TANK - LH
25 INCH DIAMETER FUEL TANK(S)
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH
FUEL TANK CAP(S)
EQUIFLO INBOARD FUEL SYSTEM
HIGH TEMPERATURE REINFORCED NYLON FUEL LINE
Tires
CONTINENTAL HSR3 11R22.5 14 PLY RADIAL FRONT TIRES
CONTINENTAL HSR3 11R22.5 14 PLY RADIAL REAR TIRES
Wheels
ACCURIDE 29169 22.5X8.25 10-HUB PILOT 5-HAND HD STEEL DISC FRONT WHEELS
ACCURIDE 29169 22.5X8.25 10-HUB PILOT 5-HAND HD STEEL DISC REAR WHEELS
NO FRONT AXLE WHEEL/HUB COVER
FRONT WHEEL MOUNTING NUTS
REAR WHEEL MOUNTING NUTS
Cab Exterior
111.6 INCH BBC CONVENTIONAL ALUMINUM CAB
STAINLESS STEEL CAB ACCENT MOLDING
FRONT FENDERS
INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES

**Prepared For :**  
Kaylyn Mitman  
NC SHERIFFS ASSOCIATION  
PO BOX 20049  
RALEIGH, NC 27619  
UNITED STATES  
Phone : 919-459-6471

**Prepared by:**  
Todd Lenhart  
PIEDMONT TRUCK CENTER, INC.  
412 SOUTH REGIONAL ROAD  
GREENSBORO, NC 27409  
Phone :3366682401

---

**Description**

---

BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK  
SCREEN

X-SERIES STEEL REINFORCED ALUMINUM CAB

X-SERIES VOCATIONAL HOOD

HOOD OPENING ASSIST WITH LOCKING STRUT

WESTERN STAR NAMEPLATES

DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR  
HORNS

SINGLE ELECTRIC HORN

REAR LICENSE PLATE MOUNT END OF FRAME

DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH  
HEATED LENS SYSTEM

ROOF MOUNTED LED MARKER LIGHTS

DAYTIME RUNNING LIGHTS

INTEGRAL LED STOP/TAIL/BACKUP LIGHTS

LED SIDE TURN SIGNAL

C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS  
WITH INTEGRAL HEATED CONVEX, DUAL REMOTE,  
STAINLESS STEEL BACK COVER, AND BLACK C-BAR

102 INCH EQUIPMENT WIDTH

LH AND RH CONVEX MIRRORS INTEGRAL WITH  
PRIMARY MIRRORS

RH DOWN VIEW MIRROR

STANDARD SIDE/REAR REFLECTORS

REAR REFLECTIVE DEVICE

UNPOLISHED ALUMINUM WST AFTERTREATMENT  
SYSTEM COVER

SINGLE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20  
INCH

1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD

Description
8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR
Cab Interior
X-SERIES BASE INTERIOR TRIM LEVEL PACKAGE
CHARCOAL BLACK VINYL BASE LEVEL INTERIOR
CARBON WITH BASE BLACK ACCENT
BLACK MATS
(2) DASH MOUNTED POWER OUTLETS AND COIN TRAY
FORWARD ROOF MOUNTED CONSOLE
LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS
(2) COAT HOOKS ON BACKWALL OF CAB
DIGITAL ALARM CLOCK IN DRIVER DISPLAY
STANDARD HEATER PLUMBING
RADIATOR MOUNTED AIR CONDITIONER CONDENSER
STANDARD INSULATION
STANDARD LED CAB LIGHTING
REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME
KEY QUANTITY OF 2
LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION
BLACK DOOR HANDLES
BASIC 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION AND TILT
BASIC 2.0 HIGH BACK NON SUSPENSION PASSENGER SEAT
NO SEAT ARMREST

Description
BLACK MORDURA CLOTH DRIVER SEAT COVER WITH EMBROIDERED LOGO
BLACK MORDURA CLOTH PASSENGER SEAT COVER WITH EMBROIDERED LOGO
3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND FIXED D-RING RETRACTOR PASSENGER SEAT BELTS
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN
4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES
DRIVER AND PASSENGER INTERIOR SUN VISORS

Instruments & Controls
STOCK TRUCK/UPFIT PACKAGE LVL 1
EXTRA GRIP FOOT CLUTCH PEDAL PAD, NON-ADJUSTABLE SUSPENDED PEDALS
ELECTRONIC ACCELERATOR CONTROL
BLACK GAUGE BEZELS
STANDARD CENTER INSTRUMENT PANEL
DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS
ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY
PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY
DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH
2 INCH ELECTRIC FUEL GAUGE
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE
NO ENGINE OIL TEMPERATURE GAUGE

**Prepared For :**  
Kaylyn Mitman  
NC SHERIFFS ASSOCIATION  
PO BOX 20049  
RALEIGH, NC 27619  
UNITED STATES  
Phone : 919-459-6471

**Prepared by:**  
Todd Lenhart  
PIEDMONT TRUCK CENTER, INC.  
412 SOUTH REGIONAL ROAD  
GREENSBORO, NC 27409  
Phone :3366682401

---

**Description**

---

ELECTRIC ENGINE OIL PRESSURE GAUGE

2 INCH TRANSMISSION OIL TEMPERATURE GAUGE

ELECTRONIC OUTSIDE TEMPERATURE SENSOR  
DISPLAY IN DRIVER MESSAGE CENTER

ENGINE, TRIP AND PTO HOUR METERS INTEGRAL  
WITHIN DRIVER DISPLAY

NO PTO CONTROLS

NO OBSTACLE DETECTION SYSTEM

ELECTRONIC STABILITY CONTROL

NO LANE DEPARTURE WARNING SYSTEM

TMC RP1226 ACCESSORY CONNECTOR LOCATED  
BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL

AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH,  
USB AND AUXILIARY INPUTS, J1939

DASH MOUNTED RADIO

STANDARD SPEAKER SYSTEM

NO AM/FM RADIO ANTENNA

POWER AND GROUND WIRING PROVISION OVERHEAD

ROOF/OVERHEAD CONSOLE CB RADIO PROVISION

SINGLE REMOTE SPEAKER WITH LEAD FOR 2-WAY  
RADIO

SINGLE FIBERGLASS LH MIRROR MOUNTED CB  
ANTENNA WITH BRACKET AND LEAD

HEADLINER MULTI-BAND ANTENNA:  
AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS

ELECTRONIC MPH SPEEDOMETER WITH SECONDARY  
KPH SCALE, WITHOUT ODOMETER

ELECTRONIC 2500 RPM TACHOMETER

DETROIT CONNECT PLATFORM HARDWARE

5 YEARS DAIMLER CONNECTIVITY BASE PACKAGE  
(FEATURES VARY BY MODEL) POWERED BY DETROIT  
CONNECT

Description
IGNITION SWITCH CONTROLLED ENGINE STOP
FOUR EXTRA HARDWIRED SWITCHES IN DASH, ROUTE TO UNDER CAB, CAPPED
HARDWIRE SWITCH #1, ON/OFF LATCHING, 10 AMPS BATTERY POWER
HARDWIRE SWITCH #2, ON/OFF LATCHING, 10 AMPS BATTERY POWER
HARDWIRE SWITCH #3,ON/OFF LATCHING, 10 AMPS BATTERY POWER
HARDWIRE SWITCH #4,ON/OFF LATCHING, 10 AMPS BATTERY POWER
PRE-TRIP INSPECTION FEATURE FOR EXTERIOR LAMPS ONLY
BW TRACTOR PROTECTION VALVE
TRAILER HAND CONTROL BRAKE VALVE
2 INCH TURBO AIR PRESSURE GAUGE
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY
ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS
TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006EY WHITE ELITE EY

BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

**Prepared For :**

Kaylyn Mitman  
NC SHERIFFS ASSOCIATION  
PO BOX 20049  
RALEIGH, NC 27619  
UNITED STATES  
Phone : 919-459-6471

**Prepared by:**

Todd Lenhart  
PIEDMONT TRUCK CENTER, INC.  
412 SOUTH REGIONAL ROAD  
GREENSBORO, NC 27409  
Phone :3366682401

**Other Factory Charges**

GHG21 ENHANCEMENT PRICE  
5 YRS DAIMLER CONNECTIVITY BASE PKG (VARY BY MODEL)  
POWERED BY DETROIT CONNECT  
FRONT TIRE SURCHARGE  
REAR TIRE SURCHARGE  
MY24/CY23 PRICING SURCHARGE  
STANDARD DESTINATION CHARGE

(+) Weights Shown are estimates only.  
If weight is critical, contact Customer Application Engineering.

(\*\*) Prices shown do not include taxes, fees, etc... "Net Equipment Selling Price" is located on the Quotation Details Proposal Report.

(\*\*\*) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.