

Prepared For :
Kaylyn Mitman
NC SHERIFFS ASSOCIATION
PO BOX 20049
RALEIGH, NC 27619
UNITED STATES
Phone : 919-459-6471

Prepared by:
Todd Lenhart
PIEDMONT TRUCK CENTER, INC.
412 SOUTH REGIONAL ROAD
GREENSBORO, NC 27409
Phone :3366682401

A proposal for
NC SHERIFFS ASSOCIATION

Prepared by
PIEDMONT TRUCK CENTER, INC.

Todd Lenhart

April 19, 2023

Western Star 49X



Components shown may not reflect all spec'd options and are not to scale

SPECIFICATION PROPOSAL

Description
Price Level
WST 47X/49X PRL-27X (EFF:MY24 ORDERS)
Data Version
SPECPRO21 DATA RELEASE VER 038
Vehicle Configuration
WESTERN STAR 49X
2024 MODEL YEAR SPECIFIED
SET FORWARD AXLE - TRACTOR
TRAILER TOWING PROVISION FORWARD OF FIFTH WHEEL
LH PRIMARY STEERING LOCATION
General Service
TRACTOR/TRAILER CONFIGURATION
DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)
PICKUP AND DELIVERY/SHORT HAUL SERVICE
GOVERNMENT BUSINESS SEGMENT
GENERAL FREIGHT COMMODITY
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS
MAXIMUM 8% EXPECTED GRADE
SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE
WESTERN STAR ON-HIGHWAY WARRANTY
EXPECTED FRONT AXLE(S) LOAD 12000.0 lbs
EXPECTED REAR DRIVE AXLE(S) LOAD 40000.0 lbs
EXPECTED GROSS VEHICLE WEIGHT CAPACITY 52000.0 lbs

Prepared For :
Kaylyn Mitman
NC SHERIFFS ASSOCIATION
PO BOX 20049
RALEIGH, NC 27619
UNITED STATES
Phone : 919-459-6471

Prepared by:
Todd Lenhart
PIEDMONT TRUCK CENTER, INC.
412 SOUTH REGIONAL ROAD
GREENSBORO, NC 27409
Phone :3366682401

Description

EXPECTED GROSS COMBINATION WEIGHT 80000.0 lbs

Truck Service

TRACTOR ONLY WITH NO BODY UPFIT

Tractor Service

VAN TRAILER

SINGLE (1) TRAILER

Engine

CUM X12 350 HP @ 1800 RPM, 1350 LB-FT @ 1000 RPM,
1800 GOV RPM

Electronic Parameters

73 MPH ROAD SPEED LIMIT

CRUISE CONTROL SPEED LIMIT 2 MPH HIGHER THAN
ROAD SPEED LIMIT

Engine Equipment

2010 EPA/CARB/GHG21 CONFIGURATION

NO 2008 CARB EMISSION CERTIFICATION

STANDARD OIL PAN

ENGINE MOUNTED OIL CHECK AND FILL

SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR
CLEANER

DR 12V 160 AMP 28-SI QUADRAMOUNT PAD
ALTERNATOR WITH REMOTE BATTERY VOLT SENSE

(3) DTNA GENUINE, HIGH TEMP AGM STARTING AND
CYCLING, MIN 2775CCA, 570RC, THREADED STUD
BATTERIES

PASSENGER SEAT BATTERY BOX VENTED TO OUTSIDE
OF CAB

BATTERY BOX MOUNTED UNDER PASSENGER SEAT

WIRE GROUND RETURN FOR BATTERY CABLES WITH
ADDITIONAL FRAME GROUND RETURN

PLASTIC BATTERY BOX COVER

CUMMINS NATURALLY ASPIRATED 25.9 CFM AIR
COMPRESSOR WITH INTERNAL SAFETY VALVE

Prepared For :
Kaylyn Mitman
NC SHERIFFS ASSOCIATION
PO BOX 20049
RALEIGH, NC 27619
UNITED STATES
Phone : 919-459-6471

Prepared by:
Todd Lenhart
PIEDMONT TRUCK CENTER, INC.
412 SOUTH REGIONAL ROAD
GREENSBORO, NC 27409
Phone :3366682401

Description

ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM

CUMMINS INTEBRAKE BRAKE WITH HIGH MED LOW
BRAKE

RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL
AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-
PILLAR MOUNTED VERTICAL TAILPIPE

ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER
THE ROAD ACTIVE REGENERATION AND VIRTUAL
REGENERATION REQUEST SWITCH IN CLUSTER AND
DASH MOUNTED INHIBIT SWITCH

11 FOOT 06 INCH (138 INCH+0/-5.9 INCH) EXHAUST
SYSTEM HEIGHT

RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED
ROUTED FROM STEP

23 GALLON DIESEL EXHAUST FLUID TANK

UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID
TANK COVER

LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID
TANK LOCATION

STANDARD DIESEL EXHAUST FLUID TANK CAP

STAINLESS STEEL AFTERTREATMENT
DEVICE/MUFFLER/TAILPIPE SHIELD

AIR POWERED ON/OFF ENGINE FAN CLUTCH

AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH,
NON ENGINE MOUNTED

DETROIT FUEL/WATER SEPARATOR WITH WATER IN
FUEL SENSOR

CUMMINS SPIN ON FUEL FILTER

FULL FLOW OIL FILTER

1400 SQUARE INCH VOCATIONAL RADIATOR

ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE)
EXTENDED LIFE COOLANT

GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT

RADIATOR DRAIN VALVE

LOWER RADIATOR GUARD

Description
DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH
Transmission
EATON FULLER FRO-16210C TRANSMISSION
Transmission Equipment
QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP
EATON ADVANTAGE 15-1/2 INCH SELF ADJUSTING CLUTCH
TORQUE LIMITING CLUTCH BRAKE
ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING
HYDRAULIC CLUTCH CONTROL
ALUMINUM CLUTCH HOUSING
NO PTO MOUNTING LOCATION SPECIFIED
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN
PAINTED SHIFT LEVER, SOLID LINKAGE
AIR TO OIL TRANSMISSION COOLER
SYNTHETIC TRANSMISSION LUBE
Front Axle and Equipment
DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE
CONMET PRESET PLUS PREMIUM ALUMINUM FRONT HUBS
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
2011/2013-FMVSS 121 RSD FRONT BRAKE LINING
CONMET CAST IRON FRONT BRAKE DRUMS
FRONT BRAKE DUST SHIELDS
FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL

Prepared For :
Kaylyn Mitman
NC SHERIFFS ASSOCIATION
PO BOX 20049
RALEIGH, NC 27619
UNITED STATES
Phone : 919-459-6471

Prepared by:
Todd Lenhart
PIEDMONT TRUCK CENTER, INC.
412 SOUTH REGIONAL ROAD
GREENSBORO, NC 27409
Phone :3366682401

Description

MERITOR AUTOMATIC FRONT SLACK ADJUSTERS

SINGLE POWER STEERING GEAR, BENDIX, 12-13.3K

2 QUART SEE THROUGH POWER STEERING RESERVOIR

CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE
LUBE

Front Suspension

12,000# DUAL TAPERLEAF FRONT SUSPENSION

MAINTENANCE FREE RUBBER BUSHINGS - FRONT
SUSPENSION

FRONT SHOCK ABSORBERS

Rear Axle and Equipment

DETROIT DA-RT-40.0-4S HH 40,000# R-SERIES TANDEM
REAR AXLE

CONMET PRESET PLUS PREMIUM ALUMINUM REAR
HUBS

3.58 REAR AXLE RATIO

IRON REAR AXLE CARRIER WITH STANDARD AXLE
HOUSING

MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE
WITH HALF ROUND YOKES

MXL 17T MERITOR EXTENDED LUBE INTERAXLE
DRIVELINE WITH HALF ROUND YOKES

(1) INTERAXLE LOCK VALVE FOR TANDEM DRIVE AXLES

INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT
SWITCH WITH IAD FEEDBACK

MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR
BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

2011/2013-FMVSS 121 RSD REAR BRAKE LININGS

BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF
DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS

GUNITE CAST IRON REAR BRAKE DRUMS

REAR BRAKE DUST SHIELDS

REAR OIL SEALS

Description
WABCO TRISTOP D LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS
MERITOR AUTOMATIC REAR SLACK ADJUSTERS
FE 75W-85 REAR AXLE LUBE
STANDARD REAR AXLE BREATHER(S)

Rear Suspension

- AIRLINER 40,000# REAR SUSPENSION
- 7.9 INCH NOMINAL RIDE HEIGHT (415MM GLOBAL
REFERENCE HEIGHT)
- STANDARD AXLE SEATS IN AXLE CLAMP GROUP
- 51 INCH AXLE SPACING
- IGNITION CONTROLLED ELECTRIC DUMP SWITCH FOR
AIR SUSPENSION WITH STATE RETENTION AND GAUGE
- REAR AIR SUSPENSION DUMP VALVE AUTOFILL >5 MPH
WITH INDICATOR LIGHT
- SINGLE AIR REAR SUSPENSION LEVELING VALVE
- TRANSVERSE CONTROL RODS
- REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR
RIDE SUSPENSION)

Brake System

- WABCO 6S/4M ABS WITH TRACTION CONTROL WITH ATC
SHUT OFF SWITCH
- REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID
CHASSIS AIR LINES
- RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO
REAR PROPORTIONING VALVE
- WABCO SYSTEM SAVER HP WITH INTEGRAL AIR
GOVERNOR AND HEATER
- WABCO OIL COALESCING FILTER FOR AIR DRYER
- AIR DRYER FRAME MOUNTED
- STEEL AIR BRAKE RESERVOIRS
- PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections

Description
12 FOOT STRAIGHT TRAILER AIR HOSE
36 INCH STAINLESS STEEL SLIDE BAR WITH SPRING TYPE AIR HOSE HANGER
COMBINATION DUMMY GLAD HANDS AND LIGHT PLUG HOLDER MOUNTED LH BACK OF CAB WITH GROUND ACCESS
PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED BACK OF CAB/BACK OF SLEEPER
INBOARD FLAG BRACKET LOCATED AT BACK OF CAB/BACK OF SLEEPER
12 FOOT DETACHABLE STRAIGHT PRIMARY TRAILER ELECTRICAL CABLE WITH SAE J560 CONNECTOR

Wheelbase & Frame
4840MM (191 INCH) WHEELBASE, SFA ONLY
8.0MM X 82.0MM X 281.0MM STEEL FRAME (0.32X3.23X11.06 INCH) 120 KSI
1475MM (58 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 51 INCH TO 60 INCH
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) 99.21 in
CALC'D FRAME LENGTH - OVERALL 277.47 in
FRAME HEIGHT TOP FRONT UNLADEN 40.86 in
FRAME HEIGHT TOP FRONT LADEN 38.73 in
FRAME HEIGHT TOP REAR UNLADEN 40.05 in
FRAME HEIGHT TOP REAR LADEN 38.48 in
FLANGE TAPERED END OF FRAME, GRIND AND POLISH WELDS
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD CROSSMEMBER BACK OF TRANSMISSION
STANDARD CAST ALUMINUM MIDSHIP

Description
STANDARD REARMOST CROSSMEMBER
STANDARD CAST ALUMINUM FORWARD CROSSMEMBER
CAST ALUMINUM REAR SUSPENSION CROSSMEMBER
Chassis Equipment
UNPOLISHED ALUMINUM WST EQUIPMENT COVERS
LH BACK OF CAB ACCESS, GRAB HANDLES WITH SINGLE RUBBER INSERT
14 INCH (350MM) DECK PLATE FLUSH MOUNTED BETWEEN RAILS
BRIGHT STEEL 1/8 INCH VOCATIONAL BUMPER
REMOVABLE FRONT TOW/RECOVERY DEVICE,STORED ON CHASSIS FRAME
BUMPER MOUNTING FOR SINGLE LICENSE PLATE
BETTS B-23 PAINTED COILED MUDFLAP BRACKETS
WESTERN STAR LOGO BLACK MUDFLAPS
HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS EXCLUDING FIFTH WHEEL
EXTERIOR HARNESES WRAPPED IN ABRASION TAPE

Fifth Wheel
FONTAINE 6000 SERIES 6NWB 24.0 INCH AIR SLIDE FIFTH WHEEL
FIFTH WHEEL 305MM (12.0 INCHES) AHEAD OF SUSPENSION CENTERLINE
197MM (7.75 INCH) FIFTH WHEEL HEIGHT
STEEL OUTBOARD ANGLE - FIFTH WHEEL MOUNTING
DASH MOUNTED CONTROL AND PLUMBING FOR FIFTH WHEEL
SIDE LEFT FIFTH WHEEL RELEASE

Fuel Tanks
80 GALLON/302 LITER ALUMINUM FUEL TANK - LH
25 INCH DIAMETER FUEL TANK(S)

Description
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH
FUEL TANK CAP(S)
EQUIFLO INBOARD FUEL SYSTEM
HIGH TEMPERATURE REINFORCED NYLON FUEL LINE

Tires
BRIDGESTONE R213 ECOPIA 11R22.5 14 PLY RADIAL FRONT TIRES
CONTINENTAL HDL2 11R22.5 14 PLY RADIAL REAR TIRES

Wheels
ACCURIDE 29169 22.5X8.25 10-HUB PILOT 5-HAND HD STEEL DISC FRONT WHEELS
ACCURIDE 51487 ACCU-LITE 22.5X8.25 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS
NO FRONT AXLE WHEEL/HUB COVER
FRONT WHEEL MOUNTING NUTS
REAR WHEEL MOUNTING NUTS

Cab Exterior
121 INCH BBC ALUMINUM CONVENTIONAL CAB
STAINLESS STEEL CAB ACCENT MOLDING
FRONT FENDERS
INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES
BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN
X-SERIES STEEL REINFORCED ALUMINUM CAB
X-SERIES VOCATIONAL HOOD

Description
HOOD OPENING ASSIST WITH LOCKING STRUT
WESTERN STAR NAMEPLATES
DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS
SINGLE ELECTRIC HORN
REAR LICENSE PLATE MOUNT END OF FRAME
DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM
ROOF MOUNTED LED MARKER LIGHTS
DAYTIME RUNNING LIGHTS
INTEGRAL LED STOP/TAIL/BACKUP LIGHTS
LED SIDE TURN SIGNAL
C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR
102 INCH EQUIPMENT WIDTH
LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS
RH DOWN VIEW MIRROR
STANDARD SIDE/REAR REFLECTORS
REAR REFLECTIVE DEVICE
UNPOLISHED ALUMINUM WST AFTERTREATMENT SYSTEM COVER
SINGLE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20 INCH
1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD
8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR
Cab Interior
X-SERIES BASE INTERIOR TRIM LEVEL PACKAGE
CHARCOAL BLACK VINYL BASE LEVEL INTERIOR

Prepared For :
Kaylyn Mitman
NC SHERIFFS ASSOCIATION
PO BOX 20049
RALEIGH, NC 27619
UNITED STATES
Phone : 919-459-6471

Prepared by:
Todd Lenhart
PIEDMONT TRUCK CENTER, INC.
412 SOUTH REGIONAL ROAD
GREENSBORO, NC 27409
Phone :3366682401

Description

CARBON WITH BASE BLACK ACCENT

BLACK MATS

(2) DASH MOUNTED POWER OUTLETS AND COIN TRAY

FORWARD ROOF MOUNTED CONSOLE

LH AND RH DOOR STORAGE POCKETS INTEGRATED
INTO MOLDED DOOR PANELS

(2) COAT HOOKS ON BACKWALL OF CAB

DIGITAL ALARM CLOCK IN DRIVER DISPLAY

STANDARD HEATER PLUMBING

RADIATOR MOUNTED AIR CONDITIONER CONDENSER

STANDARD INSULATION

STANDARD LED CAB LIGHTING

REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS

DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME

KEY QUANTITY OF 2

LH AND RH ELECTRIC DOOR LOCKS WITH AUTO
UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO
CLOSED POSITION

BLACK DOOR HANDLES

BASIC 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT
WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION
EXTENSION AND TILT

BATTERY BOX MID BACK NON SUSPENSION
PASSENGER SEAT

NO SEAT ARMREST

BLACK MORDURA CLOTH DRIVER SEAT COVER WITH
EMBROIDERED LOGO

BLACK MORDURA CLOTH PASSENGER SEAT COVER
WITH NO LOGO

3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND
FIXED D-RING RETRACTOR PASSENGER SEAT BELTS

Description
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN
4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES
DRIVER AND PASSENGER INTERIOR SUN VISORS

Instruments & Controls

- STOCK TRUCK/UPFIT PACKAGE LVL 1
- EXTRA GRIP FOOT CLUTCH PEDAL PAD, NON-ADJUSTABLE SUSPENDED PEDALS
- ELECTRONIC ACCELERATOR CONTROL
- BLACK GAUGE BEZELS
- STANDARD CENTER INSTRUMENT PANEL
- DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE
- INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS
- ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES
- KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION
OFF/RUN/START/ACCESSORY
- PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY
- DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY
- HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH
- 2 INCH ELECTRIC FUEL GAUGE
- ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE
- ENGINE OIL TEMPERATURE GAUGE
- ELECTRIC ENGINE OIL PRESSURE GAUGE
- 2 INCH TRANSMISSION OIL TEMPERATURE GAUGE
- ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER

Prepared For :
Kaylyn Mitman
NC SHERIFFS ASSOCIATION
PO BOX 20049
RALEIGH, NC 27619
UNITED STATES
Phone : 919-459-6471

Prepared by:
Todd Lenhart
PIEDMONT TRUCK CENTER, INC.
412 SOUTH REGIONAL ROAD
GREENSBORO, NC 27409
Phone :3366682401

Description

ENGINE, TRIP AND PTO HOUR METERS INTEGRAL
WITHIN DRIVER DISPLAY

NO PTO CONTROLS

NO OBSTACLE DETECTION SYSTEM

ELECTRONIC STABILITY CONTROL

NO LANE DEPARTURE WARNING SYSTEM

TMC RP1226 ACCESSORY CONNECTOR LOCATED
BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL

AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH,
USB AND AUXILIARY INPUTS, J1939

DASH MOUNTED RADIO

STANDARD SPEAKER SYSTEM

NO AM/FM RADIO ANTENNA

POWER AND GROUND WIRING PROVISION OVERHEAD

ROOF/OVERHEAD CONSOLE CB RADIO PROVISION

SINGLE REMOTE SPEAKER WITH LEAD FOR 2-WAY
RADIO

SINGLE FIBERGLASS LH MIRROR MOUNTED CB
ANTENNA WITH BRACKET AND LEAD

HEADLINER MULTI-BAND ANTENNA:
AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS

ELECTRONIC MPH SPEEDOMETER WITH SECONDARY
KPH SCALE, WITHOUT ODOMETER

ELECTRONIC 2500 RPM TACHOMETER

DETROIT CONNECT PLATFORM HARDWARE

5 YEARS DAIMLER CONNECTIVITY BASE PACKAGE
(FEATURES VARY BY MODEL) POWERED BY DETROIT
CONNECT

IGNITION SWITCH CONTROLLED ENGINE STOP

FOUR EXTRA HARDWIRED SWITCHES IN DASH, ROUTE
TO UNDER CAB, CAPPED

HARDWIRE SWITCH #1, ON/OFF LATCHING, 10 AMPS
BATTERY POWER

Description
HARDWIRE SWITCH #2, ON/OFF LATCHING, 10 AMPS BATTERY POWER
HARDWIRE SWITCH #3,ON/OFF LATCHING, 10 AMPS BATTERY POWER
HARDWIRE SWITCH #4,ON/OFF LATCHING, 10 AMPS BATTERY POWER
PRE-TRIP INSPECTION FEATURE FOR EXTERIOR LAMPS ONLY
BW TRACTOR PROTECTION VALVE
TRAILER HAND CONTROL BRAKE VALVE
2 INCH TURBO AIR PRESSURE GAUGE
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY
ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS
TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006EY WHITE ELITE EY

BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

POWDER WHITE (N0006EA) FRONT WHEELS/RIMS
(PKWHT21, TKWHT21, W, TW)

POWDER WHITE (N0006EA) REAR WHEELS/RIMS
(PKWHT21, TKWHT21, W, TW)

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND
GLIDER KITS

Prepared For :
Kaylyn Mitman
NC SHERIFFS ASSOCIATION
PO BOX 20049
RALEIGH, NC 27619
UNITED STATES
Phone : 919-459-6471

Prepared by:
Todd Lenhart
PIEDMONT TRUCK CENTER, INC.
412 SOUTH REGIONAL ROAD
GREENSBORO, NC 27409
Phone :3366682401

Other Factory Charges

GHG21 ENHANCEMENT PRICE
5 YRS DAIMLER CONNECTIVITY BASE PKG (VARY BY MODEL)
POWERED BY DETROIT CONNECT
FRONT TIRE SURCHARGE
REAR TIRE SURCHARGE
MY24/CY23 PRICING SURCHARGE
STANDARD DESTINATION CHARGE

(+) Weights Shown are estimates only.
If weight is critical, contact Customer Application Engineering.

(**) Prices shown do not include taxes, fees, etc... "Net Equipment Selling Price" is located on the Quotation Details Proposal Report.

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.