

Dempster 1303C

Hot PTO/pump

Inside air controls

In-Tank return line filter

Valve mounted pressure gauge

Standard paint w/ hardener

Complete factory mounting

Specifications are listed below (click for [comparison](#) or [chassis](#) information).



MINIMUM TRUCK CHASSIS SPECIFICATIONS

Model	Minimum bare chassis wts. Tilt or conv. Cab	W.B. for max. load	CA/CT minimum	Ground reactions with max. rated load
1303-C	Front - 4,000	148	84 CA	Front - 5,050
	Rear - 2,500			Rear - 17,500

GROSS LIFTING CAPACITIES FOR TYPICAL CONTAINER SIZES (lbs.)

Container sizes (cubic yards)

Model	3	4	5	6	8	10	12	15
1303-C	11,550	11,160	10,760	10,200	9,990	9,360	8,400	7,600

LFW MODEL SPECIFICATIONS

Model	Recommended gross lifting capacity in 3 cu. yd. container	Vert cylinder single acting dia. & stroke	Horizontal cylinder double-acting dia. & stroke	Stabilizing jacks (2) double-acting dia. & stroke	Export cube in cubic feet	Shipping weight
1303-C	11,550 lbs.	6" x 26 1/2"	5" x 49"	-	500	5,000 lbs.