

Dempster 1303H

Hot PTO/pump

Inside air controls

In-Tank return line filter

Valve mounted pressure gauge

Standard paint w/ hardener

Complete factory mounting

Specifications are listed below (click for [comparison](#) or [chassis](#) information).



MINIMUM TRUCK CHASSIS SPECIFICATIONS

Model	Minimum bare chassis wts. Tilt or conv. Cab	W.B. for max. load	CA/CT minimum	Ground reactions with max. rated load
1303-H	Front - 4,600	148	84 CA	Front - 5,750
	Rear - 3,000			Rear - 21,550

GROSS LIFTING CAPACITIES FOR TYPICAL CONTAINER SIZES (lbs.)

Container sizes (cubic yards)

Model	3	4	5	6	8	10	12	15
1303-H	13,600	12,720	12,030	11,200	10,640	9,520	7,840	N/A

LFW MODEL SPECIFICATIONS

Model	Recommended gross lifting capacity in 3 cu. yd. container	Vert cylinder single acting dia. & stroke	Horizontal cylinder double-acting dia. & stroke	Stabilizing jacks (2) double-acting dia. & stroke	Export cube in cubic feet	Shipping weight
1303-H	13,600 lbs.	6" x 24 1/2"	6" x 46"		500	6,500 lbs.