

Dempster 1403C

Hot PTO/pump

Inside air controls

In-Tank return line filter

Valve mounted pressure gauge

Standard paint w/ hardener

Complete factory mounting

Specifications are listed below (click for [comparison](#) or [chassis information](#)).



MINIMUM TRUCK CHASSIS SPECIFICATIONS

Model	Minimum bare chassis wts. Tilt or conv. Cab	W.B. for max. load	CA/CT minimum	Ground reactions with max. rated load
1403-C	Front - 5,000	166	102 CA	Front - 6,700
	Rear - 3,000			Rear - 22,050

GROSS LIFTING CAPACITIES FOR TYPICAL CONTAINER SIZES (lbs.)

Container sizes (cubic yards)

Model	3	4	5	6	8	10	12	15
1403-C	14,940	14,250	13,730	13,140	12,690	11,880	10,800	9,570

LFW MODEL SPECIFICATIONS

Model	Recommended gross lifting capacity in 3 cu. yd. container	Vert cylinder double acting dia. & stroke	Horizontal cylinder double-acting dia. & stroke	Stabilizing jacks (2) double-acting dia. & stroke	Export cube in cubic feet	Shipping weight
1403-C	15,000 lbs.	7" x 32"	6" x 52"	3" x 14"	531	7,000 lbs.