

Dempster 1603C

Hot PTO/pump

Inside air controls

In-Tank return line filter

Valve mounted pressure gauge

Standard paint w/ hardener

Complete factory mounting

Specifications are listed below (click for [comparison](#) or [chassis](#) information).



MINIMUM TRUCK CHASSIS SPECIFICATIONS

Model	Minimum bare chassis wts. Tilt or conv. Cab	W.B. for max. load	CA/CT minimum	Ground reactions with max. rated load
1603-C	Front - 6,000	162	102 CA/84 CT	Front - 7,350
	Rear - 6,500			Rear - 36,700 (Tandem)

GROSS LIFTING CAPACITIES FOR TYPICAL CONTAINER SIZES (lbs.)

Container sizes (cubic yards)

Model	3	4	5	6	8	10	12	15
1603-C	23,180	22,230	21,280	20,330	19,160	17,990	16,800	14,220

LFW MODEL SPECIFICATIONS

Model	Recommended gross lifting capacity in 3 cu. yd. container	Vert cylinder double acting dia. & stroke	Horizontal cylinder double-acting dia. & stroke	Stabilizing jacks (2) double-acting dia. & stroke	Export cube in cubic feet	Shipping weight
1603-C	23,180 lbs.	7" x 32"	6" x 52"	3" x 14"	590	8,600 lbs.