

### Heil PT1000 Rear Loader-18 Cubic Yard

#### ALL ITEMS FACTORY INSTALLED UNLESS OTHERWISE INDICATED

#### **Base Body**

Body floor- 10 Gauge 50.000 psi; Flat Floor Design with Interlaced Subframe Body Side- 10 Gauge, 50.000 psi Body Roof- 8 Gauge, 50,000 psi Tailgate Sides- 10 Gauge, 50,000 psi Hopper floor-3/16" AR 400. 184,000 psi Packer Blade-3/16", 150,000 psi Body Width - 96" Body Height 93" Body weight-10,000 to 12,300 Hopper Size – 3 Cubic Yard Hopper Loading Width – 80" Load sill Height – Even to 3.5 Below chassis frame Height Cycle Time Approximately 16-18 Seconds Compaction Ratio 800-900 lbs per Cubic Yard Sweep Cylinders - 4.5" Pack Cylinders - 4.0" Hydraulic Pump – 48 GPM System Pressure – 2,750 psi 3-Micron Return Line Oil Filter In-cab Filter Bypass Monitor One (1) Year Body Warranty Factory Mounting Direct Mount Gear Pump Hot Shift PTO with Overspeed Protection Hopper Worklight Multi-function Smart Light System with full body LED Light **Dual Rear Buzzers** Streetside Body Access Door Regenerative Valve for Faster Packer and Reload Times Body Undercoating Rear Vision Camera system with 7" flat Screen Color Monitor **Dual Factory cart Tipper Hydraulics** Incoming Freight and Service



### WE NEVER STOP WORKING FOR YOU





The proven single-axle refuse collection machine.

www.Heil.com

# The Heil<sup>®</sup> PT1000 High-performance single axle rear loader.

The **Heil** PT1000 will reset your expectations about single-axle rear loaders. With nearly 20 years of performance, the PT1000 is a proven refuse collection vehicle that delivers the fastest cycle time in its class, an outstanding payload, and a best-in-class hopper. It also fits comfortably into today's increasingly restricted budgets.

Beneath its sleek exterior, the PT1000 is a no-nonsense machine that will outperform anything else in its class. It offers a 15-second cycle time and a reload time of less than six seconds, with packing forces that take full advantage of the **Heil** brand's experience in high-pressure hydraulics and lighter weight, high-tensile steel construction.

The PT1000 features a large three-cubic yard hopper that is the best in its class, making it the ideal vehicle for those occasional commercial pick-ups. It can be equipped with a variety of container handling devices to suit just about any collection need. It also offers payloads of up to 800 lbs./cubic-yard, and a one-piece body sidewall that not only looks more modern, but is also easier to wash and maintain, resists rust and corrosion, and provides a smooth surface for signage.

Excluding the 25 cubic-yard body, all other sizes can be equipped as single axle models, making them Federal Excise Tax (FET) exempt.

To add the proven PT1000 to your fleet, contact your local Authorized **Heil** Dealer. To find the dealer nearest you, visit www.heil.com/dealers.

\* Heil does not provide tax advice. Please consult your tax advisor regarding the specific tax implications of your selected product.

### **The Heil**<sup>®</sup> **PT1000** Design, performance, and reliability that works for YOU.







Add 3rd Eye® Digital Packages Connect for service verification, body/chassis data, fuel tax reporting, and route management. Includes factory installed 3rd Eye Mobile, with the ability to connect up to eight cameras.



Add Roof Or Front Of Body CNG System Our system enables your CNG refuse fleet to deliver the same productivity you would expect from a diesel unit while saving money with clean, domestic, compressed natural gas fuel.



Add 3rd Eye<sup>®</sup> Collision Avoidance Radar 3rd Eye family of Integrated Collision Avoidance Radar Systems protects both your drivers, your assets, and those in close proximity to your vehicle using existing 3rd Eye Mobile camera cables.



Add Bayne Thinline<sup>®</sup> Premium Cart Tippers Outfit your truck with single or dual Bayne Thinline<sup>®</sup> premium mobile lifters and reduce the stress and strain on personnel who manually load the vehicle and increase route efficiency.

# Smarter By Design, With Loyalty Built In

The PT1000 was specifically designed to maximize your efficiency on daily collection routes.

# The Heil<sup>®</sup> PT1000



### **Reliable Rear Loader Performance**

- + **FAST CYCLE TIME** With the fastest cycle time in its class, the proven PT1000 can maximize your efficiency on daily collection routes.
- + SERVICE SMART DESIGN Easy-to-access UHMW wear parts can enable longer component life, while attaining the lowest total cost of collection.
- + SERVICE SMART SIDE DOOR Our Service Smart design simplifies routine maintenance, keeping your truck away from the shop and out servicing your customers, making money. The side door provides easy access for common maintenance tasks.
- + **SUPERIOR FILTRATION** Our three-micron filtration system keeps hydraulic oil cleaner and extends the life of the hydraulic components. Other manufacturers use 10-micron filtration, which can allow particulate matter to damage the hydraulic system.
- + **ONE-HANDED MANUAL PACKING** Convenient one-handed manual controls stop, start, or reverse the upper panel or sweep panel at any point in the packing cycle.
- + **ONE-PIECE BODY SIDEWALL** Resists rust and corrosion, easier to wash and maintain, plus the smooth sides provide optimal signage space for advertising.

## Discover What Sets The PT1000 Apart



#### HIGH CAPACITY HOPPER

When it comes to the mid-size rear loader, the PT1000 offers a large 3.0 cubic yard hopper that is key to optimizing productivity and easily handles even the bulkiest waste materials found in today's refuse collection applications.



#### **PACKING POWER**

The unique **Heil** track design enables more compaction force per square inch, utilizing the system pressure of 2,750 psi to its maximum capacity, and also delivering faster cycle times to expedite the operator's route time.



#### **OPTIMIZED BODY WEIGHT**

A payload density of up to 800 pounds per cubic yard, and a body sidewall constructed of single sheet, high-tensile steel deliver long-lasting performance without unnecessary weight.



#### **ELECTRICAL CONTROL BOX**

The power distribution electrical control box on the side of the body offers easier diagnostics of wiring issues, and minimizes the need to cut into the chassis cab interior for wiring integration.

## Smarter By Design, With Loyalty Built In

The PT1000 was specifically designed to maximize your efficiency on daily collection routes.



Performance Specifications				
Compaction	Up to 800 lbs. per yd³			
Hopper Size	3.0 yd <sup>3</sup>			
Packing Cycle Time	15-17 seconds			
Reload Time	6-8 seconds			
FET Exempt	13 yd³, 16 yd³, 18 yd³ & 20 yd³			

All designs, specifications, and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published new is for information purposes only and shall not be construct to warrant visuality of the unit for any particular purpose, as performance may vary with the conditions encountered. The only warranty is our standard written Warranty Statement for this product at the time of shipment.

Hydraulic Specifications				
PUMP				
Туре	High pressure gear			
Maximum Operating Pressure	2,750 psi			
GPM	48 GPM			
OIL RESERVOIR				
Tank Capacity (net)	45 gallons (170.3 liters)			
Filters	3 micron return filter; 140 micron suction line			
VALVES				
Shutoff	Ball type			
Packing Control	Spool type			
Ejector and Tailgate Raise	Spool type			

Tailgate Specifications		18 yd <sup>3</sup> & 20 yd <sup>3</sup>	<b>25 yd</b> ³
Hopper Capacity	yd <sup>3</sup>	3	3
Hopper Capacity		2.3	
	in.	0.5	3.5
Sill Height Below Chassis Frame (1)	mm	12.7	88.9
I I	in.	80	80
Hopper Loading Width	mm	yd <sup>9</sup> 3   m <sup>3</sup> 2.3   in. 0.5   mm 12.7   in. 80   mm 2,032   in. 67   mm 1,700	2,032
annar Ananing Haight	in.	67	67
Hopper Opening Height	mm 12.7   mm 12.7   in. 80   mm 2,032   in. 67   mm 1,700   complete 15-17	1,700	1,700
	complete	15-17	15-17
Cycle Time (seconds)	reload	5-6	5-6

# **PT1000 Specifications**

Typical Chassis Configuration		13 yd³	16 yd <sup>3</sup>	18 yd <sup>3</sup>	<b>20 yd</b> <sup>3</sup>	25 yd <sup>3</sup>
Minimum GVWR (1)		29,000	30,000	30,000	33,000	48,000
Minimum GAWR	front	9,000	9,000	9,000	10,000	14,000
	rear	20,000	21,000	21,000 (2)	23,000 (2)	34,000
Usable CA	in.	96	102-110	117-125	132-140	N/A
	mm	2,440	2,590-2,790	2,972-3,175	3,353-3,556	N/A
Usable CT	in.	N/A	N/A	N/A	114-120	146-154
	mm	N/A	N/A	N/A	2,896-3,048	3,734-3,886
Minimum Platform	in.	32	32	32	32/51	51
	mm	813	813	813	813/1,295	1,295

Any chassis sent to Heil Environmental with less than these minimum GVWR/GVARs will not be mounted. (1) If CA/CT is not as recommended, contact Heil Environmental for applicable weight distribution and GWWR/GVAR requirements. (2) Require 30,000 lbs. spring package

Body Specifications	-	13 yd³	16 yd <sup>3</sup>	18 yd <sup>3</sup>	<b>20 yd</b> <sup>3</sup>	25 yd <sup>3</sup>
Body Capacity	yd <sup>3</sup>	13	16	18	20	25
	m <sup>3</sup>	9.93	12.23	13.76	15.29	19.11
Overall Length	in.	189.25	206.75	220	234	269
	mm	4,807	5,251	5,588	5,944	6,833
Querell Longth With Tollante Daired	in.	229.25	246.75	272	286	321
Overall Length With Tailgate Raised	mm	5,823	6,267	6,909	7,264	8,154
Overall Width	in.	96	96	96	96	96
	mm	2,438	2,438	2,438	2,438	2,438
Overall Height Above Frame	in.	94	94	94	94	94
	mm	2,388	2,388	2,388	2,388	2,388
Overall Height With Tailgate Raised	in.	162	162	162	162	162
	mm	4115	4,115	4,115	4,115	4,115
Gross Weight (approximate)	lbs.	10,350	10,800	11,100	11,400	12,300
	kg.	4,899	4,899	5,035	5,170	5,580

Cylinder Specifications						
Body Cylinders	Туре	Model	Stages	Bore		
	ilgate Raise Single Acting A		1	in.	3	
l aligate Raise		ALL		mm	76.2	
Packer Sweep	Double Acting	ALL	1	in	4	
				mm	101.6	
Upper Panel	Double Acting	ALL	1	in	4.5	
				mm	114.3	
Ejection	Double Acting Telescopic	ALL	4	in	6.5	
				mm	165	



### WE NEVER STOP WORKING FOR YOU





#### EXPEDITE THE PURCHASE OF YOUR HEIL® UNIT THROUGH SOURCEWELL

Sourcewell Cooperative Purchasing Program has awarded Heil a nationally bid contract for "Solid Waste and Recycling Collection Equipment with Related Equipment, Accessories, and Supplies." Through the Heil contract, Sourcewell members can purchase any of the Heil line of refuse and recycling equipment, including front-loading, side-loading, and rear-loading refuse collection vehicles, without having to create an RFP and send the project through a time-consuming duplicate bid process. By using the existing nationally bid contract, members can receive the products they need more quickly and cost effectively. Best of all, Sourcewell membership is free! Qualified agencies can join online via the Sourcewell purchasing website at www.sourcewell-mn.gov. To find out more about purchasing Heil equipment via the Sourcewell contract, please contact your local Heil Dealer at www.heil.com/dealers.



#### **TRUST HEIL® CERTIFIED OEM PARTS**

**Heil** Certified OEM parts are the most reliable replacement parts for **Heil** refuse collection vehicles. They're made following the exact specifications and production processes on the same assembly lines as the parts originally installed on the bodies. This means that they fit perfectly every time. **Heil** uses only the highest-quality materials for parts that last - minimizing costly downtime. For more information on parts, contact your **Heil** dealer. Visit: **www.heil.com/dealers** to find the dealer nearest you.





#### **RELY ON EXPERIENCED LOCAL SUPPORT**

When you buy from **Heil**, you gain the aftermarket support of the industry's strongest network of dealers in North America. We stand behind our dealers, so you get the product support you need for the life of your products. Our dealers are also trained to help you find the best product for your particular route needs. To find the **Heil** dealer nearest you, visit: **www.heil.com/dealers**.



All **Heil** products are Connected Collections<sup>™</sup> ready. This is part of our vision, focused on helping fleet owners make better decisions, faster. For more information on **ESG's Connected Collections**, contact your local Heil dealer or visit us online at www.heil.com/connected-collections

### www.heil.com 🕧 😳 🐨 😁



#### **COUNT ON THE LOWEST TCC**

Helping you save money is our passion, and we apply tremendous resources to advance our product and service offerings to improve the profitability of your business and provide the lowest Total Cost of Collection and the maximum return on your investment. You can be confident that choosing **Heil** equipment brings a long-term partnership with the industry leader.



#### **CONFIGURATION ASSISTANCE**

Chassis layout drawings are available through your local **Heil** dealer. To find your dealer, visit **www. heil.com/dealers.** 



#### **INDUSTRY-LEADING TRAINING**

Heil has completely revamped their training programs with the addition of both the Heil Service Shack<sup>™</sup> and our fourtiered Nexteligence<sup>®</sup> Connected-Tech Training Program. Now, customers can visit the **Heil Service Shack** on the **Heil** website to learn the latest techniques and view helpful service and training videos any time, as well as sign up for Connected-Tech courses to better train technicians on **Heil** Refuse Products. Ensure your shops are servicing your **Heil** products correctly; check out the **Heil** training offerings at **www.heil.com/nexteligence**.



www.heil.com

Contact your Heil<sup>®</sup> authorized dealer: