



|                                 |                           |
|---------------------------------|---------------------------|
| <b><u>SwapLoader SL 400</u></b> | <b><u>\$60,608.00</u></b> |
|---------------------------------|---------------------------|

|                                 |                           |
|---------------------------------|---------------------------|
| <b><u>SwapLoader SL 406</u></b> | <b><u>\$64,186.00</u></b> |
|---------------------------------|---------------------------|

|                                 |                           |
|---------------------------------|---------------------------|
| <b><u>SwapLoader SL 412</u></b> | <b><u>\$61,268.00</u></b> |
|---------------------------------|---------------------------|

|                                 |                           |
|---------------------------------|---------------------------|
| <b><u>SwapLoader SL 330</u></b> | <b><u>\$58,840.00</u></b> |
|---------------------------------|---------------------------|

Pump/PTO

Mounting

Fenders

Hydraulic Oil

Finish Coat of Paint

Heavy Duty Bumper with LED Recessed Lights

Air Controls and Tower in Cab

Huck Bolts Used on Mounting

Hoist In-Bound Freight

Delivery in NC







An EFCO Company

# SWAPLOADER<sup>®</sup>

*"Hooked on Quality"*

U.S.A. LTD.



# ALL-MODEL SPECIFICATIONS






# ALL-MODEL SPECIFICATIONS

| MODEL                            |                                     |                                   | SL-75                                                                                   | SL-105                                                                                           | SL-160                     | SL-212                     | SL-214                     | SL-220                     | SL-222                     | SL-240          |  |
|----------------------------------|-------------------------------------|-----------------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|-----------------|--|
| MODEL DESCRIPTION                | DUMP CAPACITY (INCLUDING CONTAINER) |                                   | 7,500 lb                                                                                | 10,500 lb                                                                                        | 16,000 lb                  | 20,000 lb                  | 20,000 lb                  | 22,000 lb                  | 22,000 lb                  | 24,000 lb       |  |
|                                  | DUMP ANGLE                          |                                   | 56°                                                                                     | 58°                                                                                              | 56°                        | 58°                        | 57°                        | 53°                        | 53°                        | 53°             |  |
|                                  | LIFT CAPACITY (INCLUDING CONTAINER) |                                   | 7,500 lb                                                                                | 10,500 lb                                                                                        | 16,000 lb                  | 20,000 lb                  | 20,000 lb                  | 22,000 lb                  | 22,000 lb                  | 24,000 lb       |  |
|                                  | HOIST WEIGHT                        | FIXED                             | 1,250 lb                                                                                | 1,680 lb                                                                                         | 2,325 lb                   | 2,520 lb                   | 2,720 lb                   | 4,100 lb                   | 4,050 lb                   | 3,900 lb        |  |
| ADJ.                             |                                     | N/A                               | N/A                                                                                     | 2,467 lb                                                                                         | 2,640 lb                   | 2,860 lb                   | 4,330 lb                   | 4,280 lb                   | 4,200 lb                   |                 |  |
| GENERAL DIMENSIONS (SEE DIAGRAM) | HOOK TO REAR ROLLER (DIM. A)        |                                   | 114.38"                                                                                 | 116.00"                                                                                          | 139.63"                    | 138.00"                    | 153.63"                    | 193.81"                    | 179.81"                    | 159.81"         |  |
|                                  | HOOK HEIGHT (DIM. B)                | FIXED                             | 35.63"                                                                                  | 35.63"                                                                                           | 35.63"                     | 35.63"                     | 35.63"                     | 53.88"                     | 53.88"                     | 53.88"          |  |
|                                  |                                     | ADJ.                              | N/A                                                                                     | N/A                                                                                              | 35.63" / 53.88"            | 35.63" / 53.88"            | 35.63" / 53.88"            | 53.88" / 61.75"            | 53.88" / 61.75"            | 53.88" / 61.75" |  |
|                                  | HOIST HEIGHT (DIM. C)               |                                   | 5.25"                                                                                   | 5.5"                                                                                             | 7.5"                       | 7.5"                       | 7.5"                       | 9"                         | 9"                         | 9"              |  |
|                                  | HOIST CG (DIM. D)                   |                                   | 59.7"                                                                                   | 58.1"                                                                                            | 70.65"                     | 64.0"                      | 80.3"                      | 97.8"                      | 95.2"                      | 88.0"           |  |
|                                  | OPTIMUM BODY LENGTHS (DIM. E)       |                                   | 10' - 12'                                                                               | 10' - 12'                                                                                        | 12' - 14'                  | 12' - 14'                  | 14' - 16'                  | 18' - 20' 1                | 16' - 18'                  | 14' - 16'       |  |
|                                  | POTENTIAL BODY LENGTHS 1            |                                   | 9' - 13'                                                                                | 10' - 13'                                                                                        | 10' - 15'                  | 10' - 16'                  | 12' - 18'                  | 14' - 22'                  | 14' - 20'                  | 12' - 18'       |  |
| BODY LONGSILL WIDTH 2            |                                     | 41.63" / 39.00"                   | 41.63"                                                                                  | 41.63" / 40.50"                                                                                  | 41.63" / 40.50"            | 41.63" / 40.50"            | 41.63" / 40.50"            | 41.63" / 40.50"            | 41.63" / 40.50"            | 41.63" / 40.50" |  |
| HYDRAULIC SYSTEMS                | HYDRAULIC PUMP TYPE (CID)           |                                   | Gear (0.85)                                                                             | Gear (1.86)                                                                                      | Gear (2.96)                | Gear (2.96)                | Gear (2.96)                | Gear (4.46)                | Gear (4.46)                | Gear (4.46)     |  |
|                                  | FLOW @ PUMP RPM 3                   | 3.1 GPM @ 1,000 RPM               | 7.2 GPM @ 1,000 RPM                                                                     | 11.4 GPM @ 1,000 RPM                                                                             | 11.4 GPM @ 1,000 RPM       | 11.4 GPM @ 1,000 RPM       | 17.4 GPM @ 1,000 RPM       | 17.4 GPM @ 1,000 RPM       | 17.4 GPM @ 1,000 RPM       |                 |  |
|                                  |                                     | RELIEF PRESSURE                   | 3,250 PSI                                                                               | 3,250 PSI                                                                                        | 3,250 PSI                  | 3,250 PSI                  | 3,250 PSI                  | 2,800 PSI                  | 2,800 PSI                  | 2,800 PSI       |  |
|                                  | HYDRAULIC RESERVOIR                 |                                   | 7 gal                                                                                   | 15 gal                                                                                           | 15 gal                     | 15 gal                     | 15 gal                     | 25 gal                     | 25 gal                     | 25 gal          |  |
| LIFT CYLINDER                    | TYPE                                |                                   | ALL MODELS INCORPORATE DOUBLE ACTING CYLINDERS WITH DUAL BUILT-IN COUNTERBALANCE VALVE. |                                                                                                  |                            |                            |                            |                            |                            |                 |  |
|                                  | QUANTITY                            |                                   | 1                                                                                       | 2                                                                                                | 2                          | 2                          | 2                          | 2                          | 2                          | 2               |  |
|                                  | BORE                                |                                   | Ø 4"                                                                                    | Ø 4"                                                                                             | Ø 5"                       | Ø 5.5"                     | Ø 5.5"                     | Ø 6"                       | Ø 6"                       | Ø 6"            |  |
|                                  | STROKE                              |                                   | 38"                                                                                     | 38"                                                                                              | 43"                        | 46"                        | 54"                        | 54"                        | 54"                        | 54"             |  |
| JIB CYLINDER                     | TYPE                                |                                   | 5                                                                                       | MODELS INCORPORATE A SINGLE, DOUBLE ACTING CYLINDER WITH A SINGLE BUILT-IN COUNTERBALANCE VALVE. |                            |                            |                            |                            |                            |                 |  |
|                                  | QUANTITY                            |                                   | 2                                                                                       | 1                                                                                                | 1                          | 1                          | 1                          | 1                          | 1                          | 1               |  |
|                                  | BORE                                |                                   | Ø 1.5"                                                                                  | Ø 2.5"                                                                                           | Ø 3"                       | Ø 3"                       | Ø 3"                       | Ø 3.5"                     | Ø 3.5"                     | Ø 3.5"          |  |
|                                  | STROKE                              |                                   | 20"                                                                                     | 24"                                                                                              | 32"                        | 32"                        | 36"                        | 48"                        | 34"                        | 30"             |  |
| TRUCK SPECS (RECOMMENDED)        | GVW RANGE 6                         | 14,000 lb - 16,000 lb             | 16,000 lb - 19,000 lb                                                                   | 18,000 lb - 26,000 lb                                                                            | 25,000 lb - 35,000 lb      | 25,000 lb - 35,000 lb      | 25,000 lb - 35,000 lb      | 25,000 lb - 35,000 lb      | 25,000 lb - 35,000 lb      |                 |  |
|                                  |                                     | CAB-AXLE DIM. (SINGLE AXLE) 7     | 84" - 96"                                                                               | 84" - 96"                                                                                        | 108" - 120"                | 108" - 120"                | 120" - 138"                | 156" - 174"                | 142" - 160"                | 130" - 144"     |  |
|                                  |                                     | CAB-TRUNNION DIM. (TANDEM AXLE) 7 | N/A                                                                                     | N/A                                                                                              | N/A                        | N/A                        | N/A                        | 150" - 162"                | 130" - 142"                | 120" - 132"     |  |
|                                  |                                     | CLEAR FRAME RAIL 8                | 126"                                                                                    | 130"                                                                                             | 153"                       | 156"                       | 172"                       | 216"                       | 202"                       | 184"            |  |
|                                  |                                     | FRAME HEIGHT                      | up to 38"                                                                               | up to 40"                                                                                        | up to 40"                  | up to 40"                  | up to 40"                  | up to 43"                  | up to 43"                  | up to 43"       |  |
| PTO SPECS (RECOMMENDED)          | PUMP MOUNT 9                        | Direct Mount SAE A, 2 Bolt        | Direct Mount SAE B, 2 Bolt                                                              | Direct Mount SAE B, 4 Bolt                                                                       | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt |                 |  |
|                                  |                                     | TORQUE REQUIRED                   | 40 ft-lbf                                                                               | 80 ft-lbf                                                                                        | 125 ft-lbf                 | 125 ft-lbf                 | 125 ft-lbf                 | 200 ft-lbf                 | 200 ft-lbf                 | 200 ft-lbf      |  |





| SL-2418                                                                                          | SL-330                     | SL-400                     | SL-406                     | SL-412                     | SL-518                     | SL-520                     | SL-650                     |
|--------------------------------------------------------------------------------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| 24,000 lb                                                                                        | 33,000 lb                  | 40,000 lb                  | 40,000 lb                  | 40,000 lb                  | 54,000 lb                  | 50,000 lb                  | 65,000 lb                  |
| 57°                                                                                              | 58°                        | 58°                        | 55°                        | 60°                        | 57°                        | 57°                        | 54°                        |
| 24,000 lb                                                                                        | 33,000 lb                  | 40,000 lb                  | 40,000 lb                  | 40,000 lb                  | 53,000 lb                  | 50,000 lb                  | 65,000 lb                  |
| 3,040 lb                                                                                         | 5,170 lb                   | 5,290 lb                   | 5,920 lb                   | 4,780 lb                   | 6,600 lb                   | 7,055 lb                   | 8,050 lb                   |
| N/A                                                                                              | 5,330 lb                   | 5,450 lb                   | 6,085 lb                   | 4,930 lb                   | 6,840 lb                   | 7,310 lb                   | N/A                        |
| 118.00"                                                                                          | 167.50"                    | 167.50"                    | 209.75"                    | 143.50"                    | 201.00"                    | 222.75"                    | 226.50"                    |
| 53.88"                                                                                           | 61.75"                     | 61.75"                     | 61.75"                     | 61.75"                     | 61.75"                     | 61.75"                     | 61.75"                     |
| N/A                                                                                              | 61.75" / 53.88"            | 61.75" / 53.88"            | 61.75" / 53.88"            | 61.75" / 53.88"            | 61.75" / 53.88"            | 61.75" / 53.88"            | N/A                        |
| 9"                                                                                               | 11"                        | 11"                        | 11"                        | 11"                        | 12"                        | 12.5"                      | 13"                        |
| 63.8"                                                                                            | 88.8"                      | 88.8"                      | 114.0"                     | 75.6"                      | 108.0"                     | 118.0"                     | 125.0"                     |
| 10' - 12'                                                                                        | 14' - 16'                  | 14' - 16'                  | 18' - 20'                  | 12' - 14'                  | 18' - 20' <sup>1</sup>     | 20' - 22'                  | 20' - 22'                  |
| 10' - 13'                                                                                        | 12' - 18'                  | 12' - 18'                  | 16' - 22'                  | 12' - 15'                  | 15' - 22'                  | 17' - 24'                  | 17' - 24'                  |
| 41.63" / 40.50"                                                                                  | 40.50" / 41.63"            | 40.50" / 41.63"            | 40.50" / 41.63"            | 40.50" / 41.63"            | 40.50" / 41.63"            | 40.50" / 41.63"            | 40.50" / 41.63"            |
| Gear (4.46)                                                                                      | Gear (3.83)                | Gear (3.83)                | Gear (3.83)                | Gear (3.83)                | Gear (4.46)                | Gear (4.46)                | Gear (4.46)                |
| 17.4 GPM @ 1,000 RPM                                                                             | 22.3 GPM @ 1,500 RPM       | 22.3 GPM @ 1,500 RPM       | 22.3 GPM @ 1,500 RPM       | 22.3 GPM @ 1,500 RPM       | 26.0 GPM @ 1,500 RPM       | 26.0 GPM @ 1,500 RPM       | 26.0 GPM @ 1,500 RPM       |
| 2,800 PSI                                                                                        | 3,500 PSI                  | 3,500 PSI                  | 3,500 PSI                  | 3,500 PSI                  | 3,500 PSI                  | 3,500 PSI                  | 3,500 PSI                  |
| 25 gal                                                                                           | 30 gal                     | 30 gal                     | 30 gal                     | 30 gal                     | 30 gal                     | 30 gal                     | 30 gal                     |
| ALL MODELS INCORPORATE DOUBLE ACTING CYLINDERS WITH DUAL BUILT-IN COUNTERBALANCE VALVE.          |                            |                            |                            |                            |                            |                            |                            |
| 2 <sup>4</sup>                                                                                   | 2 <sup>4</sup>             | 2 <sup>4</sup>             | 2                          | 2 <sup>4</sup>             | 2                          | 2                          | 2                          |
| Ø 5.5"                                                                                           | Ø 5.5"                     | Ø 6"                       | Ø 6.5"                     | Ø 6"                       | Ø 7"                       | Ø 7"                       | Ø 7.5"                     |
| 39"                                                                                              | 60"                        | 60"                        | 74"                        | 56"                        | 74"                        | 82"                        | 82"                        |
| MODELS INCORPORATE A SINGLE, DOUBLE ACTING CYLINDER WITH A SINGLE BUILT-IN COUNTERBALANCE VALVE. |                            |                            |                            |                            |                            |                            |                            |
| 1 <sup>4</sup>                                                                                   | 1 <sup>4</sup>             | 1 <sup>4</sup>             | 1                          | 1 <sup>4</sup>             | 1                          | 1                          | 1                          |
| Ø 4"                                                                                             | Ø 4"                       | Ø 4"                       | Ø 4"                       | Ø 4"                       | Ø 4.5"                     | Ø 4.5"                     | Ø 4.5"                     |
| 24"                                                                                              | 38"                        | 38"                        | 52"                        | 30"                        | 48"                        | 52"                        | 52"                        |
| 25,000 lb - 35,000 lb                                                                            | 33,000 lb or greater       | 45,000 lb or greater       | 45,000 lb or greater       | 45,000 lb or greater       | 50,000 lb or greater       | 50,000 lb or greater       | 55,000 lb or greater       |
| 84" to 96"                                                                                       | 142" - 156"                | N/A                        | N/A                        | N/A                        | N/A                        | N/A                        | N/A                        |
| N/A                                                                                              | 130" - 138"                | 130" - 138"                | 174" - 180"                | 102" - 114"                | 165" - 174"                | 176" - 190"                | 172" - 190"                |
| 134"                                                                                             | 191"                       | 191"                       | 232"                       | 169"                       | 225"                       | 245"                       | 249"                       |
| up to 43"                                                                                        | up to 43"                  | up to 43"                  | up to 45"                  | up to 45"                  | up to 45"                  | up to 45"                  | up to 45"                  |
| Direct Mount SAE B, 4 Bolt                                                                       | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt | Direct Mount SAE B, 4 Bolt |
| 200 ft-lbf                                                                                       | 200 ft-lbf                 | 200 ft-lbf                 | 200 ft-lbf                 | 200 ft-lbf                 | 230 ft-lbf                 | 230 ft-lbf                 | 230 ft-lbf                 |

- 1 Hoist potential body length range may not conform with I.C.C. bumper regulations or may not achieve maximum dump angle depending on truck chassis height. Shorter bodies available on some models with use of a shelf assembly or CVS system. Contact your SwapLoader distributor for more information.
- 2 Maximum outside to outside long sill width.
- 3 Pump RPM and Flow are dependent on engine RPM and PTO ratio.
- 4 Polished nitrided cylinder rod.
- 5 Counterbalance valve manifold.
- 6 A lower GVW will limit your payload potential.
- 7 Optimum CA/CT dimension will be influenced by type of loads carried and turning radius requirements.
- 8 Clear frame dimension given is the overall length of hoist plus 5" for cab clearance and rear light bar mounting. Additional frame length may be necessary for other accessories such as cab guard, tarper, exhaust system, etc.
- 9 PTO/Pump rotation as determined by transmission.



# ONE TRUCK **UNLIMITED** **POSSIBILITIES**



- ▶ **QUALITY**
- ▶ **INTEGRITY**
- ▶ **INNOVATION**
- ▶ **SUPER SERVICE**





# WHAT COULD YOU DO WITH A **SWAPLOADER** TODAY?



## HOOKED ON **QUALITY**







An EFCO Company



# SWAPLOADER<sup>®</sup>

*"Hooked on Quality"* U.S.A. LTD.



YouTube [www.youtube.com/swaploader](http://www.youtube.com/swaploader)

**MADE IN USA** ★



1800 NE Broadway Ave. Des Moines, IA 50313

web: [swaploader.com](http://swaploader.com)

email: [sales@swaploader.net](mailto:sales@swaploader.net)

toll free: 888.767.8000

phone: 515.266.3042

SWL-055 07/2021