

WeightLifter

Tailgates By THIEMAN

Raising Performance to New Levels

Model WT





FEATURING:

- Meets TMC Electrical Guidelines
- 84" x 36" to 90" x 48" Platforms
- 2,000 to 4,000 lb. Capacities
- Bed Height Range 40" to 54"
- Dual Cylinder Lift
- Sealed Toggle Switch Control
- Latch Chains and Snubber Kit
- Power Down Lowering
- Cast Bronze Bearings at Pivot Points

Designed for use on stake and van bodies, the THIEMAN WT series is the most durable, dependable, conventional liftgate on the market today. The WT is built with many standard features including a widearm, dual cylinder lift, giving maximum lifting stability when handling sizeable loads. With the addition of cast bronze bearings at critical wear points, this conventional style liftgate is built to last for many years.

If you're searching for a conventional liftgate that improves efficiency and saves your company dollars, the THIEMAN WT is your answer.



Features, Benefits and Specifications

STANDARD FEATURES AND BENEFITS:

- Environmentally Sealed Toggle Switch Control for Enhanced Reliability and Easy Installation
- Dual Cylinder Lift for Maximum Stability
- Screw-In Grease Fittings at all Wear Points for Easy Maintenance
- Latch Chains and Snubber Kits for Increased Safety and Reduced Wear of Liftgate
- 150 Amp Circuit Breaker for Electrical Protection
- Adjustable Cylinder Shafts and Idler Arms for Precise Alignment of Truck Floor & Platform
- Power Down for Better Reliability in Cold Weather Operation
- Bronze Bushings at Critical Pivot Points for Reduced Maintenance Costs
- Wider Lift Arms for Maximum Stability
- Meets All TMC Electrical Guidelines for Reduced Service Requirements

AVAILABLE OPTIONS FOR WT:

- In-Cab Shut Off Switch
- Pump and Motor Cover
- Power Unit Enclosure
- Special Platform and Ramp Sizes

- Aluminum Platform
- Expanded Metal Platform
- Bar Grate

Model No.	Platform	Rated Load Cap. Ibs.	Lowering	Approx. Installed Weight	Bed Height Range
WT20EST	84" x 36" + 10"	2000	Power	938	40" to 54"
WT20EST	90" x 36" + 10"	2000	Power	958	40" to 54"
WT20P	84" x 36" + 10"	2000	Power	936	40" to 54"
WT20P	90" x 36" + 10"	2000	Power	956	40" to 54"
WT20EST	90" x 42" + 10"	1750	Power	981	40" to 54"
WT20EST	90" x 48" + 10"	1500	Power	1069	40" to 54"
WT20P	90" x 42" + 10"	1750	Power	989	40" to 54"
WT20P	90" x 48" + 10"	1500	Power	1051	40" to 54"
WT30EST	84" x 36" + 10"	3000	Power	936	40" to 54"
WT30EST	90" x 36" + 10"	3000	Power	956	40" to 54"
WT30P	84" x 36" + 10"	3000	Power	906	40" to 54"
WT30P	90" x 36" + 10"	3000	Power	926	40" to 54"
WT30EST	90" x 42" + 10"	2500	Power	1009	40" to 54"
WT30EST	90" x 48" + 10"	2000	Power	1081	40" to 54"
WT30P	90" x 42" + 10"	2500	Power	1037	40" to 54"
WT30P	90" x 48" + 10"	2000	Power	1101	40" to 54"
WT40EST WT40EST WT40EST WT40P WT40P WT40P	90" x 36" + 10" 90" x 42" + 10" 90" x 48" + 10" 90" x 36" + 10" 90" x 42" + 10" 90" x 48" + 10"	4000 3500 3000 4000 3500 3000	Power Power Power Power Power	1006 1059 1121 1055 1059 1135	40" to 54" 40" to 54" 40" to 54" 40" to 54" 40" to 54" 40" to 54"

Note: On "P" Model Gates a 70% ratio PTO is recommended

EST - Electric w/Toggle Switch Control, Power Down/Power Close

P - PTO w/Power Close

Distributed By:		



600 East Wayne Street Celina, Ohio 45822 Phone: 419-586-7727 or 800-524-5210

Fax: 419-586-9724

www.thiemantailgates.com info@thiemantailgates.com


THIEMAN Reserves the right to Change Products Specifications at any time Without Prior Notice. Printed in U.S.A. Rev. 5/10 • 2M • M70079


WEIGHTLIFTER

Tailgates By THIEMAN

Raising Performance to New Levels

Model TWL





FEATURING:

- Meets TMC Electrical Guidelines
- 66" x 26" to 90" x 32" Platforms
- 1250 to 2000 lb. Capacities
- Cam Activated Power Close Platform
- Gravity Down Lowering
- Adjustable Cylinder Shaft
- Bed Height Range 33"-47" and 37"-52"

Designed for use on stake and van bodies, the THIEMAN TWL series is the most versatile and durable general purpose conventional style liftgate. The TWL features a wide range of bed heights which makes it possible to meet a variety of delivery needs.

The THIEMAN TWL's proven track record of dependability makes it a top choice for many applications.



Features, Benefits and Specifications

STANDARD FEATURES AND BENEFITS:

- Screw in Grease Fittings at All Wear Points for Easier Maintenance
- Adjustable Cylinder Shaft for Precise Alignment of Truck Floor and Platform
- •150 Amp Circuit Breaker for Electrical Protection
- Gravity Down Platform for Less Demand on Power Unit
- Cam Activated, Power Close Platform for Easy Closing
- Latch Chain for Increased Safety
- Meets All TMC Electrical Guidelines for Reduced Service Requirements


OPTIONS FOR TWL SERIES:

- Push Button Control
- In-Cab Shut Off Switch
- Remote Pendant Control
- Expanded Metal Platform
- Load Area, Ramp Change

- Power Down
- PTO Power Source
- Square Edge, No Ramp
- Power Unit Enclosure

Model No.	Platform	Capacity	Lowering	Install Weight	Bed Height Range
TWL-125ET TWL-125ET TWL-125ET TWL-16ET TWL-16ET TWL-16ET TWL-20ET TWL-20ET TWL-20ET	66" x 26" + 8" 78" x 32" + 8" 84" x 32" + 8" 78" x 32" + 8" 84" x 32" + 8" 90" x 32" + 8" 78" x 32" + 8" 90" x 32" + 8" 90" x 32" + 8"	1250 lb. 1250 lb. 1250 lb. 1600 lb. 1600 lb. 2000 lb. 2000 lb. 2000 lb.	Gravity Gravity Gravity Gravity Gravity Gravity Gravity Gravity Gravity	436 lb. 531 lb. 546 lb. 561 lb. 576 lb. 596 lb. 579 lb. 599 lb.	33"-47" 33"-47" 33"-47" 37"-52" 37"-52" 37"-52" 37"-52" 37"-52"

ET - Electric w/Toggle Switch Control/Power Close





600 East Wayne Street Celina, Ohio 45822 Phone: (419) 586-7727 or

800-524-5210 Fax: (419) 586-9724 www.thieman.com ttgates@wesnet.com