



[ENLARGE ALL MEDIA](#)

## Legacy Series 1000

LIQ28804

Description ▼

Standard Features ▼

Optional Features ▼

Specifications ▲

Weight	1,200 lbs
--------	-----------

Length	110 in
--------	--------

Width	80 in
-------	-------

Height	67 in
--------	-------

Manual ▼

Warranty ▼

- **GPS Rate Control:** Electronics in the system monitor the flow to the boom and adjust according to the speed of your vehicle. It's as easy as setting your application rate in the controller and turning the boom on. No more over or under application resulting in wasted product or unsafe surfaces. The boom also shuts off on its own if the vehicle is brought to a stop even if the operator forgets to turn the switch off.
- **Honda GX200 Electric Start:** These engines are easy to start in the extreme cold and run reliably. They are paired to a 2" Banjo poly pump and provide plenty of flow to the boom to give the system a max speed of 17 MPH at 80 gallons per acre with all three booms on.
- **Single Lane "Pile Driver" Boom:** Downtime from accidentally backing into a tree or concrete light pole stand are gone. Our new boom design has been torture and field tested to hold up to accidental beatings. With the heavy duty metal shroud and the stainless pipe welded inside its almost impossible to put out of commission. Boom features jet tips for post treatment and high speed pretreatment applications, and a broadcast tip for even coverage in low speed pretreatment applications.
- **Smartphone Connection:** All sprayers are controlled via wireless connection from a smartphone or device. Provides a wide range of features for adjusting and monitoring total usage, per account usage, current tank level and adjusting application rate on a per acre or per lane mile basis. This also eliminates the need for a wiring harness.
- **IP-67 Rated Lights and Strobes:** High quality LED light to help see behind you and two strobe lights facing backwards.

- **Magnetic Flow Meter:** No moving parts on the inside to calibrate or fail. This flow meter reads accurately even with the density changes of additives that would cause a turbine flow meter to be off unless calibrated every storm. Turbine flow meters can be off up to 33% at the end of one season and quick to fail, while these will perform as expected season after season.
- **Powder Coating:** The skid is bead blasted, acid washed, epoxy primed, and powder coated for maximum durability. We spare no expense when it comes to protecting the skid from corrosion in the harsh environments that they are used in.
- **Full Tube Fork Pockets:** No risk of having your forks damage any plumbing when loading and unloading the sprayer. This sprayer is equipped with front and side fork pockets for ease of loading in multiple situations.
- **Self Loading and Pump Out:** This system is able to self fill from storage tanks or any other tanks that don't have a pump to load. No more buying extra pumps just to fill from storage tanks. It also has the ability to pump out into other sprayers with a full 2" line. Any smaller sprayer on the route can be filled in minutes by this sprayer and resume spraying.