

| MAKE | MODEL | BASE PRICE |
|------------------|------------------|-------------|
| BOSS PRODUCTS | VBX6500 AUGER | \$11,998.00 |
| | VBX6500 CHAIN | \$12,328.00 |
| | VBX8000 AUGER | \$14,132.00 |
| | VBX8000 CHAIN | \$14,462.00 |
| | VBX9000 AUGER | \$15,925.00 |
| | VBX9000 CHAIN | \$16,266.00 |

VBX TRUCK HOPPER SPREADERS

MAXIMUM SPEED & EFFICIENCY

BOSS hopper spreaders are some of the most powerful tools in your snow and ice removal arsenal. BOSS VBX spreaders are fully featured, outfitted with features for ease of use and maximum productivity for years of operation in harsh winter conditions. The VBX family features models with either pintle or auger feeds, powerful electric motors, standard worklights, easy-to-use controls and the flexibility to spread a variety of deicing materials.

STANDARD FEATURES

- **Material Feed System** features a heavy-duty pintle chain or powder-coated auger for long life and durability.
- **Poly Hopper** is built to outlast the elements.
- **Dual Variable Speed Controller** is equipped with auto-reverse (auger only) and overload protection.
- **LCD Screen In-Cab Controller** is backlit for clear visibility and ease of use.
- **14.5" Diameter Urethane Spinner** is durable and corrosion-resistant and ensures consistent distribution.
- **Enclosed Spinner Motor** is weather- and dust-resistant to ensure performance, durability and reliability.
- **Tarp With Integrated Tie-Downs** protects spreading material from the elements.
- **Dual Variable Speed Vibrators** reduce material bridging for ease of operation (standard for auger; optional for pintle).
- **Inverted V-Baffle** reduces material build-up for optimal spreading efficiency (standard for auger; available as an accessory for pintle).
- **Chain Cleaning Brush** removes excess material from chain on every pass (pintle chain only).
- **Full-Length Slide-Out Tray** captures falling deicing material, keeping it away from truck bed, preventing corrosion (pintle chain only).



> MODELS

Poly VBX 6500, VBX 8000, VBX 9000

> OPTIONAL ACCESSORIES

- Backup Camera
- Inverted V*
- Pre-Wet
- Vibrator Kit*

*Standard on auger, optional on pintle.



VBX 9000
3 cubic yards of capacity

PRE-WET

Optional pre-wet allows contractors to pre-wet solid deicing material, improving material performance.

VBX



SEE IT IN ACTION
BOSSPLOW.COM



ICE CONTROL EQUIPMENT

VBX HOPPER SPREADERS

VEHICLE APPLICATION: FULL-SIZE UTVs, ¾- TO 1-TON TRUCKS, DUMP BODY AND FLATBED TRUCKS



| Specifications | VBX 3000 | VBX 6500 Auger / Pintle Chain | VBX 8000 Auger / Pintle Chain | VBX 9000 Auger / Pintle Chain |
|-------------------------------------|--|--|--|--|
| Hopper Capacity | 12 cu ft (0.34 cu m) | 1.5 cu yd (1.15 cu m) | 2 cu yd (1.5 cu m) | 3 cu yd (2.3 cu m) |
| Hopper Length | 42" (106.7 cm) | 78" (198 cm) | 96" (244 cm) | 108" (274 cm) |
| Overall Length | 52" (132 cm) | 93½" (237.5 cm) | 112" (284.5 cm) | 122" (310 cm) |
| Hopper Height | 28" (71 cm) | 38" (96.5 cm) | 38" (96.5 cm) | 49" (124.5 cm) |
| Hopper Width | 50" (127 cm) | 48¾" (123 cm) | 48¾" (123 cm) | 48" (122 cm) |
| Complete Unit Weight (Empty) | 230 lb (104 kg) | 550 lb (250 kg) / 600 lb (272 kg) | 600 lb (272 kg) / 650 lb (295 kg) | 710 lb (322 kg) / 760 lb (345 kg) |
| Hopper Construction | ¾" (0.5 cm) double wall polyethylene hopper | ¾" (0.5 cm) double wall polyethylene hopper | ¾" (0.5 cm) double wall polyethylene hopper | ¾" (0.5 cm) double wall polyethylene hopper |
| Spreading Width | 2' - 40' (0.6 m - 12.2 m) dry, free-flowing material | 2' - 40' (0.6 m - 12.2 m) dry, free-flowing material | 2' - 40' (0.6 m - 12.2 m) dry, free-flowing material | 2' - 40' (0.6 m - 12.2 m) dry, free-flowing material |
| Max Feed Rate | 1.0 cu ft (0.022 cu m) per minute | 2.3 cu ft (0.07 cu m) per minute / 4 cu ft (0.11 cu m) per minute | 2.3 cu ft (0.07 cu m) per minute / 4 cu ft (0.11 cu m) per minute | 2.3 cu ft (0.07 cu m) per minute / 4 cu ft (0.11 cu m) per minute |
| Lighting | Single 55-watt halogen | Dual 55-watt halogen variable output worklights | Dual 55-watt halogen variable output worklights | Dual 55-watt halogen variable output worklights |
| Cover | VCP tarp w/integrated tie-downs | VCP tarp w/integrated tie-downs | VCP tarp w/integrated tie-downs | VCP tarp w/integrated tie-downs |
| Top Screen | Standard | Standard | Standard | Standard |
| Gearbox Ratio | 40:1 right angle worm | Planetary 91:1 / 137:1 | Planetary 91:1 / 137:1 | Planetary 91:1 / 137:1 |
| Motor | ¼ hp feed motor | ¾ hp stainless steel feed motor | ¾ hp stainless steel feed motor | ¾ hp stainless steel feed motor |
| Trough | 11-ga stainless steel | 11-ga stainless steel | 11-ga stainless steel | 11-ga stainless steel |
| Dual Variable Speed Control | Standard | Standard with LCD display | Standard with LCD display | Standard with LCD display |
| Variable Speed Vibrator | 80 lb (36.3 kg) 1 standard | 200 lb (90.7 kg) 2 standard (auger) / optional (pintle) | 200 lb (90.7 kg) 2 standard (auger) / optional (pintle) | 200 lb (90.7 kg) 2 standard (auger) / optional (pintle) |
| Inverted V-Baffle | Standard | Standard / optional | Standard / optional | Standard / optional |
| Feed System | 4" OD x 4" (10 cm x 10 cm) pitch shaftless full-length auger | 6" OD x 9" (15 cm x 23 cm) pitch full-length auger / 14" (36 cm) wide pintle chain | 6" OD x 9" (15 cm x 23 cm) pitch full-length auger / 14" (36 cm) wide pintle chain | 6" OD x 9" (15 cm x 23 cm) pitch full-length auger / 14" (36 cm) wide pintle chain |
| LED CHMSL | N/A | Standard | Standard | Standard |
| Adjustable Deflector | Standard | Standard | Standard | Standard |
| Spinner Assembly | Easily removable | Easily removable; swing out; height-adjustable | Easily removable; swing out; height-adjustable | Easily removable; swing out; height-adjustable |
| Hopper Tie-Down Kit | Standard | Standard | Standard | Standard |
| Spinner | 12" (30.5 cm) diameter urethane | 14½" (36.8 cm) diameter urethane | 14½" (36.8 cm) diameter urethane | 14½" (36.8 cm) diameter urethane |
| Spinner Gearmotor | ½ hp spinner gearmotor (located above spinner) | ½ hp spinner gearmotor (located above spinner) | ½ hp spinner gearmotor (located above spinner) | ½ hp spinner gearmotor (located above spinner) |
| Minimum Bed Length | 33½" (85.1 cm) | 66" (168 cm) | 78" (198 cm) | 96" (244 cm) |
| Vehicle Application | Full-size UTVs | ¾- to 1-ton trucks | 1-ton trucks and up | Dump body and flatbed with 13,000 GVWR and up |
| Minimum Bed Capacity | 1,000 lb (454 kg) | N/A | N/A | N/A |