Laydown Light Towers

LED/Metal Halide/LED Balloon





Robust and reliable with unique features

for enhanced performance

- High-output light fixtures
- Telescoping tower rotates nearly 360 degrees
- Multiple low-speed engine options
- Heavy gauge all-steel body
- Unobstructed engine accessibility

Not just another light tower, Wanco Laydown Light Towers use state-of-the-art technology for superior illumination, shining a uniform light pattern across the entire job site and exceeding government regulations for worksite illumination.

For fast job-site setup and less downtime, each light fixture can be aimed independently without the use of tools—and the fixtures stay in place once positioned. Choose either LED or metal halide lights when specifying your light tower. Wanco's proprietary LED fixtures are the brightest available on any portable light tower, and Wanco's metal halide fixtures feature high-intensity parabolic reflectors that increase illumination. Balloon lights are also available.

The telescoping tower stows securely in a travel cradle when it is horizontal, then extends vertically to 30 feet when deployed. While upright, the tower rotates nearly 360 degrees and the lights operate at any height, eliminating the need to move the trailer frequently. Two winches raise and extend the tower easily. Manual winches are standard and power winches are optional.

A choice of industrial diesel engines and four-pole generators ensure reliable performance. The high-efficiency engine and 30-gallon fuel tank provide extended run times between refuelings—up to 120 hours with Wanco's exclusive LED light fixtures. Performance enhancing options include an automated dusk-to-dawn start/stop system and cold-weather start package.

For system maintenance, Wanco's exclusive hinged top panel provides unimpeded access to the engine, generator and electrical components. The equipment bay is a rugged all-steel cabinet with gull-wing doors that can be locked closed to protect against unauthorized access.

Wanco Laydown Light Towers boast trouble-free performance and exceptional longevity—hallmarks of the Wanco brand.

To order one today, call **800.972.0755** or visit wanco.com.



Brief specifications

Physical

Deployed footprint 127×112 in. $(321 \times 285 \text{ cm})$, L \times W

Operating height Max. 30 ft (9.14m)
Min. 1214 ft (3.81m)

Min. 12½ ft (3.81m) 66 in (168cm)

Travel height 66 in (168cm)

Weight Operating Approx. 1800 lb (815kg)
Shipping Approx. 1550 lb (703kg)

 Lights
 480-watt LEDs
 350-watt LEDs
 Metal halides

 Lamps*
 Four 480W fixtures
 Four 350W fixtures
 Four 1000W lamps

 Luminosity**
 57,800 lm per fixture
 49,000 lm per fixture
 110,000 lm per lamp

 231,200 lm total
 196,000 lm total
 440,000 lm total

Power system

Engine type Tier 4 Final diesel, 3-cylinder, 4-cycle
Engine speed* 1800 rpm @ 60 Hz or 1500 rpm @ 50 Hz

Generator type Brushless, class H

Sound level 71 dB @ 23 ft (7m) at max. load

Battery 12 Vdc, 550 CCA

Kubota® D1005 Mitsubishi® L3E Kohler® KD1003 13.1 hp (9.8 kW) 15.4 hp (11.5 kW) 23.7 hp (17.7 kW) Maximum power output* 68.53 in³ (1123cm³) 62.7 in³ (1028cm³) Displacement* 61.08 in3 (1001cm3) Fuel tank capacity 30 gal (114L) 30 gal (114L) 30 gal (114L) 480-watt LEDs 350-watt LEDs Metal halides Fuel consumption* 0.31 gal/hr (1.17L/h) 0.25 gal/hr (0.096L/h) 0.49 gal/hr (1.86L/h) Runtime before refueling* Approx. 97 hrs Approx. 120 hrs Approx. 62 hrs

Output power

 Output*
 6 kW or 8 kW

 Voltage*
 120 Vac or 240 Vac

 Amperage
 50 A @ 120 V, 25 A @ 240 V

Frequency* 60 Hz or 50 Hz
Voltage regulation ±6%, no load to full load

*Depending on model **Continuous intensity for LEDs, initial intensity for metal halides



WANCO INC.5870 Tennyson Street
Arvada, Colorado 80003 USA
800-972-0755
303-427-5700
303-427-5725 fax **www.wanco.com**



