

6010FL INDUSTRIAL TUB GRINDER

Specification Sheet



SPECIFICATIONS:

Weight	51,540 lbs (23,378.15 kg)
Hitch Weight	13,200 lbs (5,987.42 kg)
Transport Width	10' (3.05 m)
Transport Height	13' 4" (4.06 m)
Transport Length	43' 9" (13.34 m)
Axles	(3) 22,500 lbs (10,208.83 kg)
Electrical	24 volt
Tires	(12) - 255 X 70R X 22.5
Engine	540 hp (402.68 kw) CAT C15 Tier IV 630 hp (479 kw) CAT C18 Tier IV
Clutch	HPTO Wet Clutch
Fuel Capacity	300 Gallons (1,135.6 Liters)
Hydraulic Oil Capacity	110 Gallons (416.6 Liters)
Lights	Clearance, Directional & Tail
Tub Width	10' (3.05 m)
Depth	46" (116.8 cm)
Tub Diameter at Base	8' (2.44 m)
Tub Wall	1/4" (.64 cm) Thick
Tub Floor	3/8" (.95 cm) Thick
Tub Drive	Direct Hydraulic Drive
Service Access	90 Degree Tilting Tub
Stacking Conveyor	26'L x 30"W x 8"D (7.92m L x 76.2cm W x 20.3cm D)
Discharge Augers	Dual 12" diameter augers with dual hydraulic motor drive
Tub Speed Sensor	Electronic Self Governing
Rotor - Shaft Diameter	6" (15.24 cm) Stress Proof Steel
Rotor Length	44" (111.76 cm)
Rotor Plates	16" (40.64 cm) Dia 1-1/2" (3.81 cm) Thick Plates
Feed Opening	25" (63.5 cm) x 45" (114.3 cm)
Screen Area	2,403 sq in 15,503 sq cm)
Hammer Rods	1-1/2" (3.81 cm) Dia 43" (109.22 cm) Long
Bearings	4" (10.16 cm) Pillow Block Bearings
Hammermill Drive	Direct Thru HPTO Oil Cooled
Screens	Split Screens 1" (2.54 cm) Thick