

TC-12 Chipper Specification Sheet



SPECIFICATIONS:

| | |
|-----------------------------|--|
| Engine | CAT C4.4 129 HP (96 kw) KUBOTA V3800 Diesel 88 hp (74 kw) |
| Gross Weight | 7,640 lbs.(3,465.5 kg) |
| Transport Width | 79" (200 cm) |
| Transport Length | 208" (528 cm) |
| Hitch | Pintle or 2-5/16" Ball |
| Tongue Weight | 740 lbs.(335.7 kg) |
| Jack | 7,000lbs (3,175.2 kg) |
| Axle | 7,000lb (3,175.2kg) Torflex |
| Suspension | Torsional |
| Brakes | Electric |
| Tires | 235/85R x 16E |
| Fuel Capacity | 40 gal (152 L) |
| Hydraulic Oil Capacity | 25 gal (95 L) |
| Electrical | 24V |
| Lights | Clearance and Directional |
| Transmission | PT Tech HPTO |
| Chipping capacity | 12" (30.5 cm) |
| Infeed Hopper opening | 40" x 62" (102 cm x 157 cm) |
| Throat opening | 12" x 20" (30 cm x 51 cm) |
| Disc size | 42" (107 cm) dia. x 2" (5 cm) |
| Disc shaft size | 3-15/16" (10 cm) dia. |
| Feed system | Hydraulic 2 Drum |
| Number of knives | 4, 2 Slots |
| Size of knives | 4-1/2" (11.5 cm) x 7-3/4" (19.5 cm) 3-bolt |
| Down pressure on feed wheel | Adjustable Spring Load, Optional Auto Feed Height System |
| Discharge System | 360 degree, Hydraulic Rotation w/ Adjustable Chip Spout |
| Safety features | Breakaway Brake Switch, 2 E-Stop Switches, 2 Infeed Hopper Light Bars, and Disc Hood Closed Proximity Switch |
| Frame size | 3" (7.6 cm) x 5" (12.7 cm) x 1/4" (0.64 cm) |