

RODDERS AND JETS SUPPLY CO.

PO BOX 2577 SUMTER, SC 29151

TOLL FREE: 1-800-293-2012

FAX: 803-773-3666

WEB: RODDERSANDJETS.COM EMAIL: roddersandjetsco@aol.com

HE-1000 HYDRO EXCAVATION, TRUCK MOUNTED, SPECIFICATION

Waste Tank:

- -1000 gallon steel holding tank
- 1/4" steel construction
- 48" Diameter, 1/4" thick steel, flanged and dished heads
- 3/4 opening rear door with manual door locks
- Hydraulically opening rear door
- Hydraulic dumping tank with twin cylinder hoist
- 6" discharge and gate valve
- 3" Inlet with Brass Ball Valve

Truck Bed

- -4"x2" Tubular Steel Frame, 120" Length, 100" width
- -4"x2" Channel Cross Members
- -Front Head Board, 48" Height, 100" Width, with Mesh Window Guard
- -10 Gauge Diamond Plate Bed
- -Stake Pockets
- -Bolt-on Ladder Mounted at Front of Bed with Grab Handle
- -Mud Flaps
- -HD Bumper
- -Cone Holder Mounted at Front of Bed, Driver Side
- -(2) Led Strobe Light Mounted on Head Board, Each Side
- -48"x18" x18" Tool Box Mounted Under Deck Passenger Side
- -24"x18"x18" Tool Box Mounted Under Deck Driver Side
- -Entire Flat Bed to be Coated with Spray-on Bed Liner (Black)

Engine:

- 40 HP gas engine
- Vernier Throttle Control
- 10 gallon fuel tank
- 12V battery system with box

Vacuum Pump:

- 900 CFM positive displacement vacuum pump
- Vacuum capability of 15in-hg
- High efficiency exhaust silencer w/ rain cap
- Cyclonic inlet air filtration system with pleated wire element
- Easy opening hatch on filter housing, no tools required
- 0-30" Hg stainless steel vacuum gauge in filter housing and panel
- Banded v-belt drive with tensioner

High Pressure Water Pump:

- 4GPM, 2000PSI Industrial duty triplex water pump
- General triplex pump
- Adjustable pressure relief valve with by-pass back to water tank
- 0-3000PSI liquid filled pressure gauge
- Drain valve at lowest point for complete system draining in freezing conditions
- Air purge valve
- Strainer on pump inlet to catch debris
- Electric Clutch with Panel Switch

Hose Reel:

- 3/8" x 100ft. Manual hand crank hose reel
- High pressure trigger gun with 24" Lance and Nozzle
- On/off high pressure shut-off valve at reel inlet

Water Tank:

- 100 Gallon high density polyethylene water holding tank
- 1-1/2" drain valve
- Anti-siphon water fill
- Steel hold down clamps

Accessories:

- 4" Hydro-excavation Tube, 4ft. long, 2 jets (qty:1)
- 4" Aluminum Suction Tube, 6ft. long (qty:2)
- 30" Fender Mounted Toolbox (qty:1)
- 3" Kanaflex Vacuum Hose (qty:25)

Finish:

- All fabricated components sandblasted
- 2 coats high build epoxy primer
- 2 coats urethane high gloss finish, white
- Certain colors extra, specify _____
- <u>Chassis</u> 2024-2025 Ford F-600, 4x2, Gas Engine, 22,000 GVW