



K&K Systems, inc.
Traffic Safety Products Manufacturer
www.k-ksystems.com | 888.414.3003

All options discounted 10% off MSRP through
NCSA Heavy Equipment Cooperative Purchasing Program
Bid 24-08-0421

AC-OPT80	Remove 80W solar panel, solar panel mounting bracket, large battery box and regulator. Add 60W power supply and small control cabinet.
ADD-LED-KIT	Includes LED, housing, and mounting bracket.
ADD20W	Additional 20 watt solar panel.
BAT-12-100A	100 amp, 12V, AGM battery; Dimensions: 12.16"x6.75"x8.70"
BAT-12-55A	55 amp, 12V, AGM battery, Dimensions: 9.40"x5.50"x8.20"
CL-1023	Cabinet lock Type 2 with tapered latch and 2 keys.
CL-3PT	3 point locking system with Type 1 or Type 2 lock and 2 keys.
CWKF-433-4	Key Fob remote for Crosstalk/CW-4 for powering unit on; 700 ft line-of-sight range.
DED-LED	Deduct 12" LED and housing
HWS	High Water Sensor - 12V epoxy-coated sensor; housed in high impact PVC construction; will detect any conductive non-flammable liquid. (for CrossTalk or SPLasher)
MS	Moisture Sensor - Dual 12V epoxy-coated sensors; no mechanical parts; triggered by a moisture bridge across the sensor contacts. (for CrossTalk or SPLasher)
DRSS400CFD	SS400 Closed Frame Doppler Radar (300'+ range)
DR600CFD	NEW DR600 Closed Frame Doppler Radar (2000'+ range; Replaced the DR500S)

More options available at 10% off MSRP!

For more information, please contact:

Amanda Robinson

662-566-2025

arobinson@k-ksystems.com