

### SYSTEM DESCRIPTION:

The model AL-2 Atlas Lightning Loader is a heavy duty twin-spar grapple loader mounted onto a chassis from behind the cab, equipped with Petersen's Big Bite® bucket at the end of the boom. The loader operates from a seated platform that rotates with the boom.

### LIFT CAPACITY

Radius	Load Capacity
10 ft. radius	9,400 lbs.
15 ft. radius	6,300 lbs.
20 ft. radius	4,500 lbs.
25 ft. radius	2,800 lbs.

**Note:** Weight of attachment not subtracted from above listed lifting capacities. Trash bucket weighs 1,000 lbs. Capacities shown do not exceed 85% vehicle tipping moment (outriggers engaged, loader on firm, level ground.)

## **GENERAL SPECIFICATIONS**

Reach	27 ft.
Main Boom & Tip Boom	23 ft.
Tip Extension	4 ft.
Tare Weight (empty)	28,000 lb. est
Outrigger Span	11 ft. 8 in.
Dump Body Hoist Capacity	31 tons

## RECOMMENDED CHASSIS (MINIMUM)

Body Style	Conventional Cab
Cab-to-Axle Dimension	Contact PI for specifics
Frame	2,500,000 RBM
Frame Thickness	Double Frame
Engine	300 HP Diesel
Transmission	Allison 3000 or 4000 RDS
Electrical	Remote engine & transmission connectors

<sup>\*</sup>Drop Axle requires special consideration due to scissor hoist clearance\*

# CONTROL OPTIONS:

DUAL WALK-THRU WITH QUADSTICK® CONTROLS (LEFT): Dual walk-thru controls are located on both sides of the truck for greater accessibility and visibility. QUADSTICK® dual joystick controls are fully proportional and mechanically linked to the valve bank.

DUAL WALK-THRU WITH PILOT CONTROL JOYSTICKS (RIGHT): Dual pilot joysticks are conveniently located on each side of the dual walk-thru operator platform. These controls are also fully proportional.





SCAN TO LEARN MORE



4000 SR 60 West Lake Wales, FL 33859

1.800.930.LOAD (5623)

LIGHTNING LOADER



PETERSENIND.COM
Contact Us Today To Learn More



<sup>\*</sup>Always contact Petersen Industries for specific chassis requirements



#### **Description**

MODEL: PETERSEN ATLAS 27' BOOM - AL-2 MODEL

STANDARD EQUIPMENT INCLUDED

BASE TRUCK MOUNT ATLAS LOADER

TOP MOUNT OPERATOR'S SEAT W/ DRIVER-SIDE LADDER

MECHANICAL JOYSTICK CONTROLS W/ FOOT PEDAL SWING CONTROLS

BIG-BITE BUCKET W/ TWIN CYLINDER BUCKET (UPGRADE)

WIRE LOOM FOR BODY WIRING

"A" STYLE 4-WAY OUTRIGGERS

**BOOM UP WARNING LIGHT & AUDIBLE ALARM** 

HD CONTROL BOX AT OPERATOR'S STATION: THROTTLE UP, HORN, & ENGINE KILL SWITCH

HOT SHIFT PTO - OPERATE IN NEUTRAL ONLY

LED LIGHTING PACKAGE

STANDARD WARRANTY: 1-YEAR HYDRAULIC & 3-YEAR STRUCTURAL

INCLUDES STD PAINT & INSTALLATION ON SUITABLE CHASSIS

NOTE: CHASSIS SPECS MUST BE APPROVED BY PETERSEN

TRASH BODY, 40 YD CAPACITY - 2240 XDX 22' X 40 YDS: 3/16" HARDOX SIDES & FLOORS

#### **DEALER SERVICES INCLUDED**

FREIGHT TO AMICK EQUIPMENT

PDI & ONE (1) LOCAL MOVE TO TRUCK DEALER OR END USER

AECI MOBILE ON-SITE WARRANTY PKG., 1 YR ON-SITE TRAINING - PROVIDED BY REQUEST