

OR SERIES **OUTSIDE RAIL HOIST**



The Outside Rail roll-off hoist is the most commonly used hoist in the industry today. Galfab offers this hoist with an 8" mainframe and 2" subframe or the very popular 10" sub frameless hoist. Available in 60k and 75k pound models to fit any application.



THE GALFAB ADVANTAGE



Outboard Supported Side Rollers

Greasable Roller shaft is removable with two bolts for ease of replacement and maintenance.



Container Long Sill Support Rails

Rails aid in loading misaligned containers and give added support to the long sills increasing the life of your container.



Autofold DOT Bumpers

Bumper folds forward reducing the chance of bending and hang-ups in the landfill.



Rear Ground Roller Cover

Standard on all Outside Rail Hoists making it easier to load and unload containers.





Galfab's sliding ratchet strap container hold downs

• Galfab's simple but innovative ratchet straps slide fore and aft apromimately 10" giving the operator the ability to easily miss container cross members when securing containers to the hoist





STANDARD FEATURES

- 8" x 4 x 1/2" Main Frame Tube
- 3" x 2" x 1/4" Subframe
- 2 1/2" Diameter Rear Hinge
- All Working Points Greaseable
- Pintle Ready Apron
- Auto Fold Forward DOT Bumper
- 1" Spring Loaded Container Locks
- 2 1/2" Diameter Lift Cylinder Shafts
- Interchangeable 10" Vertical and Horizontal Sheaves
- 3/8 inch x 3-inch Winch Cylinder Rod Covers
- 6 Inboard and Outboard Supported Outside Rollers
- Container Long Sill Supports on Rear of Hoist Mainframe
 48 Gallon Oil Reservoir with Sight and Temperature Gauge

OPTIONAL FEATURES

- Behind Cab and Oversize Oil Tanks
- Tool Boxes
- Auxiliary Stops
- Poly or Steel Fenders
- Aluminum Fenders
- Tarping Systems
- "The Hooker" Hold On System
- Ratchet Tie Down Straps
- Pintle Hook

- 25 Micron Filtration
- · Inside and Outside Controls
- LED Lighting System
- Choice of Forward or Reverse Mount Single-Stage or Telescopic Lift Cylinders
- 7/8" Cable with Heavy Duty Swivel Eye Hook
- Galfab Auto-fold DOT Bumper
- 48-Degree Dump Angle on all Models
- 2 Minute Loading Cycle Time* Keeping your Drivers on the Road
- Hoist Up Alarm
- Backup Alarm
- Front Mount Pump
- PT0
- Drop Shaft
- On Board Scale Systems
- Work Lights
- Rear View Camera Systems
- Integrated hydraulics can be used, if hydraulic tarping is used



"The Hooker" Container Securement System



Auxillary fold down stops



Hydraulic Reservoirs



Tool Boxes



Poly, Steel & Aluminum Fenders

Shop all replacement parts at:





GALFAB WARRANTY POLICY

Galfab, a Wastebuilt company warrants only products of its manufacture against operational failure caused by defected material or workmanship which occurs during normal use within two years from the date the product was put into service. A product registration card must be filled out and returned to the factory for warranty to be considered.

Galfab makes no warranty on any of its equipment used in any way except as it was designed, intended, and sold to perform. Any misuse, damage due to an accident, outside alterations or negligence voids applicable warranty.

No freight or travel cost will be covered by this warranty. All labor cost allowed shall be in accordance with established rates. In case of alleged defects, products shall be returned to Galfab with transportation charges prepaid.

Galfab will replace all parts that prove to be defective within the warranty time frame after inspection at our factory.

Warranty for replacement parts is limited to the remaining portion of the original warranty, or warranted for 30 days from date of shipment.

Galfab does not assume any liability for loss of product, time, or any other consequential damages.

All claims will be processed through an authorized designee of the factory, or the factory.